MIL-T-45555(AT)
AMENDMENT 1
2 March 1987

MILITARY SPECIFICATION

TRAINERS, TANK TURRET: GUNNERY, M26 (M48A2) AND M30A1 (M60A1); PROCESSING FOR STORAGE AND SHIPMENT OF

This amendment forms a part of Military Specification MIL-T-45555(AT), dated 30 October 1964, and is approved for use by US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the specification.

Replacement page	Page replaced
1	1
2	2
5	5
6	6
7	7
8	8

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:23Z
Check the source to verify that this is the current version before use.

PAGE 3

Add new paragraph at the top of page:

"2.1.2 other Government document. The following other Government document form a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be those in effect on the date of the solicitation.

COMMERCIAL ITEM DESCRIPTION

A-A-884 - Tape Pressure-Sensitive Adhesive, Box Closure.

(Copies of specifications, standard and other Government document required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)"

PAGE 13

Add new paragraph 6.4:

"6.4 Subject term (key word) listing.

Gunnery trainers, processing for storage and shipment o
Processing for storage and shipment of, tank gunnery trainers
Storage and shipment, processing of tank gunnery trainers for"

Custodian:
Army - AT

Review-activity
Army - SM

Preparing activity:
Army - AT

(project PACK-A324)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:23Z
Check the source to verify that this is the current version before use.

MILITARY SPECIFICATION

TRAINERS, TANK TURRET: GUNNERY, M26 (M48A2) AND M30A1 (M60A1); PROCESSING FOR STORAGE AND SHIPMENT OF

1. SCOPE

1.1 Scope. This specification covers processing of the M26 (M48A2) and M30A1 (M60A1) Gunnery, Tank Turret Trainers for storage outside of buildings, for immediate use domestic shipment, and for overseas shipment, including car-loading; meeting the requirements of levels A, B and C processing (see 1.2).

1.2 Classification. Processing shall be of the following levels as specified (see 6.1):

Level A and B -	Processing for overseas shipment and any storage outside of buildings in excess of 90 days from date of processing (periodic care and preservation during storage required).
Level C	Limited processing for immediate use domestic shipment (excluding open deck loading) and any storage not to exceed 90 days from date of processing.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standard. The following specifications and standard form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS
FEDERAL

QQ-S-781 - Strapping, Steel, and Seals.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A AREA PACK
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:23Z
Check the source to verify that this is the current version before use.

TT-E-529	- Enamel, Alkyd, Semigloss.
UU-P-268	- Paper, Kraft, Wrapping.
VV-800	- Lubricating Oil, General Purpose Preservative (Water-Displacing, Low Temperature).
ZZ-T-416	- Tire Pneumatic: Retread and Repair Materials.
NNN-P-40	- Paper, Lens.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-1055	- Barrier Material, Waterproofed, Flexible.
PPP-C-843	- Cushioning Material, Cellulosic.
PPP-F-320	- Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-T-45	- Tape Gummed, Paper, Reinforced and Plain, for Sealing and Securing.
PPP-T-60	- Tape, Packaging, Waterproof

MILITARY

JAN-P-100	- Packaging and Packing of Overseas Shipment.
MIL-P-116	- Preservation, Methods of.
MIL-B-117	- Bags, Sleeves and Tubing-Interior Packaging.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-B-131	- Barrier Materials, Water Vaporproof, Greaseproof, Flexible, Heat-Sealable.
MIL-P-3420	- Packaging Materials, Volatile Corrosion Inhibitor Treated, Opaque.
MIL-H-6083	- Hydraulic Fluid, Petroleum Base, for Preservation and Operation.
MIL-I-8574	Inhibitors, Corrosion, Volatile, Utilization of.
MIL-G-10924	- Grease, Automotive and Artillery.
MIL-B-12841	- Basic Issue Items for Military Vehicles, Carriages and Equipment; Preparation for Shipment and Storage of.
MIL-P-14232	Parts, Equipment and Tools for Army Material, Packaging of.
MIL-C-16173	Corrosion Preventive Compound, Solvent Cutback, Cold-Application.
MIL-D-16791	- Detergents, General Purpose (Liquid, Nonionic).
MIL-C-20696	- Cloth, Coated, Nylon, Waterproof.
MIL-P-45637	Periscopes, Tank; M19 and M24.
MIL-P-46329	- Periscope, Tank; M13, M14A1, M17, M26, M27, M37 and M45.
MIL-E-51454	- Ethyl Alcohol (Ethanol)

STANDARD
MILITARY

MIL-STD-129	- Marking for Shipment and Storage.

Supersedes page 2 of MIL-T-45555(AT) of 30 October 1964.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:23Z
Check the source to verify that this is the current version before use.

with barrier material conforming to MIL-B-131 and tape conforming to type I, class I of PPP-T-60. Cannon ends shall be overwrapped with barrier materials conforming to type 1, grade C, of MIL-B-121 and sealed with tape conforming to type I, class 1 of PPP-T-60 (see figures 5, 25 and 31). The muzzle brake shall remain installed on the M26 cannon tube. The bore evacuator shall remain installed on the M30A1 cannon tube.

3.1.8.2 Cannon mount. After cannon tube is removed, grease conforming to MIL-G-10924 shall be applied to all unpainted surfaces, including phosphate surfaces, of all components of the cannon mount. The preserved cannon mount shall be overwrapped with barrier material conforming to type 11, grade A, class 2 of MIL-B-121. Barrier materials shall be secured in place with tape conforming to type 111, class 2, grade B of PPP-T-45. Cannon mount shall be blocked in position by placing a nominal 4x4x8 inch wood block between the top of the mantlet and the turret (see figure 30).

3.1.8.3 Exercising of recoil mechanism. Prior to processing as specified in 3.1.8.4 and 3.1.8.4.1 and when the recoil mechanism has not been exercised, proof-fired, overhauled, or manufactured within 4 months prior to preparation for storage or shipment, the recoil mechanism shall be exercised a minimum of three extensions of the recoil piston. Extension shall be not less than 6 inches. Record of exercising shall be entered on DA Form 2408-4 “Weapon Record Data” and proof testing of the weapon shall be entered on DA Form 2408-9 “Proof Acceptance Record”.

3.1.8.4 Exercising of replenisher. Replenisher assemblies shall be exercised coinsidently with the recoil mechanism (see 3.1.8.3).

3.1.8.4.1 Processing of replenisher after exercising. Replenisher shall be filled to bleed position with hydrualic fluid conforming to type 1 of MIL-H-6083, then drained to operating level.

3.1.8.5 Commander’s cupola. Periscope guard on top of cupola shall be removed, identified and stowed in interior of turret. Bolts and washers shall be reinstalled.

3.1.9 Miscellaneous preservation. Except as otherwise specified, all exposed, unpainted, unplated surfaces including machined-metal surfaces on the interior and exterior of the trainer, shall be coated with preservative conforming to grade 4 of MIL-C-16173.

3.1.10 Hatches. Rubber seals around hatches shall be coated with powdered talc conforming to type IV, class C of ZZ-T-416. During shipment, hatches shall be closed and locked from the inside. During storage, hatches shall be blocked open as much as possible, without interfering with the cover, to allow maximum ventilation under trainer cover.

3.1.11 Fire control items.

3.1.11.1 M105C telescope, M28C periscope and M31 periscope. The M105C telescope, M28C periscope and M31 periscope shall not be removed from their installed position in the trainer for shipment or storage. Exposed optical components shall be cleaned by blowing on exposed optical glass surfaces with air from a hand syringe, or by use of a clean camel’s hair brush, followed by

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:23Z
Check the source to verify that this is the current version before use.

the use of ethyl alcohol conforming to MIL-E-51454. In cases of contamination not removable by alcohol, cleaning shall be accomplished by use of a solution consisting of 2 ounces detergent conforming to MIL-D-16791, 1/2 gallon ethyl alcohol (ethanol) conforming to MIL-E-51454 and 1 gallon of distilled water. Using a swab made of lens tissue conforming to type I, class I or II of NNN-P-40, optical glass surfaces shall be washed with the cleaning agent. Washing shall be repeated using a clean swab each time until no dirt or other foreign matter remains on the surface. Cleaning shall be accomplished with a minimum of pressure and rubbing, without the use of cloth or rubber materials, to prevent damage to lens coatings. Immediately after cleaning, the optics shall be covered or wrapped with lens tissue conforming to type 11 of NNN-P-40 secured with tape conforming to A-A-884. All exposed, unpainted metal surfaces shall be coated with grease conforming to MIL-G-10924.

3.1.11.1.1 M24 and M27 periscopes. If installed, the M24 and M27 periscopes shall be removed from the trainer, packaged and packed in accordance with the level A requirements of the applicable specification as follows, then stowed with the OVE:

Periscope M24	- MIL-P-12903
Periscope M27	- MIL-P-46329

3.1.11.2 Instrument lights (dry-cell powered). If installed, instrument lights shall be removed from the trainer and packaged and packed in accordance with level A requirements of MIL-P-14232. Packed lights shall be identified and stowed with OVE. Batteries, if installed, shall be removed, packaged, packed, identified and stowed with the OVE.

3.1.11.3 Range finders. The optical surfaces, including end box windows, shall be cleaned as prescribed in 3.1.5.1.2 then covered with four thicknesses of lens tissue conforming to type 11 of NNN-P-40. The tissue shall be secured with tape conforming to A-A-884. All exposed, unpainted, metal surfaces shall be coated with grease conforming to MIL-G-10924.

3.1. 11.3.1 Purging of range finders. Range finders on hand for over 90 days from date of receipt at trainer manufacturer, not protected as specified in 3.1.11.3 or which disclose internal moisture at time of preparation for shipment or storage, shall be processed as follows: All controls shall be exercised to full limits in all normal directions of movement and returned to normal position. Caps shall be removed from right- and left-hand valves of range finder. Valve core shall be removed from one valve of the range finder. The other valve shall be connected to cylinder of dry nitrogen and the nitrogen allowed to flow at 5 psi through the range finder for 20 to 30 minutes. Pressure shall be reduced to 1 to 2 psi and the valve core installed. Caution: a check shall be made to make certain that cylinder pressure does not exceed capacity of the pressure regulator. The nitrogen cylinder shall be disconnected and the caps shall be replaced on the right- and left-hand valves. After purging, the range finder shall be processed in accordance with 3.1.11-3. End boxes shall be purged only when internal moisture is found during inspection.

3.1.11.4 Mounts, ballistic computer and drive. All exposed, unpainted, metal surfaces of periscope and telescope mounts, also computer and drive, shall be coated with grease conforming to MIL-G-10924.

Supersedes page 6 of MIL-T-45555(AT) of 30 October 1964.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:23Z
Check the source to verify that this is the current version before use.

3.1.11.5 Infinity sight, M44C. If installed, infinity sight shall be removed from the trainer. The sight shall then be packaged in accordance with level A requirements of MIL-P-14232, then identified and stowed with OVE.

3.1. 11.6 Level vial covers. All level vial covers shall be positioned over the vials.

3.1. 11.7 Exposed optical glass. Any exposed optical glass, not otherwise provided for herein, shall be cleaned, wrapped and taped as specified in MIL-P-45637.

3.1.12 On-Vehicle-Equipment (OVE). Except as otherwise specified (see 6.1), all spare parts, tools and equipment shall be packaged, packed, and marked in accordance with MIL-P-12841. For shipping purposes, OVE containers shall be blocked, braced and anchored to prevent movement. OVE containers shall be placed in a position which will not increase the overall cube. Each container shall be secured in each direction with two 1 1/4-inch straps conforming to type 1, class B of QQ-S-781, or by placing it between two or more secured containers or any other equally effective holding device. Corner plates shall be used under strapping. Pack shall be identified to pertinent trainer by serial number and, except during shipment, shall be stored inside buildings.

3.1.13 Record form. A copy of “The Equipment Log Book” consisting of binder (FSN 7510-889-3494) with required forms, and two copies of “Processing and Reprocessing Record for Shipment, Storage, and Issue of Vehicles and Spare Engines”, DD Form 1397 (see 6.3), shall-be furnished and completed with each trainer. Instructions for preparation and attachment or location of “The Equipment Log Book” shall be supplied by the Government representative. One copy of DD Form 1397 shall be placed in an envelope conforming to type I, class e of MIL-B-117. Envelope shall be closed by stapling, identified, and secured to trainer. The duplicate copy shall be placed in the envelope with the log book.

3.1.14 Headrests and crash pads. Immediately after drying, cushioned portions of headrests and crash pads shall be covered with paper conforming to grade B of UU-P-268 and having a minimum basis weight of 60 pounds. Paper shall be secured with tape conforming to A-A-884.

3.1.15 Fire extinguisher. Carbon dioxide (CO_2) fire extinguisher cylinder shall have a minimum of 90 percent of rated full charge. All seals shall be intact and record form WD Form 253 shall be completed and securely attached to each cylinder (see 6.2).

3.1.16 Power rectifier. Rectifier and all external connectors shall be covered with barrier material conforming to class 1 of MIL-B-131. Barrier material shall be sealed with tape conforming to type I, class 1 of PPP-T-60. Preservative conforming to grade 4 of MIL-C-16173 shall be applied to unpainted, nonelectrical exterior surfaces of the rectifier and surfaces of wheels and handle. The preserved areas shall be wrapped with barrier material conforming to type 11, grade A, class 2 of MIL-B-121. Power rectifier shall then be placed in a nailed wood box conforming to class 2, style 2 of PPP-B-621, and cushioned and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:23Z
Check the source to verify that this is the current version before use.

blocked in accordance with the applicable requirements of JAN-P-100. Two nominal 2x4 inch skids shall be added to nailed, wood box. The box shall be covered with barrier material conforming to class E-2 of PPP-B-1055. Barrier material shall extend 12 inches below top of the box. Box shall be marked in accordance with MIL-STD-129.

3.1.17 Power receptacle. Power receptacle shall be sealed with tape conforming to type I, class 1 of PPP-T-60.

3.1.18. Canvas. Canvas items, including muzzle brake cover, shall be removed, thoroughly dried, and placed in a carton conforming to PPP-B-636. After packaging, carton shall be marked in accordance with Standard MIL-STD-129 and placed within turret and secured.

3.1.19 Metal stowage box. The metal stowage box provided for the M30A1 trainer shall be packed in a container constructed in accordance with figure 18. The packed container shall be placed on the skid in accordance with figure 11, and secured in that position.

3.1.20 Cartridge racks. Cartridge racks shall be loaded with empty cartridge shells.

3.1.21 Trainer skid. Trainers shall be installed on skids constructed in accordance with figures 1 through 4. Observer platforms, stowage boxes, cannon tube, boxed rectifier and OVE shall be installed and secured on the skid in accordance with figures 5 through 35 and table I, as applicable. Table I shows the figure numbers that apply to the designated level of processing for M26 and M30A1 trainers.

TABLE 1. Installation of M26 and M30A1 trainers - levels of processing

Figure numbers	M26		M30A1	
	Levels A and B	Level C	Levels A and B	Level C
1, 2, 3, 4, 6, 7, 14, 15, 19, 30	X		X	
36, 37		X		X
8, 9, 12, 16, 17, 18, 20, 21, 23, 27	X	X	X	X
25, 34, 35	X			
5, 10, 11, 13, 22, 24, 26, 28, 29, 31, 32, 33			X	

3.1.22 Trainer turret openings. The turret openings shall be closed with 1/8-inch masonite. Masonite shall be secured in place with brackets conforming to figure 17. The openings around bottom of trainer stand shall also be closed with 1/8-inch masonite conforming to figures 8 and 9. The trainer basket protective screening shall be covered with fiberboard conforming to type CF, class weather-resistant, variety SW, grade W5c of PPP-F-320. The above masonite and fiberboard closures shall be sealed with 4-inch wide tape conforming to type II, class 1 of PPP-T-60.

Supersedes page 8 of MIL-T-45555(AT) of 30 October 1964.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:23Z
Check the source to verify that this is the current version before use.