MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, PA113, FOR CANISTER, VOLCANO MINE M87/M88

This specification is approved for use within the U.S. Army Armament Munitions and Chemical Command (AMCCOM), and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, quality assurance provisions and packaging for one type of metal container used for M87/M88 VOLCANO Mine Canisters.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issues of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-490	-Cleaning Methods for Ferrous Surfaces and pretreatments for Organic Coatings.

MILITARY

MIL-W-12332	-Welding Resistance, Spot, Seam and Production, for Fabricating Assemblies of Low-Carbon Steel
MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 8140
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-171	-Finishing of Metal and Wood Surfaces
MIL-STD-1190	-Minimum Guidelines for Level C Preservation, Packing, and Marking
MIL-STD-1235	-Single-and-Multi Level Continuous Sampling Procedures and Table for Inspection by Attributes.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (see 6.3)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9390404	-Container, Ammo, Metal, PA113, for Canister Mine: M87 and Canister Mine, Practice: M88

(Copies of specifications, standards, handbooks, drawings, publications and other Government documents required by contractors in connections with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D412	-Rubber Properties in Tension, Test Methods for
ASTM-D2240	-Rubber Property-Durometer Hardness, Test Method for
ASTM-E8	-Tension Testing of Metallic Materials, Standard Method of
ASTM-E18	-Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Test for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Containers. The containers shall comply with all requirements specified on drawing 9390404 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Welding. The welding shall comply with the requirements of MIL-W-12332.

3.3.1 Tensile strength. When tested as specified in 4.5.1, the tensile strength of the body material shall be in accordance with drawing 12630901 and the tensile strength of the longitudinal body weld shall be not less than 65 percent of the tensile strength of body material.

3.4 Painted surface. The painted surface of the container shall comply with the requirements of TT-C-490. However, the film thickness and salt spray requirements of TT-C-490 shall not apply to the interior surfaces, welded spots, sharp corners and crevices of the exterior surface of the container. Bare spots permissible on all bearing surfaces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

3.5 Cover assembly. Upon assembly of the cover assembly to the body weldment (body assembly), the cover assembly shall freely engage and rotate within the body weldment. As the cover assembly is rotated with the "Y" handle in the open position, the "Y" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "Y" handle is in the closed position (rotated 180°), the spring clip shall engage and lock the handle in place and a 0.06 inch diameter pin shall pass through the handle and shaft support holes. When the spring clip is disengaged and the handle rotated to the open position, the cover assembly shall disengage from the body weldment.

3.6 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to First Article Inspection (see 4.3).

3.7 Workmanship.

3.7.1 Containers. The containers shall be regular, smooth, and free from wrinkles, pin holes, cracks, rough spots, burrs, sharp edges and any other defect that might affect the serviceability, durability, safety or appearance of the container.

3.7.2 Paint coating. The paint coating shall be in accordance with applicable drawings and comply with instructions in MIL-STD-171.

3.7.3 Parts. All parts shall be free of chips, dirt, grease, rust and foreign material. The cleaning method used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents used.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in this specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection. (see 4.3)
b. Quality conformance inspection. (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall be in accordance with Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE: Assemblies and components		SHEET 1 OF 2		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Metal containers (Dwg. 9390404)				
	a. Examination for defects	5		3.2	4.4.2.19
	Body weldment (Dwg. 12598685)				
	a. Examination for defects	10		3.2	4.4.2.15
	b. Weld of rim to body (see Note)	5		3.2	4.5.2
	Cover assembly(Dwg. 9378170)				
	Examination for defects	5		3.2	4.4.2.10
	Body (Dwg. 12630901)				
	a. Examination for defects	10		3.2	4.4.2.13
	b. Tensile strength (see Note)	5		3.2	4.5.1
	Spring (Dwg. 9344042)				
	a. Examination for defects	10		3.2	4.4.2.1
	b. Embrittlement (see Note)	3		3.2	4.5.3

NOTES:
The weld security inspections, the body tensile strength,spring tests and gasket tensile stress test shall be performed after the other inspections have been performed on the applicable samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

Table I. First article inspection - Cont'd

CLASSIFICATION OF DEFECTS & TESTS MIL-C-70734 (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Assemblies and components				See Below
					NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	c. Hardness (see Note)	3		3.2	4.5.4
	Gasket (Dwg. 9378178)				
	a. Examination for defects	10		3.2	4.4.2.8
	b. Hardness	3		3.2	4.5.6
	c. Tensile stress (see Note)	3		3.2	4.5.5
	Remaining subassemblies and components				
	Examination for defects	10		3.2	Applicable subparagraph of 4.4.2

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of containers shall contain material from lots with the same interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Continuously sampling plan in accordance with MIL-STD-1235 may be used if approved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Spring				9344042
					NEXT HIGHER ASSEMBLY 9344044
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Spring embrittlement	(a)		3.2	4.5.3
102	Hardness incorrect	(a)		3.2	4.5.4
103	Radius of bend incorrect		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:
(a) Five springs from each heat treatment lot.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Support, shaft				9344035
					NEXT HIGHER ASSEMBLY
					9344044
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness incorrect		0.40%	3.2	Gage
Minor					
201	Radius not present at edges of tab		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.3	Handle	1	1	9344036
				NEXT HIGHER ASSEMBLY: 9378179

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of hexholes incorrrect		0.40%	3.2	Gage
102	Width of hexholes, over maximum		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Shaft				9378179
					NEXT HIGHER ASSEMBLY 9378170
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of hexagon segment of shaft, under minimum		0.40%	3.2	Gage
102	Small diameter (two places) incorrect		0.40%	3.2	Gage
103	Total length of large diameters and hexagon segments incorrect		0.40%	3.2	Gage
104	Length of small diameter segment (two places) incorrect		0.40%	3.2	Gage
105	Length of large diameter segment incorrect		0.40%	3.2	Gage
106	True position of small diameter (two places) incorrect		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Washer				9344038
					NEXT HIGHER ASSEMBLY 9378170
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter incorrect		0.40%	3.2	Gage
102	Height, under minimum		0.40%	3.2	Gage
103	Outside diameter, under minimum		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.6	Retainer, washer	1	1	9344041
				NEXT HIGHER ASSEMBLY 9378170

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Height of retainer incorrect		0.40%	3.2	Gage
Minor 201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Cover		9378182
			NEXT HIGHER ASSEMBLY 9378181

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness incorrect		0.40%	3.2	Gage
102	Width of groove incorrect		0.40%	3.2	Gage
103	Length of threads, under minimum		0.40%	3.2	Gage
104	Depth from top of cover to recess incorrect		0.40%	3.2	Gage
105	Outside diameter, over maximum		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Gasket				9378178
					NEXT HIGHER ASSEMBLY 9378170
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tensile stress incorrect	5		3.2	4.5.5
102	Elongation over maximum			3.2	Gage
103	Overall width incorrect		0.40%	3.2	Gage
104	Thickness of curved section incorrect		0.40%	3.2	Gage
105	Diameter of hole in cross section incorrect	5		3.2	Gage
106	Height of rectangular cross section incorrect		0.40%	3.2	Gage
107	Overextend of joint		0.40%	3.2	Gage
108	Extrusion incorrect	5		3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Cover weldment		9378181
			NEXT HIGHER ASSEMBLY 9378170

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of shaft hole and slot incorrect		0.40%	3.2	Gage
102	True position of shaft support uprights incorrect		0.40%	3.2	Gage
Minor					
201	Spot weld missing or incomplete		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Cover assembly		9378170
			NEXT HIGHER ASSEMBLY 9390404

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Shaft free to rotate		0.40%	3.2	Manual
102	Paint thickness, under minimum		0.40%	3.2	Gage
103	Air pressure test (per Note 5 of dwg)			3.2	Certification
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Rim		9375175
			NEXT HIGHER ASSEMBLY 12598685

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of large slot, over maximum		0.40%	3.2	Gage
102	Width of large slot, over maximum		0.40%	3.2	Gage
103	Inside dimension across flats, two places (Dim A), under minimum		0.40%	3.2	Gage
104	Inside diameter of rim, two places (Dim E) incorrect		0.40%	3.2	Gage
105	Radius/chamfer at beginning of locking edge of bayonet slot missing		0.40%	3.2	Visual
Minor					
201	Step at inside of locking edge of bayonet slot missing		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Ring				9378173
					NEXT HIGHER ASSEMBLY 12598685
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of large slot, over maximum		0.40%	3.2	Gage
102	Width of large slot, over maximum		0.40%	3.2	Gage
103	Inside dimensions across flats, 2 places (Dim. A) incorrect		0.40%	3.2	Gage
104	Opening of container interlocking grip improper		0.40%	3.2	Gage
Minor					
201	True position of interlocking cutouts incorrect		0.65%	3.2	Gage
202	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Body				12630901
					NEXT HIGHER ASSEMBLY 12598685
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tensile strength incorrect		0.40%	3.3.1	4.5.1
102	Material improper			3.2	Certification
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Plug, stacking		9344045
			NEXT HIGHER ASSEMBLY 12598685

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of plug, under minimum		0.40%	3.2	Gage
102	Width of plug, under minimum		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Body weldment, prior to painting		12598685
			NEXT HIGHER ASSEMBLY 9390404

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weld of rim to body improper	10		3.2	4.5.2/Gage
102	True position of slots of ring and rim to each other incorrect		0.40%	3.2	Gage
103	True position of stacking plugs of ring and rim to each other incorrect		0.40%	3.2	Gage
104	Location of lip grip and interlocking slot incorrect		0.40%	3.2	Gage
105	Inside diameter, under minimum		0.40%	3.2	Gage
106	Perpendicularity of rings with Datum-A incorrect		0.40%	3.2	Gage
107	Distance from end of body to top of rim bayonet slot (four places) incorrect		0.40%	3.2	Gage
Minor					
201	Minimum shear load between stacking plug and rim incorrect	10		3.2	Gage
202	Minimum shear load between stacking plug and ring incorrect	10		3.2	Gage
203	Minimum tensile load between rim and body incorrect	10		3.2	Gage
204	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.16	Body Weldment, after painting	1	1	12598685
				NEXT HIGHER ASSEMBLY: 9390404

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Paint on tip edge of body weldment, not uniform, missing or improper		100%	3.2	Manual/Visual
102	Paint thickness, under minimum		0.40%	3.2	Gage
103	Marking missing, incomplete or illegible		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.17	Bottom		9378172
			NEXT HIGHER ASSEMBLY 12598685

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Bottom unable to snug fit into body		0.40%	3.2	Visual
102	Material improper			3.2	Certification
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.18	Ring	1 OF 1	12630903
			NEXT HIGHER ASSEMBLY: 12598685

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material improper			3.2	Certification
102	Dimension before forming over max.		0.40%	3.2	Gage
103	Hole diameter after forming, over max		0.40%	3.2	Gage
104	Inside dimensions across flats, 2 places (Dim. A) incorrect		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70734 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.19	Container, ammo, metal, PA113	1 OF 1	9390404
			NEXT HIGHER ASSEMBLY: ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cover assembly test		0.40%	3.5	Visual/Manual/4.5.8
102	Air pressure test		100%	3.2	4.5.7.1
103	Interchangeability test	(a)	0.40%	3.2	4.5.7.2
104	Screw torque test	(b)	0.40%	3.2	4.5.9
105	Marking, missing, incomplete or illegible		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.7	Visual

NOTES: (a) The interchangeability test shall be performed after the air pressure test.
(b) The screw torque test shall be performed after the interchangeability test and the screw has been reassembled.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.4 herein.

4.5 Methods of inspection.

4.5.1 Tensile strength. The tensile strength shall be determined in accordance with ASTM-E8. Six bodies shall be randomly selected for this test per shift. From each body, three specimens shall be selected at random for determination of body material tensile strength. Also, from each body, four specimens approximately equally spaced along the axis shall be taken at right angles to the weld and the tensile strength of their welds shall be determined. Each of these values shall be compared with the lowest determined value of the body material tensile strength for compliance with the requirement of 3.3.1. If one or more specimens (longitudinal body weld or body material) fail to comply with 3.3.1, that sample body shall be classed defective. If two or more sample bodies are classed defective, the lot shall be rejected.

4.5.2 Weld of rim to body. The test shall be performed in accordance with ASTM-E8. Five body weldments shall be randomly selected from each lot and tested. If any sample fails to comply with the applicable requirement, the lot shall be rejected.

4.5.3 Spring embrittlement. Five springs shall be randomly selected from each heat treatment lot for this test. Each spring shall be repeatedly deflected with increasing loads until it does not return to its original free height. That point shall indicate minimum distortion. Any spring which fractures prior to extension to minimum distortion shall be classed defective. If any spring fails to meet the applicable requirement, the heat treatment lot shall be rejected.

4.5.4 Hardness of spring. The hardness of the spring shall be determined in accordance with ASTM-E18. Five springs shall be randomly selected from each heat treatment lot and tested. If any spring fails to meet the applicable requirement, the heat treatment lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.5.5 Tensile stress of gasket. The tensile stress shall be determined in accordance with ASTM-D412. Five gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the applicable requirement, the lot shall be rejected.

4.5.6 Hardness of gasket. The hardness shall be determined in accordance with ASTM-D2240. If one specimen fails to meet the applicable requirement, the lot of material shall be rejected.

4.5.7 Air pressure test.

4.5.7.1 Air pressure of painted container assembly. Subject the container assembly to the internal air pressure, specified in the applicable container assembly drawing, for one of the test times specified. Observation shall be made for any evidence of leakage exceeding the requirement for the corresponding test time (as specified in the applicable drawing). A container assembly, which exceeds the requirement, shall be classed defective.

4.5.7.2 Interchangeability of painted container assemblies. Randomly interchange the cover assemblies with container body weldments while positioning the cover assembly in a random orientation and perform the air pressure test per 4.5.7.1. Failure to meet the applicable requirement shall be cause for rejection of the lot.

4.5.8 Cover assembly test. Upon assembly of the body weldment and cover assembly, the cover shall freely engage and rotate within the body weldment. The Y-handle shaft ends shall engage into the respective bayonet slots of the rim without interference and a 0.06 inch diameter pin shall pass through the cover assembly holes when in the clamping position. The spring clip shal engage and lock the handle when in this position. The Y-handle, when disengaged and in the open position, shall disengage the cover from the body. Any assembly which fails to meet this criteria shall be classed defective.

4.5.9 Screw torque test. The minimum applicable torque shall be applied to the screw. Any evidence of motion of the screw before reaching the minimum acceptable torque shall be cause for rejection of the container assembly being tested. Any container assembly which fails the screw torque test may be reworked and returned to the lot after passing the screw torque test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging requirements. None required.

5.2 Packing. Packing shall be Level C. Metal ammunition containers and components shall be prepared in accordance with the requirements of MIL-STD-1190.

5.3 Marking. Shipping marking shall comply with MIL-STD-1190 and the following additional instructions. No shipping marking shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used on the containers unless otherwise specified. The following information shall be shown: Item name and model number (if applicable), part number and revision, contract number, lot number and date, name and address of manufacturer. If containers or components are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labeling or stenciling.

6. NOTES

6.1 Intended use. The container is intended for use in the M87/M88 VOLCANO Mine Canister.

6.2 Ordering data. See MIL-A-48078.

6.3 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance ARDEC.

6.4 Submission of inspection equipment design for approvals. See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research, Development and Engineering Center (ARDEC), ATTN: AMSMC-QAT-I, Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423. Unless otherwise specified, data item DI-R-1714 will apply.

6.5 Subject term (key word) listing.

Ammunition
Mine
Canister
Container
Metal

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A750)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.