INCH-POUND

MIL-I-85352
AMENDMENT 3
14 Feb 1989
SUPERSEDING
MIL-I-85352
AMENDMENT 2
30 AUGUST 1987

MILITARY SPECIFICATION

INFLATOR ASSEMBLY AND GAGE ELEMENTS, PNEUMATIC PRESSURE, REMOTE CONTROL, DIRECT READING

This amendment forms a part of Military Specification MIL-I-85352, dated 12 MAY 1980, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

DD Form 1426 note, change the Beneficial comments block to read as follows

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Naval Air Engineering Center, Systems Engineering Standardization Department (Code 53), Lakehurst, NJ 08733-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

Change the Federal Supply Classification (FSC) number from FSC 6685 to FSC 4920

Paragraph 2.1, delete the entire paragraph and substitute the following paragraphs

2.1 Government documents

* 2.1.1 Specifications, standards, and handbooks The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

AMSC N/A FSC 4920

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:43Z
Check the source to verify that this is the current version before use.

PAGE 2

Under Federal Specification, delete the following documents
"QQ-Z-325 Zinc Coating, Electrodeposited, Requirement For "
"QQ-C-320 Chromium Plating (Electrodeposited) "
"QQ-N-290 Nickel Plating (Electrodeposited)."
"QQ-P-416 Plating, Cadmium (Electrodeposited) "

PAGE 2

Under Military Specifications,
Delete "MIL-D-1000/1 Drawings Engineering and Associated Data" and
"MIL-A-8625 Anodic Coatings for Aluminum and Aluminum Alloys "
Add "MIL-P-24074 Polytetrafluoroethylene Parts and Coatings and Polyamide Parts "

PAGE 3

Under Military Standards,
Add "DOD-STD-100 Engineering Drawing Practices "

Paragraph 2 2, Under American National Standard Institute, delete "ANSI-B40 1-1974 Gages, Pressure and Vacuum, Indicating Type, Elastic Element" and substitute "ANSI-B40 1 Gages, Pressure Indicating Dial Type, Elastic Element "

(Copies of the above publication may be obtained from the American National Standards Institute, 1430 Broadway, New York, NY 10018)

PAGE 10

Paragraph 3.8.2.2, add at the end of sentence "The petcock shall be installed such that the vented gases are directed down or away or both from the operator "

Paragraph 3.8.3, change the last sentence to read "The end of the hose that connects to the remote controller body shall include a swivel type fitting that permits the hose to easily and continuously rotate 360°, thus facilitating the winding of the hose for storage in the carrying case "

PAGE 12

Paragraph 3.8 3.1, delete the entire paragraph and substitute the following

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:43Z
Check the source to verify that this is the current version before use.

PAGE 12

3.8 3 1 Tire valve adapter The tire valve adapter shall be fabricated of stainless steel in accordance with Figure 2 One end shall be threaded to fit a tire valve stem and contain a compression resistant gasket to create an air tight seal The gasket shall be fabricated of Polytetrafluoroethylene (PTFE) in accordance with MIL-P-24074 (Ships), Type 1, grade B, 25% glass filled The other end shall be fitted with a replaceable tire valve adapter extension No special tools shall be required for attaching the adapter to the tire valve ster "

* 3 8 3 2 Service hose assembly. Add after the last sentence "The end of the hose that connects to the remote controller body shall include a swivel type fitting that permits the hose to easily and continuously rotate 360 degrees, thus facilitating the winding of the hose for storage in the carrying case "

Paragraph 3 8 5, change to read the last sentence "The carrying case shall be finishec in accordance with MIL-STD-808 "

PAGE 18

Paragraph 3 10, line 4, delete "MIL-D-1000/1" and substitute "DOD-STD-100 Chapter 600 "

Paragraph 3 11, change last sentence to read "Protective finishes shall be in accordance with MIL-STD-808 "

PAGE 22

Paragraph 4 6 2, line 15, delete "ANSI-B40.1-1974" and substitute "ANSI-B40 1 "

* Paragraph 4 6 2, change the last sentence to read "It shall have a pressure range of not more than 3000 ps , and shall be graduated in increments not larger than 30 psig "

PAGE 27

Paragraph 6.2 f(1), line 3, delete "Attn Code 92713" and substitute "Attn Code 52621 "

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:43Z
Check the source to verify that this is the current version before use.

PAGE 27

Paragraph 6.2 f(2), line 3, delete "Attn Code AIR-534" and substitute "Attn Code AIR-552 "

Paragraph 6.2 f(2), line 5, delete "Attn Code 92713" and substitute "Attn Code 52621 "

PAGE 28

Paragraph 6.3, at the end of the last sentence, delete "Attn Code 92713" and substitute "Attn Code 52621"

Add the following paragraphs to section 6

6.4 Subject term (key words) listing

a Inflator Pneumatic

b Remote controlled inflation

c Dual Chuck Stem Gages

d Operating Pressure 600 psi (maximum)

e Aircraft Tire

* 6.5 The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians.

Air Force - 99
Navy - AS
Army - AV

Review activity
DLA-GS

Preparing activity
Navy - AS
(Project No. 4920-0453)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:43Z
Check the source to verify that this is the current version before use.