MILITARY SPECIFICATION

RESISTOR NETWORK, THICK FILM, FIXED AND TRIMMABLE

This Specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification provides quality assurance provisions for the fabrication and packing of Fixed and Trimmable Film Resistors Networks for use in the M692/M731 Mine, ADAM Anti-Personnel.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-R-39032 - Resistors, Preparation for Delivery of
MIL-P-48189 - 155MM, HE, M692 and M731 Housing, Timing and Fuzing for
MIL-R-83401 - Resistor Networks, Fixed Film General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S Army Armament, Munitions and Chemical Command, Attn AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

MIL-STD-202 - Test Methods for Electronics and Electrical Component Parts
MIL-STD-883 - Test Methods and Procedures for Microelectronics
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment
MIL-STD-1285 - Marking of Electrical and Electronic Parts
MIL-STD-45662 - Calibration Systems Requirements

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9298496 - Resistor Network

(Copies of specifications, standards, drawings, and publications required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets of MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The manufacturer of the resistor network in compliance with this specification shall have production and test facilities and a quality and reliability assurance program adequate to assure successful compliance with the provisions of this speci- fication. Only resistor networks which are inspected for and meet all of the requirements specified herein shall be marked and delivered.

3.2 Detail specification. The complete requirements for the network shall be in accordance with Drawing 9298496 and as specified in this detail specification and MIL-R-83401.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

3.3 Design and construction. The resistor network shall consist of a ceramic substrate with conductors, insulating and resistance patterns applied by a thick film techniques in the order necessary to meet the requirements of this specification. The resistance patterns for the trimmable resistors (R2, R4, R7) shall be on the top side of the substrate and positioned for YAG laser trimming as specified in detailed drawing. The dc resistance between terminals shall be in accordance with the resistance table and network schematic of the detailed drawing.

3.3.1 Solderability. Terminal leads shall be free of foreign material, flash marks, and other irregularities? and conform to the requirements of the detailed drawing.

3.3.2 Enclosure. Resistor networks shall be encapsulated sufficiently to withstand the environmental tests specified and shall not be damaged by standard automatic insertion machine. The encapsulating material shall be compatible with YAG laser trimming.

3.3.3 Physical dimensions. The physical dimensions of the resistor network package shall comply with all requirements in detailed drawing. Package dimension-inspection shall be performed in accordance with MIL-STD-883, Method 2016.

3.3.4 Terminal leads, terminal and pads. Insertion terminal leads shall be termed to allow insertion onto printed wiring board by automatic insertion machines. Terminals shall be mechanically secured to the substrate by soldering or welding and shall be electrically bonded to the network terminations. All solder used, to provide electrical connections, or to secure terminals shall have a minimum solidus temperature of 182°C (360°F). Corrosive fluxes shall not be used. There shall be a minimum of 90% of the terminal connection area in electrical contact with the network terminal pad.

3.4 Electrical characteristics.

3.4.1 Network characteristics. When resistor networks are subjected to the condition or test specified in Table 1, the percent change in resistance in each resistor element shall not exceed the value specified in Table I. The examination and test requirement method shall be in accordance with MIL-R-83401 for characteristic M resistor network unless otherwise specified herein.

3.4.2 Maximum voltage. The maximum continuous working voltage applied to the resistor elements shall be 10 volts dc or 10 volts rms (root-mean-square, sine-wave).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

3.4.3 Trimmable resistors R2, R4, R7. The trimmable resistors shall not be trimmed by the resistor network manufacturer; however, their initial resistance prior to user laser trimming shall be less than the minimum specified for their trimmable resistance range. (See detailed drawing for the trimmable resistance range). The initial resistance value shall be the nominal resistance used in the dc resistance tests. The trimmable resistor shall be designed so that any resistance within its trimmable resistance range shall be obtainable with a single straight cut made with a YAG Laser set with a spot size of 2 mils, Q-switched at 3000 pulses per second, and with power of 1 watt. Windows shall expose all trimmable material and the substrate around this material as specified in the detailed drawing.

3.4.4 Voltage sensitivity. The resistance value of the individual resistance elements in the network shall not change by more than 0.5% from its initial value with 1 volt DC applied compared to the value obtained with 10 volts DC applied. The rated voltage of the circuit elements shall be 10 volts DC.

3.4.5 Insulation resistance. The insulation resistance between resistive elements and conductive paths shall be greater than 3000 megohms.

3.5 Device marking.

3.5.1 Marking. Each resistor network shall be marked in accordance with Method 1 of MIL-STD-1285 as follows:

Part number revision code: Part number plus revision letter.

b. Supplier’s code symbol.

c. Inspection lot date code: The first two digits shall be the last two digits of the number of the year. The third and fourth digits shall indicate the calendar week of the year.

d. Pin No. 1 identifier, see Dwg. 9298496.

3.5.2 Resistance to solvents. The markings on resistor networks shall be legible after being subjected to the resistance to solvents test of MIL-STD-202, Method 2015.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

TABLE I. Network characteristics.

Test or Condition	1/ MIL-R-83401 Requirement-Method Paragraphs	Value	Units
Resistance-temperature characteristic	3.13 - 4.6.8	± 300	Parts/ million/°C
Thermal shock	3.7 - 4.6.3	± 0.5	Maximum per- cent change in resistance (0.01 ohm additional measurement error)
Low-temperature operation	3.14 - 4.6.9	± 0.5	
Short time overload	3.15 - 4.6.10	± 0.5	
Terminal strength	3.16 - 4.6.11	± 0.25	
Resistance to soldering heat	3.19 - 4.6.14, Cond. B	± 0.25	
Moisture Resistance	3.20 - 4.6.15	± 0.5	
High-frequency vibration	3.22 - 4.6.17	± 0.25	
Life	3.23 - 4.6.18	± 2.0	
High temperature exposure	3.2.4 - 4.6.19	± 1.0	
Low-temperature storage	3.25 - 4.6.20	± 0.5	
D.C. resistance 2/	3.9 - 4.6.5	2/	
*Insulation resistance	3 18 4 6 13	3,000	Megohms

*These characteristics or conditions vary from Code Symbol M in MIL-R-83401.

1/ Headings of requirement and method paragraph of MIL-R-83401 (General Specification) are the same as listed above for test or condition. The headings are the prime references. Paragraph numbers are given to facilitate locating references.

2/ The nominal resistance and resistance tolerance shall be as specified in detailed drawing (see 3.3, 3.4.3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

3.6 Data requirements. Data shall be recorded and submitted in accordance with the contract.

3.7 First article inspection. This specification contains provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be specified in the contract.

3.8 Mechanical shock. (See MIL-P-48189)

3.9 Workmanship . The trimmable resistive network shall be fabricated and finished in a thorough, workmanlike manner consistent with the best practices of the industry. It shall be free of dirt, corrosion products and other foreign matter. The cleaning method used shall not be injurious to the resistive network nor shall the parts be contaminated by the cleaning agents. All markings and stampings shall be free of harmful cleaning and soldering agents that may be injurious to the thick film (TF). All markings and stampings, shall be displayed and visibly defined. The TF shall be manufactured and processed in such a manner as to be uniform in quality and free from defects that will affect life, configuration and serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the conctract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. AU items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor’s overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of two hundred four (204) trimmable resistor networks.

4.3.2 Inspections to be performed. See Table II specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-R-63993A(AR)

PARAGRAPH	TITLE Network, Resistor - Fixed and Trimmable		SHEET 1 OF 2		DRAWING NUMBER 9298496 NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group I Non-destructive	10-0-1			MIL-R-83401 1/
	Thermal shock			3.4.1	4.6.3
	DC resistance			3.4.1, 3.4.3	4.6.5
	Group IA Non-destructive				
	Voltage sensitivity			3.4.4	MIL-STD-202 Method 309
	Physical dimensions			3.2, 3.3 3.3.3	MIL-STD-883 Method 2016, 4.5.1
	Visual and mechanical examination			3.2, 3.3 3.3.4 3.9 3.5, 3.5.1, 3.3.1	MIL-STD-883 Method 2016, 4.5.1 MIL-STD-1285 Method 1
	Group II	10-0-1			
	Solderability			3.3.1	MIL-STD-202 Method 208
	Resistance to solvents			3.5.2	MIL-STD-202 Method 215

NOTES:

AMSMC Form 1570, 1 Feb 85 Repla DRSMC-QA (D) Form 160, 1 Aug 83, which may not be ed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-R-63993A(AR)

PARAGRAPH CATEGORY	TITLE / EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	DRAWING NUMBER / NEXT HIGHER ASSEMBLY / PARAGRAPH REFERENCE /INSPECTION METHOD
	Network, Resistor - Fixed and Trimmable		SHEET 1 OF 2		9298496 / ---
	Group III	10-0-1			MIL-R-83401 2/
	Resistance-temperature characteristic			3.4.1	4.6.8
	Low temperature operation			3.4.1	4.6.9
	Short time overload			3.4.1, 3.4.2	4.6.10
	Terminal strength			3.4.1	4.6.11
	Group IV	10-0-1			MIL-R-83401
	Insulation resistance			3.4.1	4.6.13
	Moisture resistance			3.4.1	4.6.15
	Resistance to soldering heat			3.4.1	4.6.14 Cond. B
	Group V	10-0-1			MIL-STD-883
	Shock, (mechanical)			3.4.1	Method 2002 Cond. F
	Vibration, high frequency			3.4.1	MIL-R-83401 4.6.17
	Group VI	10-0-1			
	Life			3.4.1	4.5.18
	Group VII	10-0-1			
	Low temperature storage			3.4.1	4.6.20
	High temperature exposure			3.4.1	4.6.19
	Group VIII				
	Yuma ballistic gun firing	3/		3.8	MIL-P-48189 (AR)

NOTES: Test headings listed above are prime references to MIL-R-83401, para. numbers are given to possibly facilitate locating references. 2/ Follow the sequence called out in MIL-R-83401, Table XI, titled "Resistance-temperature characteristics". 3/ The no. of units specified per MIL-P-48189 shall be subjected to Group VIII Yuma Ballistic Testing.

Source: https://assist.dla.mil -- Downloaded: 2024-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.3.3 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of the item in the sample to comply with any of the stated requirements.

NOTE: The Government reserves the right to terminate its inspection when any failure of an assembly. component or test specimen in the sample causes rejection per the accept-reject criteria, for that examination or test.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shal comply with the lot formation provisions of MIL-R-83401.

4.4.2 Examination. Inspection of product for delivery shall consist of groups A and B. (see 4.4.2.1 through 4.4.2.6)

4.4.2.1 Group A inspection. Group A inspection shall consist of the examinations and tests specified in 4.4.2.4, and shall be made on the same set of sample units in the order shown.

a. Sampling plan. Sampling and inspection for subgroup 1 and 2 shall be in accordance with MIL-STD-105 for general inspection level II.

4.4.2.2 Group B inspection. Group B inspection shall consist of the tests specified in 4.4.2 .5, in the order shown. They shall be performed on sample units that have been subjected to and have passed the Group A inspection.

a. Sampling plan. Sampling and inspection shall be in accordance with MIL-STD-105 for special inspection level S-4 with an AQL of 2.5 percent. Sample units which have passed all the Group B inspections may be delivered on the contract provided they are within resistance tolerance and meet requirements for visual and mechanical inspection.

4.4.2.3 Group C inspection. Group C inspection shall consist of the tests specified in 4.4.2.6, in the order shown. they shall be performed periodically, as specified in 4.4.2.6, on sample units selected from lots that have passed groups A and B inspection.

a. Sampling plans. The sample size for each subgroup in 4.4.2.6 shall be 10 units. Sample units which have been subjected to Group C inspection shall not be delivered on the contract. If rejects exceeds those allowed in 4.4.2.6, supplier shall perform failure analysis and furnish copy to technical agency listed in 6.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-R-63993 (AR)

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
	Network, Resistor - Fixed and Trimmable		1 2		9298496
					NEXT HIGHER ASSEMBLY: None
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group A subgroup (non-destructive tests)				MIL-R-83401 3/
	Thermal shock	1/	0.40%	3.4.1	4.6.3
	DC resistance		100%	3.4.1, 3.4.3	MIL-R-83401 4.6.5
	Group A, subgroup 2 (non-destructive)	1/	1.0%		
	Physical dimensions			3.5,3.9	MIL-STD-883,
				3.3.3	Method 2016
	Visual and mechanical examination			3.2,3.3	4.5.1, herein 2/
				3.3.4,	MIL-STD-1285
				3.5.1,	Method 1
				3.9	
	Group A, subgroup 3	10-0-1			
	Solderability (all terminals)			3.3.1	MIL-STD-202, Method 208
	Resistance to solvents			3.5.2	MIL-STD-202, Method 215

NOTES:
1/ See 4.4.2.1.a.
2/ Body: cracks or holes which would cause probable failure; Leads: leads broken, crushed or nicked which would cause probable failure in use, lead spacing incorrect; Markings: incorrect, illegible.
3/ Test headings listed above are prime references to MIL-R-83401, para. numbers are given to possibly facilitate locating references.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9298496
	Network, Resistor - Fixed and Adjustable				NEXT HIGHER ASSEMBLY None
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Group B Shock, (mechanical) DC resistance Visual & mechanical examinations	10-0-1		3.4.1 3.4.1	MIL-STD-883 1/ Method 2002, Cond. F MIL-R-83401, 4.6.5 4.5.1, herein 2/

NOTES: 1/ This test must be completed prior to subsequent circuit resistance and physical damage test. It is permissable to test the sample for circuit resistance and remove defective parts prior to subjecting the sample to this test. 2/ Evidence of no physical damage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method Column' of the First Article and Quality Conformance tables. Test and measuring equipment and inspection facilities of sufficient accuracy, quality and quantity to permit performance of the required inspection shall be established and maintained by the contractor. The establishment and maintenance of a calibration system to control the accuracy of the measuring and test equipment shall be in accordance with MIL-STD-45662. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract (see 6.3).

4.5 Methods of inspections. The methods of inspection and testing are given by reference in the First Article and Quality Conformance Tables and 4.5.1 herein.

4.5.1 Visual and mechanical examination. Resistor networks shall be examined to verify that the materials, design, construction, markings, and workmanship are in accordance with the applicable requirements (See 3.2, 3.3, 3.3.2, 3.3.4, 3.5, and 3.7).

5. PACKAGING

5.1 Preservation and packaging. The resistor network shall be packaged in accordance with level B of MIL-R-39032.

5.2 Packing. The resistor network shall be packed in accordance with level B of MIL-R-39032.

5.3 Marking. The packed components shall be marked in accordance with the commercial requirements of MIL-STD-1188.

5.4 Shipping. When resistor networks from more than one lot are shipped together, each lot shall be kept separate, and the divisions between lots clearly indicated to prevent mixing of lots in transit.

6. NOTES

6.1 Intended use. The networks covered by this specification are intended for single-use, non-repairable, military devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions of submission of first article samples.

c. Quantity required and delivery schedules.

d. Certificates of conformance for each lot or shipment of product.

6.3 Submission of inspection equipment designs for approval. (See 4.4.4). Submit equipment designs (DI-E-1118/DI-R-1714) as required to Commander: U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I, Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Distribution of inspection failures and analysis data reports. Distribution of inspection failures and analysis data reports shall include the following: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-M, Picatinny Arsenal, New Jersey 07806-5000.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal (ARRADCOM), or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Subject term (key word) listing.
Thick film resistor
Resistor network
Trimmable resistor network

6.7 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A529)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-63993A (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:08Z
Check the source to verify that this is the current version before use.