METRIC
MIL-DTL-24728/1C
18 September 2018
SUPERSEDING
MIL-I-24728/1B
1 June 1995

DETAIL SPECIFICATION SHEET

INTERCONNECTION BOX, FIBER OPTIC, SUBMERSIBLE, 254 X 330 MM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24728.




FIGURE 1. Enclosure assembly, M24728/1-005 and M24728/1-006.

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.





FIGURE 1. Enclosure assembly, M24728/1-005 and M24728/1-006 – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.




Millimeters	Inches
195	7.7
343	13.5
457	18.0

NOTES:

1. Dimensions are in millimeters.
2. Inch-pound equivalents are given for general information only.
3. Tolerance is ±3 mm (0.12 inch) for one-place decimals.
4. For identification of subcomponent parts (circled numbers), see table I.

FIGURE 1. Enclosure assembly, M24728/1-005 and M24728/1-006 – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.



Millimeters	Inches
117.6	4.03
145.3	5.72
235.0	9.25
290.6	11.44

NOTES:

1. Dimensions are in millimeters.
2. Inch-pound equivalents are given for general information only.
3. Tolerance is ±0.3 mm (0.01 inch) for one-place decimals.
4. Mounting holes shall accommodate M12.7 x 1.95 (0.50-13) bolts.

FIGURE 2. Box mounting hole dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.





FIGURE 3. Box assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.




Millimeters	Inches	Millimeters	Inches
4.83	0.190	184.1	7.25
17.5	0.69	254	10
63.5	2.50	330	13
92.2	3.63	457	18
124.0	4.90		

NOTES:

1. Dimensions are in millimeters.
2. Inch-pound equivalents are given for general information only.
3. Tolerance is ±3 mm (0.12 inch) for whole numbers and ±0.3 mm (0.01 inch) for one-place decimals and ±0.13 mm (0.005 inch) for two-place decimals. A tolerance of ±8 mm (0.03 inch) is acceptable on dimensions controlled by welding or brazing, provided that this tolerance does not interfere with the interchangeability of assemblies or parts.
4. For identification of subcomponent parts (circled numbers), see table I.

FIGURE 3. Box assembly – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.




NOTES:

1. Detailed layout and placement of diagram holder is not specified.
2. For identification of subcomponent parts (circled numbers), see table I.

FIGURE 4. Cover assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.




Millimeters	Inches	Millimeters	Inches	Millimeters	Inches
3.3	0.13	85.9	3.38	158.8	6.25
7.1	0.28	88.9	3.50	175.5	6.91
11.2	0.44	93.7	3.69	196.9	7.75
12.7	0.50	98.5	3.88	209.6	8.25
19.0	0.75	115.8	4.56	215.9	8.50
31.8	1.25	123.9	4.88	228.6	9.00
34.0	1.34	143.0	5.63	236.5	9.31
64.3	2.53	143.0	5.63	247.6	9.75
66.8	2.63	149.4	5.88		

NOTES:

1. Dimensions are in millimeters.
2. Inch-pound equivalents are given for general information only.
3. Tolerance is ±3 mm (0.01) for one-place decimals.
4. For identification of subcomponent parts (circled numbers), see table I.

FIGURE 5. Mounting plate assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.




Millimeters	Inches
102	4.02

NOTES:

1. Dimensions are in millimeters.
2. Inch-pound equivalents are given for general information only.
3. Tolerance is ±3 mm (0.12 inch).
4. Hole is 5.6 mm (0.22 inch) in diameter.
5. For identification of subcomponent parts (circled numbers), see table I.

FIGURE 6. Tie wrap post.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.




Millimeters	Inches
4.1	0.16
16.0	0.63
79.5	3.13
89.0	3.5

NOTES:

1. Dimensions are in millimeters.
2. Inch-pound equivalents are given for general information only.
3. Tolerance is ±3 mm (0.12 inch) for whole numbers and ±0.3 mm (0.01 inch) for one-place decimals.
4. For identification of subcomponent parts (circled numbers), see table I.

FIGURE 7. Identification plate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.



Millimeters	Inches
1.5	0.06
4.8	0.19
5.1	0.20
25.0	1.0
127.0	5.0

NOTES:

1. Dimensions are in millimeters.
2. Inch-pound equivalents are given for general information only.
3. The signal word “WARNING” shall be in yellow on a black background in the upper panel. The lower panel shall consist of black letters on a yellow background.
4. Tolerance is ±3 mm (0.12 inch) for whole numbers and ±0.3 mm (0.01 inch) for one-place decimals.

FIGURE 8. Inside warning label.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.



Millimeters	Inches
1.5	0.06
3.3	0.13
5.1	0.20
25.0	1.0
127.0	5.0

NOTES:

1. Dimensions are in millimeters.
2. Inch-pound equivalents are given for general information only.
3. The signal word “WARNING” shall be in yellow on a black background in the upper panel. The lower panel shall consist of black letters on a yellow background.
4. Tolerance is ±3 mm (0.12 inch) for whole numbers and ±0.3 mm (0.01 inch) for one-place decimals.

FIGURE 9. Outside warning label.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.

TABLE I. Parts list.

Subcomponent identification numbers, circled (see figures 1 through 9)	Part name	PIN M24728/1 dash number		Subassembly number				Remarks and reference figures
		-005	-006	01	02	03	04	
01	Box assembly with MCT frame	1		1				1 and 3
02	Box assembly without MCT frame		1		1			1 and 3
03	Cover assembly	1	1			1		1 and 4
04	Mounting plate assembly	1	1				1	1 and 5
05 1/ 2/	254 x 330 box with MCT frame			1				3
06 1/ 2/	254 x 330 box without MCT frame				1			3
07 3/ 4/	MCT frame			1				3
08 2/ 3/	Flange pad			10	10			3
09 2/ 5/	Gusset			3	3			3
10 3/	Mounting leg			3	3			3
11 3/	Mounting channel			2	2			3
12 3/	Tie wrap bracket			2	2			3
13 6/	Warning label (inside)			1	1			1 and 8
14 6/	Warning label (outside)	1	1					1 and 9
15 7/	M6.35 x 1.27 (0.25-20) insert			6	6		2	3 and 5
16 7/	M9.53 x 1.59 (0.375-16) helicoil			10	10			3
17 4/	MCT wedge pack	1	1					1
18 2/	Gasket	1	1					1
19 8/	Identification plate	1	1					1 and 7
20 8/	Blank nameplate	1	1					1
21 2/ 7/	M9.53 x 1.59 (0.375-16) hex bolt	10	10					1
22 7/	9.53 (0.375) flat washer	10	10					1
23 7/	M6.35 x 1.27 (0.25-20) x 15.9 PHMS	6	6					1
24 7/	6.35 (0.25) flat washer	6	6					1
25 7/	6.35 (0.25) split lock washer	6	6					1
26 7/	M4.0 x 0.79 (8-32) x 12.7 PHMS						16	5
27 7/	4.0 (#8) flat washer						16	5
28 7/	4.0 (#8) split lock washer						16	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.

TABLE I. Parts list – Continued.

Subcomponent identification numbers circled (see figures 1 through 9)	Part name	PIN M24728/1 dash number		Subassembly number				Remarks and reference figures
		-005	-006	01	02	03	04	
29 7/	M3.5 x 0.79 (6-32) x 6.35 PHMS	4	4					1
30 1/ 2/	254 x 330 cover					1		4
31 2/ 8/ 9/	Diagram holder					1		4
32 2/ 8/	Dowel pin					2		4
33 8/	Mounting plate						1	5
34 7/	M4.0 x 0.79 (8-32) insert						16	5
35	Tie wrap post	4	4					6

NOTES:

1/ Aluminum, 3003 or 6061 in accordance with ASTM B209.

2/ See MIL-E-24142/6 for guidance.

3/ Aluminum, 5052 H-32 or 6061 in accordance with ASTM B209.

4/ See MIL-DTL-24705/1 for guidance.

5/ Aluminum, 5052 H-32 or 6061 in accordance with ASTM B209, 2.39 mm (0.09 inch) thick.

6/ In accordance with MIL-DTL-15024, type G, adhesive-backed, metal foil.

7/ Corrosion-resistant steel (CRES).

8/ Aluminum, 5052 H-32 in accordance with ASTM B209.

9/ Constructed to hold a 216-mm (8.5-inch) by 279-mm (11.0-inch) diagram.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction. See figures 1 through 9 and table I.

Interconnection box. The interconnection box shall be constructed in accordance with M24142/6-004.

MCT. The Multiple Cable Transit (MCT) shall be constructed using MIL-DTL-24705/1 as guidance. The MCT interior dimensions shall be 159.5 by 59.9 millimeters (6.28 by 2.36 inches).

Enclosure assembly construction. The enclosure assembly shall be constructed using the following combinations of materials:

a. The box, MCT frame, flange pads, gussets, mounting legs, mounting channels, tie wrap bracket, and cover shall be aluminum, 6061 in accordance with ASTM B209.

b. The box and cover shall be aluminum, 3003 in accordance with ASTM B209. The MCT frame, gussets, flange pads, mounting legs, mounting channels, and tie wrap bracket shall be aluminum, 5052 H-32 in accordance with ASTM B209.

Enclosure assemblies constructed using aluminum, 6061 shall not be welded.

Enclosure assemblies constructed using aluminum, 6061 shall be dip-brazed in accordance with AWS C3.7.

Enclosure assemblies constructed using aluminum, 6061 shall be artificially aged at 177 °C for 12 hours to a 6061-T4 condition.

Enclosure assemblies shall be class 1A conversion coated in accordance with MIL-DTL-5541 before being epoxy powder coated.

Cable interconnection interface. The cable feed-through shall be in accordance with MIL-DTL-24705 and shall accept cables having outer diameters between 6.1 and 25.4 millimeters (0.24 and 1.00 inch) constructed in accordance with MIL-PRF-85045.

Enclosure assembly stress relief. Enclosure assemblies shall be stress relieved in accordance with MIL-E-24142.

Mass	M24728/1-005	7.72 kilograms (maximum)
	M24728/1-006	5.9 kilograms (maximum)

Interconnection box mounting. See figure 2.

Interconnect organization.

Fiber optic diagram holders. See figure 4.

Fiber optic cable tie posts. Four (see figure 6).

Fiber optic splice tray holder. One maximum (see MIL-DTL-24728/8).

Fiber optic connector module. One maximum (see MIL-I-24728/6).

Fiber optic splices. When outfitted with 2 MIL-DTL-24728/8 splice tray holders, the interconnection box shall organize up to 48 MIL-PRF-24623/6 fiber optic splices.

Fiber optic connector adapters. When outfitted with a MIL-I-24728/6 connector module, the interconnection box shall organize up to 48 MIL-DTL-83522/17 connector adapters.

Cable retention. Not applicable.

Cable seal flexing. Not applicable.

Cable twist. Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.

Compression resistance. Not applicable.

Impact. Not applicable.

Water pressure. The interconnection cover bolts and the MCT wedge pack nut shall be tightened to a minimum torque of 16.94 newton-meters (150 inch-pounds) during this test.

Flammability. Not applicable.

Salt spray. Not applicable.

Flame spread. Not applicable.

Fungus test. The fungus test shall be conducted only on polymeric materials.

Operating and storage temperature range. The operating temperature range shall be -54 to +65 °C and the storage temperature range shall be -62 to +85 °C.

Part or identifying number (PIN). See MIL-DTL-24728 and table I.

M24728/1-005, box, mounting plate, and lid, with cable entrance and wedge pack.

M24728/1-006, box, mounting plate, and lid, without cable entrance.

M24728/1-001, M24728/1-002, M24728/1-003, and M24728/1-004 have been canceled without replacement.

Gasket size. The gasket size shall be 263.53 millimeters (10.375 inches) wide by 339.73 millimeters (13.375 inches) long. This corresponds to PIN M24142/6-004 of MIL-E-24142/6.

Insert block. Insert blocks compatible with the MCT frame are specified in MIL-DTL-24705/1.

Qualification by similarity. Manufacturers who produce products for both MIL-DTL-24728/2 and this specification sheet who are qualified under MIL-DTL-24728/2, and who pass the water pressure test and size inspection specified herein, are qualified under this specification sheet.

Measurement system. The U.S. Government preferred system of measurement is the metric (SI) system. However, since this item was originally designed using inch-pound units of measurement, in the event of conflict between the metric and inch-pound units, the inch-pound units shall take precedence.

CHANGES FROM PREVIOUS ISSUE. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – SH
Air Force – 85

Review activities:
Army – AR, MI
Navy – AS, CG, EC, MC, YD
Air Force – 19, 99
DLA – CC, GS
NASA – NA

Preparing activity:
Navy – SH
(Project 6099-2017-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:24Z
Check the source to verify that this is the current version before use.