FED. SUP CLASS
5310





REVIEWER: AT, AV, 15, EA, FL, GL, MI, NSA
USER: AS, MC, ME, OS, PA, SH, WV

* Ⓐ DASH NUMBER				NOMINAL SIZE	THREAD -2B	F ACROSS FLATS			G ACROSS CORNERS		H HEIGHT	Q HEX HGT	U FULL THREAD MIN
CARBON STEEL	CRES STEEL	AL ALLOY	BRASS			NOM	MAX	MIN	MAX	MIN			
1 2	1C 2C	1A 2A	1B 2B	6 (.138)	32UNC 40UNF	5/16	.3125	.302	.361	.344	.34	.16	.16
3 4	3C 4C	3A 4A	3B 4B	8 (.164)	32UNC 36UNF	5/16	.3125	.302	.361	.344	.34	.16	.16
5 6	5C 6C	5A 6A	5B 6B	10 (.190)	24UNC 32UNF	3/8	.3750	.362	.433	.413	.41	.19	.19
7 8	7C 8C	7A 8A	7B 8B	1/4 (.250)	20UNC 28UNF	7/16	.4375	.428	.505	.488	.47	.22	.25
9 10	9C 10C	9A 10A	9B 10B	5/16 (.312)	18UNC 24UNF	1/2	.5000	.489	.577	.557	.53	.25	.31
11 12	11C 12C	11A 12A	11B 12B	3/8 (.375)	16UNC 24UNF	9/16	.5625	.551	.650	.628	.62	.28	.38
~~13~~ ~~14~~	~~13C~~ ~~14C~~	~~13A~~ ~~14A~~	~~13B~~ ~~14B~~	7/16 (.438)	14UNC 20UNF	5/8	.6250	.612	.722	.698	.69	.31	.44
15 16	15C 16C	15A 16A	15B 16B	1/2 (.500)	13UNC 20UNF	3/4	.7500	.736	.866	.840	.81	.38	.50
~~17~~ ~~18~~	~~17C~~ ~~18C~~	~~17A~~ ~~18A~~	~~17B~~ ~~18B~~	9/16 (.562	12UNC 18UNF	7/8	.8750	.861	1.010	.982	.94	.44	.56
19 20	19C 20C	19A 20A	19B 20B	5/8 (.625)	11UNC 18UNF	15/16	.9375	.922	1.083	1.051	1.00	.47	.62
21 22	21C 22C	21A 22A	21B 22B	3/4 (.750)	10UNC 16UNF	1-1/16	1.0625	1.045	1.227	1.191	1.16	.53	.75

NOTES:

1. MATERIAL: Steel, carbon, grade A, in accordance with procurement specification.
   Steel, corrosion-resisting, in accordance with procurement specification.
   Aluminum alloy in accordance with procurement specification.
   Brass in accordance with procurement specification.
   Non-metallic insert shall be nylon or equivalent.
2. PROTECTIVE COATING: Steel, carbon: Cadmium plated in accordance with procurement specification.
   Steel, corrosion-resisting: Passivated in accordance with procurement specification.
   Aluminum alloy: Anodized in accordance with procurement specification.
   Brass: Uncoated.
3. THREADS: The threads shall be in accordance with the procurement specification.
4. DIMENSIONS: All dimensions are in inches. Dimensions and tolerances not shown shall be in accordance with SAE Standard J483 (low crown).
5. PART NUMBER: The MS part number consists of the MS number, plus the dash number.
   Example: MS51865-1.
6. Referenced documents shall be of the issue in effect on date of invitations for bid.
7. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
8. These nuts shall be used in accordance with the limitations of MS33588.

Ⓐ* LINED OUT DASH NUMBERS ARE INACTIVE FOR NEW DESIGN AFTER 15 JAN 1976.

APPROVED 22 JUN 1970 REVISED Ⓐ 15 JAN 1976

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC Other Cont 82	TITLE NUT, SELF-LOCKING, CAP-GENERAL PURPOSE, 250°F	MILITARY STANDARD MS51865
PROCUREMENT SPECIFICATION MIL-N-45913	SUPERSEDES:	SHEET 1 OF 1

DD FORM 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. 5310-0806

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:11Z
Check the source to verify that this is the current version before use.