FED. SUP CLASS
2640



STYLE 1 STYLE 2

Ⓐ CANCELLED AFTER 28 JULY 1976

FOR NEW DESIGN AND PROCUREMENT USE TIRE AND RIM ASSOCIATION STANDARDS YEARBOOK

MS PART NO.	TR. NO.	STYLE	A	B	D	E FITS THD.	F	J
MS 52117 -1	BW-1	1	1 7/8	15/16	21/64	.482-26	3/8	---
-2	BW-2	1	2 1/8	1 1/8	9/32	.482-26	9/16	---
-3	BW-3	1	2 1/4	1 5/16	9/32	.482-26	1	---
-4	BW-4	2	2 3/4	2	7/32	.482-26	1 1/4	1/4
-5	BW-18	2	2 3/4	2	7/32	.687-24	1 1/4	1/4

NOTE:

1. MATERIAL-STEEL, OR TEMPER 1 QQ-S-698. FINISH-CADMIUM TYPE II, CLASS 2, QQ-P-416 OR ZINC TYPE II, CLASS 2, QQ-Z-325.
2. DIMENSIONS SHOWN ARE IN INCHES.
3. THE MS PART NUMBER CONSISTS OF THE MS SHEET NUMBER PLUS THE DASH NUMBER.
4. THIS STANDARD IS NOT INTENDED TO LIMIT CONSTRUCTION TO FEATURES OTHER THAN SHOWN HEREON BY DIMENSIONS, NOTATIONS AND REFERENCED DOCUMENTS.
5. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON THE DATE OF INVITATIONS TO BID.
6. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFFRENCED HEREIN.

Ⓐ 28 JULY 1976

APPROVED 3 MARCH 1971 REVISED

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for competitive use shall be made from this document.

P.A. ARMY-AT Other Cust	TITLE VALVE STEM WASHER, PNEUMATIC TIRE:	MILITARY STANDARD MS52117(AT)
PROCUREMENT SPECIFICATION NONE	SUPERSEDES	SHEET 1 OF 1

DD FORM 672-1 (LIMITED COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBS

2640-A166

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:20Z
Check the source to verify that this is the current version before use.