MIL-V-19772A(SHIPS)
AMENDMENT 1
7 April 1987

MILITARY SPECIFICATION

VALVES, TEMPERATURE REGULATING,
AUTOMATIC, NAVAL SHIPBOARD

This amendment forms a part of MIL-V-19772A(SHIPS), dated 3 September 1968, and is approved for use within the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under "MILITARY": Delete "MIL-B-16541" and substitute "QQ-C-390".

PAGE 2

2.2, under "Other publications": Delete "UNITED STATES OF AMERICA STANDARDS INSTITUTE (USAS)" and substitute "AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)".

3.1, line 3: Delete "opening of bids" and substitute "awarding of contracts".

PAGE 3

3.3, lines 5 and 6: Delete "The Naval Ship Engineering Center (NAVSEC)" and substitute "The Naval Sea Systems Command (NAVSEA)".

Table I: Delete "Bronze MIL-B-16541" and substitute "Cast Bronze QQ-C-390 alloy C92200". Delete "cadmium plated" and substitute "zinc plated".

PAGE 4

3.3.1, line 8: After "hardfaced", add "unless otherwise approved by NAVSEA".

3.4.2.1, line 1: After "Type II", delete ", series 100 and 250", and substitute "and type III series 100 valves and type II series 250".

PAGE 5

3.4.7, line 3: After "flanged", add "or threaded".

3.4.11, line 4: Delete "Threaded-in seat rings shall be seal welded circumferentially on valves to be used on steam service above 225 psig." and substitute "For valves to be used on steam service above 225 psig, threaded-in seat rings shall be brazed circumferentially for bronze valves and seal welded circumferentially for steel valves.".

AMSC N/A FSC 4820
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:39Z
Check the source to verify that this is the current version before use.

PAGE 6

3.4.13: Add "(c) For type III class 1 series 100 valves, cap screws may be used in place of flanged bolting or tap-end studs."

3.4.13(b): Delete "USAS" and substitute "ANSI".

Add as new paragraphs 3.4.20 thru 3.4.20.1.

3.4.20 End-to-end dimensions.

3.4.20.1 End-to-end dimensions for type III class 1 series 100 valves shall be 9-1/4 inches for a 1-inch valve, 10-3/4 inches for a 1-1/4-inch valve, 11-3/4 inches for a 1-1/2-inch valve, and 12-3/4 inches for a 2-inch valve.

PAGE 16

6.3, line 2: Delete "opening of bids" and substitute "awarding of contracts".

Preparing activity:
Navy - SH
(Project 4820-N505)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:39Z
Check the source to verify that this is the current version before use.