MIL-S-19816A(OS)
15 June 1967
Superseding
MIL-S-19816(NOrd)
31 July 1957

MILITARY SPECIFICATION

SWITCH, STERILIZING, MARK 1 MOD 0

(FOR EXPLODER MECHANISM MARK 19 SERIES)

This specification has been approved by the Naval Ordnance Systems Command, Department of the Navy.

1. SCOPE

1.1 Scope This specification states the requirements for the procurement of Sterilizing Switch MK 1 Mod 0, a single-pole, single-throw, manually operated electric switch with normally open contacts. The switch is used in the firing circuit of a torpedo to sterilize the exploder mechanism in an emergency.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-18404	Torpedoes, Environmental Requirements, General Specifications for

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage

FSC-5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

DRAWINGS

NAVAL ORDNANCE SYSTEMS COMMAND

LD 275922	Sterilizing Switch Mark 1 Mod 0 and all parts and subassemblies listed thereon

PUBLICATIONS

NAVAL ORDNANCE SYSTEMS COMMAND

WR-43	Preparation of Quality Assurance Provisions (Including classification of characteristics)
OS 6341	Miscellaneous General Design Requirements

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. Sterilizing Switch MK 1 Mod 0 shall consist of a stainless steel housing that contains a driver, springloaded contact, and stationary contact. The driver shall be covered by an aluminum foil seal which can be easily pierced by a screwdriver to operate the switch. Construction of the switch shall be such that it may be operated from an initial open circuit position to a locked and closed circuit position. For test purposes, the switch can be operated from closed to open circuit position, through the use of a suitable tool. See 4.4.8.2

3.2 General requirements

3.2.1 Preproduction samples. Unless otherwise specified in the contract or order, preproduction samples of the sterilizing switch shall be manufactured using the methods and procedures proposed for production. The sample will be tested as specified in Section 4 and is for the purpose of determining, prior to production, that the contractor's production methods are capable of yielding items that comply with the technical requirements of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

3.2.2 Contractor-furnished data. Data required by this specification, or by applicable documents referenced in Section 2, need not be furnished unless specified in the contract or order (see 6.2).

3.2.3 Materials. Unless otherwise specified in the contract, requisition, or order, all materials and purchased parts entering into the final assembly of the sterilizing switch shall conform strictly to the detailed requirements indicated on the drawings and specifications listed in LD 275922.

3.2.4 Finishes, coatings, construction, and dimensions. Finishes, coating, construction, and dimensions of the sterilizing switch shall be strictly in accordance with the applicable drawings, specifications, and publications listed in LD 275922.

3.2.5 Moisture, fungus, and corrosion resistance. The sterilizing switch shall be rendered moisture, fungus, and corrosion resistant as required by OS 6341 and in accordance with detail requirements specified in the drawings and specifications listed in LD 275922.

3.2.6 Marking. Marking of assemblies, subassemblies, and parts shall be in accordance with the applicable drawings listed in LD 275922.

3.2.7 Interchangeability. Component parts of assembled units (unless otherwise specified on the applicable drawings) fabricated in strict agreement with their applicable drawings shall be interchangeable and shall assemble with mating components of the unit without selection or fitting. If, during assembly of the fabricated parts of a unit, selection or fitting is required and changes in dimensions are necessary, no changes in the parts as delineated on applicable drawings will be made without prior revision and correction of the applicable drawings. See 3.2.9.

3.2.8 Gages. The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, order, or requisition, the Government will furnish drawings of pertinent Navy Final Inspection Gages for guidance in the design of the contractor's inspection gages. However, such procedure shall not serve to

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

relieve the contractor of his responsibility in the design and manufacture of such gages as may be required for the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy Final Inspection Gages.

3.2.9 Conflicting requirements. Conflicting requirements arising between this specification or any specifications, publications, or drawings listed herein shall be referred in writing to the procuring agency or appointed agent for interpretation, clarification, and resolution (or correction).

3.3 Definitions. The environmental requirements of this specification are defined in MIL-T-18404.

3.4 Performance requirements and product characteristics. The sterilizing switch shall meet the following performance requirements and product characteristics:

3.4.1 Fixed contact. The fixed contact assembly shall withstand a force of 10 pounds applied along the axis of the contact from either direction without showing evidence of breaking or cracking of the plastic or a loosening of the contact.

3.4.2 Contact assembly securement. After staking the contact assembly in place, it shall resist, without movement within the housing, a torque of 5 inch-pounds applied to the axially parallel bores formed in the plastic portion of the contact assembly.

3.4.3 Operating torque. The driver shall not rotate from the switch open position to the switch closed position with an applied torque up to 5 inch-ounces, but shall rotate to the switch closed position with a torque greater than 5 inch-ounces. When a torque 2 inch-ounces greater than that required to rotate the switch to the closed position is applied to the driver in the switch closed position, the driver shall not rotate to the switch open position.

3.4.4 Contact resistance. With the switch in the closed position, the electrical resistance between the stationary contact and the housing shall be not more than 0.1 ohm.

3.4.5 Dielectric strength. In the normally open position of the switch, the resistance between the stationary contact and the housing shall be not less than 10 megohms under an applied potential of 500 volts direct current (dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

3.4.6 Seal. The aluminum foil seal closing the driver end of the switch shall be held firmly and uniformly about its edge beneath the formed flange of the housing, and shall display a smooth, uniform, and undamaged surface.

3.4.7 Operating life. The sterilizing switch shall have an operating life of not less than 100 cycles as defined in 4.4.8.1.

3.5 Environmental requirements. The sterilizing switch shall meet the other applicable requirements of this specification after or while being subjected to environmental conditions defined below, when tested as specified in Section 4.

3.5.1 Vibration

3.5.1.1 Vibration; transportation, storage, and handling. The sterilizing switch, packed and packaged as defined in Section 5 and mounted rigidly on a vibration device as specified in 4.4.1.1, shall withstand the vibrations for the time and at the temperatures to which a nonoperating, ready nonoperating, or ready torpedo is exposed, as specified in MIL-T-18404. Thereafter, the switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.1.2 Vibration; ready nonoperating or ready condition. The sterilizing switch, less pack or packaging and rigidly self-mounted on a vibration device as specified in 4.4.1.2, shall withstand the vibrations for the time and at the temperatures to which a nonoperating, ready nonoperating, or ready torpedo is exposed, as specified in MIL-T-18404. Thereafter, the switch shall show no damage and shall meet all performance requirements and product characteristics of this specification.

3.5.1.3 Vibration, operating condition. The sterilizing switch, self-mounted on a vibration device as specified in 4.4.1.3, shall withstand the vibrations of an operating torpedo for the time specified in MIL-T-18404. These vibrations may occur in any direction. While undergoing and after the vibration test, the sterilizing switch shall show no damage and shall meet all performance requirements and product characteristics of this specification.

3.5.2 Shock

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

3.5.2.1 Shock; transportation, storage, and handling. The sterilizing switch, packed and packaged as defined in Section 5 and mounted rigidly on a shock testing device as specified in 4.4.2.1, shall be subjected to the shock requirements for a torpedo nonoperating, ready nonoperating or ready (transportation), as specified in MIL-T-18404. Thereafter, the switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.2.2 Shock, operating condition. The sterilizing switch, self-mounted on a shock testing device as specified in 4.4.2.2, shall be subjected to the shock requirements for a torpedo ready or operating, air-borne launching with external attachments, as specified in MIL-T-18404. Thereafter, the switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.3 Acceleration. The sterilizing switch, mounted securely on an acceleration device as specified in 4.4.3, shall be subjected to the acceleration requirements for a torpedo ready nonoperating, ready, or operating, as specified in MIL-T-18404. Thereafter, the sterilizing switch shall show no damage and shall meet all performance requirements and product characteristics of this specification.

3.5.4 Temperature and humidity

3.5.4.1 Transportation and storage condition. The sterilizing switch, packaged and packed as defined in Section 5, shall be subjected to the temperature and humidity conditions specified in 4.4.4.1 and thereafter, shall show no corrosion or damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.4.2 High and low temperature operation. The sterilizing switch, less packaging and packing and mounted as specified in 4.4.4.2, shall be subjected to the high and low temperature conditions specified in 4.4.4.2. At the conclusion of the test, and while still at the test temperature, the sterilizing switch shall show no corrosion or damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.5 Pressure

3.5.5.1 Altitude. The sterilizing switch shall be subjected to the pressure requirements for torpedoes subject to air transportation, as specified in MIL-T-18404. Thereafter, the sterilizing switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

3.5.5.2 Snorkeling. The sterilizing switch shall be subjected to the pressure requirements for torpedoes subject to snorkeling submarine transportation, as specified in MIL-T-18404. Thereafter, the sterilizing switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.5.3 External air pressure. The sterilizing switch shall be subjected to the pressure requirements for submarine launched torpedoes, as specified in MIL-T-18404. Thereafter, and while exposed to this pressure, the sterilizing switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.6 Tropical environment. The sterilizing switch shall be exposed to tropical environment conditions as specified in 4.4.6. Thereafter, the sterilizing switch shall show no fungus growth, corrosion, or other damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.7 Marine environment

3.5.7.1 Sea atmosphere. The sterilizing switch, mounted as specified in 4.4.7, shall be subjected to salt-laden atmosphere as specified in MIL-T-18404. Thereafter, the sterilizing switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.7.2 Immersion. The sterilizing switch, mounted as specified in 4.4.7, shall be subjected to immersion in sea water as specified in MIL-T-18404. Thereafter, the sterilizing switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.5.8 Storage life. The sterilizing switch, packed and packaged in accordance with 5.1.1, shall be operable and meet all the performance requirements and product characteristics of this specification after being stored for a period of at least eight years under the following temperature and humidity conditions:

3.5.8.1 Temperature: Minus 65 degrees F to plus 160 degrees F (minus 53.89 degrees C to plus 71.11 degrees C).

3.5.8.2 Humidity: Up to 95 percent relative (maximum).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

3.5.8.3 To meet the storage life requirement, rubber O-rings shall be replaced after every five years of continuous storage.

3.6 Cleanup. Prior to and after final assembly, all components shall be thoroughly cleaned of metal chips and other foreign matter. Burrs and sharp edges shall be removed.

3.8 Workmanship. The equipment, including all parts and accessories, shall be constructed and finished in a manner to ensure compliance with all requirements of this specification. Particular attention shall be paid to neatness and thoroughness of soldering, wiring, impregnation of coils, marking of parts and assemblies, plating, riveting, machine screw assemblies, welding, brazing, and freedom of parts from burrs and sharp edges. The standards of workmanship exhibited in any approved preproduction sample, subject to any qualification stated in the Government's notice of approval, shall be determinative of the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure that supplies and services conform to prescribed requirements.

4.1.1 Classification of inspections. Inspection of the sterilizing switch shall be classified as follows:

a. Preproduction inspection (paragraph 4.4)
b. Periodic production inspection (paragraph 4.4)
c. Acceptance inspection (paragraph 4.5).

4.2 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major, or Minor, in accordance with WR-43. Tests and examinations that verify critical characteristics are identified by the symbol (C), and those that verify major characteristics are identified by the symbol (M). The number following the classification symbol indicates the serial number of the test or examination. Tests and examinations that are not annotated with a classification code are classified minor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

4.2.1 Quality conformance inspection. Quality conformance inspection of the sterilizing switches shall consist of the tests of 4.4 and 4.5 and those of related drawings.

4.3 Sampling

4.3.1 Preproduction sample. A preproduction sample of five sterilizing switches manufactured in accordance with 3.2 shall be subjected to the preproduction tests detailed in 4.4 at an activity designated by the procuring activity. Acceptance of the preproduction sample shall be based on no defects in the sample. Further production of the switches by the supplier, prior to the approval of the preproduction sample, shall be at the supplier's risk.

4.3.2 Periodic production sampling. Periodic production samples shall be selected from units that have satisfactorily passed the acceptance inspections of 4.5. These samples shall be subjected to the tests of 4.4 at an activity designated by the procuring activity. Periodic production sampling shall be as follows:

Step 1. Upon initiation of production randomly select one unit from each group of 10 units. Upon satisfactory compliance of samples selected from 3 consecutive groups, shift to Step 2.

Step 2. Randomly select one unit from each group of 25 units. Upon satisfactory compliance of samples selected from 3 consecutive groups, shift to Step 3.

Step 3. Randomly select one unit from each group of 50 units. Continue Step 3 for the balance of the contract or until a defective unit is found.

When a defective unit is found in any group, acceptance of all units on hand shall be withheld and the contractor shall:

a. Determine the cause of the defect.

b. Take the necessary action to correct or eliminate the defect from all units on hand and, if so directed by the procuring activity, from those units previously shipped.

c. Submit to the procuring activity for approval the proposed corrective action to prevent recurrence of the defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

Return to Step 1 and proceed as indicated when inspection is resumed.

4.3.3 Acceptance sampling. The tests and examinations detailed in 4.5 shall be conducted on each sterilizing switch to be delivered; therefore, there shall be no sampling for acceptance. Defective units shall be rejected.

4.4 Preproduction and periodic production inspection (M101). The preproduction and periodic production samples, after satisfactorily passing the acceptance inspections detailed in 4.5, shall be subjected to the following tests and examinations. Certified inspection data covering the results of preproduction and periodic production inspections shall be forwarded to the Naval Ordnance Systems Command. Failure to meet any requirement specified herein shall be considered cause for rejection of the lot represented and units tested.

4.4.1 Vibration tests

4.4.1.1 Vibration; transportation, storage and handling. The sterilizing switch, inside of its package, with the package mounted rigidly on the vibration table to simulate as realistically as possible the service conditions, shall be subjected to vibration testing for the time periods and at the temperatures specified in MIL-T-18404 for a torpedo nonoperating, ready nonoperating, or ready.

4.4.1.2 Vibration; ready nonoperating, or ready condition. The sterilizing switch, mounted rigidly on the vibration table to simulate as realistically as possible the service installation, shall be subjected to vibration testing for the time periods and at the temperatures specified in MIL-T-18404 for a torpedo nonoperating, ready nonoperating, or ready.

4.4.1.3 Vibration, operating condition. The sterilizing switch, mounted rigidly on the vibration table to simulate as realistically as possible the service installation, shall be subjected to vibration testing for the time periods specified in MIL-T-18404 for a torpedo operating.

4.4.2 Shock tests

4.4.2.1 Shock; transportation, storage, and handling. The sterilizing switch, inside of its package, with the package mounted rigidly on the shock testing device to simulate as realistically as possible the service conditions, shall be subjected to transportation shock as specified in MIL-T-18404.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

4.4.2.2 Shock, operating condition. The sterilizing switch, mounted rigidly on the shock testing device to simulate as realistically as possible the service installation, shall be subjected to the water-entry shock for an air launched torpedo with external attachments, as specified in MIL-T-18404 for a torpedo nonoperating, ready nonoperating, ready, or operating.

4.4.3 Acceleration test. The sterilizing switch, mounted on the testing device to simulate as realistically as possible the service installation, shall be subjected to acceleration testing as specified in MIL-T-18404 for a torpedo ready nonoperating, ready, or operating.

4.4.4 Temperature and humidity tests

4.4.4.1 Transportation and storage temperature test. The sterilizing switch, when inside of its package, shall be subjected to temperature and humidity cycling as specified for a nonoperating torpedo in MIL-T-18404.

4.4.4.2 High and low temperature tests. The sterilizing switch, mounted in a simulated well or switch cavity so that only the portion above the 0-ring is exposed to the test condition, shall be subjected to low temperature testing as specified in MIL-T-18404 for a ready nonoperating, ready, or operating torpedo, air launched, and to high temperature testing as specified for a ready nonoperating, ready, or operating torpedo.

4.4.5 Pressure tests. At the discretion of the Government inspector these tests may be performed on individual sterilizing switches, or they may be performed when the switch is completely assembled in the exploder mechanism. If performed on individual sterilizing switches, only that portion above the 0-ring shall be exposed to the test conditions.

4.4.5.1 Altitude test. The sterilizing switch shall be subjected to reduced air pressure testing as specified for torpedoes subject to air transportation in MIL-T-18404.

4.4.5.2 Snorkeling test. The sterilizing switch shall be subjected to pressure testing as specified for torpedoes subject to snorkeling submarine transportation in MIL-T-18404.

4.4.5.3 External air pressure test. The sterilizing switch shall be subjected to external air pressure testing as specified in MIL-T-18404 for torpedoes that are submarine launched.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

4.4.6 Tropical environment test. The sterilizing switch shall be exposed to fungus as specified in MIL-T-18404. At the discretion of the Government inspector this test may be performed on individual sterilizing switches, or it may be performed when the switch is completely assembled in the exploder mechanism. If performed on individual sterilizing switches, only that portion above the O-ring shall be exposed to the test conditions.

4.4.7 Marine environment tests. At the discretion of the Government inspector these tests may be performed on individual sterilizing switches, or they may be performed when the switch is completely assembled in the exploder mechanism. If performed on individual sterilizing switches, only that portion above the O-ring shall be exposed to the test conditions.

4.4.7.1 Sea atmosphere test. The sterilizing switch shall be exposed to salt-laden atmosphere as specified in MIL-T-18404 for a torpedo ready nonoperating.

4.4.7.2 Immersion test. The sterilizing switch shall be immersed in natural sea water as specified in MIL-T-18404 for a torpedo ready nonoperating.

4.4.8 Operating life

4.4.8.1 Definition of one cycle. One cycle of operation for the sterilizing switch shall be defined as the 90 degree rotation of the driver from the normally open position to the closed and locked position.

4.4.8.2 Operating life test. Secure the sterilizing switch in a fixture, and by means of a screwdriver, pierce the aluminum foil seal and rotate the driver of the switch to the closed position. To reset the switch prior to each succeeding cycle, the movable contact must be depressed against its spring load by inserting a suitable tool through the holes in the plastic base, and the driver rotated to the switch open position. Subject the sterilizing switch to not less than 100 cycles as specified herein.

4.5 Acceptance inspection. Each sterilizing switch delivered under contract shall be subjected to the following tests and examinations. Failure to meet any requirement specified herein shall be considered cause for rejection.

4.5.1 Test conditions. Unless otherwise specified, the sterilizing switch shall be subjected to acceptance tests under the following conditions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

4.5.1.1 Temperature: Room ambient plus 65 degrees F to plus 95 degrees F (plus 18.33 degrees C to plus 35.0 degrees C.)

4.5.1.2 Altitude: Normal ground.

4.5.1.3 Vibration: None.

4.5.1.4 Humidity: Room ambient to 95 percent relative (maximum).

4.5.2 Test and inspection equipment and facilities. The manufacturer shall furnish and maintain all necessary test equipment and facilities and shall provide personnel for performing all acceptance tests. The test equipment shall be adequate in quantity and, where definite requirements are not specified, shall be of sufficient accuracy and quality to permit performance of the required acceptance tests.

4.5.3 Test equipment. The following items of test equipment are required to perform the acceptance tests set forth in this specification:

4.5.3.1 A means for exerting a force of 10 pounds.

4.5.3.2 A suitable torque-indicating instrument capable of measuring torques up to 5 inch-pounds.

4.5.3.3 An ohmmeter capable of measuring resistances in the order of 0.1 ohm.

4.5.3.4 A megohmmeter with an integral source of 500 volts dc and a midscale reading in the order of 10 megohms.

4.5.3.5 A rubber tipped tool or pointer capable of imparting a tractional force by manual manipulation.

4.5.4 Test procedure. The acceptance tests shall be performed in accordance with the following procedures:

4.5.4.1 Fixed contact test (M102). Before assembling the fixed contact in the housing, apply a force of 10 pounds (4.5.3.1) along the axis of the contact from either direction. The contact shall meet the requirements of 3.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

4.5.4.2 Contact assembly securement test(M103). After the contact assembly is staked within the housing during the assembly of the sterilizing switch, apply a 5 inch-pound torque (4.5.3.2) through the axially parallel bores in the plastic base. The contact assembly shall meet the requirements of 3.4.2.

4.5.4.3 Operating torque test(M104). This test is performed on the sterilizing switch before the foil seal is secured in place. In the switch open position apply a torque of up to 5 inch-ounces to the driver in either direction. The driver shall not rotate to the switch closed position. Then increase the applied torque. The driver shall rotate to the switch closed position with an applied torque greater than 5 inch-ounces. Then apply a torque that is 2 inch-ounces more than is required to rotate the switch to the closed position. The driver shall not rotate to the switch open position. For test purposes the switch may be operated from closed to open circuit position by inserting a suitable tool through the holes in the contact assembly to lift the moving contact piece sufficiently to be rotated 90 degrees by the driver.

4.5.4.4 Contact resistance test(M105). With the switch in the closed position, apply the test probes of the ohmmeter to the stationary contact and the housing. The switch shall meet the requirements of 3.4.4.

4.5.4.5 Dielectric strength test(M106). With the switch in the normally open position, apply the test probes of the megohmmeter to the stationary contact and the housing. The switch shall meet the requirements of 3.4.5.

4.5.4.6 Seal test(M107). Take a fully assembled sterilizing switch and secure it against movement within a suitable fixture. With the rubber tipped tool apply a tractional force to the surface of the aluminum foil in several directions, tending to shift the foil beneath the formed edge of the housing. If the foil seal is loose, wrinkled, or improperly secured, the switch shall be regarded as defective.

4.5.4.7 Visual and dimensional examination. Each sterilizing switch shall be examined to determine conformance with the requirements for workmanship and dimensions.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Unless otherwise specified, the sterilizing switch shall be packaged and packed as an integral component of the exploder mechanism in the containers specified for the exploder mechanism as set forth in the applicable NAVORDSYSCOM drawings.

5.1.2 Level B. Not applicable.

5.1.3 Level C. Not applicable.

5.1.4 Spare or replacement parts. When procured as spare or replacement parts, sterilizing switches shall be packaged and packed as specified by the procuring activity.

5.2 Labeling and marking. Unless otherwise specified, labeling and marking of all shipping containers shall be in accordance with MIL-STD-129. Each container shall be marked with the serial number of the unit it contains.

6. NOTES

6.1 Intended use. Sterilizing Switch MK 1 Mod 0 is intended for use in the Exploder Mechanism MK 19 series.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification

(b) Any exceptions to this specification, applicable drawings, or other documents.

(c) Applicable preservation, packaging and packing if sterilizing switches are procured as spare or replacement parts. See 5.1.4

(d) Assigned activity for preproduction and periodic production tests.

(e) Data required.

(f) That certified inspection data covering the results or preproduction and periodic production inspections shall be forwarded to the Naval Ordnance Systems Command when testing is accomplished at other than a Government activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

MIL-S-19816A(OS) SWITCH, STERILIZING, MARK 1 MOD 0 (FOR EXPLODER MECHANISM MK 19 SERIES)

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD, FORM 1 APR 63 1426

0-88178

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.