MIL-S-19816A(OS)
AMENDMENT 2
9 March 1973

Superseding
AMENDMENT 1
6 November 1967

MILITARY SPECIFICATION

SWITCH, STERILIZING, MARK 1 MODS 0 AND 1

(For Exploder Mechanism Mark 19 Series)

This amendment forms a part of Military Specification MIL-S-19816A(OS) of 15 June 1967 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

Page 1: In specification title, delete "MARK 1 MOD 0" and substitute "MARK 1 MODS 0 AND 1".

Page 1, paragraph 1.1: Delete "Mark 1 Mod 0" and substitute "Mark 1 Mods 0 and 1".

Page 1, bottom: Delete "FSC 5930" and substitute "FSC 1355".

Page 2, under "DRAWINGS": Add "LD 620286 Sterilizing Switch Mark 1 Mod 1 and all parts and subassemblies listed thereon."

* Page 2, under "PUBLICATIONS". Add the following:

"OR-11 Development of Packaging, Handling, Storage and Transportation Systems for Weapons"

Page 2, paragraph 3.1. Delete and substitute:

"3.1 Description. The sterilizing switch shall consist of a stainless steel housing that contains a driver, springloaded contact, and stationary contact. The driver of the Mod 0 switch shall be covered by an aluminum foil seal, while the driver of the Mod 1 switch shall be covered by a plastic sheet seal. Both types of seals shall be easily pierced by a screwdriver to operate the switch. The construction of the switch shall be such that it may be operated from an initial open circuit position to a locked and closed circuit position. For test purposes, the switch may be operated from closed to open circuit position through the use of a suitable tool. See 4.4.8.2."

Page 3, paragraphs 3.2.3, 3.2.4, 3.2.5, and 3.2.6: Delete "in LD 275922" and substitute "in LD 275922 or LD 620286".

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

* Page 3, paragraphs 3.2.7 and 3.2.8: Delete in their entirety.

* Page 4, paragraph 3.2.9. Delete and substitute:
"3.2.9 Conflicting requirements. In the event of conflict between the documents referenced herein and the contents of this specification, the contents of this specification shall apply."

Page 5, paragraph 3.4.6: Delete paragraph title and substitute: "Seal (applicable to Mod 0 Switch only)."

* Page 5, paragraph 3.5.1.1. Delete and substitute:
"3.5.1.1 Vibration; transportation, storage, and handling. The sterilizing switch, packaged and packed as specified in Section 5, shall be tested in accordance with 4.4.1.1. Thereafter, the switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification."

* Page 6, paragraph 3.5.2.1. Delete and substitute:
"3.5.2.1 Shock; transportation, storage, and handling. The sterilizing switch, packaged and packed as specified in Section 5, shall be tested in accordance with 4.4.2.1. Thereafter, the switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification."

* Page 8, paragraph 4.1. Delete and substitute:
"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

* Page 10, paragraph 4.4.1.1. Delete and substitute:
"4.4.1.1 Vibration; transportation, storage, and handling. The sterilizing switch, packaged and packed as specified in Section 5, shall be subjected to the appropriate vibration testing specified in OR-11."

* Page 10, paragraph 4.4.2.1. Delete and substitute:
"4.4.2.1 Shock; transportation, storage, and handling. The sterilizing switch, packaged and packed as specified in Section 5, shall be subjected to the appropriate shock testing specified in OR-11."

Page 12, paragraph 4.4.8.2, lines 2 and 3: Delete "pierce the aluminum foil seal and rotate the driver" and substitute "pierce the aluminum foil seal on the Mod 0 or the plastic sheet seal on the Mod 1 and rotate the driver."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.

Page 14, paragraph 4.5.4.3, line 2: Delete "before the foil seal is secured" and substitute "before the foil or plastic seal, whichever is used, is secured".

Page 14, paragraph 4.5.4.6: Delete paragraph title and substitute "Seal test (M107) (applicable to Mod 0 Switch only)"

Page 15, paragraph 6.1: Delete "Sterilizing Switch Mk 1 Mod 0 is" and substitute "Sterilizing Switches Mk 1 Mods 0 and 1 are".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian
Navy - OS

Preparing Activity
Navy - OS
Project No. 1355-N315

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.