MILITARY SPECIFICATION

SWITCH, HYDROSTATIC, MARK 24, MODS 0, 1, 2, AND 3

(For Exploder Mechanism Mark 19 Series)

This amendment forms a part of Military Specification MIL-S-19820B(OS) of 8 November 1967 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

Page 2, paragraph 2.1, under "PUBLICATIONS". Add the following:

"OR-11	Development of Packaging, Handling, Storage and Transportation Systems for Weapons"

Page 4, paragraph 3.2.6 and 3.2.7: Delete in their entirety.

Page 4, paragraph 3.2.9. Delete and substitute:
"3.2.9 Conflicting requirements. In the event of conflict between the documents referenced herein and the contents of this specification, the contents of this specification shall apply."

Pages 8 and 9, paragraph 4.1. Delete and substitute:
"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 10, paragraph 4.4.1.1. Delete and substitute:
"4.4.1.1 Vibration; transportation, storage, and handling. The hydrostatic switch, packaged and packed as specified in Section 5, shall be subjected to the appropriate vibration testing specified in OR-11.

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 202640-19T06:43Z
Check the source to verify that this is the current version before use.

Thereafter, the switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification."

Page 12, paragraph 4.4.2.1. Delete and substitute:
"4.4.2.1 Shock; transportation, storage, and handling. The hydrostatic switch, packaged and packed as specified in Section 5, shall be subjected to the appropriate shock testing specified in OR-11. Thereafter, the switch shall show no damage and shall meet all the performance requirements and product characteristics of this specification."

Custodian:
Navy - OS

Preparing Activity
Navy - OS
Project No. 1355-N316

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T06:43Z
Check the source to verify that this is the current version before use.