
MILITARY SPECIFICATION SHEET

BIT, SCREWDRIVER, TORQ-SET, RIBBED, EXTERNAL HEX SHANK, MANUALLY DRIVEN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the bits described herein shall consist of this specification and the latest issue of MIL-B-9946.



NOTES:
1. All dimensions are in inches.
2. Bit and retaining groove shall be in accordance with TABLE I.

FIGURE 1. BIT, SCREWDRIVER, TORQ-SET, RIBBED, EXTERNAL HEX SHANK, MANUALLY DRIVEN

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:14Z
Check the source to verify that this is the current version before use.

TABLE I. DASH NUMBERS AND DIMENSIONS

DASH NUMBER	DRIVER SIZE	RECESS SIZE	A HEX +.000 -.004	Ø D SHANK	N ±.120 BIT LENGTH	ULTIMATE TORQUE MIN LBf - IN	FATIGUE TORQUE LBf - IN
6	# 6	# 6	.250	.185 / .180	1.00	35	16
8	# 8	# 8	.250	.247 / .242	1.00	65	30
8A	# 8	# 8	.312	.309 / .304	1.25		
10	#10	#10	.250	.247 / .242	1.00	100	45
10A	#10	#10	.312	.309 / .304	1.25		
250A	1/4	1/4	.312	.437 / .429	1.25	250	115
312A	5/16	5/16	.312	.437 / .429	1.25	500	200

REQUIREMENTS:

1. Material: Alloy Tool Steel in accordance with American Society for Testing Material (ASTM) A681, Shock-Resisting Steel, Type S-2 (UNS T41902).

2. Hardness: Macrohardness, (Rockwell C Scale) 56-62HRC. Three macrohardness readings shall be taken at the locations shown in FIGURE 2. Each hardness value must be within the range specified.




FIGURE 2. MACROHARDNESS READING LOCATIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:14Z
Check the source to verify that this is the current version before use.

Superficial hardness, (Rockwell HR15N Scale) 87-90. Superficial hardness readings shall be taken on bid samples at two locations on sectionalized specimens along the blade.

3. Tip point: Tip point shall be in accordance with MS14191.

4. Driver bit gage: Measures the alignments of the opposed wing surfaces and the maximum and minimum material conditions of the driver by means of a "GO" and "NO GO" criteria. The driver tip profile notch on this gage measures, by eye, the dimensional accuracy of the driver tip profile. The driver bit gage shall be in accordance with FIGURE 3 and TABLE II.

5. Test block: As shown in FIGURE 4 is used to conduct torque tests on the tool bit. This test block shall have the recess penetration values, as specified in TABLE III, in order to properly conduct the required torque tests as described herein and in MIL-B-9946.

6. Identification marking: Driver bits shall be marked by etching, stamping or engraving onto each bit the following minimum information:

   a. Military specification part number.

   b. Manufacturer's symbol or code.

   c. Country of manufacture.

7. Part number: The part number consists of the letter"M", the basic number of this specification sheet, followed by a dash number taken from TABLE I.

   Example: M9946/16-8A

   - Dash number
   - Specification sheet number

   M9946/16-8A indicates - Bit, Screwdriver, Torq-Set, Ribbed, External Hex Shank, Manually Driven; Driver Size #8; Recess Size #8; Hex .312; Length 1.25.

8. Torq-Set® is a registered trademark of Phillips Screw Company. Patent 4,187,892 expires 12 February 1997. The Government does not have a royalty-free license.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:14Z
Check the source to verify that this is the current version before use.




FIGURE 3. DRIVER BIT GAGE

TABLE II. DIMENSIONS FOR OFFSET CRUCIFORM DRIVER BIT GAGE

RECESS SIZE NOMINAL	S MIN WIDTH	T ±.005 THICK	GO GAGE DIMENSIONS						NO-GO GAGE DIMENSIONS					
			W ±.005	G ±.005	F +.0002 -.0000	R +.000 -.001	X +.000 -.001	θ +1° -0°	W ±.005	G ±.005	F +.0000 -.0002	R +.000 -.001	X +.000 -.001	θ +1° -0°
# 6	1.00	.187	.188	.083	.0245	.018	.026	47	SAME AS GO DIMENSIONS	SAME AS GO DIMENSIONS	.0230	SAME AS GO DIMENSIONS	SAME AS GO DIMENSIONS	SAME AS GO DIMENSIONS
# 8	1.00	.187	.223	.097	.0295	.018	.026	47			.0280			
#10	1.00	.187	.258	.112	.0345	.025	.036	47			.0330			
1/4	1.00	.187	.340	.148	.0465	.025	.036	48			.0435			
5/16	1.00	.187	.377	.186	.0595	.031	.044	48			.0565			

NOTES:
1. All dimensions are in inches.
2. Tolerance: ±.015 unless otherwise noted.
3. Material: CRES in accordance with ASTM A276, Type 440C (UNS S44004).
4. Hardness: 58-62HRC.
5. Surface texture: 35 microinches max.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:14Z
Check the source to verify that this is the current version before use.




FIGURE 4. TEST BLOCK

TABLE III. DIMENSIONS FOR TEST BLOCK WITH RESTRICTED GAGE PENETRATION FOR TESTING OFFSET CRUCIFORM BITS

RECESS SIZE NOMINAL	DIMENSIONS									
	N		Ø G		R RADIUS		Ø Y TOL	Ø W WING	J RECESS DEPTH	GAGE PEN
	MAX	MIN	MAX	MIN	MAX	MIN				
# 6	.029	.026	.082	.078	.030	.016	.012	.193 .183	.072 .062	.0555 .0535
# 8	.034	.031	.096	.092				.228 .218	.085 .075	.0660 .0640
#10	.039	.036	.111	.107	.040	.023		.263 .253	.098 .088	.0760 .0740
1/4	.051	.048	.147	.143			.016	.345 .335	.128 .118	.0990 .0970
5/16	.064	.061	.184	.180	.052	.031		.382 .372	.134 .124	.0985 .0965

NOTES:
1. All dimensions are in inches.
2. Material: Alloy steel in accordance with AMS 6485, (UNS T20811) or AMS 6487, (UNS T20811).
3. Heat treatment: 270,000 PSI minimum tensile strength 52-56HRC.
4. Finish: None.
5. Recesses to be gaged per MS14191 except gage penetration is limited to this drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:14Z
Check the source to verify that this is the current version before use.

Custodians:
Army - GL
Navy - AS
Air Force - 99

Review Activities:
Army - AV
Air Force - 80
DLA - IS

User Activities:

Civil Agencies Coordinating Activities:
GSA - FSS

Preparing Activity:
Air Force - 84

Agent:
DLA - IS

(Project 5120-B065)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:14Z
Check the source to verify that this is the current version before use.