MILITARY SPECIFICATION

BATTERY, NICKEL - CADMIUM, VENTED: 10541198

This amendment forms a part of Military Specification MIL-B-60298A(MU), dated 18 June 1970.

* Page 3, Paragraph 3.5.1; Delete and substitute the following:

Full capacity charge.- From an initial terminal voltage of 7.0 ± 0.2 volts obtained while under a discharge load specified in 3.5.2.1 and 3.5.2.2, each section of the battery shall be capable of attaining the voltage specified below when recharged at a constant current of 500 ma to 120% of the 1.5 ampere hour capacity of section 10541201 and 10558189 and the 2.0 ampere hour capacity of section 10541200.

11.9 ± 0.7V	at	70°F
11.2 ± 0.7V	at	155°F
12.3 ± 0.7V	at	-25°F

* Paragraph 4.6.6" Change first sentence: Discharge the 3 sections of the battery at the rates specified in 3.5.2.1 and 3.5.2.2 for a period of time sufficient to lower the terminal voltage of each section as specified in 3.5.1.

Paragraph 4.6.9: Change "4.4.6" to "4.6.6."

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A331

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.