MILITARY SPECIFICATION

PRIMER, BATTERY, ELECTRIC PARTS, FOR AND LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-P-63316(AR), dated 24 July 1979.

PAGE 14

4.4.2.6, Major 101: "Certificaiton" corrected to "Certification".

PAGE 15

4.4.2.7, Major 101: "Diamter" corrected to "Diameter" - "Gage" to "Visual".

Major 104: "Separted" corrected to "Separated".

PAGE 16

4.4.2.8, Major 113: Correct "place" to "plate".

PAGE 17

4.4.2.8, Major 118: Add 3.5.2 to requirement paragraph.

PAGE 19

4.4.5.1: Delete Dwg 9275629.

4.4.5.1.a: Change Dwg "9275663" to "9275631". Change ".003 to 0.55 ± .001" to ".003 to 0.055 ± .001".

4.4.5.1.b: Delete "copper-zinc lead alloy rod . . . . on the outside diameter". Add "Brass alloy 360, having a hardness equivalent to Rockwell A 40-55 measured on the outside diameter while supporting the inside diameter."

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.

4.4.5.1: Add paragraph d and e:

"d. The material for the witness plate, Dwg 9275633 shall be Grade C lead.

e. The iridite finish of the base, Dwg 9275632 is optional."

PAGE 20

4.5.4.1: Add sentence: "No-fire may be performed on a group of units connected in series before assembly to test equipment for output test. If one or more primers function, the remaining primers connected in series shall be retested."

PAGE 22

4.5.7: Delete "The measurement shall be made with a meter capable of measurement to the nearest 0.01 ohm.

PAGE 23

6.1: Change "XM74" and "XM75 AT/AV" to "M74" and "M75 AT".

Add: XM77 AP, XM78 AT/AV.

6.5: After the words "period of time." add "or at the request of the Contracting Officer."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No.: 1345-A-136

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:38Z
Check the source to verify that this is the current version before use.