MIL-W-63389 (AR)
AMENDMENT 2
28 May 1981
SUPERSEDING
AMENDMENT 1
23 JULY 1980

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M207E1
LINER FOR

This Amendment forms a part of Military Specification MIL-W-63389 (AR) dated 7 January 1980.

Pages 1, 2, 3, 4, 5, 6, & 7 change "Liner" to "Liner, Improved TOW."

PAGE 2

* Add 3.5 as follows:

"3.5 Data Requirements: The contractor shall generate data in accordance with requirements of data item description cited in 6.4."

PAGE 6

4.4.2.1 Majors 101, 104, 105, 110 and 111 change "0.40% to "0.25% under "AQL or 100% column."

Majors 107, 108, 109, 110 and 111 delete and substitute:

"107. Length from datum B to inside spherical radius.
108. Length from datum B to basic dimension at apex end
109. Length from large to small basic dimensions at apex end
110. Wall thickness at large basic dimension at apex end
111. Wall thickness at small basic dimension at apex end."

Add majors 114 and 115 as follows:

"114. Runout between two basic dimensions - 0.25, 3.2, Gage on outside surfaces at apex end (See Note 8 on dwg)
115. Wall thickness at apex 0.40, 3.2, Gage."

* 4.4.2.1 Add major defects, 116, 117, 118 and 119 as follows:

"116	Inside diameter	0.40%	3.2	Gage
117	Length of liner step	0.40%	3.2	Gage

Source: https://assist.dla.mil -- Downloaded: 2020-10-23T20:46Z
Check the source to verify that this is the current version before use.

118	Wall thickness at large datum, 42° section	0.40%	3.2	Gage
119	Wall thickness at small datum, 42° section	0.40%	3.2	Gage"

Add minor defects, 203, 204 and 205 as follows:

"203	Presence of four slots on O.D.	0.65%	3.2	Visual
204	Inside spherical radius, apex (see Note 1)		3.2	Gage
205	Outside spherical radius, apex	0.65%	3.2	Gage"

NOTE: 1. All new and resharpened tooling shall be certified prior to use. A cast of the inside spherical radius of the liner shall be made from "dental plaster" or equivalent, which shall be inspected by an optical comparator of 10X magnification or greater. This inspection shall be performed at the beginning of the shift, half way through the shift and whenever tooling is changed.

PAGE 7

* Add 6.4 and 6.5 as follows:

"6.4 Data Requirements. Deliverable data required by the specification is cited in the following paragraph:

Paragraph	Data Requirement	Applicable DID
6.5	Ammunition Data	DI-L-1410"

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing Activity
Army-AR

Project Number: 1336-A398

Source: https://assist.dla.mil Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.