NOT MEASUREMENT SENSITIVE


MIL-B-3628/56D
30 July 1993
SUPERSEDING
MIL-B-3628/56C
9 July 1990

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, OFFICER IN CHARGE (AFLOAT), ENLISTED PERSONNEL, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-3628.



DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Number 14.

DIMENSIONS:

HEIGHT (Overall):
-1: 1-5/8 inches (4.13 cm) (REF)
-2: 13/16 inch (2.06 cm) (REF)

WIDTH (Overall):
-1: 1-7/16 inches (3.65 cm) (REF)
-2: 23/32 inch (1.83 cm) (REF)

THICKNESS (At Thickest Point of Shield):
-1: 0.100 inch ± 0.005 inch (0.254 cm ± 0.012 cm)
-2: 0.100 inch ± 0.005 inch (0.254 cm ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:11Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. A mock forcer may be used to bring up the design of the shield on the regular size badge only.

4. The attaching device shall be prong and clutch type. The prongs shall be located as follows:

   Dash No. 1 - Attaching device shall be three prongs and clutches. Two of the prongs shall be located on the intersections of the center of the rope at the horizontal center line above the base of the badge. The third prong shall be located at the top of the badge centered on the rope at the anchor eye.

   Dash No. 2 - Attaching device shall be two prongs and clutches. The prongs shall be located on the intersections of the center of the rope at the horizontal center line 3/8 inch ± 1/64 inch (0.95 cm ± 0.04 cm) above the base of the badge.

Custodian:
Army - IH
Coast Guard - CG

Preparing activities:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0693)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:11Z
Check the source to verify that this is the current version before use.