MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION; DIVER, NATIONAL OCEANIC & ATMOSPHERIC ADMINISTRATION

This document is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.



MATERIAL: 1/20 - 10 KARAT GOLD FILLED (FRONT ONLY) OVER A COMMERCIAL COPPER BASE ONLY.
DIMENSIONS (INCHES):
DIAMETER: 3/4 (REF)
THICKNESS (AT THICKEST POINT): .105 ± .010
FINISH: GOLD PLATED, SATIN FINISH WITH THE DOLPHINS AND PYRAMID HIGHLIGHTS BURNISHED

NOTES:

1. THE ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. TWO PRONGS SHALL BE SOLDERED OR FUSED ON THE HORIZONTAL CENTERLINE EQUIDISTANT FROM EACH SIDE AND 5/8 ± 1/32 INCH ON CENTERS.

2. A MOCK FORCER MAY BE USED TO BRING UP THE CENTER OF THE BADGE.

CUSTODIANS:
ARMY IH
OTHER

REVIEW ACTIVITIES:
DP

PREPARING ACTIVITY:
THE INSTITUTE OF HERALDRY, UNITED STATES ARMY

Project No. 8455-A558

/FSC 8455/

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:13Z
Check the source to verify that this is the current version before use.