MIL-B-3628 / 59A
10 February 1988
SUPERSEDING
MIL-B-3628 / 59(IH)
19 May 1976

MILITARY SPECIFICATION SHEET

BADGE, QUALIFICATION, DIVER, NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-3628.



MATERIAL: 1/20 10 KARAT GOLD FILLED (FRONT ONLY) OVER A COMMERCIAL BRASS

DIMENSIONS (INCHES):
DIAMETER: 3/4 (REF)
THICKNESS (AT THICKEST POINT): .105 ± .010

FINISH: GOLD PLATED, SATIN FINISH WITH THE DOLPHINS AND PYRAMID HIGHLIGHTS BURNISHED

NOTES:

1. THE ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. TWO PRONGS SHALL BE SOLDERED OR FUSED ON THE HORIZONTAL CENTERLINE EQUIDISTANT FROM EACH SIDE AND 5/8 ± 1/32 INCH ON CENTERS.
2. A MOCK FORCER MAY BE USED TO BRING UP THE CENTER OF THE BADGE.

Custodians:
Army - IH

Review activities:
DLA - CT

User activities:
Other - NOAA

Preparing activity:
Army - IH

(project No. 8455- 0268)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:13Z
Check the source to verify that this is the current version before use.