NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/59C
15 November 1996
SUPERSEDING
MIL-B-3628/59B
30 July 1993

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, DIVER, NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass

FINISH: Gold Plated, Matte Finish with the Dolphins and Pyramid Highlights Polished and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
DIAMETER: 3/4 inch (1.91 cm) (REF)
THICKNESS (At Thickest Point): 0.105 inch ± .010 inch (0.267 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:13Z
Check the source to verify that this is the current version before use.

2. The attaching device shall be prong and clutch type. Two prongs shall be located equidistant from each side and 5/8 inch ± 1/32 inch (1.59 cm ± 0.08 cm) apart.

3. A mock forcer may be used to bring up the center of the badge.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0864)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:13Z
Check the source to verify that this is the current version before use.