NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/61D
15 November 1996
SUPERSEDING
MIL-B-3628/61C
30 July 1993

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, EXPERT PISTOL, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
HEIGHT (Excluding Lug): 1-5/16 inches (3.33 cm) (REF)
WIDTH (Overall): 1-5/16 inches (3.33 cm) (REF)
THICKNESS (At Edge): 0.100 inch ± .010 inch (0.254 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:14Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Lug shall be formed from 0.050 inch ± 0.002 inch (0.127 cm ± 0.005 cm) diameter brass wire and shall have an outside diameter of 13/64 inch ± 1/64 inch (0.52 cm ± 0.04 cm).

3. Lug shall be hard soldered to the top of the pendant.

4. The reverse of the pendant is flat.

5. The attaching device, ribbon length and ribbon drape shall be as specified in MIL-DTL-3943.

6. The ribbon for the ribbon drape shall conform to MIL-DTL-11589/29.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Coast Guard - CG

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0864)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:14Z
Check the source to verify that this is the current version before use.