NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/62D
15 November 1996
SUPERSEDING
MIL-B-3628/62C
30 July 1993

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, COMMAND ASHORE, COAST GUARD

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass

DASH NO.
-1: Regular Size
-2: Miniature Size

FINISH:
WREATH AND EAGLE: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
SHIELD, ANCHOR AND ROPE: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:14Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (Overall):		
	-1:	1-3/8 inches (3.49 cm) (REF)
	-2:	11/16 inch (1.75 cm) (REF)
WIDTH (Overall):		
	-1:	1-9/16 inches (3.97 cm) (REF)
	-2:	13/16 inch (2.06 cm) (REF)
THICKNESS (Thickest Point at Shield):		
	-1:	0.125 inch ± 0.005 inch (0.317 cm ± 0.012 cm)
	-2:	0.085 inch ± 0.005 inch (0.215 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated.

3. The attaching device shall be prong and clutch type. The prongs shall be located as follows:

Dash No. -1: One prong shall be located on the vertical center line 1/8 inch ± 1/16 inch (0.32 cm ± 0.16 cm) from the bottom of the badge. Two prongs shall be located on a horizontal line 1-3/16 inches ± 1/16 inch (3.02 cm ± 0.16 cm) from the bottom of the badge, equidistant from each side and 1-3/16 inches ± 1/16 inch (3.02 cm ± 0.16 cm) apart.

Dash No. -2: Two prongs shall be located on a horizontal line 7/16 inch ± 1/6 inch (1.11 cm ± 0.16 cm) from the bottom of the badge, equidistant from each side and 11/16 inch ± 1/16 inch (1.75 cm ± 0.16 cm) apart.

4. Shield, anchor and rope may be rhodium plated, mirror-like polished and shall match TIOH Metal Finish Chip Number 16 at the option of the manufacturer.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Coast Guard - CG

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0864)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:14Z
Check the source to verify that this is the current version before use.