QUALIFICATIONS VALIDATED
SEMIANNUALLY

QPL-122-17
26 June 1997
SUPERSEDING
QPL-122-16
17 January 1997

QUALIFIED PRODUCTS LIST

OF

PRODUCTS QUALIFIED UNDER MILITARY SPECIFICATION

MIL-R-122

RESISTOR, FIXED, PRECISION, ESTABLISHED RELIABILITY

GENERAL SPECIFICATION FOR

This list has been prepared for use by or for the Government in the procurement of products covered by Specifications MIL-R-122. Listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice. Revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

THE ACTIVITY RESPONSIBLE FOR THIS QPL IS THE DEFENSE SUPPLY CENTER COLUMBUS (DSCC-VQ), COLUMBUS, OH 43216-5000.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFICATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
M122/1 Chars. A, B and C, reactance H, C, D, J, K and E, res. values 25.5 ohms thru 99.9 ohms, res. tols. and failure rates I, J, K, M, N, O, Q, R, S, U, V and W.	S22-1	122-327-84 122-167-88 22-57-90	/1	Vishay Resistive Systems Group 63 Lincoln Highway Malvern, PA 19355 Plant: Same Address CAGE CODE: 18612
M122/1 Chars. A, B and C, reactance H, C, D, J, K and E, res. values 100 ohms thru 50,000 ohms, res. tols. and failure rates A, B, C, E, F, G, I, J, K, M, N, O, Q, R, S, U, V and W.	S22-1	122-327-84 122-167-88 22-57-90	/1	Vishay Resistive Systems Group
M122/3 Chars. A, B and C, reactance H, C, D, J, K and E, res. values 25.5 ohms thru 99.9 ohms, res. tols. and failure rates I, J, M, N, Q, R, U, and V.	S22-3	122-327-84 122-57-90	/3	Vishay Resistive Systems Group
M122/3 Chars. A, B and C, reactance H, C, D, J, K and E, res. values 100 ohms thru 50,000 ohms, res. tols. and failure rates A, B, E, F, I, J, M, N, Q, R, U, and V.	S22-3	122-327-84 122-57-90	/3	Vishay Resistive Systems Group
M122/10 Chars. A, B and C, reactance H, C, D, J, K and E, res. values 25.5 ohms thru 99.9 ohms, res. tols. and failure rates I, J, M, N, Q, R, U, and V.	S22-10	122-327-84 122-57-90	/10	Vishay Resistive Systems Group
M122/10 Chars. A, B and C, reactance H, C, D, J, K and E, res. values 100 ohms thru 50,000 ohms, res. tols. and failure rates A, B, E, F, I, J, M, N, Q, R, U, and V.	S22-10	122-327-84 122-57-90	/10	Vishay Resistive Systems Group

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T13:03Z
Check the source to verify that this is the current version before use.