INCH-POUND

MIL-DTL-25666F (USAF)
AMENDMENT 1
24 July 2000

DETAIL SPECIFICATION

CONVERTER, LIQUID OXYGEN, CAPACITANCE TYPE GAUGING,

GENERAL SPECIFICATION FOR

This document remains inactive for new design.

This amendment forms a part of MIL-DTL-25666F (USAF), dated 15 September 1995, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 14

4.6.12.2: Delete and substitute:

"4.6.12.2 High temperature. The converter shall be installed in an environmental temperature chamber and connected into a simulated aircraft oxygen system. The converter shall be filled with liquid oxygen or liquid nitrogen and conditioned at plus 160º ±5º F for at least 3 hours. The delivery rate shall be 80 to 110% of the maximum flow required by the applicable associated specification until the converter is within 5% of empty. If the converter does not deliver the flow of oxygen specified above, after allowing 10 minutes for stabilization, the converter shall be rejected. Momentary pressure drops below the specified normal operating pressure during the first 10 minutes of flow will be acceptable."

Custodian:
Air Force – 99

Reviewer:
Air Force - 11

Preparing activity:
Air Force – 71

Agent:
Air Force – 99

Project 1660-F0813

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T06:53Z
Check the source to verify that this is the current version before use.