INCH-POUND

A-A-52149
February 28, 1994

COMMERCIAL ITEM DESCRIPTION

JUGS, VACUUM OR INSULATED, THERMAL EFFICIENT

The General Services Administration has authorized the use of this Commercial Item Description in preference to Military Specification MIL-J-23049 and Federal Specification RR-J-800 (see 5.7).

1. ABSTRACT

1.1 Abstract. This commercial item description covers thermal efficient vacuum or insulated jugs of the following sizes (capacities) and finishes:

Size 1	-	1 gallon
Size 2	-	2 gallons
Size 3	-	3 gallons
Size 5	-	5 gallons
Size 10	-	10 gallons
Finish 1	-	Satin or Butler (manufacturer's option)
Finish 2	-	Green 383

1.2 CID based part identification number (PIN). A document based PIN to identify size and finish of items is included in section 5. This identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor except as information on "Government unique" data nameplates (see 5.4).

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The jugs shall consist of an inner and outer shell joined in such a manner as to produce a space for a vacuum or material

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-WEE, Natick, MA 01760-5018 by using the Standardization Documents Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

insulated chamber in order to produce a thermal efficient jug. The jugs shall be equipped with covers, cover gaskets, faucets, faucet guards, and handles (or bails). Inner and outer shells, covers, faucet guards, and handles shall be fabricated of 300 series stainless steel. The bottom of inner shells of size 2 through size 10 jugs shall allow for drainage of the contents by an attached faucet. The jugs shall have a satin or butler finish (finish 1) or a MIL-T-704K Green 383 finish (finish 2), as specified (see 5.2 and 5.6). Each jug shall be permanently and legibly marked with the following: "DO NOT USE FOR MILK OR ANY MILK PRODUCTS".

2.1.1 Covers. When specified (see 5.2), a venting device shall be a part of the cap assembly. The cap shall be equipped with a device to prevent the loss of the cap. The covers shall be secured to the jug by means of a cam-locking device. The covers shall be sealed with a removable rubber or plastic gasket. At the option of the manufacturer, size 1 jugs may be equipped with a screw-type cover.

2.1.2 Faucets. Faucets may be either key or diaphragm type and shall be protected from damage by guards. Faucets without guards shall be so constructed as to prevent accidental opening.

2.1.3 Handles and bails. Size 1 and size 2 jugs shall be supplied with bails and bail mounts. Size 3, 5, and 10 jugs shall be supplied with two rigid drop handles with mounts, located diametrically opposite each other on the upper side walls of the jugs. At the manufacturer's option, size 1 and size 2 jugs may be supplied with rigid handles.

2.2 Size of jug for Air Force procurements. When specified for Air Force procurements (see 5.2), size 2 jugs shall have an overall height of 19 $\pm$ 1/4 inches, and an overall diameter of 8-3/8 $\pm$ 1/8 inches, exclusive of faucet, faucet guards, handles, and cover.

2.3 Thermal efficiency. Jug contents shall not exceed the following temperature losses (^{o}F) when filled to capacity with water at a temperature of 204°F to 207°F for six hours at an ambient temperature of 73°F $\pm$ 3°F.

Temperature Loss (Maximum)

Size 1	-	60°F
Size 2	-	45°F
Size 3	-	40°F
Size 5	-	35°F
Size 10	-	30°F

2.4 Codes and standards. The jugs shall comply with the requirements of NSF International Standard No. 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

2.5 Data nameplate ("Government unique" requirement)(see 5.5). Jugs shall be furnished with a data nameplate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) methods of applying, (b) identification tags, (c) information not required, and (d) optional marking information shall not apply. The data nameplate shall be made of minimum 20 gauge corrosion-resisting metal and attached by rivets, screws, or welding in such a manner as to meet the applicable NSF International sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved, or applied by photosensitive means:

Contract Number
National Stock Number
Procurement Instrument Identification Number
Manufacturer's Name, Address, and Telephone Number
Supplier's Name, Address, and Telephone Number (list only if different from manufacturer)
Manufacturer's Model and Serial Number
Government Approved Manual Number (when specified, see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use so as to not adversely affect the life and utility of the jugs.

2.6 Workmanship. The jugs shall be complete, clean, and free of fabrication marks, scratches, dents, sharp edges, sharp corners, burrs, slivers, or visible evidence of rust. Welds shall be clean, continuous, sound, and free of flux, pits, buildups, undercuts, and shall be ground so as to blend with the adjacent surfaces. Spot welds shall be free from pits, burn throughs, and flashes.

3. QUALITY ASSURANCE

3.1 Contractor certification. The contractor shall certify, and maintain substantiating evidence, that the product offered meets the salient characteristics and requirements of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

3.3 Regulatory requirements. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580 to the maximum extent possible.

3.4 NSF International. Acceptable evidence of meeting the requirements of NSF International No. 2 shall be a listing in the current edition of the NSF International "Listing of Food Service Equipment" and display of the NSF International mark on the finished product, or a certified test report from a recognized independent laboratory acceptable to the Government indicating compliance with the applicable NSF International requirement(s).

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export, as specified (see 5.2).

4.2 Commercial packaging and packing. The jugs shall be packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. The removable cover gasket shall be packed within the interior of the jug and the cover secured in place on the jug. Each jug shall be unit packed in a fiberboard box conforming to style RSC, type CF, variety SW, class domestic, of PPP-B-636. The jugs shall be cushioned to afford protection against damage during shipment and storage. Box closure shall be in accordance with PPP-B-636.

4.3.2 Export packing. Jugs, of one size only, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V3c, V3s, or V4s, of PPP-B-636. Each shipping container shall be closed and waterproofed in accordance with PPP-B-636.

4.3.3 Palletization. When specified (see 5.2), shipping containers shall be palletized in accordance with MIL-STD-147.

4.4 Marking (commercial and export). Marking of unit packs, shipping containers, and palletized unit loads shall be in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5. NOTES

5.1 Intended use. The jugs are intended to be used to keep liquids hot or cold during military operations.

5.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this commercial item description.
b. Size and finish required (see 1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

c. When a venting device is required on the cap (see 2.1.1).
d. When size 2 jugs are for Air Force procurement (see 2.2).
e. The Government approved manual number is to be included on the data nameplate when manuals are purchased under the contract (see 2.4).
f. Type of packaging and packing required (see 4.1).
g. When palletization of shipping containers is required (see 4.3.3)

5.3 Sources for documents.

5.3.1 Sources for non-Government association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

American Society for Testing Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103-1187

NSF International Standard No. 2 - Food Service Equipment is available from:


NSF International
3475 Plymouth Road
P.O. Box 130140
Ann Arbor, MI 48113-0140

5.3.2 Source for Government documents. Copies of military and federal documents are available from:

Standardization Documents Order Desk
Building 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

5.4 Part identification number (PIN). The PIN's to be used for items required by this CID are created as follows:

A 52149 -2 -1 (Eample: A52149-2-1)



5.5 "Government unique" requirements. Whenever a "Government unique" requirement is included in the title of a paragraph under "Salient Characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

5.6 Green 383. The MIL-T-704K refers to Federal Standard 595 and Federal Color Number 34094.

5.7 Supersession data. The sizes and finishes of jugs covered by this commercial item description replace the items covered by MIL-J-23049 and RR-J-800 as indicated below:

CID A-A-52149	MIL-J-23049	RR-J-800
		Type I - SS inner shell Gr. A - SS outer shell Gr. B - CS outer shell
Size 1 - 1 gallon Size 2 - 2 gallons Size 3 - 3 gallons Size 4 - 5 gallons Size 10 - 10 gallons	Size 1 - 2 gallons Size 2 - 3 gallons Size 3 - 5 gallons Size 4 - 10 gallons	Size 1 - 1 gallon Size 2 - 2 gallons Size 3 - 3 gallons Size 5 - 5 gallons
Finish 1 - Satin or Butler (Mfg option) Finish 2 - Green 383	Finish (1) - Satin or Butler (Mfg option) Finish (2) - Marine Corps Green 23	
		Type IV - Plastic inner shell, material insul. (NO USER REQMTS.)

MILITARY INTERESTS:

Custodians

Army - GL
Navy - SA
Air Force - 99

Review Activities

Army - MD, QM
Air Force - 35, 84
DLA - GS

User Activities

Navy - MC, MS, YD

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project 7330-0659

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revisi letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)

3. DOCUMENT TITLE

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)
U.S. Army Natick RD&E Center	(1) Commercial: 508-651-5175 (2) AUTOVON/DSN: 256-5175
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WEE Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-01-26T09:07Z
Check the source to verify that this is the current version before use.