MILITARY SPECIFICATION

TUBE, EXTENSION, GYRO STABILIZED DRIFT METER

This amendment forms a part of MIL-T-7771B, dated 13 FEB 80, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete "2.1" and add:
"2.1 Government documents."

Add:
"2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and thereto, cited in the solicitation."

Under SPECIFICATIONS, Federal, delete "WW-T-700/3E" and add: "WW-T-700/3"; "PPP-B-601 Boxes, Wood, Cleated Plywood".

Under SPECIFICATIONS, Military, delete "MIL-D-7106" and add: "MIL-M-7106 Meter, Drift, Electrically Driven Gyro Stabilizer".

Delete address on lines 3 and 4 of beneficial comments and add: "Oklahoma City Air Logistics Center/MMEDOA, Tinker AFB OK 73145-5990".

PAGE 2

Under STANDARDS, Military, delete "MIL-STD-100" and add: "DOD-STD-100".

Add:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These are documents also may be available in or through libraries or other informational services.)"


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:52Z
Check the source to verify that this is the current version before use.

PAGE 3

Add:
"3.1.4.2 Recoverd materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item."

3.3 Line 4 delete "WW-T-700/3E" and add: "WW-T-700/3".

PAGE 4

3.4 Line 5 delete "MIL-STD-100" and add: "DOD-STD-100".

PAGE 6

4.1 Lines 10 thru 14 delete "The contractor shall furnish test reports, in duplicate, showing quantitative results for all tests required by this specification, and signed by an authorized representative of the contractor or laboratory, as applicable."

4.2.2 Line 3 delete "MIL-D-7106" and add: "MIL-M-7106".

PAGE 7

Delete Section 5 in its entirety and add:

"5 PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Tube shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Tube shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each tube shall be packaged in quantity unit packs of one each in accordance with Method 1C2 of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the tube when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each tube shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physicla damage during shipment form supply source to the first recieving activity.

5.1.3 Industrial. The industrial preservation of tube shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:52Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. Tube packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistant with the protection required.



5.2.2 Level B. Tube packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged tube shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

Delete "6.2".

Delete "6.3".

Custodian:
AIR FORCE - 99
NAVY - AS

Preparing Activity:
AIR FORCE - 71

Project Number:
6605 - 0355



Source: https://assist.dla.mil -- Downloaded: 202610-17T08:52Z
Check the source to verify that this is the currentversion before use.