

MILITARY SPECIFICATION SHEET

CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA (UNCABLED, SOCKET CONTACT, JAM NUT MOUNTED, HERMETIC SEAL, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connector described herein shall consist of this specification and the latest issue of MIL-C-39012.







MS39012/62 -3001
-4001


FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.





BODY "D"
MOUNTING SURFACE



RECOMMENDED
MOUNTING HOLE


INCHES	MM
.002	0.05
.003	0.08
.004	0.10
.018	0.46
.029	0.74
.045	1.14
.065	1.65
.088	2.24
.103	2.62
.125	3.18
.250	6.35
.265	6.73
.279	7.09
.281	7.14
.312	7.92
.315	8.00
.404	10.26
.460	11.68
.505	12.83
.718	18.24


MS39012/62-3002
MS39012/62-4002

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Dimension .505 (12.83 mm) is the largest overall diameter of the connector.
4. All undimensioned pictorial configurations are for reference purposes only.


FIGURE 1. General configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.





DETAIL-B-



DETAIL-A-

INCHES	MM
.002	0.05
.003	0.08
.005	0.13
.015	0.38
.030	0.76
.0355	0.902
.0370	0.940
.045	1.14
.049	1.24
.051	1.30
.074	1.88
.078	1.98
.115	2.92
.170	4.32
.1810	4.597
.208	5.28
.216	5.49
.218	5.54

NOTES:
1. Dimensions are in inches.
2. Slitting of inner contact optional.
3. Metric equivalents are given for general information only.

FIGURE 2. Mating dimensions for female termination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: (Not rated.)

Voltage rating: 335 V rms maximum at sea level. 85 V rms maximum at 70,000 feet.

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Force to engage and disengage:

Longitudinal force - Not applicable.
Torque - 2 inch-pounds maximum.

Coupling proof torque: Not applicable.

Inspection conditions: For each test of threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

Mating characteristics (see figures 2 and 3 for dimensions):

Contacts with spring members:

Center contact (female):

Oversize test pin - .0375 + .0001.

Test pin finish - 16MICROINCHES

Insertion depth - .030/.045.

Number of insertions - 3.

Insertion force test: Steel test pin diameter .0370 + .0001.

Insertion depth - .050/.075.

Test pin finish - 16MICROINCHES

Insertion force - 3 lbs maximum.

Withdrawal force test: Steel test pin diameter .0355 - .0001.

Insertion depth - .050/.075.

Withdrawal force - 1 ounce minimum.

Test pin finish - 16MICROINCHES




FIGURE 3. Test pin data.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.

Hermetic seal: Leakage shall not exceed 1×10^{-5} cc/sec of tracer gas at atmospheric pressure when mounted in mounting hole specified on figure 1.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: Method 3003, MIL-STD-1344. 5,000 megohms minimum.

Center contact retention: 6 lbs minimum axial force. 4 inch-ounces minimum radial torque.

Solderability: Method 208 of MIL-STD-202. 1/

Resistance to test prod damage: Not applicable.

Corrosion (salt spray): Method 1001, test condition B, MIL-STD-1344.

Voltage standing wave ratio (VSWR): Not applicable.

Swept frequency VSWR test setup: Not applicable.

Connector durability: Method 2016, MIL-STD-1344. 500 cycles minimum at 12 cycles/min. maximum. The connector shall meet mating characteristics and force to engage and disengage requirements.

Contact resistance: In milliohms maximum.

	Initial	After environment
Center contact:	7.0	8.0
Outer contact:	2.0	Not applicable

Dielectric withstanding voltage at sea level: Method 3001, MIL-STD-1344. 1,000 V rms.

Vibration high frequency: Method 2005, test condition IV, MIL-STD-1344.

Shock: Method 2004, test condition G, MIL-STD-1344.

Thermal shock: Method 1003, test condition A, MIL-STD-1344, except test high temperature to be +200°C.

Humidity: Method 1002 of MIL-STD-1344. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:

Voltage - 250 volts minimum.
Altitude - 70,000 feet.

RF high potential withstanding voltage:

Frequency - 670 V rms at 5 MHz.
Leakage current - Not applicable.

Cable retention force: Not applicable.

Coupling mechanism retention force: Not applicable.

RF leakage: Not applicable.

RF insulation loss: Not applicable.

1/ For quality conformance inspection, the test shall be performed in group B following VSWR; inspection level shall be S-1 of MIL-STD-105 and AQL 10 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.

TABLE I. Group qualification and retention testing.

Group	Submission and qualification of any one of the following connectors 1/ 2/	Qualifies the following connectors
I	M39012/62-†001 M39012/62-†002	M39012/62-†001 M39012/62-†002

1/ Qualification of connectors qualifies connectors of the same material only.

2/ For qualification retention, where more than one part is listed in a group in this column, data may be supplied on any of those parts in order to retain qualification for those parts in the corresponding right hand column. The part does not necessarily have to be the part initially qualified.

† Material.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - EC
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AM, AT, ME
Navy - AS, MC, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - CR

(Project 5935-3435-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.