INCH-POUND


MIL-PRF-39012/62C
w/AMENDMENT 1
30 December 2005
SUPERSEDING
MIL-PRF-39012/62C
14 May 2004

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA
(UNCABLED, SOCKET CONTACT, JAM NUT MOUNTED, HERMETIC SEAL, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall
consist of this specification sheet and MIL-PRF-39012.





REAR MOUNT (M39012/62-3001 AND M39012/62-4001)

Inches	mm	Inches	mm	Inches	mm
.002	0.05	.103	2.62	.315	8.00
.003	0.08	.125	3.18	.404	10.26
.004	0.10	.250	6.35	.410	10.41
.018	0.46	.265	6.73	.460	11.68
.029	0.74	.279	7.09	.505	12.83
.045	1.14	.281	7.14	.718	18.24
.065	1.65	.312	7.92		

FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.





FRONT MOUNT (M39012/62-3002 AND M39012/62-4002)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Dimension .505 inch (12.83 mm) is the largest overall diameter of the connector.
4. All undimensioned pictorial configurations are for reference purposes only.
5. Solder lug shall be gold plated in accordance with ASTM B488, type II, class I.27.
6. Series SMA, socket contact interface shall be in accordance with MIL-STD-348.

FIGURE 1. General configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: Not rated.

Voltage rating: 335 volts rms maximum at sea level, 85 volts rms maximum at 70,000 feet.

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and MIL-STD-348.

Force to engage and disengage:

Longitudinal force: Not applicable.

Torque: 2 inch-pounds, maximum.

Coupling proof torque: Not applicable.

Inspection conditions: For each test of threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

Mating characteristics: See MIL-STD-348 and figure 2 for dimensions.

Contacts with spring members:

Center contact (female):

Oversize test pin: .0375 + .0001/-.0000 inch.

Test pin finish: 16 microinches.

Insertion depth: .030/.045 inch.

Number of insertions: 3.

Insertion force test:

Steel test pin diameter: .0370 + .0001/-.0000 inch.

Insertion depth: .050/.075 inch.

Test pin finish: 16 microinches.

Insertion force: 2 pounds, maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.

Withdrawal force test:

Steel test pin diameter: .0355 + .0000/-.00001 inch.
Insertion depth: .050/.075 inch.

Test pin finish: 16 microinches.

Withdrawal force: 1 ounce, minimum.




FIGURE 2. Test pin data.

Hermetic seal: Leakage shall not exceed 1 x 10^{-5} cm^3/s of tracer gas at atmospheric pressure when mounted in mounting hole specified on figure 1.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: In accordance with test procedure EIA 364-021, 5,000 megohms minimum.

Center contact retention:

Axial force: 6.0 pounds minimum.

Radial torque: 2 inch-ounces minimum.

Solderability: Method 208 of MIL-STD-202 (for quality conformance inspection, the test shall be performed in group B following the insulation resistance test.)

Resistance to test probe damage: Not applicable.

Corrosion (salt spray): In accordance with test procedure EIA 364-026 condition B.

Voltage standing wave ratio (VSWR): Not applicable.

Connector durability: In accordance with test procedure EIA 364-009, 500 cycles minimum at 12 cycles per minute maximum. The connector shall meet mating characteristics and force to engage and disengage requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.

Contact resistance: In milliohms, maximum.

	Initial	After environment
Center contact:	7.0	8.0
Outer contact:	2.0	Not applicable

Dielectric withstanding voltage at sea level: In accordance with test procedure EIA 364-020 1,000 volts rms, minimum.

Vibration, high frequency: In accordance with test procedure EIA 364-028 test condition IV.

Shock: In accordance with test procedure EIA 364-027 condition G.

Thermal shock: In accordance with test procedure EIA 364-032 condition I, 5 cycles, except test high temperature shall be +200°C.

Humidity: In accordance with test procedure EIA 364-031 method IV. No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

Corona level:

Voltage: 250 volts minimum.

Altitude: 70,000 feet.

RF high potential withstanding voltage:

Voltage and frequency: 670 volts rms at 5 MHz.

Leakage current: Not applicable.

Cable retention force: Not applicable.

Coupling mechanism retention force: Not applicable.

RF leakage: Not applicable.

RF insertion loss: Not applicable.

Group qualification: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.

TABLE I. Group qualification and retention testing.

Group	PINs 1/ 2/
I	M39012/62-3001 M39012/62-3002
II	M39012/62-4001 M39012/62-4002

1/ Submission and qualification of any connector in a group qualifies any and all connectors of the entire group.

2/ For qualification retention, data may be supplied on any part in a group to retain qualification for that entire group.

Referenced documents. In addition to MIL-PRF-39012, this document references the following documents:

MIL-STD-202
MIL-STD-348
ASTM B488
EIA 364-009
EIA 364-020
EIA 364-021
EIA 364-026
EIA 364-027
EIA 364-028
EIA 364-031
EIA 364-032

Changes from the previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2005-095)

Review activities:
Army - AM, AT, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:02Z
Check the source to verify that this is the current version before use.