INCH-POUND
MIL-PRF-39012/70D
16 November 2011
SUPERSEDING
MIL-PRF-39012/70C
18 January 2007

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMB (CABLED, PIN CONTACT, JAMNUT MOUNTED, REAR MOUNTED, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39012.




FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.018	.46	.187	4.75
.023	.58	.190	4.83
.065	1.65	.192	4.88
.074	1.88	.197	5.00
.077	1.96	.312	7.92
.079	2.01	.320	8.13
.082	2.08	.400	10.16
.096	2.44	.440	11.18

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. For dimension A, see table I.
4. Dimension A defines the overall length of the connector when assembled to the cable.
5. Wrench flats are to accommodate standard wrench opening in accordance with FED-STD-H28, appendix 10.
6. Maximum overall diameter of the connector is .320 inch (8.13 mm).
7. All undimensioned pictorial configurations are for reference purposes only.
8. Series SMB, pin contact in accordance with MIL-STD-348.

FIGURE 1. General configuration – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross-reference, and dimensions.

Dash No. M39012/70-	# Applicable cable group from MIL-PRF-39012, appendix B M17/	Typical mating Connector 1/	Dimensions	Inches (millimeters) Maximum 2/
CATEGORY A – FIELD SERVICEABLE (NO SPECIAL TOOLS REQUIRED)				
0003 3/ 4/	Cable group I 93-RG178 * @ 169-00001 %	M39012/67-0003 M39012/69-0003	A	.88 (22.35)
0004 3/ 4/	Cable group II 113-RG316 * @ 172-00001 % 94-RG179 ^	M39012/67-0004 M39012/69-0004		
0103 3/	Cable group I 93-RG178 * @ 169-00001 %	M39012/67-0103 M39012/69-0103		
0104 3/	Cable group II 113-RG316 * @ 172-00001 % 94-RG179 ^	M39012/67-0104 M39012/69-0104		
4101 3/	Cable group I 93-RG178 * @ 169-00001 %	M39012/67-4101 M39012/69-4101		
4102 3/	Cable group II 113-RG316 * @ 172-00001 % 94-RG179 ^	M39012/67-4102 M39012/69-4102		
CATEGORY C – FIELD REPLACEABLE (MIL-C-22520/5 BASIC CRIMP TOOL) 5/				
0011 3/ 4/	Cable group I ~ 93-RG178 * @ 169-00001 %	M39012/67-0011 M39012/69-0011	A	1.20 (30.48)
0012 3/ 4/	Cable group IIa & 113-RG316 * @ 172-00001 % 94-RG179 ^	M39012/67-0012 M39012/69-0012		

See notes at end of table.


Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers, cross-reference, and dimensions – Continued.

Dash No. M39012/70-	# Applicable cable group from MIL-PRF-39012, appendix B M17/	Typical mating connector 1/	Dimensions	Inches 2/ (millimeters) Maximum
CATEGORY C – FIELD REPLACEABLE (MIL-C-22520/5 BASIC CRIMP TOOL) 5/				
0016 3/	Cable group I ~ 93-RG178 * @ 169-00001 %	M39012/67-0016 M39012/69-0016	A	1.20 (30.48)
0017 3/	Cable group IIa & 113-RG316 * @ 172-00001 % 94-RG179 ^	M39012/67-0017 M39012/69-0017		
4001 3/	Cable group I ~ 93-RG178 * @ 169-00001 %	M39012/67-4001 M39012/69-4001		
4002 3/	Cable group IIa & 113-RG316 * @ 172-00001 % 94-RG179 ^	M39012/67-4002 M39012/69-4002		

1/ Mating connector Part or Identifying Number (PIN) is for reference only. All mating connectors may not be listed.
2/ Dimensions are in inches. Metric equivalents are given for information only.
3/ These connectors have captivated center contacts.
4/ Connector bodies shall be gold plated in accordance with ASTM B488, type II, code C, class 1.27.
5/ Category C connectors are assembled by means of the applicable crimping tool in accordance with MIL-DTL-22520 to the specified cable stripped as specified on figure 2 herein.
The latest version of each cable shall be applicable.
* Cable to be used when performing tests requiring cable except as in notes @ and ^.
@ Cable to be used for the +200°C thermal shock tests.
^ These are not 50 ohm cables, therefore, when attached to the specified connectors, VSWR, RF leakage and insertion loss are not applicable.
~ M22520/5-33 closure B or M22520/5-03 closure B.
& M22520/5-35 closure B or M22520/503 closure A.
% Caution is directed to the applicable of this cable above 400 MHz. Attenuation is tested only at 400 MHz. SRL and power handling capabilities are not stipulated herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.



Inches	mm
.010	0.25
.020	0.51
.234	5.94
.516	13.11
.609	15.47

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 2. Cable stripping dimensions for category C connectors.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: 0 to 4 GHz.

Voltage rating: The voltage rating shall be as specified in table II.

TABLE II. Voltage rating.

Cables	Voltage max. (sea level) V rms	Voltage max. at 70,000 ft. (4.437 kPa) V rms
Cable group I	250	60
Cable group II, IIa,	335	85

Temperature rating: -65°C to +165°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and MIL-STD-348.

Force to engage and disengage:

Longitudinal force: Not applicable.

Torque: Not applicable.

Coupling proof torque: Not applicable.

Inspection conditions: Not applicable.

Mating characteristics: See MIL-STD-348.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: In accordance with MIL-STD-202, method 302, test condition B, 1,000 megohms minimum.

Center contact retention:

Axial force: 4 pounds (17.79 N), minimum axial force. Applicable to captivated center contacts only.

Radial torque: Not applicable.

Corrosion (salt spray): In accordance with MIL-STD-202, method 101, test condition B.

Voltage standing wave ratio (VSWR): From 500 MHz to 4 GHz, or approximately 80 percent of the upper cutoff frequency of the cable, whichever is lower.

Cable group	VSWR
I	1.30 + 0.04 (F) GHz
II, IIa,	1.25 + 0.04 (F) GHz

Swept frequency VSWR test setup:

Item 6: VSWR shall be less than 1.05 +.0025F (F in GHz).

Item 16: VSWR shall be less than 1.05 +.0025F (F in GHz).

Second step of VSWR checkout procedure – VSWR shall be less than 1.10 +.01F (F in GHz).

Group B inspection: VSWR shall be less than 1.08 +.017F (F in GHz).

Qualification and group C inspection: VSWR shall not exceed 1.15.

Connector durability: 500 cycles minimum at 12 cycles per minute maximum. The connector shall meet mating characteristics and force to engage and disengage requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

Initial: 14 pounds (62.27 N), maximum.

Final: 14 pounds (62.27 N), maximum engage and disengage: 2 pounds (8.90 N) minimum disengagement.

Contact resistance: In milliohms, maximum.

	Initial	After environment
Center contact:	6.0	8.0
Outer contact:	1.0	1.5
Braid to body:	1	Not applicable

Dielectric withstanding voltage at sea level: In accordance with MIL-STD-202, method 301.

Cable group	V rms (at sea level)
I	750
II, IIa	1,000

Vibration, high frequency: In accordance with MIL-STD-202, method 204, test condition B.

Shock: In accordance with MIL-STD-202, method 213, test condition B.

Thermal shock: In accordance with MIL-STD-202, method 107, test condition B, except test high temperature shall be +85°C. High temperature shall be +200°C for connectors using +200°C cables (see tables I and III).

Moisture resistance: Not applicable.

Corona level:

Altitude: 70,000 feet (4.437 kPa).

Cable group	Volts, min.
I	185
II, IIa	250

RF high potential withstanding voltage:

Voltage and frequency: Tested at a frequency from 5 to 7.5 MHz.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

Leakage current: Not applicable.

Cable group	Volts, rms min.
I	500
II, IIa	700

Cable retention force: The cable retention force shall be as specified in table III.

TABLE III. Cable retention force. 1/ 2/

Cable dielectric Outer diameter	Pounds, min. (N)	
	Non-crimp Single braid	Crimp Single braid
	Center contact	Center contact
	Captive	Captive
Inches, max. (mm)		
.036 (0.91)	13 (57.83)	13 (57.83)
.066 (1.68)	25 (111.20)	25 (111.20)

1/ Dimensions are in inches.
2/ Metric equivalents are given for information only.

Coupling mechanism retention force: Not applicable.

RF leakage: -55 dB minimum, tested at frequency between 2 and 3 GHz.

RF insertion loss: .30 dB maximum tested at 4 GHz.

PIN: M39012/70 (dash number in table I or IV as applicable).

Group qualification: See table V.

Cross-reference of PIN: See table VI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

TABLE IV. Category B – non-field replaceable (special tools may be required).

NOT FOR ARMY, NAVY, OR AIR FORCE USE. FOR OEM USE ONLY

Dash no. 1/ M39012/70	# Applicable cable group from MIL-PRF-39012, appendix B M17/	Typical mating connector 2/	Dimensions	Inches (millimeters) maximum 5/ 6/
B0008 3/ 4/	93-RG178 * @ 169-00001 %	M39012/67B0008 M39012/69B0008	A	1.20 (30.48)
B0009 3/ 4/	113-RG316 * @ 172-00001 % 119-RG174 173-00001 %	M39012/67B0009 M39012/69B0009		
B0010 3/ 4/	94-RG179 * @ ^	M39012/67B0010 M39012/69B0010		
B0013 3/	93-RG178 * @ 169-00001 %	M39012/67B0008 M39012/69B0008		
B0014 3/	113-RG316 * @ 172-00001 % 119-RG174 173-00001 %	M39012/67B0009 M39012/69B0009		
B0015 3/	94-RG179 ^ @ *	M39012/67B0010 M39012/69B0010		

1/ For cross-reference of dash number to superseded PIN or type designation, see table VI.
2/ Mating connector PIN is for reference only. All mating connectors may not be listed.
3/ These connectors have captive center contacts.
4/ Connector bodies shall be gold plated in accordance with ASTM B488, type II, code C, class 1.27.
5/ Dimensions are in inches.
6/ Metric equivalents are given for information only.
The latest version of each cable shall be applicable.
* Cable to be used when performing tests requiring cable except as in note @.
@ Cable to be used for the +200°C thermal shock tests.
% Caution is directed to the application of this cable above 400 MHz. Attenuation is tested only at 400 MHz. SRL and power handling capabilities are not stipulated herein.
^ These are not 50 ohm cables, therefore, when attached to the specified connectors, VSWR, RF leakage and insertion loss are not applicable.

NOTE: Connectors mate with connectors of the same material only; Example: M39012/68-3001 mates with M39012/67-3001, and M39012/68-4001 mates with M39012/67-4001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

TABLE V. Group qualification and retention testing.

Group	Submission and retention of Qualification of any of the following connectors 1/ M39012/	Qualifies the following connectors M39012/
I	68-0003 70-0003	68-0003 68-0103 2/ 70-0003 70-0103 2/
II	68-0004 70-0004	68-0004 68-0104 2/ 70-0004 70-0104 2/
III	68B0008 70B0008	68B0008 68B0013 2/ 70B0008 70B0013 2/
IV	68B0009 70B0009	68B0009 68B0010 68B0014 2/ 68B0015 2/ 70B0009 70B0010 70B0014 2/ 70B0015 2/
V	68B0010 70B0010	68B0010 68B0015 70B0010 70B0015 2/
VI	68-0011 70-0011	68-0011 68-0016 70-0011 70-0016 2/
VII	68-0012 70-0012	68-0012 68-0017 70-0012 70-0017 2/

1/ Individual connectors other than listed are self qualifying only.
2/ Corrosion and contact resistance test data must be submitted to DSCC-VQ before qualification approval may be granted.

NOTES:

1. If a connector manufacturer produces a connector which meets all the requirements for two or more connector PINs (within the same series), the manufacturer may receive qualification approval for two or more connector PINs by qualifying the one connector. It is not necessary that such connectors be in the same group. Each connector, however, must be marked with its own appropriate PIN. For group qualification, the connectors must be of similar design.
2. For qualification retention, where more than one part is listed in a group in this column, data may be supplied on any of those parts in order to retain qualification for those parts in the corresponding right-hand column. The part does not necessarily have to be the part initially qualified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.

TABLE VI. Cross reference of PIN.

Preferred PIN M39012/70	Substitute for PIN or type designation
-0003	M39012/70-0001
-0004	M39012/70-0002
B0008	M39012/70-0008, M39012/70-0005
B0009	M39012/70-0009, M39012/70-0006
B0010	M39012/70-0010, M39012/70-0007

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-39012, this document references the following:

MIL-STD-348
MIL-DTL-22520
MIL-C-22520/5
MIL-STD-202
FED-STD-H28
ASTM B488

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2009-105)

Review activities:
Army - AT, AV, EA MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:04Z
Check the source to verify that this is the current version before use.