INCH-POUND
MIL-PRF-39012/77B
16 November 2011
SUPERSEDING
MIL-PRF-39012/77A
22 June 1971

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, RECEPTACLE, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMC (UNCABLED, MALE, JAMNUT MOUNTED, CLASS 2)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39012.




FIGURE 1. General configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:07Z
Check the source to verify that this is the current version before use.




FIGURE 1. General configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:07Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.018	0.46	.079	2.01	.248	6.30
.023	0.58	.082	2.08	.300	7.62
.029	0.74	.096	2.44	.312	7.92
.065	1.65	.187	4.75	.320	8.13
.074	1.88	.190	4.83	.414	10.52
.077	1.96	.192	4.88	.440	11.18
.078	1.98	.197	5.00	.630	16.00

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Wrench flats are to accommodate standard wrench opening in accordance with FED-STD-H28, appendix 10.
4. All undimensioned pictorial configurations are for reference purposes only.
5. Connector bodies shall be gold plated in accordance with ASTM B488, type II, code C, class 1.27.
6. Series SMC, pin contact interface in accordance with MIL-STD-348.

FIGURE 1. General configuration - Continued.

ENGINEERING DATA:

Nominal impedance: 50 ohms.

Frequency range: 0 to 4 GHz.

Voltage rating: 335 V rms maximum at sea level; 85 V rms maximum at 70,000 feet.

Temperature rating: -65°C to +165°C.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and MIL-STD-348.

Force to engage and disengage:

Longitudinal force: Not applicable.

Torque: Not applicable.

Coupling proof torque: Not applicable.

Inspection conditions:

Torque: 35 to 50 inch-pounds.

Mating characteristics: See MIL-STD-348.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:07Z
Check the source to verify that this is the current version before use.

Hermetic seal: Not applicable.

Leakage (pressurized connectors): Not applicable.

Insulation resistance: In accordance with MIL-STD-202, method 302, test condition B, 1,000 megohms minimum.

Center contact retention:

Axial force: 6 pounds minimum axial force from mating end; 4.0 pounds from opposite end.

Radial torque: 3 inch-ounces, minimum.

Resistance to test prod damage: Not applicable.

Salt atmosphere (corrosion): In accordance with MIL-STD-202 method 101, test condition B.

Voltage standing wave ratio (VSWR): Not applicable.

Connector durability: 500 cycles minimum at 12 cycles per minute maximum. The connector shall meet mating characteristics and force to engage and disengage requirements.

Contact resistance: In milliohms, maximum.

	Initial	After environment
Center contact:	6.0	8.0
Outer contact:	1.0	Not applicable

Dielectric withstanding voltage at sea level: In accordance with MIL-STD-202, method 301. 1,000 V rms, minimum at sea level.

Vibration, high frequency: In accordance with MIL-STD-202, method 204, test condition D.

Shock: In accordance with MIL-STD-202, method 213, test condition C.

Thermal shock: In accordance with MIL-STD-202, method 107, test condition B.

Moisture resistance: Not applicable.

Corona level: Not applicable.

RF high potential withstanding voltage:

Voltage and frequency: 600 V rms, tested at a frequency from 5 to 7.5 MHz.

Leakage current: Not applicable.

Cable retention force: Not applicable.
Coupling mechanism retention force: Not applicable.

RF leakage: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:07Z
Check the source to verify that this is the current version before use.

RF insertion loss: Not applicable.

Part or Identifying Number (PIN): M39012/77 (dash number in table I).

TABLE I. Dash numbers and mounting configuration reference.

PIN M39012/77-	Type of mount
0001, 0003, 4001	Rear
0002, 0004, 4002	Front

Group qualification: See table II.

TABLE II. Group qualification.

Group	Submission and retention of qualification of any of the following connectors M39012/77-	Qualifies the following connectors M39012/77-
I	0001 0002	0001, 0003 1/ 0002, 0004 1/

1/ Salt atmosphere (corrosion) and contact resistance test data must be submitted to DSCC-VQ before qualification approval may be granted.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-39012, this document references the following:

MIL-STD-348
MIL-STD-202
ASTM B488
FED-STD-H28

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:07Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2009-111)

Review activities:
Army - AT, AV, EA, MI
Navy - AS, MC, OS, SA, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:07Z
Check the source to verify that this is the current version before use.