INCH-POUND

MIL-C-71044 (AR)
06 February 1992

MILITARY SPECIFICATION

CIRCUIT CARD, BATTERY TEST: 11784531

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements and tests for the Battery Test Card, which is a component in the Electronic Control Unit (ECU). The ECU is a part of the Target Holding Mechanism/Tank Gunnery (THM/TG) (See 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (See 6.2).

SPECIFICATIONS

MILITARY

MIL-F-13926 - Fire Control Materiel, Manufacture and Inspection, General Specification for

MIL-I-45607 - Inspection Equipment, Acquisition, Maintenance and Disposition of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 9999

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:31Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-810	-	Environmental Test Methods and Engineering Guidelines
MIL-STD-2000	-	Standard Requirements for Soldered Electrical and Electronic Assemblies

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.4)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

11784531	-	Battery Test Card
11784533	-	Schematic Diagram, Battery Check
11785556	-	Requirements for soldered Electrical and Electronic Assemblies (RETS)

SPECIAL PACKAGING INSTRUCTIONS

PS11784531 - Packaging of Battery Test Card

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 11784531, all associated drawings, and with all requirements specified in applicable specifications and standards. Where applicable, the Battery Test Card shall meet the requirements of MIL-F-13926 as follows:

a. Dimensions and tolerances
b. Inorganic protective surface finishings
c. Part identification and marking
d. Workmanship

3.3 Environmental service conditions.

3.3.1 Vibration. The Battery Test Card shall not suffer damage and shall meet the requirements of 3.4 and 3.7 after exposure to sinusoidal vibrations for 1 hour along the vertical axis within the frequency range of 10 to 40 hertz (Hz). The rate of change of frequency at each frequency range shall not exceed 1 Hz per second.

Frequency Range	Amplitude
10 to 15 hertz	0.06 inches double amplitude
15 to 25 hertz	0.04 inches double amplitude
25 to 40 hertz	0.02 inches double amplitude

The frequency of vibration shall be swept logarithmically.
The cycling time shall be 60 minutes.
The sweep rate shall be 3.75 minutes ± 10%.
The 10-40-10 hertz sweep time is 2 minutes 30 seconds ± 10%.

3.3.2 Temperature.

3.3.2.1 Operating. The Battery Test Card shall meet the requirements of 3.4 and 3.7 when stabilized thermally at any temperature between -25 degrees F and + 125 degrees F.

3.3.2.2 Non-operating (storage). The Battery Test Card shall not suffer permanent damage when subjected to the constant temperature extremes of -40 degrees F for a period of 4 hours and +160 degrees F for a period of 4 hours (after temperature stabilization), and shall meet the requirements of 3.4 and 3.7 when returned to room ambient.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3.4 Electrical. The electrical characteristics and continuity of the Battery Test Card shall be as specified on the Battery Check Schematic Diagram drawing 11784533. Refer to this schematic diagram for the performance requirements of 3.7 and performance testing of 4.7.5.

3.5 Soldering. The circuit board shall be soldered per drawing 11785556.

3.6 Circuit identification. The circuit board shall have adequate permanent labeling for proper identification of pins (contact fingers) in the circuitry. Pins are located in the male connector on the printed circuit.

3.7 Performance.

3.7.1 Functional description. The Battery Test Card is the section of the circuitry in the Electronic Control Unit (ECU) that will indicate the condition of the 12 volt battery used in the Target Holding Mechanism/Tanks Gunnery (THM/TG). The test card has a voltage indicator light, which is a Light Emitting Diode (LED) soldered in the circuit board. The light will constantly remain on after the ECU is turned on, providing that sufficient power is available during operation of the lifting mechanism (raise and lower the target). The battery test light will flash in the event the voltage in the system drops below 10.5 volts.

3.7.2 Supply voltage. The Battery Test Card shall function when a +12 Volt direct current (Vdc) is connected to Pin 6 with return to ground (GND) Pin 8.

3.7.3 Battery indication satisfactory. When +12 Vdc is applied, the LED on the circuit board shall go on and glow continuously.

3.7.4 Battery indication unsatisfactory. When the voltage supply is reduced to 10.5 Vdc - 0.1 Vdc, the LED shall commence to flash.

3.7.5 Flash rate. With the reduced voltage as in 3.7.4 the LED shall remain flashing at a rate of 3.0 Hz $\pm$ 1.0 Hz.

3.7.6 Normal condition. With the voltage returned to normal as in 3.7.3, the LED shall commence to glow continuously.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3.7.7 Circuit check. When the voltage in the LED diode circuit is depleted the LED shall go out.

With +12 Vdc applied, the following voltage shall be present:

Pin 1	0.1 Vdc ± 0.1 Vdc
Pin 3	0.1 Vdc ± 0.1 Vdc

With Pin 2 opened with respect to GND and within 2 seconds ± 1 second, the following voltage shall be present:

Pin 1	+12 Vdc ± 0.1 Vdc

With Pin 4 opened with respect to GND and within 2 seconds ± 1 second, the following voltage shall be present:

Pin 3	+12 Vdc ± 0.1 Vdc

3.8 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with technical provisions herein (see 4.3).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contact or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Special sampling inspection (see 4.5).

4.2.1 Inspection conditions. Unless otherwise specified, all examinations and tests shall be conducted at the following standard ambient conditions:

a.	Temperature	+60 deg to +90 deg F.
b.	Relative humidity	90% RH Max.
c.	Pressure	28 to 32 inches of Hg.

4.3 First article inspection.

4.3.1 First article submission. The contractor shall submit a first article sample as designated by the contracting officer consisting of three (3) Battery Test Cards for inspection in accordance with 4.3.2.

4.3.2 Inspections to be performed. First article assemblies, components and test specimens may be subjected by the Government to any or all of the examinations and tests specified in Table I (Functional test) and Table II (Special Sampling) herein and to any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly, component or test specimen to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.2 Examinations and tests.

4.4.2.1 Components, assemblies and subassemblies.

a. The contractor's quality program or detailed inspection plan shall provide assurance of compliance of all characteristics with the applicable drawings and specifications utilizing as a minimum the conformance criteria specified in this document and the Quality Assurance Provisions (QAP) listed in the Technical Data Package (TDP). In the absence of QAP's, the applicable quality assurance provisions of MIL-F-13926 shall apply.

b. Alternative inspection procedures, methods or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the procuring contracting officer for evaluation and approval by the Government. When required the contractor shall demonstrate that the effectiveness of the proposed alternative(s) is equal to or better than the specified quality assurance provisions herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

In cases of dispute as to whether the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program plan or detailed inspection system, as applicable.

4.4.2.2 Final acceptance inspection. Subsequent to first article approval, examination and tests related to Section 3 herein shall be performed as specified in 4.4.2.3 and 4.5.

4.4.2.3 Functional tests. The tests in Table I shall be performed on a 100% basis.

TABLE I. Functional tests
(100% Inspection)

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
Critical:	None	N/A
Major:		
101. Electrical	3.4	4.7.2
102 Soldering	3.5	4.7.3
103. Performance	3.7	4.7.5
104. Workmanship	3.2d	Visual
Minor:		
201. Identification	3.6	4.7.4

4.5 Special sampling. One Battery Test Card out of the first 50 produced and one out of each 100 produced thereafter shall be selected at random. The sample shall have met the requirements and tests of Table I and shall then meet the tests in Table II. Unless otherwise specified in the contract the items shall be returned to the lot upon successful completion of testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE II. Special sampling

CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
Critical:	None	N/A
Major:		
105. Vibration	3.3.1	4.7.1.1
106. Temperature	3.3.2	4.7.1.2
Minor:	None	N/A

4.5.1 Failure of sample. Should any one item of a special sampling fail to meet any of the specified test requirements, acceptance of the product shall be suspended by the Government until necessary corrections to all production since the last test as well as to current production has been accomplished in accordance with the provisions of the contract.

4.6 Inspection equipment.

4.6.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements of MIL-I-45607.

4.6.2 Contractor-furnished inspection equipment.

4.6.2.1 Government design. Unless otherwise specified in the contract, all inspection equipment identified by drawing number in specifications or QAPs forming a part of the contract shall be supplied by the contractor in accordance with the design specified. The contractor may, however, propose alternatives to Government designs for approval in accordance with 6.3.

4.6.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the "Methods of Inspection" specified in 4.7 of this specification and with the components inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926 whenever Government designs are not specified (see 4.6.2.1). Since tolerance of test equipment is normally considered to be within 10 percent of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:31Z
Check the source to verify that this is the currentversion before use.

Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to ensure that the test equipment will reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed tolerance limit and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of test equipment. Contractor inspection equipment designs shall be submitted for approval in accordance with 6.3.

4.6.2.3 Test equipment. In conjunction with 4.6.2.1 and 4.6.2.2, the test equipment listed in Table III (Test equipment list), or equivalent meeting minimum requirements, shall be used in the performance of the applicable test methods and procedures as specified in 4.7.

TABLE III. Test equipment list

ITEM NUMBER	DESCRIPTION
1. DC Power Supply	+12 Vdc ± 0.1 Vdc. HP Model 6284A or equivalent
2. Oscilloscope	Dual time base with mixed sweep capabilities. Input impedance of 1 megohm or greater, 0 - 15 Vdc range. Tektronix 2235 or equivalent
3. Digital Multimeter	Accuracy and resolution of ± 0.2 % from 1 - 100 Vdc. Input Impedance 10 megohms or greater. Fluke Model 8060A or equivalent
4. Resistors	180 + 5% ohm 1W or greater (2 req'd)
5. Temperature Chamber	-40 deg C to +71 deg C at a rate of ± 6 deg C/minute minimum

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.7 Methods of inspection.

4.7.1 Environmental. Environmental tests shall be conducted in accordance with the test conditions, general test performance guidance, and individual test methods of MIL-STD-810 except as specified herein. Test facilities, chambers and apparatus used in conducting the tests contained in this specification shall be capable of meeting the conditions required.

4.7.1.1 Vibration. The test shall be performed as specified in Method 514, Category 8, Procedure I, of MIL-STD-810 as modified by 3.3.1 herein. In Step 1 of Procedure I only steps 4 through 8 of paragraph II-2.1 apply. The Battery Test Card shall be secured to the vibration generator using a suitable fixture in a vertical position with the male connector pointing to the left when viewing the component side of the board. After vibration, the Battery Test Card shall be tested as specified in 4.7.2 and 4.7.5 herein to determine compliance with 3.3.1. If the requirements are not met, the item shall be rejected.

4.7.1.2 Temperature.

4.7.1.2.1 High (operating and non-operating). This test shall be performed as specified in Procedures I and II, Method 501 of MIL-STD-810 with constant temperature extremes as specified in 3.3.2. The operational checkout shall be as specified in 4.7.2 and 4.7.5 for compliance with 3.3.2. If the requirements are not met, the item shall be rejected.

4.7.1.2.2 Low (operating and non-operating). This test shall be performed as specified in Procedures I and II, Method 502 of MIL-STD-810 with constant temperature extremes as specified in 3.3.2. The operational checkout shall be as specified in 4.7.2 and 4.7.5 for compliance with 3.3.2. If the requirements are not met, the item shall be rejected.

4.7.2 Electrical. Continuity shall be inspected by standard measuring equipment (SME) and visual examination for compliance with 3.4. If the requirements are not met, the item shall be rejected.

4.7.3 Soldering. Soldering processes and workmanship shall be inspected by inspectors per drawing 11785556 as specified by 3.5 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.7.4 Identification. Visually inspect circuit boards for adequate labeling to locate contact pins, as required by 3.6 herein.

4.7.5 Performance. The performance of the Battery Test Card shall be tested using the equipment listed in Table III. All input and output parameters shall comply with the requirements of 3.7. If the requirements are not met, the item shall be rejected.

4.7.5.1 Step-by-step procedure. The following test procedure shall be conducted in order to comply with the requirements of 3.7. If the requirements are not met, the item shall be rejected.

4.7.5.1.1 Initial conditions. Test set-up

a. Connect the power supply (12 Vdc ± .01) positive output to Pin 6 and return to ground Pin 8.

b. Connect a jumper wire from Pin 5 to Pin 7.

c. Connect two (2) 180 ohm resistors to the positive terminal of the 12 volt power supply, and the other ends to Pin 1 and Pin 3 respectively.

d. Short (less than 1 ohm) Pin 2 and Pin 4 to ground.

e. Connect the oscilloscope to Pin 6 with respect Pin 5.

Notes:

a. All voltages are measured with respect to ground or power supply return.

b. The Pins as refered to in the procedure are the male Pins on the Battery Test Card connector. They start with Pin number One (1) on the left side of the male connector, viewing the Circuit Board on the component side with the connector at the top.

4.7.5.1.2 Battery indication satisfactory. Test to meet the requirement of 3.7.3.

a. Apply the +12 Vdc ± 0.1 Vdc to Pin 6.

b. Observe the LED (CR7) which shall be on continuously.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.7.5.1.3 Battery indication unsatisfactory. Test to meet the requirement of 3.7.4.

a. Reduce the +12 Vdc power supply at a rate not greater than 0.50 Vdc per second. Stop lowering the voltages as soon as the LED (CR7) starts to flash.

b. Observe that the LED (CR7) shall begin to flash when the reading on the supply voltage is 10.5 Vdc - 0.1 Vdc.

4.7.5.1.4 Flash rate. Test to meet the requirements of 3.7.5.

a. Reduce the supply voltage to 10.5 Vdc - 0.1 Vdc.

b. Observe that the LED (CR7) shall remain flashing at a rate of 3.0 Hz ± 1 Hz.

4.7.5.1.5 Normal condition. Test to meet the requirement of 3.7.6.

a. Return the power supply to +12 Vdc ± 0.1 Vdc.

b. Observe that the LED (CR7) is on, and glowing continuously.

4.7.5.1.6 Circuit check. Test to meet the requirement of 3.7.7.

a. Remove the ground jumper wire from between Pin 5 and Pin 7. The LED (CR7) shall go out.

b. Measure the voltage at Pin 1 and Pin 3. The reading shall be 0.1 Vdc ± 0.1 Vdc.

c. Open Pin 2 with respect to ground. Measure the voltage at Pin 1. The reading shall be +12 Vdc ± 0.1 Vdc within 2 seconds ± 1 second.

d. Open Pin 4 with respect to ground. Measure the voltage at Pin 3. The reading shall be +12 Vdc ± 0.1 Vdc within 2 seconds ± 1 second.

5. PACKAGING

5.1 General. Preservation, packing, and marking shall be in accordance with Packaging Data Sheet 11784531. The level of protection shall be as specified in the procurement document.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:31Z
Check the source to verify that this is the currentversion before use.

6. NOTES

(This section contains information of a general explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Battery Test Card is one of three (3) Circuit Card Assemblies used in the Electronic Control Unit (ECU) of the Target Holding Mechanism/Tank Gunnery (THM/TG).

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).
c. Applicable stock number.
d. First article sample requirements.
e. Packaging requirements, if other than specified in Section 5.
f. Serialization requirements, if applicable.
g. Certification of conformance for each lot of shipment of product.

6.3 Submission of contractor inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army AMCCOM, ATTN: SMCAR-QAF-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as, U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.5 Subject term (key word) listing.

a. Electronic Control Unit (ECU)
b. Target Holding Mechanism/Tank Gunnery (THM/TG)
c. Flash Rate

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 5999-A123)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-71044 (AR)	6 FEBRUARY 1992

3. DOCUMENT TITLE: CIRCUIT CARD, BATTERY TEST: 11784531

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
US ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial (201) 724-6674	(2) AUTOVON 880-6674
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.