INCH-POUND

MIL-C-71134 (AR)
1 July 1992

MILITARY SPECIFICATION

CARTRIDGE, HE, 120MM, M933 W/FUZE M745 LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements and quality provisions for loading, assembling and packing for one type of mortar cartridge designated as Cartridge, HE, 120MM, M933 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (See 6.2).

SPECIFICATIONS

FEDERAL

TT-C-490	- Cleaning Methods and Pre-Treatment of Ferrous Surfaces and Organic Coatings

MILITARY

MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification for
MIL-C-71035	- Charge Propelling, M230 Loading, Assembling and Packing

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Standardization Document Improvement Proposal - DD Form 1426
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-410	- Nondestructive Testing Personnel Qualification and Certification (Eddy Current, Liquid Penetrant, Magnetic Particle, Radiographic and Ultrasonic)
MIL-STD-453	- Inspection, Radiographic
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issue are those cited in the solicitation.

DRAWINGS (see 6.6)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

12577504	- Cartridge, 120mm: M933, with Fuze, Multi-Option Fuze: M745
12577509	- Container, Ammunition, Fiber, PA153
12577511	- Body Loading Assembly
12577512	- Body
12577513	- Adapter
12577514	- Booster Assembly
12577517	- Felt Disc
12577522	- Charge Propelling M230
12577543	- Pellet
12577551	- Packing and Marking for Container, Ammunition Fiber for Cartridge, 120mm, M929, M930, M933 and M934
12577570	- Packing and Marking for Box, Ammunition for Cartridge, 120mm: M929, M930, M933, and M934

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

12588571	- End Plate, Plywood
12577572	- Pull Strap
12577573	- Corrugated Fiberboard, Wide
12577574	- Corrugated Fiberboard, Narrow
19-48-4116	- Unitization Procedure, for Box Ammunition and Components on 4-way Entry Pallets

(Copies of drawings and other publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B-117	- Standard Test Method of Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society of Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable specifications, drawings and this specification.

3.1.1 Clean explosive scrap. Clean scrap (see 6.8) produced in regular operations may be remelted and reused provided that it complies with the requirement, except for form, for the grade of high explosive specified. Scrap from floor sweepings, ventilation, and suction apparatus (other than from drilling operations specifically controlled to prevent contamination of explosive) shall not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3.2 Assembly. The cartridge shall comply with all requirements specified on drawing 12577501, associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Surface cavitation. Cavities formed due to chipped or broken explosive from the sidewalls of the fuze well shall not exceed in aggregate more than 1/4 of the circumference. The maximum (max.) dimension of any visible cavity in the faced (bottom) surface of the fuze well shall not exceed 1/4 inch in any direction and the total area of all cavities shall not exceed 80 percent of the faced surface area (cavities having a max dimension of 1/16 inch or less shall be disregarded in this computation).

3.4 Foreign matter in projectile cavity. There shall be no foreign matter in the projectile cavity prior to high explosive pouring. Solid explosive shall not be present.

3.5 High explosive on threads. Threads shall be free of high explosive to minimum depth shown on drawing.

3.6 High explosive on projectile body. The exterior surface of the projectile body shall be free of high explosive.

3.7 Cavitation in high explosive charge (see 4.4.3.3).

3.7.1 General. Cavities having a maximum projected dimension of 3/32 inch or less shall be disregarded provided that they are separated by 1/2 inch or more of solid explosive.

3.7.2 Maximum projected areas and dimensions of cavities. The aggregate of the projected area of all cavities shall not exceed one square inch and no individual cavity shall exceed 1/2 square inch. Cavities located in the area of the charge which extends from the base of the fuze well shall not exceed 3/4 inch in any direction and their aggregate projected area shall not exceed 5/8 square inch.

3.7.3 Piping cavity. A piping cavity on the longitudinal axis of the projectile shall be permitted provided that its projected length does not exceed 1 1/2 inches and its width does not exceed 1/4 inch. The projected area of such a cavity shall not be included when determining cavity area in the charge.

3.7.4 Cracked charges and annular rings. Not more than four transverse cracks shall be permitted in any charge. The cracks shall be no wider than 1/32 inch. Longitudinal cracks shall be disregarded. The presence of annular rings with a projected width of 1/16 inch max. and extended from the shell wall 1/4 inch max. into the charge shall not be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3.7.5 Base separation. The base separation from the inside of the rear of the shell to the base of the explosive shall be not more than 1/32 inch.

3.8 Ballistic performance (proving ground). The cartridges shall comply with the following requirements when tested as specified in 4.5.1.

3.8.1 Misfire. The cartridges shall not fail to fire from the weapon.

3.8.2 Duds.. The cartridges shall function on impact (prior or on impact if set proximity).

3.8.3 Short rounds. No cartridge shall have a horizontal range less than 80 percent of the average horizontal range when calculated without the short round(s).

3.8.4 Premature burst. There shall be no premature burst in the gun bore or in the first 100 meters of flight.

3.8.5 Metal parts separation. There shall be not metal parts separation in the gun bore or in-flight.

3.8.6 Range precision. The horizontal range probable error shall be less than 1.5% of mean ranges for ranges greater than 2000 meters or 30 meters or less at mean ranges at 2000 meters or less.

3.8.7 Deflection precision. The horizontal deflection probable error shall be less than 1% of mean range for ranges greater than 2000 meters or 20 meters or less at mean ranges at 2000 meters or less.

3.8 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with technical provisions herein (see 4.3 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3.9 Workmanship. All parts and assemblies shall be fabricated in a thorough workmanlike manner. Threads shall be full and undamaged for the entire minimum length as required by the applicable drawings. No part shall have a burr which might be injurious to personnel handling the item. No part or assembly shall contain dirt, grease, chips, rust, corrosion, or other foreign matter. Particular attention shall be given to the cavity of the body assembly, to insure that no grit, scale, corrosion or other foreign matter remains therein after final cleaning. Adapters shall be prepared for painting in accordance with TT-C-490. The cleaning method used shall not be injurious to any part nor shall parts be contaminated by the cleaning agent. Painting shall comply with the requirements of the applicable drawing. All paint shall be dry to the touch before packing for shipment. Drying time prior to testing shall be in accordance with the applicable specification. After painting, the body shall be free from bare spots, blisters, grease, dirt and other foreign matter. All required markings shall be neat and sharply defined. All packaging and packing shall be secure, undamaged and parts shall not be missing or loose. All packaging and packing of parts shall meet respective drawings and specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.1.2 General provisions. The requirements of MIL-A-48078 form a part of the quality assurance provisions of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The following types of inspection shall be considered on this item:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer in accordance with the provisions of 4.3.2. The first article sample shall consist of the items in the quantities indicated in Table I.

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I.

4.3.3 Rejection. See MIL-A-48078 and the first article ballistic test shall be rejected if:

a. One or more misfires occur.
b. Four or more duds occur.
c. One or more short rounds occur.
d. One or more premature bursts occur.
e. One or more metal parts separation occur.
f. Horizontal range probable error is exceeded. (70 degrees F conditioned samples only)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

Table I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71134 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
	Cartridge, 120MM, HE, M933		See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Body Loading Assembly			
	(Dwg. 12577511)			
	Examination for defects	25	3.2	4.4.2.5
	Cartridge			
	(Dwg. 12577504)			
	Examination for defects	25	3.2	4.4.2.7
	Proving ground	144	3.8	4.4.3.1/4.5.1
	Adapter			
	(Dwg. 12577513)			
	Examination for defects	25	3.2	4.4.2.2
	Salt spray test	3	3.2	4.4.3.4/4.5.5
	Paint adhesion test	2	3.2	4.4.3.4
	Pellet			
	(Dwg. 12577543)			
	Examination for defects	25	3.2	4.4.2.3
	Booster Assembly			
	(Dwg. 12577514)			
	Examination for defects	25	3.2	4.4.2.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078. In addition, inspection lots of cartridges shall contain:

a. Projectile metal parts assemblies from one lot interfix from one manufacturer.

b. Composition B from one lot interfix from one manufacturer.

c. Fin assemblies from one lot interfix from one manufacturer.

d. Ignition cartridges from one lot interfix from one manufacturer.

e. Propelling charges from one lot interfix from one manufacturer.

f. Obturating rings from one lot interfix from one manufacturer.

g. Fuzes from one lot interfix from one manufacturer.

h. Booster assemblies from two (2) lots from one manufacturer.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels cited in the classification of characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

Table II. Attributes Sampling Inspection

Lot Size	Inspection Levels					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	5	3
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13

Numbers under inspection levels indicate sample size; asterisks indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.10). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality conformance provision(s) herein. In case of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Body	1 OF 1	12577512
			NEXT HIGHER ASSEMBLY 12577511

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
a	Foreign object in charge cavity	100%	3.4	Visual
Major	None defined			
Minor				
201	Interior protective coating with bare spot	Level V	3.2	Visual
202	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Adapter	1 OF 1	12577513
			NEXT HIGHER ASSEMBLY 12577504

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Pitch diameter forward thread	Level III	3.2	Gage
102	Minor diameter forward thread	Level III	3.2	Gage
103	Pitch diameter rear thread	Level III	3.2	Gage
104	Minor diameter rear thread	Level III	3.2	Gage
105	Runout of forward thread to overall diameter, forward surface, shoulder and rear pitch diameter	Level III	3.2	Gage
106	Forward thread minimum full thread	Level III	3.2	Gage
107	Depth from rear surface to shoulder	Level III	3.2	Gage
108	Failure of protective finish (Salt spray and adhesion tests) 1/	Level III	3.2	Visual/4.5.5
109	Adapter assembling holes functionally improper	Level III	3.2	Gage
Minor				
201	Overall diameter	Level V	3.2	Gage
202	Evidence of poor workmanship	Level V	3.9	Visual

NOTES: 1/ See 4.4.3.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Pellet	1 OF 1	12577543
			NEXT HIGHER ASSEMBLY 12577514

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of pellet	Level III	3.2	Gage
102	Length of pellet	Level III	3.2	Gage
103	Chipped edge corners exceeding .25"	Level III	3.2	Gage
104	Density of pellet	Level III	3.2	4.5.6
Minor				
201	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Booster Assembly	1 OF 1	12577514
			NEXT HIGHER ASSEMBLY 12577504

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Height	Level III	3.2	Gage
102	Outside diameter, max.	Level III	3.2	Gage
103	Outside surface split, bulged, or damaged	Level III	3.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Body Loading Assembly		12577511
			NEXT HIGHER ASSEMBLY 12577504

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
a	High explosive on projectile body	100%	3.6	Visual
b	High explosive on threads	100%	3.5	Visual
c	Radiographic inspection	4.4.3.3	3.7	X-Ray
Major				
101	Depth of fuze well	Level III	3.2	Gage
102	Max. diameter of fuze well	Level III	3.2	Gage
103	True position of fuze well	Level III	3.2	Gage
Minor				
201	Surface cavitation excessive	Level V	3.3	Visual
202	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 12577522
4.4.2.6	Charge, Propelling, M230		NEXT HIGHER ASSEMBLY 12577504

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical 1	Container or container seal damaged to the extent that propellant will escape 1/	100%	3.2	Visual/Manual (see 4.5.4)
Major 101	Container or container seal damaged but not to the extent that propellant will escape 1/	100%	3.2	Visual/Manual (see 4.5.4)
102	Gross weight of propelling charge, min. 1/	100%	3.2	Gage
Minor	None defined			

NOTES:
1/ If LAP of propelling charge and cartridge is performed at the same location, these inspections are not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.7	Cartridge, 120MM, HE, M934		12577504
			NEXT HIGHER ASSEMBLY: Final

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Ignition cartridge not properly assembled or fully seated	100%	3.2	Gage
2	Propelling charge missing or damaged to the extent that propellant will escape	100%	3.2	Visual/Manual (see 4.5.4)
3	Obturating ring missing	100%	3.2	Visual
Special				
a	Fin blade distorted	100%	3.2	Gage
Major				
101	Adapter not properly assembled or fully seated	100%	3.2	Visual
102	Obturating ring not flush or below bourrelet diameter 1/	100%	3.2	Gage
103	Outside diameter of body, max.	100%	3.2	Gage
104	Cartridge assembly fails to fully enter profile and alignment gage	100%	3.2	Gage
105	Obturating ring damaged	Level III	3.2	Visual
106	Adapter Torque	Level III	3.2	Test
107	Fin assembly torque	Level III	3.2	Test
108	Fuze torque	Level III	3.2	Test
109	Ignition cartridge torque	Level III	3.2	Test
110	Fin assembly not fully seated	Level III	3.2	Visual

NOTES: 1/ This inspection may be performed at a prior station when deemed necessary.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Cartridge, 120MM, HE, M934	2 OF 2	12577504
			NEXT HIGHER ASSEMBLY: Final

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major Continued				
111	Fuze not fully seated	Level III	3.2	Visual
112	Number of felt discs not properly placed 2/	Level III	3.2	Visual
113	Obturator weld strength 1/	4.4.3.2	3.2	4.5.2
114	Propelling charge damaged but not to the extent that propellant will escape	100%	3.2	Visual/Manual (see 4.5.4)
Minor				
201	Paint damage area in excess of 1/4 square inch	Level V	3.2	Visual
202	Marking missing, misleading or unidentifiable	Level V	3.2	Visual
203	Cement application improper	Level V	3.2	Visual
204	Evidence of poor workmanship	Level V	3.9	Visual
	Proving ground test			
	Ballistic acceptance			
	First lot	144	3.8	4.4.3.1/4.5.1
	Subsequent lots	80	3.8	4.4.3.1/4.5.1

NOTES: 2/ Quantity of felt discs shall be established to allow fuze to fully seat without damage to the booster, but with no booster free movement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 12577509
4.4.2.8	Container, Ammo, Fiber, PA153		NEXT HIGHER ASSEMBLY 12577551

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Parts loose or not secured	Level III	5.1	Manual/Visual
102	Container damaged	Level III	5.1	Visual
Minor				
201	Marking missing, incorrect, illegible	Level V	5.1	Visual
202	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Packing & Marking for Cntnr Ammo, Fiber, for Ctg. 120MM, M929, M930 M933, and M934 (unsealed)	1 OF 1	12577551
			NEXT HIGHER ASSEMBLY 12577570

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Propelling charge damaged to the point that propellant has escaped	Level III 1/	3.2	Visual
Special				
a	Propelling charge support assembly missing or improperly positioned	100%	5.1	Visual
Major				
101	Fuze support missing - prior to insertion of cartridge	Level III	5.1	Visual
102	Cushion missing	Level III	5.1	Visual
103	Fiber container parts not secure	Level III	5.1	Manual
104	Propelling charge damaged but not to the point that propellant has escaped	Level III 1/	3.2	Visual/Manual (See 4.5.4)
Minor				
201	Length of sealing strip tab (min)	Level V	5.1	Gage
202	Length of propelling charge support tab (min)	Level V	5.1	Gage
203	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

1/ The containers housing the cartridges should have the cover compressed to the body but not sealed. The cartridges shall be down loaded from the container, the support removed, the four propellant charges removed and inspected for damage per MIL-C-71035, para 4.4.2-1, Major 103. A damaged propellant cartridge shall be considered a defect. The lot shall be rejected for one or more defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Packing & Marking for Cntnr Ammo, Fiber, for Ctg., 120MM, M929, M930 M933 and M934 (sealed)	1 OF 1	12577551
			NEXT HIGHER ASSEMBLY 12577570

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Container damaged	Level III	5.1	Visual
102	Sealing strip incomplete, badly wrinkled or missing	Level III	5.1	Visual
103	Contents loose	Level III	5.1	Manual
Minor				
201	Marking missing, misleading or unidentifiable	Level V	5.3	Visual
202	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Packing & Marking for Box Ammo, for Ctg. 120MM, M929, M930, M933 and M934	1 OF 1	12577570
			NEXT HIGHER ASSEMBLY: Final

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Fiber container loose	Level III	5.1	Visual
102	Containers improperly oriented	Level III	5.1	Visual
103	Corrugated fiberboard damaged, missing, or improperly placed	Level III	5.1	Visual
104	Plywood end plates damaged, missing, or improperly placed	Level III	5.1	Visual
Minor				
201	Firing table not present in one of every twelve boxes	Level V	5.1	Visual
202	Marking missing, misleading or unidentifiable	Level V	5.3	Visual
203	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	End Plate, Plywood	1 OF 1	12577571
			NEXT HIGHER ASSEMBLY 12577570

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length	Level III	5.2	Gage
102	Width	Level III	5.2	Gage
103	Thickness	Level III	5.2	Gage
104	Delamination	Level III	5.2	Visual
105	One or more holes missing	Level III	5.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Corrugated Fiberboard, Wide	1 OF 11	12577573
			NEXT HIGHER ASSEMBLY 12577570

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length	Level III	5.2	Gage
102	Width	Level III	5.2	Gage
103	Thickness	Level III	5.2	Gage
104	Delamination	Level III	5.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Corrugated Fiberboard, Narrow	1 OF 1	125775[illegible]4
			NEXT HIGHER ASSEMBLY 125775[illegible]0

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length	Level III	5.2	Gage
102	Width	Level III	5.2	Gage
103	Thickness	Level III	5.2	Gage
104	Delamination	Level III	5.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.9	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Ballistic testing. The cartridges shall be observed for the following characteristics:

a. Misfires, Major defect (see 3.8.1).
b. Duds, Major defect (see 3.8.2).
c. Short rounds, Critical defect (see 3.8.3).
d. Premature burst, critical defect (see 3.8.4).
e. Metal parts separation, Special defect (see 3.8.5).
f. Range precision, Major defect (see 3.8.6).

Testing shall be conducted as specified in 4.5.1.

4.4.3.1.1 First article. A sample of 144 cartridges shall be used for this test. Accept/reject criteria shall be in accordance with 4.3.3.

4.4.3.1.2 First production lot. A sample of 144 cartridges shall be randomly selected from each lot for this test. The lot shall be rejected if:

a. One or more misfires occur.
b. Three or more duds occur.
c. One or more short rounds occur.
d. One or more premature bursts occur.
e. One or more metal parts separation occur.
f. Horizontal range probable error is exceeded (70 degree F conditioned samples only).

4.4.3.1.3 Production. A sample of 85 cartridges shall be randomly selected from each lot for this test. The lot shall be rejected if:

a. One or more misfires occur.
b. Three or more duds occur.
c. One or more short rounds occur.
d. One or more premature bursts occur.
e. One or more metal parts separation occur.
f. Horizontal range probable error is exceeded. (70 F conditioned samples only)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.3.2 Strength of adhesive weld. One obturating ring sample, minimum, after every three hundred (300) projectiles, shall be assembled to a fixture, introduced to the production line, sealed and tested as specified in 4.5.2. Failure of the sample to meet the requirement shall be cause for those three hundred (300) preceding projectiles represented by the sample to be rebanded and retested.

4.4.3.3 Cavitation (see 3.7) major defect. The sampling plan and procedure for this test shall be in accordance with MIL-STD-1235 using CSP-1 plan having the following parameters; i value shall be 210, f value shall be 1/25, and the s value shall be 1350. Any cartridge having cavitation in excess of that permitted by the applicable requirement for any segment shall be classed defective. The test shall be performed as specified in 4.5.3.

4.4.3.4 Salt spray test (See 4.5.5). In performing the following tests, TT-C-490 shall apply unless specified otherwise herein. The test shall be performed for first article inspection, each day of painting during production and whenever a change is made to the paint process, until all samples from five consecutive days of painting have passed the test. Thereafter the sample frequency may be reduced to twice per week during continuous days of painting. Five specimens shall be selected, consisting of randomly chosen projectiles which have been processed through all the same cleaning, phosphating, painting and drying steps at the same time using the same equipment as other production projectiles. The samples shall be taken from each continuous final paint operation up to 24 hours long. One projectile shall be taken during the first thirty (30) minutes of painting, one during the last thirty (30) minutes and the other at any other time.

Prior to salt spray testing, two (2) of the specimens must only pass an adhesion test using the procedures and pass-fail criteria contained in 4.2.8 and 3.5.6, respectively, of TT-C-490. If both specimens pass the adhesion test, the three (3) remaining specimens shall be scored lengthwise using a precision scribing tool/insert or equivalent in preparation for the salt spray test. The adapter shall withstand a 48 hour exposure to 5% salt spray, method ASTM B117.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.5 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Proving ground test. The test shall be performed at a Government proving ground in accordance with the applicable USATECOM Acceptance Test Procedure.

The cartridges for first article testing and the first production lot shall be separated into three equal groups: one group of 36 conditioned to 120 +/- 2.5 degrees F for 24 hours; one group of 72 conditioned to 70 +/- 2.5 degrees F for 24 hours; and one group of 36 conditioned to -25 +/- 2.5 degrees F for 24 hours. The quantities shall be tested at charges as indicated in Table III.

The cartridges for production lot acceptance (subsequent to passing first lot w/o waiver) shall be separated in three groups. The first group of 20 rounds shall be conditioned to 120 degrees F ± 2.5 degrees for 24 hours. The second group of 45 rounds shall be conditioned to 70 degrees F ± 2.5 degrees. The third group of twenty rounds will be conditioned to -25 degrees F ± 2.5 degrees for 24 hours. the quantities shall be tested at charges as indicated in the Table III.

TABLE III - Proving Ground Tests

	120 ± 2.5 F		70 ± 2.5 F		-25 ± 2.5 F	
Charge Number	1st Article & 1st Prod. Lot	Prod Lat	1st Article & 1st Prod Lot	Prod Lat	1st Article & 1st Prod Lot	Prod Lat
4	24	10	24	15	24	10
1			24	15		
0	12	10	24	15	12	10

The cartridge shall be fired from a M120 Mortar at an elevation of forty-five degrees within two minutes after removal from the conditioning chamber. All fuzes will be set for super quick. The individual weights, velocities, pressures, deflections, and ranges shall be recorded on the firing record. Photos will be taken of each fuze setting to verify the setting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

Observation shall be made for misfires, premature bursts, early functions, and duds, and shall be recorded. Should a premature burst or metal parts separation occur, a photograph shall be taken of the evidence and attached to the firing record. The velocity and range standard deviations and arithmetic averages shall be calculated and recorded. Temperature of the day, weather and the time of firing shall also be recorded.

HAWK radar or equivalent shall be used to observe for metal parts separation, unobserved short rounds and unobserved duds. In these events, an analysis should be made of the radar data and should be noted on the firing record. This shall include a comparison of times of flight of the unobserved rounds, with that of the normal rounds. Prints of the radar traces of these rounds, and prints of the preceding and succeeding rounds, shall be attached to the firing record. Data from ballistically acceptable lots may be discarded.

A smear camera shall be used to photograph all test samples. The camera shall be positioned to pick up each round 40 feet from the muzzle of the gun. Should an unobserved dud, short round or any other abnormal performance occur, a photo print of these rounds, and prints of all other rounds in that particular charge zone, shall be attached to the firing record. Film from acceptable lots may be discarded.

4.5.1.1 Test validity. If for any reason the proving ground personnel considers that the test conditions have detrimentally affected the test results, the test result shall be declared invalid and a new test shall be performed on additional sample cartridges.

4.5.2 Strength adhesive weld. The sample shall be tested for integrity by applying the required load at the weld radially and in a direction away from the axis (center) of the ring.

4.5.3 Determination of cavities. The sample cartridges (HE filled) shall be subjected to radiographic examination. The radiographic beam shall form a 90 degree angle with the longitudinal axis of the projectile. Examinations of the radiograph shall be made to determine compliance with applicable requirements. Radiographic equipment, operations and procedures shall be qualified in accordance with MIL-STD-453. In addition, the sensitivity of the radiographic technique shall be 2.0 percent, and the photographic density of the film used shall be no less than 1.23 as determined in accordance with 4.5.3.2. In the event an original radiograph leaves doubt as to acceptability, the cartridge shall be re-radiographed at an angle 90 degrees from that of the original exposure and in the same plane.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.5.3.1 Sensitivity check of radiographic technique. The sensitivity of radiographic technique shall be determined by the means of a penetrameter fabricated as specified herein. Location of the penetrameter hole shall be 6 3/4 inches measured from base shoulder of projectile body towards fuze nose threads. The projectile, with attached penetrameter, shall be positioned between the radiographic source and the radiographic film with the penetrameter facing the radiographic source. When radiographing a group of projectiles on a rotating ring, the penetrameter, taped to a projectile, may be used to represent the group when checking sensitivity. The sensitivity of radiographic technique shall be considered satisfactory when the image of the penetrameter, including the holes, is sharply defined on the radiograph. The penetrameters shall be made of steel having an approximate specific gravity of 7.8. Penetrameter thickness shall be .020 plus or minus .010 inches. Each penetrameter shall have a circular hole with a diameter twice that of the penetrameter thickness. For further details on construction of the penetrameter, see MIL-STD-453. Frequency of sensitivity check shall be no less than one in each fifty (50) radiographs.

4.5.3.2 Check of photographic density of film. The photographic density of the film shall be determined on the film in the region of the maximum equivalent thickness to be radiographed. Film density shall be checked each hour of operation, or fraction thereof, for each film processor. Greater frequency shall be required for any period during which difficulty is encountered in establishing the required densities. To judge densities, it is recommended that standards be used. Comparison of the film with standards may be made visually; however, the use of a densitometer is recommended.

4.5.3.3 Personnel qualification and certification. Personnel performing the radiographic examination in accordance with paragraph 4.5.3 shall meet the qualification and certification requirements defined in MIL-STD-410 as follows:

4.5.3.3.1 Set up and calibration. Level II.

4.5.3.3.2 Operator. Level I.

4.5.3.3.3 Documentation. The contractor will prepare and submit for approval, detailed procedures for qualification and certification of personnel performing the nondestructive testing procedures required herein in accordance with the approved Data Item description specified on the Contract Data Requirements List in the contract (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.5.4 Damaged propelling charge. To ascertain that a damaged propelling charge is to be classed as critical or major, the following procedure shall be used:

a. Place the damaged charge on a M31 fin, oriented such that the propellant would be resting against the damaged surface.

b. The fin-charge shall be hand-shaken vigorously three times.

c. Examination shall be made for propellant spillage if any propellant is observed, the damaged propelling charge shall be classed as a critical defect; if no propellant is observed, the damaged propelling charge shall be classed as a major defect.

4.5.5 Salt spray test. (see 4.4.3.4) The salt solution, test equipment and drying procedures shall be in accordance with ASTM B-117, Salt Spray (Fog) Testing, unless specified otherwise herein. Specimens shall be positioned between 15 and 30 degrees from vertical during the test. No coating of any kind shall be permitted over the paint on stamp marks of the specimens prior to testing, however areas in contact with racks or supports, unpainted surfaces and areas within 3/16 inch of unpainted surfaces may be protected.

When examining the specimens for signs of paint failure, the surface of the adapter (defined on the drawing) shall be considered the significant surface

As used herein, the term "blister" refers to an unbroken area of paint with a bubble-like appearance whereas "pits" or "spots" are exposed phosphate pre-treatment or bare metal visible through holes in the paint. Blisters which are present when the test is over are to be counted within five (5) minutes of removal from the test chamber.

Adapter shall be tested for the duration specified on drawing 12577513. After testing, any projectile which fails for any of the following reasons shall be cause for rejection of all parts painted since the last successful test and a return to the original sampling plan if failure occurred during reduced sampling. The failure criteria in a-j applies to the significant surfaces only.

a. The paint shows more than 1/8 inch creepage, blistering or loss of adhesion of paint from the scribe mark, stamp mark, or edge.

b. There are more than one (1) blisters total.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

c. Any blister exceeds 1/16 inch average diameter.

d. Any pit exceeds 1/8 inch average diameter.

e. There are four (4) or more scattered pits exceeding 1/16 inch average diameter.

f. There are four (4) or more spots within one square inch.

g. There are three (3) spots within one square inch in two (2) or more places.

h. There are more than six (6) scattered spots, total.

i. There is evidence of rust under the paint (a brown discoloration showing through the paint) in excess of 1/4 inch in diameter total area.

j. There is some variation of the above or an unlisted defect anywhere which the Government representative deems excessive.

4.5.6 Density of booster pellet. The density of each pellet shall be determined by using the following calculation:

$$\text{Density g/cc} = \frac{\text{Mass, in grams/(height in inches)}}{\text{(diameter in inches.)} \quad (12.87)}$$

5. PACKAGING

5.1 Packaging.

5.1.1 Level A. Packaging for cartridge shall be in accordance with the requirements of drawing 12577551.

5.1.2 Level B. Same as level A.

5.1.3 Level C. Same as level A.

5.2 Packing.

5.2.1 Level A. Packing for cartridge shall be in accordance with requirements of drawing 12577570.

5.2.2 Level B. Same as level A.

5.2.3 Level C. Same as level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

5.3 Marking.

5.3.1 Level A. Unit packaging for cartridge shall be marked in accordance with the requirements of drawing 12577551. Packing shall be marked in accordance with the requirements of drawing 12577570.

5.3.2 Level B. Same as level A.

5.3.3 Level C. Same as level A.

5.4 Unitization procedure. Unitization procedure will be in accordance with drawing 19-48-4116 for box, ammunition and components on 4-way entry pallets.

6. NOTES

(This section contains information of general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The components covered by this specification are intended for assembly to the M934 cartridges for use with the 120MM mortar.

6.2 Acquisition requirements.

a. See MIL-A-48078.

b. Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1).

c. Provisions for submission of first article sample.

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first production item, or a standard production item from the contractor's current inventory and the number of items to be tested as specified in 4.3. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such product, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

6.4 Consideration of data requirements. The following data requirements should be considered when this specification is applied to the contract.

Reference Paragraph	DID Number	DID Title
4.5.3.3.3	DI-S-3628	Nondestructive Inspection Plan

The above DIDs were those cleared as the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be research to ensure that only current, cleared DIDs a (copies of data item descriptions required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

6.5 Submission of inspection equipment designs for approval. See paragraph 6.2.3 of MIL-A-48078 (AR). Submit equipment designs, as required, to: Commander, U.S. Army Armament Research, Development and Engineering Center (ARDEC), ATTN: SMCAR-QAT-I, Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 on the contract.

6.6 Drawings. Drawings listed in Section 2 of this specification under the heading of U.S. Army Armament, Research Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as ARRADCOM, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.7 Submission of test data. One copy of proving ground ballistic acceptance test data (i.e., firing record) shall be forwarded to each of the following:

Commander
U.S. Army Armament Research, Development
and Engineering Center
ATTN: SMCAR-QAT-B/SMCAR-FSA-IM
Picatinny Arsenal, NJ 07806-5000

6.8 Clean scrap. Clean scrap is defined as scrap formed in kettles, pails, riser and loading machines used in the pouring and cooling operations, and scrap formed during the drilling operation. Scrap from floor sweepings, ventilation, and suction apparatus (other than that of drilling operations) is not defined as being clean scrap and shall not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

6.9 Loading of high explosive. Solid explosives shall not be added to the melted explosives or to the projectile body during pouring or cooling.

6.10 Submission of alternative quality conformance provisions. All contractor proposed alternative quality conformance provisions will be submitted to the Government for evaluation/approval by the technical activity responsible for the preparation of this specification.

6.11 Subject term (key) listing.

Ammunition, mortar
Ballistics
Explosive, high
Radiography

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AE27)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-71134 (AR)	920701

3. DOCUMENT TITLE: CARTRIDGE, HE, 120MM, M933 W/FUZE M745 L.A.P.

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that the content is current before use.