INCH-POUND

MIL-C-71144 (AR)
27 September 1994

MILITARY SPECIFICATION

CHARGE, PROPELLING, M229, FOR 105MM HOWITZER LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers the requirements, examinations and tests for the loading, assembling and packing for one type of propelling charge designated as Charge, Propelling, M229, for Howitzer M119 and is intended for use in the M913 RA cartridge.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-P-193	- Potassium Sulfate (For Ordnance Use)
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander, U.S. Army, ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, NJ 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

MIL-C-48360	- Charge, Propelling, M200, for 105MM Howitzer, M119, Loading, Assembling and Packing
MIL-P-70539	- Propellant, M30 for Use in Charge, Propelling, 105MM, M200

STANDARDS

MILITARY

MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-1168	- Lot Numbering of Ammunition

(Unless otherwise indicated, copies of the federal and military specifications, standards, and handbooks are available from the DODSSP - Customer Service, Standardization Documents Order Desk, Bldg 4D, 700 Robbins Ave., Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9282042	- Charge, Propelling M200 Loading Assembly
9345265	- Container, Steel
12630698	- Flash Reducer Loading Assembly for 105MM M229 Propelling Charge
12630699	- Charge, Propelling 105MM M229
12953551	- Packing and Marking for Container, Steel for 105MM Howitzer Propelling Charges

(Copies of other Government documents, drawings and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained. (See contract provisions for additional precedence criteria.)

3. REQUIREMENTS.

3.1 Material. Material shall be in accordance with applicable drawings and specifications.

3.2 Propelling charge assembly. The M229 propelling charge consists of an M200 charge as the main increment loaded in accordance with drawing 9282042 which meets all of the requirements of MIL-C-48360 (with the exception of marking requirements) and a flash reducer assembly loaded in accordance with drawing 12630698 sewn to the main charge assembly. The complete assembly shall comply with all requirements specified on drawing (dwg) 12630699 and with all the requirements specified in applicable specifications.

3.3 Propellant weight.

3.3.1 Flash reducer. The flash reducer assembly shall be loaded with 3.0 ± 0.05 ounces of M30 propellant conforming to the requirements of MIL-P-70539 and 1.5 ± 0.05 ounces of Type II potassium sulfate meeting the requirements of MIL-P-193.

3.3.2 Flash reducer assembly weight. The flash reducer assembly weight shall not differ by more than ± 0.10 ounces from the total weight of the propellant, plus that of the potassium sulfate, plus the average tare weight of the bag assembly.

3.3.3 Charge, propelling assembly weight. The charge, propelling assembly weight of the M229 propelling charge shall not differ by more than ± 0.15 ounces from the total weight of that specified on the loading authorization plus the average tare weight of the bags.

3.4 Proving ground. Ballistic testing shall be performed on the main increment of the charge only. The charge when tested in accordance with 4.4.3.3 shall meet the ballistic requirements of MIL-C-48360.

3.5 First article inspection. Test samples shall be withdrawn from the first lot produced by the contractor. Samples will be tested in accordance with all the requirements of this specification. Until the first article test has been performed and found to be acceptable, the contractor is in no way authorized by the Government to initiate production of a second lot unless otherwise directed by the contracting officer.

3.6 Initial production inspection (see 6.7). This specification contains provisions for the submission of a initial

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

production sample. This is a one time qualification test for a new contractor to load assemble and pack M229 propelling charges. Test samples shall be withdrawn from the first lot produced by the contractor. Charges will be tested in accordance with all the requirements of this specification and with Table III (see 6.7). Until the initial production sample has been found to be acceptable, the contractor is in no way authorized by the Government to initiate production of a second lot unless otherwise directed by the contracting officer.

3.7 Workmanship. The propellant grains shall be free of dirt, foreign material and other defects that would make the item unsuitable for its intended use. The cloth and thread used for the manufacture of propelling charge bags shall be void of grease, oil, dirt, foreign material, holes, rips or tears. All components and assemblies shall be fabricated and finished in a thorough workmanlike manner. All required marking shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set for in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 apply and form a part of this specification. References shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

a. Initial Production Inspection (see 6.7).

b. First Article Inspection (see 4.3).

c. Quality Conformance Inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of fifteen (15) propellant charge assemblies packed in a fiber drum and fifteen (15) complete sets of parts (i.e. 15 each of every component and every sub assembly) which have been produced by the contractor.

4.3.2 Inspections to be performed. The first article assemblies submitted in accordance with 4.3.1 will be subjected by the Government to any or all of the requirements of the applicable drawings and to the inspections and tests of Table I. All inspections in Table I shall be classified Major unless otherwise specified.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71144 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
			NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH / INSPECTION METHOD REFERENCE
	Body ---- (Dwg - 12630696) Examination for defects.	100 %	3.2 / 4.4.2.1
	Body Assembly ------------- (Dwg 12630697) Examination for defects.	100 %	3.2 / 4.4.2.2
	Flash Reducer Loading Assembly for 105MM M229 Propelling Charge --------- (Dwg 12630698) Examination for defects.	100 %	3.2 / 4.4.2.3
	Charge, Propelling, M229, Assembly --------- (Dwg - 12630699) Examination for defects.	100 %	3.2 / 4.4.2.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4. Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078 and MIL-STD-1168. In addition:

a. Flash reducers shall contain M30 propellant, Type I, from not more than one lot from one manufacturer.

b. Main increments shall contain propellant from not more than one lot.

c. The same lot of propellant loaded into the main increment shall be loaded into the flash reducer.

d. Potassium sulfate from not more than one manufacturer.

e. An entire lot of M30 propellant shall be used to form a lot of M229 propelling charges unless otherwise directed by the contracting officer.

4.4.2 Examination and tests. See MIL-A-48078.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawings and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II
Attributes sample inspection levels.

Lot Size	Major Sample Size	Minor Sample Size
2 to 8	*	see note
9 to 15	*	5
16 to 25	*	5
26 to 50	32	5
51 to 90	32	12
91 to 150	32	12
151 to 280	32	14
281 to 500	32	17
501 to 1200	74	20
1201 to 3200	74	24
3201 to 10000	87	30
10001 to 35000	109	36
35001 to 150000	124	40
150001 to 500000	156	40
500001 and over	187	40

* - 100 % inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

NOTE: Use 100 % inspection when lot size is less than 5 units. Use sample size when lot size is greater than 5 units.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, other types of sampling procedures, etc. may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.9). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71144 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Body	1 OF 1	12630696
			NEXT HIGHER ASSEMBLY: 12630697

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Cloth improper.	Acc-0/Rej-1	3.1	4.5.1
102	Diameter.	Acc-0/Rej-1	3.2	Gage/Scale
Minor				
201	Evidence of poor workmanship.	Acc-0/Rej-1	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71144 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Body Assembly	1 OF 1	12630697
			NEXT HIGHER ASSEMBLY: 12630698

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Broken or incomplete stitches.	Acc-0/Rej-1	3.2	Visual
Minor				
201	Evidence of poor workmanship.	Acc-0/Rej-1	3.7	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71144 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Flash Reducer Loading Assembly	1 OF 1	12630698
			NEXT HIGHER ASSEMBLY: 12630699

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Weight of propellant.	100 %	3.3	Scale
102	Weight of Potassium Sulfate.	100 %	3.3	Scale
103	Weight of Assembly	100 %	3.3	Scale
104	Assembly damaged to the extent that propellant or Potassium Sulfate can escape.	Acc-0/Rej-1	3.2	Visual
105	Any seam or opening incompletely stitched.	Acc-0/Rej-1	3.2	Visual
106	Excessive thread used in sewing assembly	100 %	3.2	Visual/manual
107	Thread broken.	Acc-0/Rej-1	3.2	Visual
Minor				
201	Evidence of poor workmanship.	Acc-0/Rej-1	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71144 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Charge, Propelling, 105MM M229	1 OF 1	12630699
			NEXT HIGHER ASSEMBLY: NA

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical				
1	Pressure exceeds PIMP.	note 1/	3.4	Test
Major				
101	Weight of assembly.	100 %	3.3	Scale
102	Assembly damaged to the extent that propellant or Potassium Sulfate can escape.	Acc-0/Rej-1	3.2	Visual
103	Any seam or opening incompletely stitched.	Acc-0/Rej-1	3.2	Visual
104	Thread broken.	Acc-0/Rej-1	3.2	Visual
105	Muzzle velocity and muzzle velocity standard deviation.	note 1/		
106	Excessive thread used in tacking operation.	100 %	3.2	Visual/manual
Minor				
201	Evidence of poor workmanship.	Acc-0/Rej-1	3.7	Visual

NOTES:
1/ Ballistic testing/conformance shall be in accordance with the requirements of MIL-C-48360.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71144 (AR)

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.5	Steel container, prior to filling	SHEET 1 OF 1	9345265
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Foreign material in drum.	100 %	5.1	Visual
102	Gasket missing or damaged.	100 %	5.1	Visual
104	Holes in cover or end.	100 %	5.1	Visual
104	Locking device damaged.	100 %	5.1	Visual
Minor				
201	Nicks, dents, body bulged or scratched.	Acc-0/Rej-1	5.1	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71144 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Unsealed,steel container.	1 OF 1	12953551
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Contents missing.	Acc-0/Rej-1	5.1	Visual
102	Packing component missing.	Acc-0/Rej-1	5.1	Visual
Major				
201	Packing component improperly assembled.	Acc-0/Rej-1	5.1	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71144 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Steel container, sealed	1 OF 1	12953551
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Contents move when drum is tilted.	Acc-0/Rej-1	5.1	Manual
102	Locking device damaged or improperly closed.	Acc-0/Rej-1	5.1	Visual
103	Holes or breaks in cover or body.	Acc-0/Rej-1	5.1	Visual
104	Damage to coating or cover.	Acc-0/Rej-1	5.1	Visual
105	Pressure test.	Acc-0/Rej-1	5.1	Gage
Minor				
201	Marking missing, misleading or illegible.	Acc-0/Rej-1	5.2	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89

Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Applicable to reusable steel container before filling	1 OF 1	12953551
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Top chime bent, deformed or cut.	100 %	5.1	Visual
102	Bottom bulged, cut or dented.	100 %	5.1	Visual
103	Body bulged, cut or dented.	100 %	5.1	Visual
104	Gasket in cover missing or damaged.	100 %	5.1	Visual
105	Cover bent, creased or deformed in gasket area or around edge.	100 %	5.1	Visual
106	Locking ring damaged so as to prevent closing.	100 % 100 %	5.1 5.1	Visual Visual
Minor				
201	Outer body surface seriously scuffed or metal scratched.	Acc-0/Rej-1	5.1	Visual
202	Nicks or dents in chimes or cover not affecting function.	Acc-0/Rej-1	5.1	Visual
203	Locking rings bent or deformed.	Acc-0/Rej-1	5.1	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Flash reducer propellant weight. The propellant to be loaded into the flash reducer increment shall be weighed and check weighed 100 percent. Any propellant which fails to comply with the applicable requirements shall be classed defective and removed from the lot.

4.4.3.2 Charge, propelling M200 assembly weight. The defects shall be classified as follows: Critical defect: Weight deviation in excess of 3 times that specified in 3.3. Major defect: Weight deviation in excess of that specified in 3.3 but not greater than three (3) times that in 3.3. The assemblies shall be weighed 100 % and compliance with 3.3 shall be used by using the average weight of the empty bag assemblies, plus the specified weight of propellant and potassium sulfate loaded in the flash reducer, plus the weight of propellant specified on the loading authorization.

4.4.3.3 Ballistic testing. Ballistic testing will be performed on the M200 increment only in accordance with the requirements of MIL-C-48360. Prior to temperature conditioning, the flash reducer assembly shall be removed from the charge.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections specified herein is identified in the "Inspection Method Reference" column of the Classification of Characteristics listing starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.4 herein.

4.5 Methods of inspection.

4.5.1 Cloth. At the time the cloth is introduced to the sewing or cutting operation, an identification will be made for each roll to verify that the proper material is used. Any cloth failing to be identified as proper material in accordance with applicable drawings and specifications shall be rejected and removed from the operation.

5. PACKAGING

5.1 Packing. Level B - Propelling charges shall be packed in a steel container in accordance with dwg 12953551. Storage of propelling charges shall not exceed two years.

5.2 Marking. Level B - In addition to any special marking required by the contract or purchase order, marking shall be in accordance with 12953551.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The M229 Propelling charge covered in this specification is intended for use in the 105MM M913 cartridge for Howitzer, M119.

6.2 Acquisition requirements. Acquisition documents must specify the following (see MIL-A-48078):

a. Title, number and date of the specification.

b. Issue of the DODISS to be cited in the solicitation, and if required, the specific issue of the individual documents referenced (see 2.1).

c. Requirements for the submission of first article samples.

d. Requirements for the submission of initial production test samples.

6.3 Charge, propelling assembly weight. This requirement applies to the load plant only due to changes in tare weight of the bags because of variation in bag material and moisture content.

6.4 Submission of contractor inspection equipment designs for approval. Submit equipment designs, as required to: Commander, ARDEC, ATTN: SMCAR-QAR-R, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List in the Contract, DD Form 1423 in the contract.

6.5 Submission of ammunition data cards. In addition to the normal distribution of records, when charges are procured by the Army, one copy of all ammunition data cards shall be forwarded to each of the following:

Commander
ARDEC
ATTN: SMCAR-QAR-R
SMCAR-AEE-BP
Picatinny Arsenal, NJ 07806-5000

6.6 Drawings. Drawings listed in section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

6.7 Initial production test. The initial production test is a one time qualification test for a new contractor to load, assemble and pack acceptable M229 propelling charges. Once a contractor has demonstrated the ability to load, assemble and pack the propelling charges, the initial production test may be waived by the contracting officer. The following test program shall be used for the initial production test:

TABLE III
Initial Production Test

Test Phase	Temp (deg F)	No. Control Rounds	No. Test Rounds	TECOM TOP
Propellant checkout	70		10	TOP-4-2-504
	145		10	TOP-4-2-504
	-60		10	TOP-4-2-504
Sequential environmental	145 -60	15	60	TOP-4-2-504

6.8 Subject term (key word) listing.

Semi-fixed ammunition
Artillery ammunition
Triple base propellant
Rocket assisted projectiles

6.9 Submission of alternate quality conformance provisions. All contractor proposed alternative quality conformance provisions will be submitted to the Government for evaluation/approval as directed by the contracting activity.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AD86)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-71144 (AR)	940927

3. DOCUMENT TITLE: CHARGE, PROPELLING, M229, FOR 105MM HOWITZER LOADING, ASSEMBLING AND PACKING

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: AMSTA-AR-EDE-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.