INCH-POUND

MIL-C-71145 (AR)
12 May 1993

MILITARY SPECIFICATION

CASE, CARTRIDGE, 105MM W/CHARGE M67/M200 and PRIMER M28B2

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, examinations and tests for assembly and packing of the Case Cartridge, Primer and Propelling Charge (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-P-46565	- Primer Percussion, M28A2 and M28B2, Loading, Assembling and Packing.
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-109	- Quality Assurance Terms and Definitions

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Bldg, 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.8)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

9240919	- Case, Cartridge w/Charge M67/M200 and Primer M28B2, for 105MM.
12953460	- Packing and Marking for Case, Cartridge, 105MM Howitzer

(Copies of other Government documents, drawings and publications required by contractors in connection with specific aquisition functions should be obtained from the Contracting activity or as directed by the Contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and specifications.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.3 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be clean and free of burrs, sharp edges, unblended radii, cracks, surface defects, chips, dirt, grease, dust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078, apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the assemblies, components and test specimens listed below in the quantities indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Packing and Marking for Case, Cartridge, 105MM Howitzer	12953460	3
Case, Cartridge w/charge M67/M200 and Primer M28B2 for 105MM	9240919	6(a)
Case, Cartridge M14B1 or M14B4	7548025, 8595386 or 12938083 as applicable	5
Primer Percussion M28B2	8838130	5
Propelling Charge M67	9205472	5
Propelling Charge M200	9282042	5

(a) These six (6) samples will come from the Pack and Marking Ammunition box (Dwg. 12953460).

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all of the examinations and tests specified in this detail specification (See Table I) and be inspected for compliance with any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145 (AR)

PARAGRAPH	TITLE: Case Cartridge w/charge M67/M200 and Primer M28B2, Assemblies and Components for 105MM	SHEET 1 OF 1	DRAWING NUMBER: See below
			NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Packing and Marking for Case, Cartridge, 105MM Howitzer (Dwg. 12953460) Examination for Defects	3, Level I	3.1	4.4.2.8, 4.4.2.9 and 4.4.2.10
	Case Cartridge w/charge M67/M200 and Primer M28B2 for 105MM (Dwg. 9240919) Examination for Defects	6(a), Level I	3.1	4.4.2.3, 4.4.2.4, 4.4.2.5, 4.4.2.6, and 4.4.2.7 as appl.
	Components Case Cartridge 105MM, M14B1 or M14B4 (Dwg. 7548025, 8595386,or 12938083 as applicable) Examination for Defects	5, Level 1	3.1	4.4.2.1
	Primer Percussion M28B2 (Dwg. 8838130) Examination for Defects	5, Level I	3.1	4.4.2.2
	Propelling Charge M67 (Dwg. 9205472) Examination for Defects	5, Level I	3.1	4.4.2.4
	Propelling Charge M200 (Dwg. 9282042) Examination for Defects	5, Level I	3.1	4.4.2.5

NOTES: (a) Use the six (6) samples from the packing and marking ammunition box (Dwg. 12953460) for these tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II. Attributes sampling inspection

Lot Size	Inspection Levels		
	I	III	V
2 to 8	*	*	5
9 to 15	*	*	5
16 to 25	*	*	5
26 to 50	*	32	5
51 to 90	*	32	13
91 to 150	*	32	13
151 to 280	*	32	20
281 to 500	*	32	20
501 to 1200	*	80	20
1201 to 3200	1250	80	32
3201 to 10000	1250	125	32
10001 to 35000	1250	125	50
35001 to 150000	1250	125	50
150001 to 500000	1250	200	50
500001 and over	1250	200	50

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.11). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality conformance provision(s) herein. In case of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.1	Case, cartridge, 105MM (prior to assembly of primer)	1	1	7548025, 8595386 or 12938083 as applicable
				NEXT HIGHER ASSEMBLY: 9240920, 12953457 or 12953459 as applicable

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Evidence of corrosion	Level III	3.1	Visual
Minor				
201	Dent or damaged	Level V	3.1	Visual
202	Damaged primer hole	Level V	3.1	Visual
203	Protective coating damaged	Level V	3.1	Visual
204	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145 (AR)

PARAGRAPH 4.4.2.2	TITLE Primer, percussion, M28B2 assembly (prior to assembly to case)	SHEET 1 OF 1	DRAWING NUMBER 8838130
			NEXT HIGHER ASSEMBLY 9240920, 12953457 or 12953459 as applicable

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special a	One or more flash holes missing	100%	3.1	Visual
Major	None defined			
Minor	None defined			

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.3	Cartridge case (prior to assembling propelling charge)	1	1	9240920, 12953457 or 12953459 as applicable
				NEXT HIGHER ASSEMBLY: 9240919

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special a	Primer damaged	100%	3.1	Visual
Major 101	Primer missing	Level III	3.1	Visual
Minor 201	Foreign matter in interior of case	Level V	3.1	Visual
Minor 202	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145 (AR)

PARAGRAPH 4.4.2.4	TITLE Propelling charge M67 (prior to assembly to cartridge case)	SHEET 1 OF 1		DRAWING NUMBER 9205472
				NEXT HIGHER ASSEMBLY 9240919
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
a	Increment missing or propellant missing	100%	3.1	Visual
b	Any opening in bag large enough to permit escape of propellant	100%	3.1	Visual
Major	None defined			
Minor				
201	Lacing cord broken	Level V	3.1	Visual
202	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Propelling charge M200 (prior to assembly to cartridge case)	1 OF 1	9282042
			NEXT HIGHER ASSEMBLY
			9240919

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special a	Any opening in bag large enough to permit escape of propellant	100%	3.1	Visual
Major	None defined			
Minor 201	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://asist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.6	Cartridge case with M67 propelling charge	1	1	9240919
				NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical 1	Primer above flush	100%	3.1	Gage
Special a	Incorrect sequence of increments	100%	3.1	Visual
Major 101	Foil side of bag, charge 5, not facing primer	Level III	3.1	Visual
Minor 201	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Cartridge case with M200 propelling charge			NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical 1	Primer above flush	100%	3.1	Gage
Special a	Propelling charge missing	100%	3.1	Visual
Major	None defined			
Minor 201	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145 (AR)

PARAGRAPH 4.4.2.8	TITLE Unsealed fiber container	SHEET 1 OF 1		DRAWING NUMBER 12953460
				NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Packing component missing, damaged or improperly assembled	Level III	3.1	Visual
102	Cartridge case cannot be removed by hand	Level III	3.1	Manual
103	Container cap cannot be removed by hand	Level III	3.1	Manual
104	Insufficient fillers for tight pack (slight gap between body and covers)	Level III	3.1	Visual
105	Moisture content of packing material	Level III	3.1	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145(AR)

PARAGRAPH 4.4.2.9	TITLE Sealed fiber container	SHEET 1 OF 1	DRAWING NUMBER 12953460
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Tape incomplete, wrinkled, incorrect material or damaged during insertion/ extraction from wood packing box	Level III	3.1	Visual
102	Contents loose	Level III	3.1	Manual
103	Marking missing, misleading illegible or incorrect	Level III	3.1	Visual
104	Any component missing or damaged	Level III	3.1	Visual
Minor				
201	Tear tab length, minimum	Level V	3.1	Gage
202	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71145 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.10	Sealed wood packing box	1	1	12953460

NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Box damaged exposing contents	Level III	3.1	Visual
102	Hardware or strapping missing, broken, loose or improperly assembled	Level III	3.1	Visual-Manual
103	DOD symbol missing or incorrect	Level III	3.1	Visual
104	Board broken	Level III	3.1	Visual
105	Handle missing or insecure	Level III	3.1	Visual-Manual
106	Car seal missing, unsealed or improperly positioned	Level III	3.1	Visual
107	Marking incorrect, missing or unidentifiable	Level III	3.1	Visual
108	Contents loose	Level III	3.1	Manual
Minor				
201	Evidence of poor workmanship	Level V	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables and the following:

4.4.3.1 Check test for possible deterioration of primer, percussion, M28, (see specification MIL-P-46565). If the total elapsed time between original acceptance of the M28 primer lot and the assembly of that lot is not complete round cartridges exceeds two years, or if the M28 primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in Specification MIL-P-46565 immediately before the M28 primer lot is assembled into the cartridges. The test shall be performed by the contractor on assemblies selected by the Government inspector at the facility assembling the complete cartridges (see 6.9).

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Inspection Method Reference" column in the table starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A.

5.1.1.1 Fiber container. The loaded cartridge case assemblies shall be packaged in accordance with dwg. 12953460.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Level A. The loaded fiber containers (dwg 12953460) shall be packed in a wood box in accordance with drawing 12953460 or as directed by Government Procuring Activity.

5.3 Marking.

5.3.1 Marking. Marking of the wood box shall be in accordance with dwg. 12953460. The fiber container shall likewise be marked in accordance with dwg. 12953460.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The cartridge case covered by this specification is intended for 105MM renovation program and other use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Applicable stock number.

c. First article sample requirements.

d. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (See 2.1.1).

6.3 Submission of contractor inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required, to: Commander, U.S. Army Armament, Munitions and Chemical Command, ATTN: SMCAR-QAR-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Inspection lot size. It is noted that the size of inspection lots of components, assemblies or items of delivery may differ from the actual quantities contractually scheduled for delivery. However, in order to facilitate scheduling of tests or deliveries, inspection lots of items of delivery may be equivalent to such contract quantities provided all of the lot formation criteria and sampling provisions of this specification are maintained.

6.5 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristics may be measured or gaged to determine acceptability.

6.6 Submission of ammunition data cards. In addition to the normal distribution of records, when the cartridge case assembly is procured by the U.S. Army Armament, Munitions and Chemical Command, one copy of all ammunition data cards shall be forwarded to each of the following: Commander, ARDEC, ATTN: SMCAR-FSA-MS and SMCAR-QAR-Q, Picatinny Arsenal, NJ 07806-5000, and Commander, ARRCOM, ATTN: AMSMC-QAD, Rock Island, IL 61299-6000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

6.7 Alternative testing procedures. Alternative testing procedures may be used by the contractor when such testing and procedures provide as a minimum the quality assurance provisions specified herein. Prior to applying alternative procedures, the contractor shall describe them in a written proposal and shall demonstrate for the approval of the responsible Government technical agency that their effectiveness is equal to, or better than the quality assurance provisions specified herein.

6.8 Drawings. Drawings listed in section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, U.S. Army Research and Development Command (ARRADCOM) or U.S. Army Armament Research and Development Center (ARDC) drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.9 Cost of check test. The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction or either contractor.

6.10 Subject term (key word) listing.

Ammunition
Renovation program

6.11 Submission of alternative quality conformance provision. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AD87)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-71145 (AR)	930512

3. DOCUMENT TITLE: CASE, CARTRIDGE, 105MM W/CHARGE M67/M200 AND PRIMER M28B2

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.