MILITARY SPECIFICATION

CONTAINER, AMMUNITION, LIGHTWEIGHT METAL FOR STINGER WEAPON SYSTEM

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements and quality assurance provisions for the manufacture of a metal container used for packing Stinger Basic/POST/RMP Guided Missile System FIM92A/92B/92C/92D (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-C-490	-	Cleaning Methods for Ferrous Surfaces and Pretreatments for Organic Coatings

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 8140
DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-W-12332	-	Welding Resistance, Spot, Seam and Projection, for Fabricating Assemblies of Low-Carbon Steel
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-A-70625	-	Automated Acceptance Inspection Equipment for Non-Electronic Components, Design, Testing and Approval of

STANDARDS

MILITARY

MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-171	-	Finishing of Metal and Wood Surfaces
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1261	-	Arc Welding Procedures for Constructional Steel

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of the specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

12960903	-	Container, Ammo, Metal PA 158

(Copies of drawings and publications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D2240	-	Rubber Property-Durometer Hardness, Standard Method of Test for (DoD adopted)
ASTM-D3951	-	Commercial Packaging, Practice for (DoD adopted)

(Application for copies for ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Containers. The complete container assemblies shall comply with all requirements specified on drawing 12960903 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Welding. The welding shall comply with the requirements of MIL-W-12332 or MIL-STD-1261.

3.3.1 Tensile strength of body weld. The tensile strength of the longitudinal body weld shall not be less than 65 percent of the tensile strength of body material.

3.3.2 Tensile strength of body material. The tensile strength of the body material shall not be less than 50,000 pounds per square inch (psi).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

3.4 Painted surface. The painted surfaces of the container shall comply with the requirements of TT-C-490. However, the film thickness and salt spray requirements of TT-C-490 shall not apply to the interior surfaces, exterior surface welded spots and exterior surface sharp corners of the container.

3.5 Cover assembly. Upon assembly of the cover assembly to the body assembly (body weldment), the cover assembly shall freely engage and rotate within the body assembly. As the cover assembly is rotated with the "D" handle in the open position, the "D" handle shaft ends shall freely engage into the respective bayonet slots of the rim. When the "D" handle is rotated toward the closed position the hairpin spring clip shall be snapped into place locking the "D" handle. When the hairpin is removed, the "D" handle is allowed to go to the open position. Rotation of the cover assembly will permit disengagement from the body assembly.

3.6 Air pressure test.

3.6.1 Air pressure of unpainted cover assembly. The unpainted cover assembly shall withstand an internal air pressure of 3.0 + .5 psig for five (5) seconds minimum under water, without leakage occurring.

3.6.2 Air pressure of unpainted body assembly. The unpainted body assembly shall withstand an internal air pressure of 3.0 + .5 psig for five (5) seconds minimum under water, without leakage occurring.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship.

3.8.1 Containers. The containers shall be regular, smooth, and free from wrinkles, pin holes, cracks, rough spots, burrs, sharp edges and any other defect that might affect the serviceability, durability, and safety of the container.

3.8.2 Paint coating. The paint coating shall be in accordance with applicable drawings and comply with instructions in MIL-STD-171.

3.8.3 Parts. All parts shall be free of chips, dirt, grease, rust and foreign material. The cleaning method used shall not be injurious to any of the parts nor shall any of the parts be contaminated by the cleaning agents used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2. General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the assemblies, components and test specimens listed below in the quantities indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

Drawings	Part Description	Quantity
12960904	Body, Unpainted	10
12960994	Cover, Weldment	10
12934837	Spring Clip	10
12944489	Gasket	10
12944480	Rim	10
12960903	Container Assemblies, painted	15
12960905	Body Weldment, unpainted	10
12960905	Body Weldment, painted	5
12960995	Cover Assembly, unpainted	5
12960995	Cover Assembly, painted	5

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I First article inspection.

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71170 (AR)

PARAGRAPH	TITLE Assemblies and Components	SHEET OF	DRAWING NUMBER NEXT HIGHER ASSEMBLY See below
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Body, unpainted (Dwg 12960904)			
	Examination for defects	10	3 2	4.4.2.14
	Tensile strength 1/	5	3 3.1	4 5 1
	Cover, weldment (Dwg 12960994)			
	Examination for defects	10	3 2	4 4.2 9
	Spring Clip, (Dwg 12934837)			
	Examination for defects	10	3.2	4.4.2 1
	Gasket (Dwg 12944489)			
	Examination for defects	10	3.2	4.4.2 8
	Hardness	5	3.2	4 5 3
	Remaining subassemblies and components			
	Examination for defects	10	3 2	Applicable subparagraph of 4 4 2
	Rim (Dwg 12944480)			
	Examination for defects	10	3 2	4.4 2 12

NOTES 1/ The weld security inspections and painted surface shall be performed after the other inspections have been performed on the applicable samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

TABLE I First article inspection.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
	Assemblies and Components		See below
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Container assemblies, painted			
	(Dwg. 12960903 as applicable)			
	Examination for defects	5	3 2	4 4 2 17
	Air pressure	15	3 6 2	4 5.4.2
	Painted surface 1/	3	3.4	4.5 5
	Body weldment, unpainted			
	(Dwg 12960905)			
	Examination for defects	10	3 2	4.4.2 16
	Air pressure	5	3.6.2	4.5.4.1
	Weld strength of rim to body 1/	5	3.2	4.5.2
	Body weldment, painted			
	(Dwg. 12960905)			
	Paint thickness	5	3.2	4.5 5
	Paint adhesion	5	3.2	4.5.5
	Cover assembly, unpainted			
	(Dwg. 12960995)			
	Air pressure	5	3 6.1	4.4 3 4 1
	Examination for defects	5	3.2	4.4 2 10
	Cover assembly, painted			
	(Dwg 12960995)			
	Examination for defects	5	3.2	4.4.2.11
	Paint adhesion	5	3.2	4.5 5

NOTES 1/ The weld security inspections and painted surface shall be performed after the other inspections have been performed on the applicable samples

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II. Attributes sampling inspection

	Inspection Levels					
Lot Size	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	12	4
91 to 150	*	125	32	13	12	5
151 to 280	*	125	32	30	14	6
281 to 500	*	125	32	30	17	7
501 to 1200	*	125	74	35	20	9
1201 to 3200	1250	125	74	43	24	10
3201 to 10000	1250	125	87	50	30	10
10001 to 35000	1250	296	109	61	36	10
35001 to 150000	1250	296	124	74	40	10
150001 to 500000	1250	346	156	91	40	10
500001 and over	1250	431	187	102	40	10

Numbers under inspection levels indicate sample size, asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.5). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality conformance provision(s) herein. In case of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4 4.2.1	Spring Clip, Hairpin		12934837
			NEXT HIGHER ASSEMBLY 12960995

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Profile of bends	Level III	3.2	Gage
102	Radius of the loop	Level III	3 2	Gage
103	Overall length	Level III	3.2	Gage
104	Wire diameter	Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.2	TITLE Support, Shaft	SHEET OF	DRAWING NUMBER 12960992
			NEXT HIGHER ASSEMBLY 12960994

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of large hole, maximum (max.)	Level III	3.2	Gage
102	True position of large hole	Level III	3.2	Gage
103	True position of slot	Level III	3.2	Gage
104	Distance between shaft support uprights	Level III	3.2	Gage
105	Material thickness	Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71170 (AR)

ITEM NO.	TITLE	SHEET OF	DRAWING NUMBER
4.4.1.3	Handle, Square		12944482
			NEXT HIGHER ASSEMBLY
			12960995

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
201	Width of hexhole, max (three readings, 60 degress apart)	Level III	3.2	Gage
202	True position of small hole (two places)	Level III	3.2	Gage
203	Width, Dimension (Dim.) A	Level III	3.2	Gage
204	Distance from end to center of hexhole (Dim. B)	Level III	3.2	Gage
205	Material thickness	Level IV	3.2	Gage
Minor				
301	Evidence of poor workmanship	Level V	3.8	Visual

NOTE:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.4	TITLE Shaft	SHEET OF	DRAWING NUMBER 12944484
			NEXT HIGHER ASSEMBLY 12960935

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD OR GAGE NO.
Critical	None defined			
Major				
101	Width across flats of hexagon segment minimum (min.) (three readings, 60 degrees apart)	Level III	3.2	Gage
102	Length of hexagon segment of shaft	Level III	3.2	Gage
103	Length of small diameter segment (two places)	Level III	3.2	Gage
104	Large diameter (two places)	Level III	3.2	Gage
105	Small diameter (two places)	Level III	3.2	Gage
106	Total length of large diameters and hexagon segments (Dim B)	Level III	3.2	Gage
107	Small diameter segment not tangent to large diameter segment and side of hexagon segment	Level III	3.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71170 (AR)

PARAGRAPH 4.4.2.5	TITLE Washer	SHEET OF	DRAWING NUMBER 9344038
			NEXT HIGHER ASSEMBLY 12960995

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter	Level III	3.2	Gage
102	Height, min	Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4.4.3.6	Retainer, Washer		9344041
			NEXT HIGHER ASSEMBLY
			12960995

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD OR TECHNIQUE
Critical	None defined			
Major				
101	Height	Level III	3.2	Gage
102	Diameter of hole	Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.7	TITLE Cover	SHEET OF	DRAWING NUMBER 1296099
			NEXT HIGHER ASSEMBLY 12960995

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Outside diameter, max	Level III	3.2	Gage
102	Width of groove	Level III	3.2	Gage
103	Depth from top cover to recess	Level III	3.2	Gage
104	Height of threads, min, when applicable 1/	Level III	3.2	Gage
105	Flatness of bottom surface inner annular ring and surrounding air test hole	Level III	3.2	Gage
106	Material thickness	Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

1/ Threads may be formed on cover (instead of cover assembly).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4 4 2 8	Gasket		12944489
			NEXT HIGHER ASSEMBLY
			12960995

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Inside diameter, max (Dim. A)	Level III	3.2	Gage
102	Large width	Level III	3.2	Gage
103	Middle width	Level III	3.2	Gage
104	Height of rectangular cross section	Level III	3.2	Gage
105	Material certification		3.2	Certification
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.9	TITLE Cover Weldment	SHEET OF	DRAWING NUMBER 12960994
			NEXT HIGHER ASSEMBLY 12960995

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	True position of shaft support slot with respect to cover air hole	Level III	3.2	Gage
102	Weld missing, incomplete or visually inadequate	Level III	3.2	Visual/Manual
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71170 (AR)

DATA GRID	TITLE	SHEET OF	DRAWING NUMBER
4.4 2.10	Cover Assembly, Prior to Painting		12960995
			NEXT HIGHER ASSEMBLY
			12960903

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD (METHOD REFERENCE)
Critical	None defined			
Major				
101	725 Distance from top of shaft (in closed position) to inside surface of the gasket retainer section of cover	Level II	3.2	Gage
102	Component missing or inadequately assembled	Level III	3.2	Visual
103	Rotating of shaft inadequate after crimping	Level III	3.2	Manual
104	Torque to the humidity plug indicator	Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

AMSMC Form 1570b-1, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71170 (AR)

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4 4 2 11	Cover Assembly, Painted		12960995
			NEXT HIGHER ASSEMBLY
			12960903

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Gasket not secured or secured improperly to cover	Level III	3.2	Visual/Manual
102	Paint thickness (min)	Level IV	3.2	Gage
Minor 201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4 4 2 12	TITLE Rim	SHEET OF	DRAWING NUMBER 12944480
			NEXT HIGHER ASSEMBLY 12960905

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of larger slot (on side of rim), max	Level III	3.2	Gage
102	Width of larger slot (on side of rim), max	Level III	3.2	Gage
103	Location of bayonet slot, four places 1/	Level III	3.2	Gage
104	Inside diameter of rim, two places (Dim E)	Level III	3.2	Gage
105	Outside dimension across flats, two places (Dim A)	Level III	3 2	Gage
106	Outside dimension across corners, two places (Dim F)	Level III	3 2	Gage
107	Radius chamfer at beginning of locking edge of bayonet slot missing 1/	Level IV	3.2	Visual
108	Min Dim. across bayonet slot	Level III	3.2	Gage
109	Inside diameter of the rim (Dim C)2/	Level III	3.2	Gage
Minor				
201	Drainage hole missing	Level IV	3.2	Visual
202	Step at inside of locking edge of bayonet slot missing 1/	Level IV	3.2	Visual
203	Evidence of poor workmanship	Level V	3.8	Visual

NOTES 1/ See note 6 of the drawing
2/ See note 4 of the drawing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4 4 2.13	Bottom		12944486
			NEXT HIGHER ASSEMBLY 12960905

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Height, minimum (min)	Level III	3.2	Gage
102	Material thickness	Level IV	3.2	Gage
103	Outside Dia of the bottom (Dim A)	Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3 8	Visual

NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71170 (AR)

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4.4.2.14	Body		12960904
			NEXT HIGHER ASSEMBLY
			12960905

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD OR REFERENCE
Critical	None defined			
Major				
101	Length, min.	Level III	3.2	Gage
102	Inside diameter, min. 1/	Level III	3.2	Gage
103	Flatness of body end 1/ 2/	Level III	3.2	Gage
104	Material thickness	Level IV	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

1/ Inspections 102 and 103 may be done on the next higher assembly (Dwg. 12960905).

2/ See note 4 of the drawing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.15	TITLE Plug, Stacking	SHEET OF	DRAWING NUMBER 9386837
			NEXT HIGHER ASSEMBLY 12960905

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Length of plug, min	Level III	3.2	Gage
102	Width of plug, min	Level III	3.2	Gage
Minor				
201	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.1.2.16	TITLE Body Weldment (3 Rims) painted	SHEET OF	DRAWING NUMBER 12960905
			NEXT HIGHER ASSEMBLY 12960903

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD (LETTER) NOT
Critical	None defined			
Major				
101	True position of slots of rims to each other	Level III	3.2	Gage
102	True position of stacking plugs of rims to each other	Level III	3.2	Gage
103	Perpendicularity of rim with datum A	Level III	3.2	Gage
104	Inside diameter of body, min	Level III	3.2	Gage
105	Body (seam) weld (if applicable) or rim or bottom to body missing, incomplete or visually inadequate	Level III	3.2	Visual
106	Paint thickness, min	Level IV	3.2	Gage
107	Shear load min. between stacking plug and rim 1/	Level V	3.2	Gage
108	Shear load min. between rim and body	Level V	3.2	Gage
Minor				
201	Marking missing, illegible or incorrect	Level V	3.2	5.3/Visual
202	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

1/ These shear load inspections may be performed on the subassembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-71170 (AP)

PARAGRAPH 4 4 2 17	TITLE Container Assembly	SHEET OF	DRAWING NUMBER 12960903
			NEXT HIGHER ASSEMBLY N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Cover assembly assembled to body assembly	Level III	3.5	Visual
Minor 201	Protective finish damaged, bare spots exposing metal, etc	Level IV	3 2	Visual
202	Evidence of poor workmanship	Level V	3.8	Visual

NOTES

AMSMC Form 1570b 1, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Tensile strength of body material and weld (see 3.3), Major defect. During the first half of a production shift and during the last half of a production shift, a body shall be selected for this test. From each body, three (3) specimens shall be selected at random for determination of body material tensile strength. Also from each body, four (4) specimens, approximately equally spaces along the axis, shall be taken at right angles to the weld and the tensile strength of their welds shall be determined. Each of these values shall be compared with the lowest determined value of the body material tensile strength for compliance with the requirement of 3.3.1. If one or more specimens (longitudinal body weld or body material) fail to comply with 3.3.1 or 3.3.2, the quantity of bodies which were welded during this shift and the earlier strength test (if applicable) shall be rejected. The test shall be performed as specified in 4.5.1.

4.4.3.2 Weld strength of rim to body (see Dwg. 12944480), Major defect. During the first half of a production shift and during the last half of a production shift, a body assembly shall be randomly selected for this test. From each body assembly, two (2) specimens of welded rim to body segments shall be taken at random. If any specimen fails to meet the requirement when tested in accordance with 4.5.2, the quantity of body assemblies which were welded during this shift between this weld strength test and the earlier weld strength test and (if applicable) shall be rejected.

4.4.3.3 Hardness of gasket (see Dwg. 12944489), Major defect. Five (5) gaskets shall be randomly selected from each lot for this test. If any gasket fails to meet the requirement, the lot shall be rejected. The test shall be performed as specified in 4.5.3

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.4.3.4 Air pressure.

4.4.3.4.1 Air pressure of unpainted cover assembly (see 3.6.1), Major defect. The cover assemblies shall be checked 100 percent. If any cover assembly fails to comply with the requirement, the cover assembly shall be rejected. The test shall be performed as specified in 4.5.4.1.

4.4.3.4.2 Air pressure of unpainted body assembly (body weldment) (see 3.6.2), Major defect. The body assemblies shall be checked 100 percent. If the body assembly fails to comply with the requirement, the body assembly shall be rejected. The test shall be performed as specified in 4.5.4.1.

4.4.3.4.3 Air pressure of painted container assembly (see Dwg. 12960903 as applicable), Major defect. Container assemblies shall be selected in accordance with MIL-STD-1235, continuous sampling plan CSP-1, using Sample Frequency Code D with a value of i of 135 consecutive units. The test shall be performed as specified in 4.5.4.2.

4.4.3.5 Painted surface (see 3.4), Major defect. Sampling shall be in accordance with TT-C-490 and testing shall be in accordance with 4.5.5.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. and in 4.5. When Automated Acceptance Inspection Equipment is to be used, the provisions of MIL-A-70625 shall apply. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection. (see 6.4)

4.5.1 Tensile strength of body material and weld. The tensile strength shall be determined in accordance with ASTM-E8.

4.5.2 Weld strength of rim to body. The strength of the weld shall be determined in accordance with ASTM-E8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

4.5.3 Hardness of gasket. The hardness shall be determined in accordance with ASTM-D2240.

4.5.4 Air pressure test.

4.5.4.1 Air pressure of unpainted cover assembly and unpainted body assembly. (Water immersion method) Subject the cover assembly and container body to the specified internal air pressure for the test time specified. For the cover assembly, apply the pressure when the cover assembly is assembled to a master body assembly (or its equivalent) equipped with a gasket. For the body assembly, apply the pressure when the body assembly is assembled to master cover (or equivalent) and gasket. The master cover and the master body assembly shall be provided with satisfactory means for applying and maintaining the pressure during the test and for showing evidence of leakage. Observation shall be made for the presence of bubbles. No bubbles (other than surface bubbles) shall be permitted. A cover assembly or body assembly which does not meet the requirements, shall be classed defective.

4.5.4.2 Air pressure of painted container assembly. Subject the painted container assembly to an air pressure test as specified in the applicable container assembly drawing. A container assembly which does not meet the requirement, shall be classed defective. When cover assemblies or body weldments (container bodies) are procured separately, the contractor shall submit for Government (SMCAR-QAR-R) approval, the test procedure that will be followed to meet the applicable test requirement.

4.5.5 Painted surface. The painted container assembly and associated subassemblies shall be tested in accordance with TT-C-490.

5. PACKAGING

5.1 Packaging requirements. None required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

5.2 Marking.

5.2.1 Commercial. Shipping marking shall comply with ASTM-D3951 and the following additional instructions. No shipping markings shall be placed directly on the containers. Commercial shipping tags attached with wire shall be used unless otherwise specified. The following information shall be shown: Item name and model number, part number and revision, contract number, lot number and date, name and address of manufacturer. If containers are bundled, boxed or palletized, the gross weight and quantity shall be included. The above information may be placed on pallets or boxes by labelling or stenciling.

5.2.2 Shipping. When pallets from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing lots in transit.

6.1 Intended use. This lightweight metal ammunition container is used for packing Stinger Basic/POST/RMP Guided Missile system FIM 92A/92B/92C/92D.

6.2 Acquisition requirements. See MIL-A-48078

6.3 Submission of contractor inspection equipment designs for approval. See MIL-A-48078 submit copies of designs as required to: Commander, U.S. Army ARDEC, ATTN: SMCAR-QAR-R, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Submission of alternative quality conformance provisions. All contractor proposed alternative quality conformance provisions will be submitted to: Commander, U.S Army Armament Research, Development and Engineering Center, ATTN: SMCAR-QAR-R, Picatinny Arsenal, NJ 07806-5000 for evaluation/approval by the technical activity responsible for the preparation of this specification.

6.5 Subject term (key word) listing
Hardness testing
Air pressure leak testing
Container

Custodian:
Army-AR

Preparing Activity:
Army - AR

(Project 8140-A973)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	2. DOCUMENT NUMBER	3. DOCUMENT DATE (YYMMDD)
	MIL-P-71170 (AR)	930405

3 DOCUMENT TITLE: CONTAINER, AMMUNITION, LIGHTWEIGHT METAL FOR STINGER WEAPON SYSTEM

4 NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5 REASON FOR RECOMMENDATION

6 SUBMITTER

6a. NAME (Last, First, Middle Initial)	6b. ORGANIZATION
6c. ADDRESS (Include Zip Code)	6d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	6e. DATE SUBMITTED (YYMMDD)

8 PREPARING ACTIVITY

8a. NAME	8b. TELEPHONE (Include Area Code)
U S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial: 201-724-6675 (2) AUTOVON: DSN-880-6675
8c. ADDRESS (Include Zip Code) ATTN SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS CONTACT Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:31Z
Check the source to verify that this is the current version before use.