INCH-POUND

MIL-C-70793(AR)
31 March 1989

MILITARY SPECIFICATION

CARTRIDGE, 20MM, MULTIPURPOSE, TRACE SELF-DESTRUCT, M940

This specification is approved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements, quality assurance provisions and preparation for delivery for Cartridge 20mm, Multipurpose, Trace Self Destruct M940 for use in Gun, Automatic, 20mm, M168 and M61.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-12560 - Armor Plate, Steel, Wrought, Homogeneous (for use in Combat-Vehicle Ammunition Testing)
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-A-70625 - Automated Acceptance Inspection Equipment for Non-Electronic Components, Design Testing and Approval, of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions, and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

STANDARDS

MILITARY

MIL-STD-105-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-644-	Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking for Small Arms Ammunition
MIL-STD-651-	Visual Inspection Standards for 20MM Ammunition and Components

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (SEE 6.5)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

7258928	-	Marking on M548 Shipping and Storage Container for 20mm Cartridges
7258969	-	Method of Packing 100 Cartridges, 20mm, in M14 Type Links, in M548 Container
12551767	-	Cartridge 20mm MPT-SD, M940
12551768	-	Projectile
12551770	-	Projectile Body Assembly, Charged
12551772	-	Nose Assembly, Charged
12551774	-	Projectile Body Assembly, Tracer

INSPECTION EQUIPMENT DRAWINGS

7258801	-	Classification of Defects for Case, Cartridge, 20mm, M103, M103A1, and M103B1
7259424	-	Gage, Torque Testing
7259443	-	Rack, Cartridge
7296962	-	Indicator Gage
7555162	-	Gage, Chamber
11075126	-	Test Fixture (Projectile Extraction)
11075284	-	Primer Resistance Test Circuit

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

U.S. ARMY MATERIEL COMMAND

AMCR 715-505- Ammunition Ballistics Acceptance Test Methods, Volume 8, Test Procedures for 20mm Cartridges.

U.S. ARMY TEST AND EVALUATION COMMAND

TECOM TOP 2-2-710 - Ballistic Test of Armor Materials

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of nongovernment documents which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI Z1.1 - Guide for Quality Control Charts
ANSI Z1.2 - Control Chart Method of Analyzing Data
ANSI Z1.3 - Control Chart Method of Controlling Quality During Production

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General.

3.1.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.1.2 Manufacturing process. All parts and assemblies shall be manufactured by a process approved by the contracting officer, and no deviation from that process shall be made without prior approval (6.6).

3.2 Cartridge. The cartridge shall comply with all requirements specified on Drawing (Dwg.) 12551767, all associated drawings, and with all requirements specified in applicable specifications.

3.2.1 Projectile extraction. The force necessary to extract the projectile from the cartridge case shall be 1100 to 2800 pounds, inclusive.

3.2.2 Projectile torque. The projectile shall withstand a minimum torque of 10 inch pounds without movement.

3.3 Contamination of energetic components. Extreme care shall be exercised to avoid contamination of primers and propellant by oil, grease or other foreign matter since such contamination can cause misfires or increase action time and lot rejection. Propellant contamination shall not exceed 0.10% by weight of charge.

3.4 Electrical resistance of primed case. The electrical resistance of the primed case shall not be less than 500 ohms or more than 1,200,000 ohms.

3.5 Cartridge functioning.

3.5.1 Velocity. The average velocity of the sample cartridges conditioned at 68°F to 72°F shall be 3350 $\pm$ 45 feet per second (fps) at 78 feet from the muzzle of the gun and the sample standard deviation shall not exceed 30 fps. (see 6.7)

3.5.2 Pressure. The average peak chamber pressure ($\bar{X}$) of the sample cartridges conditioned at 68°F to 72°F plus 0.84 times the average range ($\bar{R}$) (see 6.8) of the chamber pressure shall not exceed 60,500 pounds per square inch (psi).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

3.5.3 Waterproofness. There shall be no evidence of water entry into the propellant of the cartridge and the cartridge shall function following exposure. The average velocity of the wet sample cartridges conditioned at 68°F to 72°F shall not vary from the average velocity of the dry sample cartridges by more than 100 fps.

3.5.4 Accuracy. The average mean radius of a 10 round shot group shall not exceed 15 inches (accuracy) at a range of 547 yards.

3.5.5 Action time. The action time of the sample cartridges and the average action time ($\bar{X}$) plus four sample standard deviation(s) shall not exceed 4.0 milliseconds from -65°F to 145°F (see 6.7).

3.5.6 Function and casualty. The cartridge shall function without casualty when fired in the M61 and M168, 20MM Automatic Gun.

3.6 Projectile functioning.

3.6.1 Projectile trace. The projectile shall exhibit a visible trace against a dark background for a minimum of 4.1 seconds at -65°F to 145°F.

3.6.2 Projectile self-destruct. The projectile shall self-destruct between 4.1 and 7.0 seconds during uninterrupted flight from the muzzle at 65°F to 145°F.

3.6.3 No arm sensitivity. The projectile shall not function on an .040 inch thick aluminum (2024-T3) target plate at 39 + 1 inches at 0° obliquity (NATO) from the muzzle. A projectile function beyond 39 + 1 inch shall not create a hazardous environment for user personnel by evidence of back scatter of fragments toward the breech.

3.6.4 Arming sensitivity. The projectile shall function on a .080 inch thick aluminum target plate at 210 $\pm$ 10 yards from the muzzle and a .080 inch thick aluminum target plate at 2180 $\pm$ 10 yards from the muzzle at -65°F to 145°F and 0° obliquity (NATO).

3.6.5 Detonation delay. The projectile shall function on an .080 inch thick aluminum target at 210 $\pm$ 10 yards from the muzzle with a delay not less than 8 inches or more than 24 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

3.6.6 Fragmentation. The projectile body shall provide no less than 8 peforations in the last witness sheet of the target array.

3.6.7 Penetration. The projectiles of the sample cartridges, conditioned at 68°F to 72°F shall exhibit an R50 of 547 yards minimum against 3/8 inch rolled homogeneous armor (RHA) having a nominal Brinell Hardness of 360 (conforming to MIL-A-12560) at $45 \pm 2^{\circ}$ obliquity.

3.7 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3 and 6.13)).

3.8 Workmanship. The requirements for workmanship are as specified by applicable drawings, referenced specifications and the following:

3.8.1 Processing defects. The metal parts and assemblies shall be free of splits, perforations, scratches (other than draw scratches), folds, wrinkles, buckles, bulges, cracks, dents, ruptures, deformities, exposed explosive and other forms of substandard workmanship.

3.8.2 Cleanliness. All components and assemblies shall be free of oil, grease, corrosion, dirt, chips and all other detrimental contaminants.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of any defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection (4.3)

b. Quality Conformance Inspection (4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Projectile Body Assembly, Tracer	12551774	125
Projectile Body Assembly, Charged	12551770	125
Nose Assembly, Charged	12551772	125
Projectile	12551768	125
Cartridge 20mm MPT-SD, M940	12551767	716

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET 1 OF 5		DRAWING NUMBER
	Cartridge, 20mm, MPT-SD, M940 and Components 1/ 2/				SEE BELOW
					NEXT HIGHER ASSEMBLY
					Not Applicable
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Projectile Body, Assembly, Tracer (Dwg. 12551774)				
	Examination for defects.	125	ACC-0 REJ-1	3.2	4.4.2.1
	Projectile Body Assembly, Charged (Dwg. 12551770)				
	Examination for defects	125	ACC-0 REJ-1	3.2	4.4.2.2
	Nose Assembly, Charged (Dwg. 12551772)				
	Examination for defects	125	ACC-0 REJ-1	3.2	4.4.2.3
	Projectile (Dwg. 12551768)				
	Examination for defects	125	ACC-0 REJ-1	3.2	4.4.2.4
	Cartridge, 20mm MPT-SD, M940 (Dwg. 12551767				
	Examination for defects	125	ACC-0 REJ-1	3.2	4.4.2.5

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE			SHEET 2 OF 5	DRAWING NUMBER
	Cartridge, 20mm, MPT-SD, M940 and Components 1/ 2/				SEE BELOW
					NEXT HIGHER ASSEMBLY
					Not Applicable
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Test requirements Non-functioning				
	(1) Projectile extraction	20	ACC-0 REJ-1	3.2.1	4.5.1.1/11075126/ 7259443
	(2) Projectile torque	20	ACC-0 REJ-1	3.2.2	4.5.1.2/7259424
	(3) Propellant contamination/ charge weight verification	20	ACC-0 REJ-1	3.3	4.5.1.3 6/
	(4) Electrical resistance of primed case, verification	20	ACC-0 REJ-1	3.4	4.5.1.4.b 6/
	Cartridge Functioning				
	(1) Velocity	20	3/	3.5.1	4.5.2.2 4/
	(2) Pressure	20	3/	3.5.2	4.5.2.2 4/
	(3) Waterproofness	20	3/	3.5.3	4.5.2.2
	(4) Accuracy	50	3/	3.5.4	4.5.2.3
	(5) Action Time			3.5.5	4.5.2.4
	$-65^{o} \pm 5^{o}F$	20	3/		
	$145^{o} \pm 5^{o}F$	20	3/		
	(6) Function and Casualty			3.5.6	4.5.2.5
	$-65^{o} \pm 5^{o}F$	100	ACC-0 REJ-1		
	$145^{o} \pm 5^{o}F$	100	ACC-0 REJ-1		

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET 3 OF 5		DRAWING NUMBER
	Cartridge, 20mm, MPT-SD, M940 and Components 1/ 2/				SEE BELOW
					NEXT HIGHER ASSEMBLY
					Not Applicable
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Projectile Functioning				
	(1) Projectile Trace			3.6.1	4.5.3.1 5/
	-65° ± 5°F	100	ACC-0 REJ-1		
	145 ± 5°F	100	ACC-0 REJ-1		
	(2) Projectile Self-Destruct			3.6.2	4.5.3.1 5/
	-65° ± 5°F	100	ACC-0 REJ-1		
	145° ± 5°F	100	ACC-0 REJ-1		
	(3) No Arm Sensitivity			3.6.3	4.5.3.2
	-65° ± 5°F	16	ACC-0 REJ-1		
	70° _ 2°F	15	ACC-0 REJ-1		
	145° ± 5°F	16	ACC-0 REJ-1		

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET 4 OF 5		DRAWING NUMBER
	Cartridge, 20mm, MPT-SD, M940 and Components 1/ 2/				SEE BELOW
					NEXT HIGHER ASSEMBLY
					Not Applicable
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	(3) Arming Sensitivity			3.6.4	4.5.3.3 7/
	a. 210 yards				
	-65° ± 5°F	10	ACC-0 REJ-1		
	70° ± 2°F	10	ACC-0 REJ-1		
	145° ± 5°F	10	ACC-0 REJ-1		
	b. 2100 yards				
	-65° ± 5°F	10	ACC-0 REJ-1		
	70° ± 2°F	10	ACC-0 REJ-1		
	145° ± 5°F	10	ACC-0 REJ-1		
	(5) Detonation Delay			3.6.5	4.5.3.4 7/
	-65° ± 5°F	10	ACC-0 REJ-1		
	70° ± 2°F	10	ACC-0 REJ-1		
	145° ± 5°F	10	ACC-0 REJ-1		

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-C-70793(AR)

PARAGRAPH	TITLE: Cartridge, 20mm, MPT-SD, M940 and Components 1/ 2/		SHEET 5 OF 5		DRAWING NUMBER: SEE BELOW NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	(6) Fragmentation	29	ACC-0 REJ-1	3.6.6	4.5.3.5
	(7) Penetration		3/	3.6.7	4.5.3.6
NOTES:					

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

FOOTNOTES:

1/ MIL-STD-651 shall apply in defining and evaluating cartridge visual defects.

2/ Primed cases used in first article production shall be tested in accordance with paragraph 4.4.2.e.

3/ Failure of the cartridges to comply with the applicable requirement shall be cause for rejection of the first article quantity. Second sample not permitted.

4/ Velocity and pressure readings shall be recorded in a single test.

5/ In each temperature phase, projectile trace and projectile self-destruct are to be conducted simultaneously.

6/ Test may be conducted using same sample cartridges.

7/ Projectile sensitivity and detonation delay tests are to be conducted simultaneously.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.3.3 Rejection. See MIL-A-48078. Failure of the original first article sample to be in accordance with the applicable drawings and requirements of Table I, as specified herein will result in sample disapproval.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Cartridge cases from one interfix lot number from one manufacturer.

b. Projectiles from one interfix lot number from one manufacturer.

c. Primers from one interfix lot number from one manufacturer and no more than three lot numbers.

d. Propellant from one lot number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

b. Major and minor defects. To determine product acceptability, major and minor defects as listed herein may be considered collectively on a class basis or defects may be considered individually. When a class basis is utilized the Acceptable Quality Level (AQL) for major defects shall be 1.5 percent and the AQL for minor defects shall be 2.5 percent. However, when major defects are considered collectively on a class basis, the AQL for any individual defect shall be limited to .40 percent. In addition, where three or less defects appear in a classification sampling plans applicable to a class shall not be used for major defects (see 6.9).

c. Critical defect. If a critical defect is found the contractor shall determine the cause of the defect and submit to the contracting officer, his report of findings and corrective action taken to preclude recurrence of such defects. The government shall suspend production of all units until the contractor's Failure Analysis Report is submitted to the government and corrective action taken.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

d. Cartridge. Each cartridge shall be inspected in process for chamber gage failure (profile and alignment, max). Cartridges which fail to meet the requirement of 3.2 shall be removed.

e. Primed cartridge cases. Each primed cartridge case shall be tested in process for electrical resistance subsequent to primer crimping and waterproofing, using the method of 4.5.1.4.a Primed cases which fail to meet the requirement of 3.4 shall be removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Projectile Body Assembly, Tracer	1 OF 1	12551774
			NEXT HIGHER ASSEMBLY 12551770

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	.06 depth from metering disc seat to tracer igniter, max. (prior to insertion of seal and metering disc) ($\bar{X}$ & R Chart)		100%	3.2	AAIE 4.4.6.1/ SPC 4.4.4
2.	Seal missing or perforated (P-Chart)		100%	3.2	AAIE 4.4.6.1/ SPC 4.4.4
Major					
101.	.06 depth from metering disc seat to tracer igniter, min (prior to insertion of seal and metering disc		.25	3.2	Gage
102.	Metering disc missing		.25	3.2	Visual
103.	Metering disc crimp defective		.25	3.2	Visual/Manual
104.	Foreign matter		.25	3.8.2	Visual
105.	70000 to 90000 psi, tracer mixture consolidation pressure ($\bar{X}$ & R Chart)			3.2	Gage/SPC 4.4.4
106.	70000 to 90000 psi, tracer and igniter mixtures consolidation pressure ($\bar{X}$ & R Chart)			3.2	Gage/SPC 4.4.4
Minor					
201.	Poor workmanship		.65	3.8	Visual

NOTES: 1/ If the crimp closure is not pressed tightly against the metering disc for 360° or the metering disc can be moved manually, the assembly shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 12551770
4.4.2.2	Projectile Body Assembly, Charged				NEXT HIGHER ASSEMBLY 12551768
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	.525 depth, mouth to incendiary mix		100%	3.2	Gage
102.	.865 depth, mouth to HE mix		.25	3.2	Gage
103.	33,000 PSI, propellant and comp A-4 consolidation pressure ($\bar{X}$ & R Chart)			3.2	Gage/SPC 4.4.4
Minor					
201.	Poor workmanship		.65	3.8	Visual.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2025-10-25T10:43:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Nose Assembly, Charged		12551772
			NEXT HIGHER ASSEMBLY 12551768

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101.	.218 height of third incendiary increment		.25	3.2	Gage
102.	12500 psi, first increment consolidation pressure ($\bar{X}$ & R Chart)			3.2	Gage/SPC 4.4.4
103.	13500 psi, second increment consolidation pressure ($\bar{X}$ & R Chart)			3.2	Gage/SPC 4.4.4
104.	7000 psi, third increment consolidation pressure ($\bar{X}$ & R Chart)			3.2	Gage/SPC 4.4.4
Minor					
201.	Poor workmanship		.65	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:00Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Projectile 1/				12551768
					NEXT HIGHER ASSEMBLY 12551767
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1.	Crack in projectile (P-Chart)		100%	3.2	AAIE 4.4.4.6.1/ SPC 4.4.4
Major					
101.	Loose nose		.25	3.2	Manual
102.	.015 runout nose to datum -A-		.25	3.2	Gage
103.	2.597 max, nose to rear of rotating band		.25	3.2	Gage
104.	3.775 max, overall length		.25	3.2	Gage
Minor					
201.	.007 max gap between nose and body		.40	3.2	Gage
202.	Protective coating damaged or incomplete		.40	3.2	Visual
203.	Poor workmanship		.65	3.8	Visual

NOTES: 1/ MIL-STD-651 shall apply in defining and evaluating cartridge visual defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.5	Cartridge, 20mm MPT-SD, M940 1/		1 OF 2		12551767
					NEXT HIGHER ASSEMBLY: Not applicable
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Split or perforated case (P-Chart)		100%	3.2	AAIE 4.4.6.1/ SPC 4.4.4
2	Case to projectile crimp missing (P-Chart)		100%	3.2	AAIE 4.4.6.1 SPC 4.4.4
Major					
101	Chamber gage failure (profile and alignment, Max)		.25	3.2	7555162
102	.002 Depth of primer seating		.25	3.2	7296962
103	6.615 Total length, max		.25	3.2	Gage
104.	Improper or incomplete crimp (case-projectile)		.25	3.2	Visual
105.	Corrosion		.25	3.2	Visual
106.	Head configuration		.25	3.2	Visual
107.	Metal sliver(s) on head face		.25	3.2	Visual
108.	Loose primer		.25	3.2	Manual
109.	Inverted primer		.25	3.2	Visual
110.	Crack, split or dent in nose cap		.25	3.2	Visual

NOTES: 1/ MIL-STD-651 shall apply in defining and evaluating cartridge visual defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 12551767
4.4.2.5	Cartridge, 20mm MPT-SD, M940 1/				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201.	Waterproofing missing around primer		.40	3.2	Visual
202.	Lacquer on primer button		.40	3.2	Visual
203.	Primer crimp missing or incomplete		.40	3.2	Visual
204.	Rotating band damaged		.40	3.2	Visual
205.	Cartridge case damaged		.40	3.2	Visual
206.	Marking misleading or unidentifiable		.40	3.2	Visual
207.	Projectile protective coating damaged or incomplete		.40	3.2	Visual
208.	.007, max. gap between nose and projectile body		.40	3.2	Gage
209.	Foreign matter, except corrosion		.40	3.2	Visual
210.	Poor workmanship		.65	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.6	Cartridge, 20mm MPT-SD, M940 1/ (Test Requirements)		3 of 3	12551767
				NEXT HIGHER ASSEMBLY: Not applicable

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Non-functioning				
	(1) Projectile extraction	20	4.4.3.1	3.2.1	4.5.1.1/11075126/7259443
	(2) Projectile torque	20	4.4.3.2	3.2.2	4.5.1.2/7259424
	(3) Propellant contamination/ charge weight verification	20	ACC-0 REJ-1	3.3	4.5.1.3
	(4) Electrical resistance of primed case, verification	20	ACC-0 REJ-1	3.4	4.5.1.4
	Cartridge Functioning		4.4.3.3		4.5.2.1
	(1) Velocity	20	4.4.3.4	3.5.1	4.5.2.2
	(2) Pressure	20	4.4.3.5	3.5.2	4.5.2.2
	(3) Waterproofness	20	4.4.3.6	3.5.3	4.5.2.2
	(4) Accuracy	50	4.4.3.7	3.5.4	4.5.2.3
	(5) Action time			3.5.5	4.5.2.4
	-65° + 5°F	20	2/		
	145° + 5°F	20	2/		

NOTES: 1/ MIL-STD-651 and Dwg. 7258001 apply in defining and evaluating cartridge visual defects

2/ Failure of the cartridges to comply with the applicable requirement shall be cause for rejection of the lot.

3/ 210 yard arming sensitivity and detonation delay tests are to be conducted simultaneously.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE			SHEET 2 OF 3	DRAWING NUMBER 12551767
4.4.2.6	Cartridge, 20mm MPT-SD, M940 1/ (Test Requirements)				NEXT HIGHER ASSEMBLY Not applicable
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	(6) Function and Casualty				
	-65° + 5°F	100	4.4.3.10	3.5.6	
	145° ± 5°F	100	4.4.3.10	3.5.6	
	Projectile Functioning				
	(1) Projectile Trace			3.6.1	4.5.3.1
	-65° + 5°F	100	4.4.3.8		
	145° ± 5°F	100	4.4.3.8		
	(2) Projectile Self-Destruct			3.6.2	4.5.3.1
	-65° + 5°F	100	4.4.3.8		
	145° ± 5°F	100	4.4.3.8		
	(3) No Arm Sensitivity		4.4.3.11	3.6.3	4.5.3.2
	-65° + 5°F	6			
	70° ± 2°F	6			
	145° ± 5°F	6			

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-01-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-70793(AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
4.4.2.6	Cartridge, 20mm MPT-SD, M940 1/ (Test Requirements)				12551767
					NEXT HIGHER ASSEMBLY: Not applicable
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	(4) 210 Yard Arming Sensitivity		4.4.3.9	3.6.4	4.5.3.3 3/
	-65° ± 5°F	5			
	70° ± 2°F	5			
	145° ± 5°F	5			
	(5) Detonation Delay		4.4.3.9	3.6.5	4.5.3.4 3/
	-65° ± 5°F	5			
	70° ± 2°F	5			
	145° ± 5°F	5			

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-28 04:30:24
Check the source to verify that this is the current version before use.

4.4.3 Tests. The tests listed in 4.4.2.6 shall be performed on each cartridge lot in accordance with the test methods prescribed in 4.5. Sample size and acceptance criteria for each test shall be as specified. Only cartridges which have met the visual and dimensional requirements and which have been selected in such a manner that the sample is representative of the entire lot shall be used in the tests. The selected cartridges shall be mixed thoroughly before being divided into samples for the various tests.

4.4.3.1 Projectile extraction.

a. Failure of two or more sample cartridges to comply with the minimum requirement shall cause rejection of the lot. If one cartridge of the sample fails to comply with the minimum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if two or more cartridges of the combined sample fail to comply with the minimum requirement.

b. Failure of four or more cartridges to comply with the maximum requirement shall be cause for rejection of the lot. If more than one but less than four cartridges fail to comply with the maximum requirement, a second sample of 20 cartridges shall be tested. The lot shall be rejected if five or more cartridges of the combined sample fail to comply with the maximum requirement.

4.4.3.2 Projectile torque. Failure of two or more of the sample cartridges to comply with the specified torque requirement shall cause rejection of the lot. If one cartridge of the sample fails to comply, a second sample of 20 cartridges shall be tested. The lot shall be rejected if two or more cartridges of the combined samples fail to comply with the applicable requirement.

4.4.3.3 All cartridge firing tests. The lot shall be rejected if in any firing test one or more of the following casualties occur:

a. Misfire associated with e or f of 6.10.

b. Projectile remaining in bore.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

c. Metal parts separation, except rotating band separation. (See 6.11.1).

d. Premature projectile functioning (see 6.15).

4.4.3.4 Velocity. If the sample fails to comply with either or both requirements a retest sample of 40 cartridges shall be tested. The lot shall be rejected if the retested samples fails to comply with the applicable requirement(s) (see 6.7).

4.4.3.5 Pressure. If the average pressure ($\bar{X}$) plus 0.84 times the average range ($\bar{R}$) of the sample cartridges exceeds 51,000 psi a retest sample of 40 cartridges shall be tested. The lot shall be rejected if the average pressure ($\bar{X}$) plus 0.91 times the average range ($\bar{R}$) of the retest sample fails to comply with the applicable requirements (see 6.8).

4.4.3.6 Waterproofness. If the average velocity (wet) of the sample fails to comply with the applicable requirement, a retest sample of 40 cartridges shall be tested. The lot shall be rejected if the average velocity (wet) differs by more than 100 fps from the average velocity (dry) of 40 additional sample cartridges fired to establish a new base for comparison. The lot shall not be penalized for failure of the last named sample cartridges to comply with the requirements of 3.5.3.

4.4.3.7 Accuracy. If the average mean radius of the sample cartridges exceeds the applicable requirement, a retest sample of 100 cartridges shall be tested. The lot shall be rejected if the average mean radius of 10 retest accuracy targets exceeds the applicable requirements (see 3.5.4).

4.4.3.8 Projectile self-destruct and trace. For acceptance, each temperature phase shall be considered individually. Failure of 12 or more sample cartriges to comply with the requirement shall cause rejection of the lot. If more than eight and less than 12 cartridges of the sample fail to comply with the requirement, a second sample of 100 cartridges shall be tested for that temperature phase. The lot shall be rejected if 11 or more cartridges of the combined sample fail to comply with either test requirement.

4.4.3.9 Projectile arming sensitivity and detonation delay. For acceptance, all temperature phase shall be considered collectively. Failure of three or more sample cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If two samples fail to comply, a second sample of 15 cartridges shall be tested. The lot shall be rejected if five or more cartridges of the combined samples fail to comply with the applicable requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4.3.10 Function and casualty. Two-hundred cartridges shall be subjected to this test. The lot shall be rejected if, at any time, any of the following occurs:

a. Any fire "out of battery" (See 6.11.2).

b. Any primer misfires. (See 6.10)

c. Any cartridge case fails to extract.

d. Any cartridge case longitudinal split occurs (L or M) (Dwg. 7258801).

e. Any cartridge case circumferential rupture, partial (L) or complete (Dwg. 7258801).

f. Any detached metal from cartridge case occurs (See 6.11.3).

g. Any cartridge fails to chamber.

In addition, if defects occur listed in Table II, equal to or less than the "ACC" number, the lot shall be accepted. If any defect(s) occur equal to or exceeding the "REJ" number, the lot shall be rejected. If any defect(s) occur in excess of the "ACC" number, but less than the "REJ" number, a second sample of 400 cartridges shall be selected and fired in the M168 or M61 automatic cannon. The lot shall be rejected if any defect occurs equal to or greater than the "CUMULATIVE REJ" number.

4.4.3.11 Projectile no arm sensitivity. For acceptance, all temperature phases shall be considered collectively. Failure of three or more sample cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one sample fails to comply, a second sample of 18 cartridges shall be tested. The lot shall be rejected if four or more cartridges of the combined samples fail to comply with the applicable requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE II Firing Defects

		ACC	REJ	CUMULATIVE REJ
1.	Primer missing or button missing from primer	0	2	2
2.	Primer leak (see Note 1)	9	20	25
3.	Longitudinal case split (I or S) (Dwg. 7553663)	10	21	31
4.	Longitudinal case split (K) (Dwg. 7553663)	0	2	2
5.	Case circumferential rupture, partial (S, J, or K) (Dwg. 7553663)	4	9	11
6.	Longitudinal case split (J) (Dwg. 7553663)	4	9	11
7.	Projectile rotating band separation complete or partial separation having band seat knurling imprint. (See 6.11.4)	0	3	3
8.	Projectile rotating band separation having greater than 0.5 inch and without band seat knurling imprint. (See 6.11.4)	1	4	6

Note 1. For primer defect definitions, see AMCR 715-505, Volume 8, Chapter 1, Section 3, Paragraph 3.6.

4.4.4 Statistical process control (SPC). Acceptance shall be in accordance with the government approved SPC plan. The SPC plan shall be prepared by the contractor in accordance with the Appendix of this specification. The SPC plan shall include as a minimum:

a. A control chart for the percentage of defective units (P-Chart) (attribute data) or the average and range ($\bar{X}$ and R Chart) (variable data) as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

b. Control Charts that comply with American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3.

c. Use of Shewhart's eight tests for special causes to determine an out of control process.

d. Action to be taken when the process capability (CP) and Process Capability Index (CPK) is less than the value 1.33.

The contractor shall submit for approval a SPC plan in accordance with the terms of the contract.
See Section 6.14 herein.

4.4.5 Packaging, packing and marking. Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644.

4.4.6 Inspection equipment. The inspection equipment required to perform the tests and examination prescribed herein is described in the Paragraph Reference/Inspection Method Column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.12 herein.

4.4.6.1 Automated acceptance inspection equipment (AAIE). AAIE shall be used to perform all critical defect examination and tests prescribed herein. AAIE shall be in accordance with MIL-A-70625 and approved by the government.

4.5 Methods of inspection.

4.5.1 Non-functioning.

4.5.1.1 Projectile extraction. The cartridge shall be placed in the applicable fixture specified herein and the tension force specified shall be applied. The projectile must separate from the cartridge case in the range specified. The method of test shall be as specified in AMCR 715-505, Volume 8, Chapter 1, Section 10. This is a destructive test.

4.5.1.2 Projectile torque. The cartridge shall be marked with a light scratch extending axially across the nose, body, rotating band and onto the case neck. Then the cartridge shall be placed in the applicable fixture specified herein and the inch pound torque shall be applied slowly to the projectile. Observation shall be made for movement of the projectile with respect to the misalignment in the scratch mark. This test is a non-destructive test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.1.3 Propellant contamination and charge weight verification. After completion of test specified in 4.5.1.1, each of the cartridges tested shall be examined visually for contamination as described in AMCR 715-505, Volume 8, Chapter 1, Section 10. The charge from each of the sample cartridges shall be weighed.

4.5.1.4 Electrical resistance.

a. Electrical resistance of primed case. The primed case shall be tested for the applicable requirement using Government approved equipment and circuitry specified on dwg. 11075284 to measure the resistance of the primer.

b. Verification. A Simpson volt-ohm-ammmeter, Model 260, or approved equivalent shall be used to measure the resistance of the primer in each primed cartridge case from the projectile extraction test. Only the RX100 and RX10,000 scales of the meter shall be used in order to limit the applied voltage and current respectively to 7.5 volts and 1.4 millamperes, maximum.

4.5.2 Cartridge functioning.

4.5.2.1 Ammunition conditioning. The cartridges shall be conditioned for a period of not less than six (6) hours after the conditioning chamber has stabilized at the specified test temperature. Timing for the conditioning period shall start when the chamber has stabilized following the sample being place in the conditioning chamber.

4.5.2.2 Velocity, pressure and waterproofness. These tests shall be conducted in accordance with AMCR 715-505, Volume 8, Chapter 1, Section 2. Standard deviation and range shall be computed in accordance with 6.7 and 6.8 respectively.

4.5.2.3 Accuracy. The method of test and measurement of targets shall be in accordance with AMCR 715-505, Volume 8, Chapter 1, Section 4. The specified range may be shortened in decrements of 100 yards, to a minimum range of 200 yards. For ranges less than 600 yards, the average mean radius shall be reduced in direct proportion to the reduction in range. Any variation from the 200 yard range requires direct proportional adjustment of the average mean radius.

4.5.2.4 Action time. The method of test shall be as prescribed in AMCR 715-505, Volume 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.2.5 Function and casualty. The method of testing shall be in accordance with AMCR 715-505, Volume 8, Chapter 1, Section 3. The test sample shall be fired in bursts of 50 cartridges in the M168 or M61 cannon. The weapon barrels shall be at ambient temperature at the beginning of the test and cooled to ambient after each 100 rounds.

4.5.3 Projectile functioning.

4.5.3.1 Projectile trace and self-destruct. Projectile trace and self-destruct tests shall be conducted simultaneously. The method of test shall be as specified in AMCR 715-505, Volume 8, Chapter 1, Section 8. Projectile trace and self-destruct time shall begin at cartridge ignition and continue until end of the tracer burn or at self-destruct, whichever comes first. Observation shall be from near the gun position.

4.5.3.2 No arm sensitivity. The no arm sensitivity test shall be conducted by firing the sample cartridges from a test barrel at a six inch by six inch, .040 inch thick rigid aluminum (2024-T3) target plate located 39 + 1 inches from the muzzle of the barrel 0° obliquity (NATO). Arming of the fuze shall be determined by the placement of an .080 inch thick aluminum (2024-T3) detonation plate located a minimum of 210 $\pm$ 10 yards from the muzzle of the barrel. Observation shall be made for functioning on the target plate or the detonation plate.

4.5.3.3 Arming sensitivity. The sensitivity test shall be conducted by firing the sample cartridges at a .080 inch 2024-T3 aluminum target plate. No impact shall be less than 3 calibers from the edge of the sheet or less than 1 caliber between holes. Cardboard witness panels shall be placed at 4 and 6 feet behind the target plate. A valid projectile function is defined as a fragment signature on the witness panels indicating projectile breakup.

4.5.3.4 Detonation delay. The detonation delay shall be measured by plate array. The detonation delay on a multiplate array is determined by placing corrugated cardboard sheets at 4 feet and 6 feet behind the target plate and tracing a minimum of 3 fragment paths back to the center of detonation. The detonation plate shall be 0.080 inch thick 2024-T3 aluminum and shall meet the requirements of 3.6.5. Premature detonation is considered to be the occurrence of any of the following:

a. Any detonation within the weapon.

b. Any detonation within 200 feet of uninterrupted flight from the weapon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.5.3.5 Fragmentation. The fragmentation test shall utilize a 10 plate multiple plate target with an 0.080 inch thick detonation plate of 2024-T3 aluminum placed 210 ± 10 yards from the muzzle. The nine witness sheets shall be placed 8 inches apart. The witness sheets shall be 0.040 inch thick 2024-T3 aluminum. The last witness sheet shall be 72 inches from the detonation plate (see 3.2.11). Cartridges shall be conditioned at 70° ± 2°F and fired from a test barrel.

4.5.3.6 Penetration. The R_{50} shall be determined by the Langile Sampling Techinque. All cartridges shall be conditioned at 70 ± 2°F and fired from a test barrel. The position of the target shall be varied in order to obtain the desired target range. All cartridges will be tested at service velocity. For each target, estimate an upper and lower limit of range that will provide a reasonable certainty that the R_{50} will occur somewhere between these selected limits. Fire the first cartridge at the target positioned at a range midway between these two limits. Continue testing using the paragraph 5.1.1.2 TECOM TOP 2-2-710 until the R_{50} is statistically established. A .040 inch aluminum (2024-T3) witness panel shall be positioned six inches behind an parallel to the target to determine if penetration has occurred.

4.5.4 Defective weapon. If a test weapon fails to comply with the minimum cyclic rate during a normal burst operation or is found to be defective during or at the end of burst, the test shall be suspended and Government approval sought for a new test. The cyclic rate of each burst shall not be less than 3,000 shots per minute in the gun. The cyclic rate for each burst shall be recorded.

4.5.5 Test validity. If for any reason the test activity considers that the test conditions have detrimentally affected the test results, the test activity may request the Government to declare the test invalid and authorize a new test.

5. PACKAGING

5.1 Preservation and packaging. The M940 cartridge shall be preserved and packaged in accordance with Dwg. 7258969.

5.2 Unitization. The packed containers shall be unitized in accordance with the instructions from the procuring agency.

5.3 Marking. Marking of the packed container shall be in accordance with Dwg. 7258928.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This specification covers the loading, assembling and packing for Cartridge, 20MM, Multipurpose, Trace Self-Destruct, M940 for use in the M168 automatic cannon systems which are designed to utilize electric primed cartridges with M103 type case.

6.2 Acquisition requirements. See MIL-A-48078.

6.3 Submission of test data. In addition to the normal distribution of records, when the cartridge is procured by AMCCOM, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commander, U.S. AMCCOM ATTN: AMSMC-QAF-A (D) and SMCAR-CCL-CE, Picatinny Arsenal, NJ, 07806-5000.

6.4 Safety data. For the safety data requirements refer to Safety Data Document as listed on Product Drawings.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, U.S. Army Armament Research and Development Command (ARRADCOM) or U.S. Army Armament Reasearch and Development (ARDC) drawings. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.6 Process deviation. A process deviation is defined as a change in the approved basic method of manufacture, or an operational change which may alter the metallurgical or physical properties of the item.

6.7 Standard deviation. Standard deviation shall be calculated from the following formula or other approved formula:

$$S = \sqrt{\frac{\Sigma(X_i - \bar{X})^2}{n-1}}$$

where:

X_i	=	Each individual value
$\bar{X}$	=	Sample arithmetic mean
n	=	Sample size

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

6.8 Range plan. Where a range plan is specified, the individual values shall be recorded in subgroups of 5 in the order in which they are observed. The ranges for the subgroups shall be added and the sum of the ranges shall be divided by the number of subgroups to determine the average range ($\bar{R}$).

6.9 Intermediate point inspection. The classification of defects identifies the defect characteristics for acceptance inspection. It may be necessary to modify the sequence of inspection stations to best suit the manufacturing process. Inspection for defect characteristics which will be hidden or altered by subsequent processing operations (including unrelated operations), should be scheduled to prevent premature acceptance which could be detrimental to the attainment of optimum product quality of the end item.

6.10 Misfires. Misfiring test cartridges, except those from the waterproofness test shall be retested in equipment identified in the accuracy test. If a cartridge fails to function in that test, examinations shall be conducted for the following conditions:

a. Excessive primer seating depth.

b. Metal slivers across primer insulator.

c. Electrical continuity.

d. Missing or obstructed case vent.

e. Missing or insufficient primer composition or propellant.

f. Partially burned or contaminated primer composition or propellant.

The lot shall not be penalized if condition a. is observed. However, this condition shall be reported for information. The "Acc" number shall be zero (0) and the "Rej" number 3, for misfires associated with conditions b, c, or d. The second sample for evaluation of misfires associated with conditions b, c, or d shall consist of the function and casualty second sample (see 4.4.3.10). The lot shall be rejected if either condition e or f is observed. Misfire(s) occurring in the waterproofness test shall be handled in accordance with AMCR 715-505, Volume 8.

6.11 Defect definitions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

6.11.1 Metal part separation. Separation or breakup of projectile part(s), except rotating band separation, as evidenced by recovery of the part(s) or fragment(s), or hole(s) in the fragmentation screen(s).

6.11.2 "Out of battery". A cartridge shall be classed defective if it fires, due to delayed ignition, after the bolt has been unlocked and extraction has been initiated or completed.

6.11.3 Detached metal from cartridge case. Metal sheared or missing from the fired cartridge case exterior, such as rim or neck shears. Shavings of metal from the interior wall of the case neck, in the crimped area, shall not be considered as detached metal.

6.11.4 Rotating band separation. For classification as a defect, there must be evidence by recovery of the band, or portion thereof, or by hole(s) in the fragmentation screen(s). Normal band fringing or slivering shall not be classed as a defect.

6.12 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ARDEC, ATTN: AMSMC-QAF-A (D), Picatinny Arsenal, NJ, 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, Data Item DI-R-1714 will apply.

6.13 Firing tests. In order to minimize inspection costs, the firing tests of 4.4 will be performed after the sample has been provisionally accepted by the Government for all other requirements. Additional cartridges may be required by the test facility.

6.14 Submission of SPC plan for approval. Submit SPC plan as required to Commander, ARDEC, ATTN: AMSMC-QAF-A (D), Picatinny Arsenal, NJ 07806-5000.

6.15 Premature burst. A premature burst is considered to have occurred if the round functions in the gun bore or during uninterrupted flight at a distance less than 200 yards from the gun muzzle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

6.16 Subject term (key words) listing.

Multipurpose
Ammunition
Armor Piercing Ammunition
Bursting Charges
Cartridge Cases
Electric Primers
Explosives
Incediary Ammunition
Nose Fuzes
M940
Projectiles
MP-T-SD
Small Arms Ammunition
20 millimeter
Trace
Self-Destruct

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1305-AD13)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

APPENDIX

PREPARATION OF STATISTICAL PROCESS CONTROL PLANS

10. SCOPE

10.1. Scope. This document is intended to serve as a guide to the preparation of statistical process control (SPC) plans by government contractors. It identifies the minimum amount of information deemed necessary to adequately describe an SPC program. But the contractor is encouraged to include whatever additional information he feels will further clarify his particular situation. A specific format for the SPC plan is proposed, mainly for the purpose of standardization. The contractor is free to vary this format, provided all information called for is included and clearly identified.

10.1.2 Application. It is the intent to require an SPC plan from a contractor under the following circumstances:

a. When called for in a contract through an "E-clause".

b. When called for in the Quality Assurance Provisions of a Military Specification.

c. Whenever a situation requires intensive control of quality.

10.1.3 Organization. This document is organized as follows:

SECTION I: Preparation of SPC Plan by Contractor

PART A: SPC Management Plan
PART B: Detailed SPC Plan

20. APPLICABLE DOCUMENTS

20.1 Government documents

20.1.1 Specifications, standards, and handbooks.

MIL-Q-9858 - Quality Program Requirements

30.0 REQUIREMENTS

This section is not applicable to this appendix.

40.0 SECTION I: PREPARATION

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

APPENDIX

40.1 General. The Government's intent to institute SPC in order to improve the quality of the materiel it procures will only be successful through a joint cooperative effort between the contractor and those government personnel responsible for monitoring the SPC program in question. This effort is substantially aided by formal documentation of the contractor's general SPC policies and his procedures specific to the item being procured. Such a document, to be called the SPC Plan, serves to insure that the interests of both the contractor and the government are protected. It may reveal where additional guidance by the government Product Quality Manager (PQM) may be needed. The SPC Plan, therefore, is a major source document in an SPC program and must be carefully prepared and reviewed.

40.2 Relation to MIL-Q-9858 and quality program plan. Nothing in this document is to be taken as superceding the provisions of MIL-Q-9858, which remains as the primary document governing contractor quality programs. Similarly, SPC Plans are to be considered an integral part of the contractor's overall Quality Program Plan (QPP). The purpose of calling for a separate document for the SPC portions of the quality program is to facilitate the evaluation of the provisions therein and to highlight the use of statistics in controlling production. Information from the overall QPP may in fact be repeated in the SPC Plan, but only in that the information relates specifically to SPC.

40.3 Format. This document calls for an SPC Plan in two parts. These two parts are the SPC Management Plan and the Detailed SPC Plan. Each part of the SPC Plan is described separately in the paragraphs that follow. In each case, though, specific information will be asked for in a specific order. This information should be regarded as not exhaustive, in the sense that it is the minimum amount of information deemed necessary to adequately describe that portion of the SPC Plan. In some cases, the information asked for will not be applicable. In such cases, the contractor shall indicate why that information does not apply. Furthermore, the contractor is encouraged to include whatever additional information is felt will further explain the policies and procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

APPENDIX

50. PART A: SPC MANAGEMENT PLAN

The intent of the SPC Management Plan is to provide an overview of the contractor's SPC involvement, without reference to any specific materiel item or manufacturing process. It should be a relatively brief, stand-alone document and if necessary may repeat information in the general QPP.

The contractor shall include in the SPC Management Plan a paragraph dealing with each of the following topics, including information sufficient to allow an evaluator to assess the Plan without resort to any other sources:

50.1 Policy/scope.

a. Applicability. The contractor shall discuss the policies for applying SPC, including:

- What are contractor's goals and commitments regarding SPC?
- What criteria are used to decide when SPC shall be applied?
- What alternatives to SPC have been used which have successfully reduced/prevented the production of defects?

b. Applicable documents. The contractor shall indicate the prime source documents that form the basis of the SPC Program, including ANSI/ASQC standards, text books, government documents, internal documents, etc.

50.2 SPC management structure.

a. Internal organization. The contractor shall discuss the nature of the SPC structure within the corporation, including the relationship of quality to manufacturing and to the overall organizational structure.

b. SPC responsibilities. The contractor shall discuss the responsibilities of specific positions within the SPC structure. (Individuals are not to be named, only the positions.) The discussion shall be of the nature of who does what when. Typical responsibilities to be addressed shall include:

- Who performs inspections?

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

- Who has authority for acting on problems?
- Who decides on corrective action?
- Who implements the corrective action?
- Who performs audits?

50.3 SPC training. The contractor shall discuss the nature and extent of the training program for SPC. Included should be the general policy for who receives training, how much, and where. Indicate whether training is at a university, trade school, or in-house. If certain disciplines receive different types of training (such as management vs. manufacturing), this should be made clear. Discuss any formal certification or qualification programs that exist, either for individuals or for the company as a whole.

If no formal training program currently exists, discuss any plans to implement one in the future.

50.4 Vendor, subcontractor/purchase controls. The requirement to implement a formal SPC Program extends beyond those manufacturing processes over which the contractor has direct control. This requirement must be passed to all subcontractors and vendors with whom the contractor deals in the manufacture of this item. In this regard, the contractor shall discuss the policy for ensuring the use of SPC by the suppliers or subcontractors. How consistent are the vendor's procedures with the contractor's? How is it determined that suppliers have adequate controls and what degree of influence does the contractor have in modifying those controls? What provisions exist for the contractor to audit the procedures and records of subcontractors and vendors?

50.5 Manufacturing controls. SPC involves tracking performance characteristics of the product for the purpose of assessing the stability of the process. An out-of-control condition requires positive feedback to some facet of the manufacturing process in order to make the necessary adjustments. A definite portion of those adjustments relate to the manufacturing equipment itself, as opposed to raw material, personnel, or some other category. With regard to this relationship between SPC and the manufacturing equipment, the contractor shall discuss his procedures for implementing the required adjustments. Attention should be paid

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

to frequency of setup, calibration, and verification. If automatic monitoring of process parameteres is used for feedback/control, is such a procedure used in lieu of SPC? Are engineering studies performed to eliminate or minimize the influence of process variation on product quality?

50.6 General SPC procedures.

50.6.1 Criteria for use of SPC. Experience has shown that SPC can effectively be applied under specific circumstances. The contractor shall discuss the criteria used to evaluate whether a particular product would benefit from SPC. Include any relationships to volume of production, classification of defects (critical/special/major/minor), degree of automation, etc. Whenever traditional SPC is not applied, what alternative procedures are used to assure quality?

50.6.2 Process capability studies. Normally, control charts are not implemented on a process until a formal capability study has been performed. The contractor shall discuss the general procedures for conducting process capability studies, especially the following topics:

- When are they used and when not?
- What is the duration of the study, in terms of sampling occasions?
- What is the timing of the study, in relation to scheduled startup of production?
- What general criteria are used for determining capability?
- What definitions of good, marginal and poor capability are generally used?
- If a process ever proves to be other than highly capable, what actions are taken?
- What steps are used to determine the true nature of the statistical distribution of the process?

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

APPENDIX

50.6.3 Control chart policy. With respect to the design and utilization of SPC control charts, the contractor shall discuss the general policies and procedures, including among others the following topics:

- What types of charts are generally used and what rationale is used for their selection?
- How are control limits established? How are they adjusted? How often are they adjusted?
- What combination of criteria are used to trigger an out-of-control signal? What criteria are used to determine non-conforming product?
- What criteria are used for the selection of sample size and frequency of sampling occasions? How are these related to production rate?
- How are control charts maintained in the instance of redundant operations, i.e. where output from identical machine or stations is potentially mixed?
- What is the policy for establishing rational subgroups?
- Has an SPC corrective Actions/Failure Analysis Program been established? Are any of its details different from those already discussed under paragraph 50.2.b (SPC Responsibilities) above?
- What provisions are in place for recording on control charts all pertinent ancillary information, such as changes in raw material supply, etc.?

50.6.4 SPC computer hardware/software. The contractor shall detail the extent to which computerized data processing and analysis ae used in his SPC effort.

- Which steps of the control process are computerized?
- Are the computer programs constant and fixed, or are they customized for each application?

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

- Are computers used to make the actual decisions, or only to aid in the production of charts and reports?

- Are computer services centralized, or does each application have access to its own facilities?

50.7 Test/measurement equipment control. Controlling a process through repeated and frequent measurement of product requires a stable and accurate test and measurement system. The contractor shall explain any provisions for determining and maintaining the reliability of test and measurement equipment, when used in an SPC environment. Are different calibration and control procedures used than for equipment not involved in SPC? Is calibration information recorded on the pertinent control charts?

50.8 SPC auditing and review procedures. A major element of an SPC Program is the systematic audit and review of all critical decision points. The contractor shall discuss his provisions for performing regular audits and reviews, especially in the following areas:

50.8.1 Audit of inspection accuracy. How often and in what manner is the accuracy of inspection equipment verified? How is intervening material disposed of whenever it is found that inspection equipment has drifted?

50.8.2 Audit of control charting procedures. What provisions exist for determining the accuracy and adequacy of the control charts themselves and any subsequent decisions made based on these charts? If any discrepancies are found, how are they disposed of?

50.8.3 Reviews. How often are reviews of SPC procedures held? Who participates? Is management involved? What topics are discussed? How are proposed changes implemented?

50.9 SPC records. Thorough and efficient record-keeping is a vital facet of a responsive SPC Program. The contractor shall indicate the nature and extent of his SPC record-keeping effort, emphasizing the control and management aspects, such as who is in charge, how long are records kept, how often are they reviewed, etc. The discussion should include at least the following types of records:

a. Incoming Inspection

b. Manufacturing Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

c. Vendor/Subcontractor Inspection

d. Failure Reports (internal and external)

e. Corrective Action Reports

f. Control Charts

g. Scrap and Rework Reports

h. Lessons Learned, Recommendations and Feedback

60. PART B: DETAILED SPC PLAN

The contents of the Detailed SPC Plan shall describe the specific actions to be taken in order to provide SPC on all characteristics enumerated by the government. Aside from paragraph 60.1 (Generic Procedures), which is to be included only once, the intent and design of Part B is such that each paragraph is to be included as many times as is necessary to completely describe the Plan. In other words, paragraph 60.2 (Specifics) is to be included for each characteristic called for. Each such paragraph shall include a paragraph 60.2.2 (Process Identification) for each related process to be controlled. These paragraphs in turn shall include repeated paragraphs 60.2.2.(c) (Charts to be Maintained) for each individual control chart to be maintained for that process. The Detailed SPC Plan, then, can be viewed as a tree structure, beginning with a branch for each characteristic and ending with a leaf for each control chart. Table I illustrates the recommended structure for this part of the SPC Plan.

60.1 Generic procedures. The purpose of this general paragraph is to present only once all common information which would otherwise be repeated several times in embedded paragraphs. Typical information the contractor is to place here are the make and model of any computer system used throughout the line, any major software packages, any inspection equipment used at more than one location, etc. The contractor shall also make note of any unusual circumstances, such as if portions of the line are geographically disjointed from one another, if selected personnel are to work at more than one location, if portions of the line are used to manufacture other items other than under control of this contract, etc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

APPENDIX

60.2 Specifics. This paragraph, along with its related subparagraphs, is to be repeated for each characteristic cited for implementation of SPC. Each such repetition shall be clearly marked with the characteristic name to properly identify it.

60.2.1 Manufacturing system for characteristic X. The contractor shall provide a brief narrative description of all pertinent details of how this characteristic is manufactured. The description shall be sufficient to allow a reviewer unfamiliar with the item to properly assess the applicability of the control measures being proposed. Included shall be such information as chain of events, sequencing in relation to other characteristics, type and number of machines involved, location of manufacturing facility if separate from the rest of the line, tolerances maintained, etc. As a minimum, the following topics shall be addressed:

a. Production Machinery

(1) How many redundant tools/machines for this characteristic?

(2) How many redundant stations on each machine?

(3) Are machines fully automatic? Semi?

(4) What is designed production rate? Will machine run continuously or in batch mode?

(5) How many shifts per day? Length of shifts?

(6) How many operators are involved in relation to the number of machines?

(7) Is the source of each in-process part or subcomponent identifiable?

(8) Is this equipment dedicated to this one characteristic, or is it shared with other lines?

(9) What is the proposed frequency of tooling changes/adjustments/calibration?

b. Inspection System

(1) How many redundant machines?

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

(2) How many redundant stations on each machine?

(3) Is inspection fully automatic, semi-automatic, or manual? Likewise for gages.

(4) What is the designed inspection rate?

(5) How timely is the inspection in relation to manufacture?

(6) Is the inspection equipment operated on shifts comparable to the manufacturing equipment?

(7) Are the same personnel involved?

(8) Is the inspection system dedicated to this characteristic, or does it also do other tasks?

c. Is this characteristic produced in-house or is it contracted out? If produced by a subcontractor, who is it?

d. Capability study. Prior to implementation of SPC on a characteristic, a capability study must be conducted, the intent of which is to determine the relationship of the natural manufacturing tolerance to the specified drawing tolerance. The contractor shall discuss his proposed capability study for this characteristic, including at least the following topics:

(1) When is the study to be performed, in relation to award of contract?

(2) What sampling strategy is to be employed, in terms of occasions and sample sizes?

(3) How is the shape of the distribution determined?

(4) How is the standard deviation of the individuals calculated?

(5) What is to be done if normality does not apply?

(6) What criteria will be used to characterize capability?

(7) What will be done if the process proves to be not capable or not in control?

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

60.2.2 Process identification. Repeat this paragraph for each specific process to be controlled for the above characteristic.

a. Process name and rationale. The contractor shall identify the process to be controlled and present the rationale for its selection. Attention shall be paid to such elements as narrow tolerances, lack of redundancy, history of prior difficulty, etc.

b. Capability study. The contractor shall present the details of his proposed capability study activities for this process. Note that, in general, this is a different study than the one cited in paragraph 60.2.1.(d) above, although the same guidelines apply. The capability study on the characteristic itself will normally involve reference to firm specification tolerances, whereas the capability study on the process will usually involve informal in-process dimension tolerances.

Also to be included is any prior experience with this process that might aid in evaluating the control provisons proposed.

(c) Charts to be maintained. This paragraph is to be repeated for each distinct type of chart to be used for this process. The discussion shall address at least the following points:

(1) Type of chart, to include rationale for its selection, in terms of the particular situation intended to be detected.

(2) Number to be maintained, as a function of the number of machines involved, their interdependence and equivalence, etc.

(3) Sampling procedures, to include sample size, frequency, equipment involved, basis for determination of rational subgroups, etc.

(4) Establishment of control limits, to include size of data base used, techniques employed, frequency of review, etc.

(5) Out-of-control criteria to be applied, to include the particular combination proposed and any special priority assigned to any individual criteria.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

(6) Out-of-control action to be taken, to include relation to stopping production, recalling product, replacing tooling, etc. What are the responsibilities of the individual inspectors and line supervisors?

(7) Actions to be taken when non-conforming product is found, including what actions are taken at different limits to preclude continual production of questionable quality material.

TABLE I: Example of Structure of Detailed SPC Plan

The information presented here is to serve as a clarification of the intended structure of PART B: DETAILED SPC PLAN. It illustrates the recommended manner of imbedding each required subparagraph in its proper location.

XM1 WIDGET SPC PLAN
PART B: DETAILED SPC PLAN

B.1 Generic Procedures

B.2 Characteristic A

B.2.a Description of Characteristic A
B.2.b Process 1
B.2.b.(3) Chart X
B.2.b.(3) Chart Y

B.2.b Process 2
B.2.b.(3) Chart Z

B.2 Characteristic B

B.2.a Description of Characteristic B
B.2.b.(3) Chart X

B.2 Characteristic C

B.2.a Description of Characteristic C
B.2.b Process 1
B.2.b.(3) Chart X

B.2.b Process 2
B.2.b.(3) Chart X
B.2.b.(3) Chart Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Picatinny Arsenal, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-70793 (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.