INCH-POUND

MIL-K-70840 (AR)
26 May 1992

MILITARY SPECIFICATION

KIT, INSTALLATION, FOR ARMOR TILES M3, M4, M5, M6, M7 FOR THE M2A2/M3A2 BRADLEY FIGHTING VEHICLE SYSTEM (BFVS)

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provision and preparation for delivery for Kit, Installation for Armor Tiles, M3, M4, M5, M6, M7, for the M2A2/M3A2 BFVS.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 2350

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-171	- Finishing of Metal and Wood Surfaces
MIL-STD-1949	- Inspection, Magnetic Particle
MIL-STD-2219	- Fusion Welding for Aerospace Applications
MIL-STD-6866	Inspection, Liquid Penetrant

(Unless otherwise indicated copies of federal military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT DRAWINGS

12556221	- Clip
12556222	- Bar, Mounting
12576336	- Bracket, Mounting
12576358	- Kit, installation hardware, for tile, armor, M3, M4, M5, M6 & M7
12576365	- Guard, armor, tile, Front, left
12576366	- Guard, armor, tile, Front, right
12576367	- Guard, armor, tile, Center
12576368	- Guard, armor, tile, rear
12556299	- Bracket (long)
12556310	- Bracket (short)
12576359	- Screw, Fully Threaded
12576361	- Screw, Painted, Wiz Lock
12576362	- Screw, Fully Threaded
12576363	- Screw, Painted Head
12576364	- Washer Painted

SPECIAL PACKING INSTRUCTIONS

P12556221	- Clip for Tile, Armor M32nd M4
P12556222-1	- Bar, Mounting for Tile, Armor, M3 and M4
P12556222-2	- Bar, Mounting for Tile, Armor, M3 and M4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

P12556299 - Bracket, Mounting for Tile, Armor, M5
P12556310 - Bracket, Mounting for Tile, Armor, M5
P12576336 - Bracket, Mounting for Tile, Armor, M6 and M7
P12576345 - Washer, Special
P12576358 - Kit, Installation, Hardware, for Tile, Armor, M3, M4, M5, M6 and M7

P12576359 - Screw, Fully Threaded
P12576361 - Screw, Painted, Wiz Lock
P12576362 - Screw, Fully Threaded
P12576363 - Screw, Painted head
P12576364 - Washer, Painted
P12576365 - Guard, Armor Tile, Front, Left
P12576366 - Guard, Armor Tile, Front, Left
P12576367 - Guard, Armor Tile, Center
P12576368 - Guard, Armor Tile, Rear

(Copies of drawings and other publications required by manufacturers in connection with specified acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts. The parts shall comply with all requirements specified on the specified drawings (dwgs) and with all associated drawings and with all requirements specified in applicable specifications.

3.3 Welds. Welds shall be performed in accordance with MIL-STD-2219 by qualified operators and operations.

3.3.1 Weld inspection. Welds shall be inspected for discontinuities, porosity, and cracks in accordance with MIL-STD-1949 or MIL-STD-6866 as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

3.4 Protective finish. Unless otherwise specified, the exterior and interior of parts that require finishing shall be prepared and finished in accordance with drawings 12556221 12556222, 12556299, 12556310, 12576336, 12576365, 12576366, 12576367, 12576368 and MIL-STD-171 (as applicable).

3.5 Identification and marking. Identification and marking shall be in accordance with MIL-STD-129 and as specified on applicable drawings.

3.6 Workmanship. All plastic parts shall be fabricated from virgin resins in a thorough workmanlike manner. They shall be free of porosity, twist, warpage, heat marks, sinks, voids, cracks, chipped edges, burrs, bubbles, blisters, burn marks or other defects that would affect their serviceability. All metal parts shall be fabricated in a thorough workmanlike manner. They shall be free of burrs, chips, chipped edges, gouges, cracks, splits, surface defects, dirt, grease, oil, lacquer smears, and other foreign matter. The cleaning methods used shall not be injurious to any part, nor shall the parts be contaminated by any cleaning agent. All assemblies shall be assembled in a thorough workmanlike manner.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5 and all applicable drawings. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General Provisions. The requirements of MIL-A-48078 form a part of the quality assurance provisions of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (See 4.3).
b. Quality Conformance Inspection (See 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with Table I. The first article sample shall be of the same design as will be suitable for regular production. It shall be manufactured using the same materials, equipment, process and procedures for regular production. First article samples shall not be specifically selected as custom or marked in a way that cause the product quality to be different than what can be expected from regular production.

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I.

4.3.3 Rejection. See MIL-A-48078

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Kit Installation, for the Armor Tiles M3, M4, M5, M6, M7, for the M2A2/M3A2	SHEET 1 OF 2	DRAWING NUMBER See below
			NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH / INSPECTION METHOD REFERENCE
	Bar, Mounting (Dwg. (12556222) Examination for defects	10	3.2 / 4.4.2.1
	Bracket, Mounting (Dwg. (12556299) Examination for defects	10	3.2 / 4.4.2.2
	Bracket, Mounting (Dwg. 12556310) Examination for defects	10	3.2 / 4.4.2.3
	Bracket, Mounting (Dwg. 12576336) Examination for defects	10	3.2 / 4.4.2.4
	Clip (Dwg. 12556221) Examination for defects	10	3.2 / 4.4.2.9

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Kit Installation, for the Armor Tiles M3, M4, M5, M6, M7, for the M2A2/M3A2	SHEET 2 OF 2	DRAWING NUMBER See below
			NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Guard, Armor Tile, Front Left (Dwg. 12576365)			
	Examination for defects	10	3.2	4.4.2.5
	Guard, Armor Tile, Front Right (Dwg. 12576366)			
	Examination for defects	10	3.2	4.4.2.6
	Guard, Armor Tile, Center (Dwg. 12576367)			
	Examination for defects	10	3.2	4.4.2.7
	Guard, Armor Tile, Rear (Dwg. 12576368)			
	Examination for defects	10	3.2	4.4.2.8

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078 and the following as applicable:

4.4.1.1 Lot submission. The component and assembly of the installation kit shall be submitted in accordance with Table I and Table II.

4.4.1.2 Lot identification. Each lot of installation kits shall be identified in accordance with MIL-STD-1168.

4.4.2 Examinations and tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When specified herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II. Attributes sampling inspection

Lot Size	Inspection Levels					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

them in a written proposal submitted to the Government for evaluation (see 6.7). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Bar, Mounting		12556222
			NEXT HIGHER ASSEMBLY: M2/M3A2 BFVS

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Total length	V	3.2	Gage
102	Thickness	V	3.2	Gage
103	Length from end to mounting hole (3 places)	V	3.2	Gage
104	Diameter of hole (3 places)	V	3.2	Gage
105	Radius improper	V	3.2	Gage
Minor				
201	Protective finish incomplete or inadequate	VI	3.4	Visual
202	Evidence of poor workmanship	VI	3.6	Visual
203	Incorrect marking	VI	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Bracket, Mounting	1 OF 1	12556299
			NEXT HIGHER ASSEMBLY: M2/M3A2 BFVS

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Total length	V	3.2	Gage
102	True position of mounting hole (3 places)	V	3.2	Gage
103	Thickness of material	V	3.2	Gage
104	Profile of mounting hole (3 places)	V	3.2	Gage
105	Outside width	V	3.2	Gage
106	Outside height	V	3.2	Gage
107	Height of tab (after bending)	V	3.2	Gage
108	Weld incomplete or missing	V	3.3	Visual
109	Component loose or missing	V	3.2	Visual
Minor				
201	Protective finish incomplete or inadequate	VI	3.4	Test/Visual
202	Evidence of poor workmanship	VI	3.6	Visual
203	Incorrect marking	VI	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE		DRAWING NUMBER
4.4.2.3	Bracket, mounting	SHEET 1 OF 1	12556310
			NEXT HIGHER ASSEMBLY: M2/M3A2

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Total length	V	3.2	Gage
102	True position of mounting hole (2 places)	V	3.2	Gage
103	Thickness of material	V	3.2	Gage
104	Profile of mounting hole (2 places)	V	3.2	Gage
105	Outside width	V	3.2	Gage
106	Outside height	V	3.2	Gage
107	Height of tab (after bending)	V	3.2	Gage
108	Weld incomplete or misssing	V	3.3	Visual
109	Component loose or missing	V	3.2	Visual/Manual
Minor				
201	Protective finish incomplete or inadequate	VI	3.4	Visual/Test
202	Evidence of poor workmanship	VI	3.6	Visual
203	Incorrect marking	VI	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-K-70840

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Bracket, mounting	1 OF 1	12576336
			NEXT HIGHER ASSEMBLY: M2/M3A2 BFVS

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	True position of hole (2 places) prior to assembly of special nut	V	3.2	Gage
102	Diameter of hole, max (2 places), prior to assembly of special nut	V	3.2	Gage
103	Material thickness of tab, min	V	3.2	Gage
104	Height of tab	V	3.2	Gage
105	Position of hole at narrow (closed end)	V	3.2	Gage
106	Diameter of hole at narrow (closed end)	V	3.2	Gage
107	Radius between closed end and open end improper	V	3.2	Gage
108	Total length	V	3.2	Gage
109	Total width	V	3.2	Gage
110	Width across tab toward open end	V	3.2	Gage
111	Component loose or missing	V	3.2	Visual
112	Weld incomplete or missing	V	3.3	Visual/Manual
Minor				
201	Protective coating incomplete or inadequate	VI	3.4	Visual/Test
202	Evidence of poor workmanship	VI	3.6	Visual
203	Incorrect marking	VI	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-K-70840 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Guard, Armor Tile, Front Left	1 OF 1	12576365
			NEXT HIGHER ASSEMBLY: M2/M3A2 BFVS

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Position of thru holes (4 places)	V	3.2	Gage
102	Diameter of thru holes (4 places)	V	3.2	Gage
103	Material thickness	V	3.2	Gage
104	Angle of short plate to long plate	V	3.2	Gage
105	Weld incomplete or missing	V	3.3	Visual
Minor				
201	Marking missing, incorrect or illegible	VI	3.5	Visual
202	Protective finish incomplete or inadequate	VI	3.4	Visual/Test
203	Evidence of poor workmanship	VI	3.6	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-K-70840 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Guard, Armor Tile, Front Right	1 OF 1	12576366
			NEXT HIGHER ASSEMBLY: M2/M3A2 BFVS

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Position of thru holes (6 places)	V	3.2	Gage
102	Diameter of thru holes (6 places)	V	3.2	Gage
103	Material thickness	V	3.2	Gage
104	Angle of short plate or long plate	V	3.2	Gage
105	Weld incomplete or missing	V	3.3	Visual
Minor				
201	Marking missing, incorrect or illegible	VI	3.5	Visual
202	Protective finish incomplete or inadequate	VI	3.4	Visual/Test
203	Evidence of poor workmanship	VI	3.6	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Guard, Armor Tile, Center	1 OF 1	12576367
			NEXT HIGHER ASSEMBLY: M2/M3A2 BFVS

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Position of thru holes (3 places)	V	3.2	Gage
102	Diameter of thru holes (3 places)	V	3.2	Gage
103	Plate thickness	V	3.2	Gage
104	Radius, max.	V	3.2	Gage
105	Weld incomplete or missing	V	3.3	Visual
Minor				
201	Marking incorrect, incomplete or inadequate	VI	3.5	Visual
202	Protective finish incomplete or inadequate	VI	3.4	Visual/Test
203	Evidence of poor workmanship	VI	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-K-70840 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Guard, Armor Tile, Rear	1 OF 1	12576368
			NEXT HIGHER ASSEMBLY: M2/M3A2 BFVS

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None Defined			
Major				
101	Position of thru holes (5 places)	V	3.2	Gage
102	Diameter of thru holes (5 places)	V	3.2	Gage
103	Plate thickness	V	3.2	Gage
104	Weld missing or incomplete	V	3.3	Visual
105	Radius over max. outside corner (2 places)	V	3.2	Gage
Minor				
201	Marking incorrect, incomplete or inadequate	VI	3.5	Visual
202	Protective finish incomplete or inadequate	VI	3.4	Visual/Test
203	Evidence of poor workmanship	VI	3.6	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-K-70840 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Clip			12556221
				NEXT HIGHER ASSEMBLY
				M2A2/M3A2 BFVS
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Position of thru hole (2 places)	V	3.2	Gage
102	Weld missing or incomplete	V	3.3	Visual
103	Dimension of gap	V	3.3	Gage
Minor				
201	Protective finish incomplete or inadequate	VI	3.4	Visual/Test
202	Evidence of poor workmanship	VI	3.6	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4.3 Rejection. Failure of the Quality Conformance Inspection to be in accordance with the applicable drawings, requirements and Table II will result in the disapproval of the Quality Conformance Inspection.

4.5 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables I, II and starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6, of MIL-A-48078 and 6.3 herein.

4.6 Methods of inspection.

4.6.1 Materials, components and processes. Compliance with all requirements of section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies and materials) have been inspected and tested and found to comply with the respective drawing, specification or specification requirements, and that all specified manufacturing processes have been followed.

4.6.2 Visual and mechanical inspection. The visual, manual and mechanical requirements of sections 3, 4, and 5 of this specification, in accordance with Table I and Table II herein.

5. PACKAGING

5.1 Preservation and packaging. Preservation and packing shall be performed in accordance with special packaging instructions P12556221, P12556222-1, P12556222-2, P12556299, P12556310, P12576336, P12576345, P12576358, P12576359, P12576361, P12576362, P12576363 and P12576364.

5.2 Marking. Marking shall be in accordance with special packing instruction P12556221, P12556222-1, P12556222-2, P12556299, P12556310, P12576336, P12576345, P12576358, P12576359, P12576361, P12576362, P12576363, P12576364, P12576365, P12576366, P12576367 and P12576368."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The installation kit covered by this specification is intended for use on the Bradley Fighting Vehicle system, M2A2/M3A2.

6.2 Acquistition requirements.

a. See MIL-A-48078.

b. Issues of DODISS to be cited in the solicitation and if required, the specifiec issue of the individual document referenced (see 2.1).

c. Provisions for submission of first article sample.

6.3 Submission of inspection designs for approval. See paragraph 6.2.3 of MIL-A-48078. Submit design as required to: Commander, U.S. Army ARDEC, ATTN: SMCAR-QAT-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Data requirement. Deliverable data required by the specification cited as follows:

Paragraph	Data Requirements	Applicable Data Item
6.4.1	Ammunition Data Card	DI-MISC-80043

6.4.1 Submission of test data and ammunition data card. One copy of all test data and ammunition data card shall be forwarded to each of the following: Commander, U.S. Army ARDEC, ATTN: SMCAR-CCH-A(D), Picatinny Arsenal, New Jersey 07806-5000 and Commander, U.S. Army ARDEC, ATTN: SMCAR-QAT-B, Picatinny Arsenal, New Jersey 07806-5000.

6.5 Contractor. Unless otherwise specified, the word "contractor", as used throughout this specification, shall mean any supplier or producer of items or material to the Government. This shall include commercial contractor, subcontractor, Government-Owned, Contractor-Operated (GOCO) and Government-Owned Government-Operated (GOGO) plants.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

6.6 Drawings. Drawings listed in paragraph 2.1.2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as, ARDC, Picatinny Arsenal or Rock Island Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.7 Submission of alternative inspection provisions. Proposed alternative inspection provisions should be submitted by the contractor to the procurement contracting officer for evaluation and approval by the technical activity responsible for preparation of this specification.

6.8 Subject term (key word) listing.

Weld, inspection
Protective finish

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 2350-A414)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-K-70840 (AR)	26 May 1992

3. DOCUMENT TITLE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME US ARMY ARDEC STANDARDIZATION OFFICE	b. TELEPHONE (Include Area Code) (1) Commercial: (201) 724-6662 (2) AUTOVON: 880-6662
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL,NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.