MILITARY SPECIFICATION

MINE, ANTI-PERSONNEL: M86
ARMING ASSEMBLY FOR

This specification is approved for use within the U.S. Army Armament Munitions anti Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the Hardware for Arming Assembly for the Mine, Anti-Personnel M86.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

FEDERAL

QQ-P-416 - Plating, Cadmium (Electrodeposited)

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to. Commander, U.S Army Armament, Munitions and Chemical Command, Attn AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A
FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

2.1.2 Other government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

12579590	Clip, Safety
12579591	Ring, Hookup
9366659	Ring, Pull
12579586	Clip, Shorting Bar
12579585	Hook, Shorting Bar
12579594	Insulator, Mounting Plate
9366650	Ring, Coated
12579597	Ring, Retaining, External
12579589	Pin, Safety
12579600	Washer, Safety Pin
12579580	Lever, Arming
12579583	Stiffener, Plate
12579584	Plate, Mounting
12579582	Cam
NAS1635-0GLL3	Screw, Pan Head
12579587	Sleeve, Lever
12579588	Rivet, Lever
12579595	Arming Assembly - PDM

(Copies of specifications, standards, handbooks, drawings, publications and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 "Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD " adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B 117-73 - Standard Method of Salt Spray (Fog) Testing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

(Application for copies shoud be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards) , the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Hardware. The hardware shall comply with all requirements specified on drawings (Dwgs) referenced in Section 2 and with all requirements specified in applicable specifications.

3.3 Mechanical properties. Cold-working or heat-treating (including quenching-and-tempering , normalizing, normalizing-and-tempering, annealing, and stress-releiving) operations, shall be performed in such a manner as to produce the specified properties uniformly throughout the entire lot. The contractor shall determine the detailed procedures to produce parts meeting the required mechanical properties. These procedures shall be documented and submitted with the first article sample to the Contracting Officer. Changes in these procedures shall also be documented and submitted to the Contracting Officer.

3.4 Salt spray testing. All parts shall have a salt spray performed as per QQ-P-416, ASTM-B-117-73 and 4.5.2 of this specification.

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

Part Description	Drawings	Quantity
Clip, Safety	12579590	25
Ring, Hookup	12579591	25
Ring, Pull	9366659	25
Clip, Shorting Bar	12579586	25
Hook, Shorting Bar	12579585	25
Insulator, Mounting Plate	12579594	25
Ring, Coated	9366650	25
Ring, Retaining, External	12579597	25
Pin, Safety	12579589	25
Washer, Safety Pin	12579600	25
Lever, Arming	12579580	25
Stiffener, Plate	12579583	25
Plate, Mounting	12579584	25
Cam	12579582	25
Screw, Pan Head	NAS1635-OGLL3	25
Sleeve, Lever	12579588	25
Rivet, Lever	12579588	25

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE: Arming Assembly Hardware		SHEET OF		DRAWING NUMBER: ---
					NEXT HIGHER ASSEMBLY: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Clip, Safety (Dwg. 12579590) Examination for Defects	25	--	3.2	4.4.2.5
	Ring, Hookup (Dwg. 12579591) Examination for Defects	25	--	3.2	4.4.2.4
	Ring, Pull (Dwg. 9366659) Examination for Defects	25	--	3.2	4.4.2.18
	Clip, Shorting Bar (Dwg. 12579586) Examination for Defects	25	--	3.2	4.4.2.16
	Hook, Shorting Bar (Dwg. 12579585) Examination for Defects	25	--	3.2	4.4.2.15

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE: Arming Assembly Hardware		SHEET OF		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Insulator, Mounting Plate (Dwg. 12579594) Examination for Defects	25		3.2	4.4.2.12
	Ring, Coated (Dwg. 9366650) Examination for Defects	25		3.2	4.4.2.17
	Ring, Retaining, External (Dwg. 12579597) Examination for Defects	25		3.2	4.4.2.9
	Pin, Safety (Dwg. 12579584) Examination for Defects	25		3.2	4.4.2.11
	Washer, Safety Pin (Dwg. 12579600) Examination for Defects	25		3.2	4.4.2.10

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

TABLE I - First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE: Arming Assembly Hardware		SHEET OF		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Lever, Arming (Dwg. 12579580) Examination for Defects	25		3.2	4.4.2.13
	Stiffener, Plate (Dwg. 12579583) Examination for Defects	25		3.2	4.4.2.2
	Plate, Mounting (Dwg. 12579584) Examination for Defects	25		3.2	4.4.2.1
	Cam (Dwg. 12579582) Examination for Defects	25		3.2	4.4.2.14
	Sleeve, Lever (Dwg. 12579587) Examination for Defects	25		3.2	4.4.2.7
	Rivet, Lever (Dwg. 12579588) Examination for Defects	25		3.2	4.4.2.8

NOTES:

(((

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance-with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Plate, Mounting				12579584
					NEXT HIGHER ASSEMBLY 12579581
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material per NOTE 2		each lot	3.1	Certification
102	Length from datum b to Theoretical nose point		0.40%	3.2	Gage
103	Size of lever rivet hole		0.40%	3.2	Gage
104	Position of lever rivet hole		0.40%	3.2	Gage
105	Position of two radiused sensor cutouts		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

Replaces DPSMC-QA (D) Form 160, 1 Aug 82, which may not be used.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Stiffener, Plate	1	1	12579583
				NEXT HIGHER ASSEMBLY 12579581

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position incorrect		0.40%	3.2	Gage
102	Incorrect material			3.2	Certification
103	Incorrect thickness		0.40%	3.2	Gage
104	Distance between angle legs incorrect		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

DD FORM 24 (R) Form 160, 1 Aug 83, which may not be used

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Mounting Plate and Stiffener Assembly				12579581
					NEXT HIGHER ASSEMBLY 12579595
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Presence of all parts		0.40%	3.2	Visual/Print
102	True position of stiffener plate incorrect		0.40%	3.2	Gage
103	Pivot end ears incorrect distance		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Ring, Hookup				12579591
					NEXT HIGHER ASSEMBLY 12579595
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material incorrect		--	3.1	Certification
102	Wire diameter incorrect	50	--	3.1	Gage
103	Incorrect finish		--	3.1	Certification
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Clip, Safety				12579590
					NEXT HIGHER ASSEMBLY 12579595
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material incorrect		--	3.1	Certification
102	Incorrect wire diameter	50	--	3.1	Gage
103	Incorrect loop heights		0.40%	3.2	Gage
104	Length between end loops incorrect		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Safety Clip Assembly		12579598
			NEXT HIGHER ASSEMBLY 12579595

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Presence of all parts		0.40%	3.2	Visual
Minor 201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Sleeve, Lever	1 OF 1	12579587
			NEXT HIGHER ASSEMBLY: 12579595

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Overall length		0.40%	3.2	Gage
102	Incorrect material		--	3.1	Certification
103	Position of diameter(s)		0.40%	3.2	Gage
104	Diameter(s) incorrect		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Rivet, Lever				12579588
					NEXT HIGHER ASSEMBLY 12579595
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material per print		each lot	3.1	Certification
102	Length of shank		0.40%	3.2	Gage
103	Position(s) of diamter(s)		0.40%	3.2	Gage
104	Chamfer incorrect		0.40%	3.2	Gage
105	Diameter(s) incorrect		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Ring, Retaining, External				12579597
					NEXT HIGHER ASSEMBLY 12579595
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material incorrect		--	3.1	Certification
102	Inside diameter of hole		0.40%	3.2	Gage
103	Thickness incorrect	50	--	3.1	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Washer, Safety Pin	1 OF 1	12579600
			NEXT HIGHER ASSEMBLY: 12579595

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material incorrect		--	3.1	Certification
102	Outside diameter		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
104	Finish incorrect		0.40%	3.2	Gage
105	Position of diameter(s) incorrect		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Pin, Safety				12579589
					NEXT HIGHER ASSEMBLY 12579595
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
1	OD of pin shaft with flat		100%	3.2	Gage
2	OD of pin shaft		100%	3.2	Gage
3	OD of pin head collar		100%	3.2	Gage
4	Material per NOTE 2		each lot	3.1	Lab verification
5	Broken on length incorrect		100%	3.2	Gage
Major					
101	OD of pin head		0.40%	3.2	Gage
102	OD of slot		0.40%	3.2	Gage
103	True position of slot		5-0-1	3.2	Gage
104	Inner radius of slot		0.40%	3.2	Gage
105	Height of slot		0.40%	3.2	Gage
106	Height from slot to head		0.40%	3.2	Gage
107	Height from upper collar surface to head		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Insulator Mounting Plate	1 OF 1	12579594
			NEXT HIGHER ASSEMBLY: 12579595

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material per print		each lot	3.1	Certification
102	Profile of surface with respect to datums a and b		0.40%	3.2	Optical comparator
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Replaces DRSMC QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Lever, Arming	1 OF 1	12579580
			NEXT HIGHER ASSEMBLY: 12579595

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material per print		each lot	3.1	Certification
102	Width of slot		0.40%	3.2	Gage
103	True position of slot		0.40%	3.2	Gage
104	Distance between outside faces of drilled ears, wide end		0.40%	3.2	Gage
105	Size of hole in small end (2)		0.40%	3.2	Gage
106	True position of holes in small end (2)		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Cam		12579582
			NEXT HIGHER ASSEMBLY 12579595

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material per print		each lot	3.1	Certification
102	Radius of cam lobe to horizontal centerline of slot		0.40%	3.2	Gage
103	True position of cam lobe radius		0.40%	3.2	Gage
104	Thickness of lobe at outside edge		0.40%	3.2	Gage
105	True position of thickness of lobe		0.40%	3.2	Gage
106	Width of slot		0.40%	3.2	Gage
107	True position of slot		0.40%	3.2	Gage
108	Size of hole at end opposite lobe		0.40%	3.2	Gage
109	True position of hole at end opposite lobe		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Hook, Shorting Bar	1 OF 1	12579585
			NEXT HIGHER ASSEMBLY: 12579601

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Material per print		each lot	3.1	Certification
102	Diameter of wire		0.40%	3.2	Gage
103	Distance between vertical shanks at hook end		0.40%	3.2	Gage
104	Height of hook shank at hook end		0.40%	3.2	Gage
105	Length of tand on hook end		0.40%	3.2	Gage
106	Distance from outside of hook radius to first bend in shank		0.40%	3.2	Gage
107	Distance from first bend in shank to bend radius parallel with tang		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Clip, Shorting Bar				12579586
					NEXT HIGHER ASSEMBLY 12579601
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Size of hole		0.40%	3.2	Gage
102	True position of hole		0.40%	3.2	Gage
103	Overall width		0.40%	3.2	Gage
104	Depth of slot formed by bend radius		0.40%	3.2	Gage
105	Width of slot formed by bend radius		0.40%	3.2	Gage
106	Diameter of slot aligned with hole		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.17	Ring, Coated				9366650
					NEXT HIGHER ASSEMBLY 12579595
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Coating improperly applied			3.2	Certification
Minor 201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.18	Pull, Ring				9366659
					NEXT HIGHER ASSEMBLY
					12579598
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Coating improperly applied		---	3.2	Certification
Minor 201	Poor workmanship		1.0%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-70780 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Arming Assembly, PDM				12579595
					NEXT HIGHER ASSEMBLY 12579601
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special					
1	Warning notice missing		100%	3.2	Visual
Major					
101	Presence of all parts		0.40%	3.2	Visual
102	Coated ring properly seated in arming lever		0.40%	3.2	Visual
103	Pull force per drawing 9366663 NOTE 6		0.40%	3.2	Force Gage/Set Up
104	Salt Spray failure			3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1, The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See MIL-A-48078.

4.5 Methods of inspection.

4.5.1 Dimensional control of stamped parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.5.2 Salt spray test of protective finish. Five parts of each part number shall be selected from each lot in accordance with the lot formation provisions of specification QQ-P-416. The test shall be tested as-specified in ASTM B 117-73. The parts shall be tested for the duration specified on the applicable drawing. At the end of the required time, the parts shall be examined for evidence of white corrosion products (See Section 3 of QQ-P-416).

If any part shows any evidence of corrosion the lot represented by the sample shall be rejected.

This is a destructive test. Parts so tested shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level B. The hardware shall be preserved and packaged in accordance with MIL-STD-1169. Each package shall contain only one part number.

5.2 Packing.

5.2.1 Level B. The hardware, preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with MIL-STD-1169. Each pack shall contain only one part number.

5.3 Marking. Marking of the carton shall comply with MIL-STD-1169.

5.4 Shipping. When components from more than one lot are shipped at one time, each lot shall be kept seperate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The components covered by the specification are intended for use on the M86 - Mine, Anti-Personnel.

6.2 Submission of designs for approval. See MIL-A-48078. submit equipment designs, as required, to Commander, Picatinny Arsenal, ATTN: AMSMC-QAT-M (D), Picatinny Arsenal, NJ 07806-5000. This address shall be specified on the Contract Data Requirements List, DD Form 1423 in the Contract. Unless otherwise specified, DI-R-1714 will apply.

6.3 Submission of results of contractor-conducted examinations and tests. Data shall be submitted in accordance with data item DI-R-1721 on the DD Form 1423 for the contract.

6.4 Distribution of ammunition data cards, inspection and test results, process controls. Distribution of ammunition data cards, inspection and test results, process controls shall be sent to:

Commander
ARDEC
Picatinny Arsenal, NJ 07806-5000
ATTN: AMSMC-QAT-M (D)

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project: 1345-A513)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-70780	MINE, ANTI-PERSONNEL; M86 ARMING ASSEMBLY FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:30Z
Check the source to verify that this is the current version before use.