MIL-M-80044D
11 September 1987
SUPERSEDING
MIL-B-80044C
30 June 1986

MILITARY SPECIFICATION

MILLING MACHINES, HORIZONTAL SPINDLE, KNEE TYPE, SIZE NUMBERS 2, 3, 4, AND 5

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers sizes 2, 3, 4, and 5, horizontal, knee type, electric motor driven milling machines with equipment and accessories specified herein.

1.2 Classification. The milling machines shall be of the following types, sizes, and classes. The type, size, and class to be furnished shall be as specified (see 6.2.1).

Type I - Plain table
Type II - Universal table

Type I and type II machines shall include sizes and classes as follows:

Size Number 2 - 28 inches longitudinal table travel

Size Number 3 - 34 inches longitudinal table travel

Class 1	- 7-1/2	horsepower spindle drive
Class 2	- 10	horsepower spindle drive
Class 3	- 15	horsepower spindle drive

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSM, Memphis, Tennessee 38114-5051, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3417
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

Size Number 4 - 42 inches longitudinal table travel

Class 1 - 15 horsepower spindle drive
Class 2 - 20 horsepower spindle drive

Size Number 5 - 48 inches longitudinal table travel

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services.

FED-STD-376 - Preferred Metric Units for General Use by the Federal Government.

MILITARY

MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.

MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.

2.1.2 Other Government documents. The following other Government document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be that in effect on the date of the solicitation.

U. S. DEPARTMENT OF LABOR

29 CFR 1910 - Occupational Safety and Health Standards (OSHA).

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402-0001).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the non-Government document which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/NEMA MG 1 - Motors and Generators.

ANSI/NFPA 79 - Electrical Standard for Industrial Machinery.

ANSI B5.1 - T-Slots, Their Bolts, Nuts and Tongues.

ANSI B5.18 - Spindle Noses and Tool Shanks for Milling Machines.

ANSI B5.45 - Milling Machines.

ANSI B11.8 - Drilling, Milling, and Boring Machines - Safety Requirements for the Construction, Care, and Use.

ANSI/ISO 54 - Cylindrical Gears For General Engineering and for Heavy Engineering, Modules and Diametral Pitches of.

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018-3308.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103-1187.)

AMERICAN GEAR MANUFACTURERS' ASSOCIATION (AGMA)

AGMA 360.02 - Manual for Machine Tool Gearing.

AGMA 390.03 - Gear Classification, Materials and Measuring Methods For Unassembled Gears.

(Application for copies should be addressed to the American Gear Manufacturers' Association, Standards Department, 1500 King Street, Suite 201, Alexandria, VA 22314-2717.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations which prepare or distribute the documents. These documents also may be available in or through libraries or other informational services).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2.1), a sample shall be subjected to first article inspection (see 4.4 and 6.3).

3.2 Design. The milling machine shall be new and one of the manufacturer's current models capable of operations in accordance with the requirements herein. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair. The machine shall be designed in accordance with ANSI B5.45.

3.2.1 Measurement system. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the milling machine. When only one system of measurement is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes, and capacities are given in US units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.1.1 Measuring and indicating device calibrations. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used on graduate measuring and indicating devices such as scales, depth stops, carriage stops, dial indicators, pressure gauges, temperature indicators, and other similar devices. When only one system of graduation is acceptable, the particular graduation required shall be as specified (see 6.2.1). Regardless of the measurement system used, all measuring and indicating devices on the machine shall be graduated in the same system. All feed dials shall have independent zero adjustments and shall be calibrated in such a manner that the last dial graduation progresses into and is continuous with the first dial graduation as the dial is rotated through the zero position.

3.2.1.2 Digital readout (DRO) system. Unless otherwise specified (see 6.2.1), a DRO system shall be provided on the axes of travel. The DRO system shall consist of a position feedback device, an electronic display for each axis,

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

and all related components, mounting hardware, and electrical equipment necessary to assure complete operation of the system. The system shall provide a readily visible digital display over the full working range of each axis on which installed. The system resolution shall be 0.0005 inch. The system accuracy shall be equal to the system resolution, verified upon installation and calibration of each system on the machine. The repeatability shall be 0.0002 inch, measured over the full travel on each axis. Special requirements for the DRO system components shall be as specified (see 6.2.1). The DRO shall indicate axis location in both the US and SI units. The DRO system shall be provided with electronic and manual calibration to the machine on which it is installed to eliminate the effects of distortion error.

3.2.1.2.1 Position feedback device. A position feedback device including all related components, hardware, and electrical equipment shall be provided for each axis having a readout system. The feedback device shall be of the independent type. Each feedback device shall be installed with a cover or guard to prevent physical damage to any portion of the feedback device. The device shall provide axis travel feedback over the entire range of axis travel for each specified axis. Provisions shall be made to prevent damage to the feedback device in the event of overtravel. The feedback unit shall be protected from contamination of oil, dust, chips, and coolant.

3.2.1.2.2 Electronic display console. The electronic display console for the digital readout system shall contain a universal digital display with individual digits not less than 0.560 inch high. The console shall be capable of displaying at least six digits simultaneously. The display console shall also provide keyboard entry, memory, absolute/incremental counting, data preset, power failure indicator, inch/metric conversion, absolute zero recall, and calculator add and subtract. The electronic display console shall be installed so as to be readily accessible and easily read from the operator's work position. The console shall be mounted to withstand shock and vibration generated by the milling machine. The connecting cable shall be armored and shall be installed so as not to interfere with the normal operation of the milling machine. The cable shall be securely fastened to the structure of the milling machine in accordance with the requirements of the contract.

3.2.2 Reclaimed materials. The milling machine may contain reclaimed materials provided such materials will not jeopardize the machine's intended use, performance, or design life. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the milling machine.

3.2.3 Energy efficiency. The milling machine shall be designed and constructed for energy efficiency as governed by the developments available within the industry.

3.2.4 Safety and health requirements. Covers, guards, or other safety devices shall be provided for all parts of the milling machine that present safety hazards. The safety devices shall not interfere with the operation of the machine. The safety devices shall prevent unintentional contact with the guarded part and shall be removable to facilitate inspection, maintenance, and repair of the parts. All machine parts, components, mechanisms, and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

assemblies furnished on the unit, whether or not specifically required herein, shall comply with all of the requirements of OSHA 29 CFR 1910 and ANSI B11.8 that are applicable to the milling machine itself. Additional safety and health requirements shall be as specified (see 6.2.1).

3.2.5 Mercury restriction. The milling machine shall not contain mercury or mercury compounds nor be exposed to free mercury during manufacture.

3.2.6 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the milling machine.

3.2.7 Environmental protection. The milling machine shall be so designed and constructed that, under the operating, service, transportation, and storage conditions described herein, the machine shall not emit materials hazardous to the ecological system as prescribed by Federal, state, or local statutes in effect at the point of installation.

3.2.8 Lubrication. Means shall be provided to ensure adequate lubrication for all moving parts. Recirculating lubrication systems shall include a filter which is cleanable or replaceable. Each lubricant reservoir shall have means for determining fluid level. All oil holes, grease fittings, and filler caps shall be accessible. An automatic lubrication system shall be provided for all ways and axes screws. An audible buzzer and low-lube light shall alert the operator of a low-lube condition. The lube reservoir and pump for this system shall be self-contained, easily accessible, adjustable, and have adequate capacity to sustain the unit for a minimum of 24 hours of continuous operation without replenishing the reservoir.

3.2.9 Interchangeability. Foreign sourced replacement parts shall be interchangeable with domestically supplied components or be logistically supportable and readily available from a domestic source. Replacement parts are those that are normally subject to wear such as gears, bearings, shafts, feed screws, drive belts, pumps, and seals. Electrical replacement parts shall include motors, relays, switches, magnetics, pushbuttons, light bulbs, fuses, braking mechanisms, and solid-state devices. Tooling and accessories normally supplied as standard items shall also be considered replacement parts. All replacement parts shall be completely interchangeable without need for any modifications.

3.3 Construction. The milling machine shall be constructed of parts which are new, without defects, and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free of defects, scale, and mismatching. No processes such as welding, peening, plugging, or filling with solders or pastes shall be used for reclaiming any defective part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

3.3.2 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

3.3.3 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.4 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the milling machine shall be painted in accordance with the manufacturer's standard commercial practice.

3.3.6 Threads. All threaded parts used on the milling machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Dials. All rotating dials or handwheels which are used to position machine axes or for tool movement shall be graduated in increments not larger than 0.001 inch. Dial and handwheel diameters shall be permanently and legibly engraved or etched on a nonglare background with graduations that can be read from the operator's normal position.

3.3.8 Gears. All gears and pinions shall be designed and manufactured of suitable ferrous material for the intended purpose. All gears shall be machined and heat treated by a process that will impart the hardness, surface finish, and toughness that will enable the gear train to transmit full-rated torque to the drive motor without gear damage, failure, or premature deterioration and wear. All gears and pinions of spindle and axis drive train shall be designed and manufactured of a suitable ferrous material to meet or exceed the requirements of AGMA 360.02 and 390.03 for the English (US) system or ISO 54 for the metric (SI) system. The gears shall be proper width and size to transmit full-rated torque and horsepower throughout the speed ranges without failure for the expected service life of the machine. Gears in the drive train shall be hardened and ground steel. Hardness shall be not less than Rockwell C-45.

3.3.9 Electromagnetic interference control. When specified (see 6.2.1), equipment furnished under this specification shall comply with MIL-STD-461. The equipment and subsystems class and the emission and susceptibility requirement shall be as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

3.4 Components. The milling machine shall consist of a column and base, knee, saddle, worktable, overarm with arbor support, spindle, electric motor drive, and such other components as are required to perform as specified herein.

3.4.1 Column and base. The column and base shall be either one piece or two piece construction with access doors or removable covers for servicing the drive motor, main drive clutch, and the adjusting mechanism. The walls shall be ribbed for rigidity. The column shall have machined ways of the square or dovetail design for vertical travel of the knee. Unless otherwise specified (see 6.2.1), all ways shall be hardened and precision ground for smooth, accurate travel. Means shall be provided for securing the machine to the floor.

3.4.2 Knee. The knee shall be of the box-type construction with cross or transverse ribbing. The knee shall be fitted to the column ways with adjustable gibs. The ways shall have wipers or other means for preventing dust and chips from entering the ways. Means shall be provided to clamp the knee in any position within its travel on the column. The knee elevating screw shall have either square or acme threads and shall run in a bath of oil. The knee adjusting crank or handwheel shall positively and automatically release when power feed or rapid traverse is engaged. The knee shall have ways to support the saddle in its cross movement. Unless otherwise specified (see 6.2.1), the ways shall be replaceable, hardened, and ground inserts, or hardened as part of the knee and precision ground.

3.4.3 Saddle. Unless otherwise specified (see 6.2.1), all way surfaces of the saddle shall be equipped with adjustable gibs and guide, as necessary, to maintain alignment in cross and longitudinal planes. Wipers or other means shall be provided to prevent dust and chips from entering ways. Means shall be provided for clamping the saddle to the knee in any position within its travel on the knee. The cross feed crank or handwheel shall positively and automatically disengage when power feed or rapid traverse is engaged.

3.4.4 Universal table mounting. On type II machines, the universal saddle and swivel block shall permit the table to swivel not less than 45 degrees right and left of zero position. The swivel block shall have a bearing area large enough to support the table with a workpiece of maximum rated load in any angular position, without distortion, while performing any type of milling operation basic to the requirements of the milling machine covered by this specification. The swivel block shall be provided with a distortion and deflection free clamping arrangement and shall have graduations in increments of not more than 1 degree to accurately indicate its angular setting.

3.4.5 Table. The table shall have not less than three equally spaced, manufacturer's standard size T-slots conforming dimensionally with ANSI B5.1. The table working surface shall be the manufacturer's standard size, but shall be not less than the size shown in table I, applicable to class and size machine procured. The top of the table shall have a finished surface having a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

slot or slots running the full length of the table for mounting adjustable table stops. The table shall have coolant drain channels with chip screen and provisions for return of coolant to the reservoir. Means shall be provided for clamping the table to the saddle at any point in its range of travel. The table feed screw shall have a mechanism to control backlash in longitudinal table movement during climb milling operations. When specified (see 6.2.1), when backlash eliminator control is set and engaged for one table movement direction, the backlash eliminator shall automatically disengage during rapid traverse or conventional power feed in the opposite direction and shall automatically re-engage when original table movement is achieved for climb milling.

3.4.6 Spindle. The spindle shall be heat treated, hardened, and ground to a precision finish. It shall be supported by not less than two precision tapered roller bearings or two pairs of precision angular contact bearings that can be adjusted for axial alignment and not less than one other precision bearing of either the ball or roller type for radial support of the spindle. The spindle shall be equipped with a fly wheel or fly wheel integral with the bull gear, and shall be operable in both directions. The spindle shall have a precision ground nose in accordance with ANSI B5.18 and table I. An automatic braking mechanism shall stop the spindle when a lever or push button is placed in the off position or when the power to the spindle motor is turned off. Spindle speed changes shall be accomplished by movement of not more than three levers, a knob, or a push button with a direct reading indicator to show selected speed of operation.

3.4.7 Feed mechanism. The feed changes shall be accomplished by means of a single rotating lever, knob, or push button with a direct reading open faced dial to indicate the feed rate engaged. The feed control levers shall be directional and shall allow independent reversing of each feed. The feed mechanism shall be equipped with safety overload protection devices. Power feed shall automatically stop when the spindle is stopped.

3.4.8 Power rapid traverse. Power rapid traverse independent of feed changes shall be provided for the table in both directions of longitudinal, vertical, and cross travel. Power rapid traverse rates shall be in accordance with table I.

3.4.9 Stops. Adjustable and positive stops shall be provided for the knee, the table, and the saddle.

3.4.10 Clamping levers. Levers or screws shall be provided for clamping the knee to the column, the saddle to the knee, and the table to the saddle.

3.4.11 Feed screws and bearings. The feed screws for all axes shall be hardened and ground and shall be mounted in precision type ball or roller bearings. Bushings or insert type bearings are not acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

3.4.12 Controls. All operating controls and all manual adjustments shall be grouped in a location convenient to the operator except as otherwise specified herein. All front handwheels and cranks shall be safety interlocked or shall automatically and positively disengage during power rapid traverse and power table feeds. When specified (see 6.2.1), the machine shall be provided with controls for starting and stopping the spindle and initiating any table movement from the front and rear of the machine.

3.4.13 Automatic cycle table control. When specified (see 6.2.1), type I milling machines shall have automatic cycle table control to provide for automatic work cycles by controlling power feed, rapid traverse, automatic reverse, and stop.

3.4.13.1 Automatic knee retraction. When specified (see 6.2.1), automatic knee retraction to lower the table during power rapid traverse shall be provided on the machines having automatic cycle table control.

3.4.14 Coolant. A coolant system shall be furnished. The system shall be a flood or mist type, as specified (see 6.2.1). The coolant system shall include a sump or reservoir, a power driven pump, motor, and all necessary piping. The sump or reservoir shall have sufficient capacity to permit full flow of coolant. The system shall have means for draining and cleaning and shall include a strainer or baffle which is easily removable for cleaning. A coolant delivery nozzle and valve shall be provided to permit the operator to direct and control the amount of coolant flow. The shut-off control shall be independent of flow control.

3.4.15 Hydraulic system. The hydraulic system, when furnished, shall be complete, including all pumps, valves, piping, cylinders, and pressure controls. Overpressure protection shall be provided in the high pressure line to prevent damage to components. A filter system shall be provided to ensure delivery of clean fluid. The hydraulic reservoir shall have means for determining fluid level. A provision for draining and a cleanout access plate shall be provided.

3.4.16 Electrical system. The machine and all accessories shall conform to ANSI/NFPA 79. Each machine shall have a fused safety disconnect switch or circuit breaker. An identified terminal for grounding the machine when installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in ANSI/NFPA 79 for the disconnect fuse rating. Unless otherwise specified (see 6.2.1), each machine shall draw all electrical power from a single 230/460-volt, 3-phase, 60-hertz (Hz) circuit. The machine shall be initially wired for operation on 460 volts or as specified in 6.2.1.

3.4.16.1 Motors. Motors shall be rated for continuous duty and shall have ball or roller bearings of the sealed and permanently lubricated type. Alternating-current (AC) motors shall be designed to operate on 60-hertz (Hz). Unless otherwise specified (see 6.2.1), each motor enclosure shall meet the requirements for a drip-proof enclosure. All motors shall be in accordance with ANSI/NEMA MG 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

3.4.16.2 Solid-state components. Solid-state design shall be used throughout for electrical components.

3.4.16.3 Control circuit voltage. Auxiliary control circuits shall be isolated from the input electric power supply by a low-voltage transformer having a secondary nominal voltage of 120 volts.

3.4.16.4 Hour meter. When specified (see 6.2.1), the milling machine shall have a nonmanual reset hour meter to record the operating time of the feed drive motor. The hour meter shall accumulate not less than 99,999 hours in increments of 1 hour or less. Upon reaching the maximum accumulative hours, the meter shall automatically reset to zero and continue to record. The meter shall be mounted to withstand shock and vibration generated by the milling machine. The meter shall be enclosed in a dust-proof and moisture-proof case.

3.4.16.5 Electrical load indicator. Unless otherwise specified (see 6.2.1), the machine shall have a meter to indicate the electrical load on the spindle drive motor. The meter shall be current actuated. The dial shall indicate either amperes or percent of rated full-load current, and shall be clearly marked to indicate the rated reading for continuous operation of the machine. The currency of the meter shall be within 2 percent of full-rated load. The meter shall be clearly readable from the operator's normal position.

3.5 Size and capacity. Unless otherwise specified (see 6.2.1), the size and capacity of the milling machine shall be not less than specified in table I for the machine size specified.

3.6 Performance. The milling machine shall be capable of satisfactory performance when tested in accordance with 4.7.1 through 4.7.4.

3.6.1 Additional performance requirements. Performance features required in addition to or in lieu of the requirements herein shall be as specified and fully described (see 6.2.1).

3.7 Alignment tolerances. Each milling machine shall meet the alignment tolerances specified in table II.

3.8 Standard equipment. Unless otherwise specified, all standard equipment normally furnished by the manufacturer shall be furnished. Additional equipment shall be furnished as specified and fully described (see 6.2.1).

3.9 Optional equipment. Optional equipment specified in the following subparagraphs shall be furnished with each machine as specified (see 6.2.1).

3.9.1 Universal dividing head. Unless otherwise specified (see 6.2.1), the universal dividing head shall be the standard commercial model and size normally furnished by the manufacturer for the size and class machine required. The dividing head shall be designed to index work and rotate work in conjunction with longitudinal movement of the table. It shall be operable

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

with the front end of the spindle inclined at any angle from 0 degrees horizontal plane to 90 degrees vertical plane. The standard index plates shall be those normally furnished with the standard model dividing head. When specified (see 6.2.1), sufficient additional index plates shall be furnished to provide for dividing a single spindle rotation into any integral number of equal divisions from 2 to 100 when using the plain indexing method. When specified (see 6.2.1), a complete driving mechanism with enclosed gears shall be provided to drive the dividing head by power from the table feed screw. The spindle nose taper of the dividing head shall be the manufacturer's standard. The dividing head shall be complete with centers, steady rest, and 3-jaw universal chuck with reversible jaws. The tailstock shall be complete with bolts, nuts, washers, and centers. An index table and a table of leads for cutting spirals shall be provided.

3.9.2 Vertical milling head. When required, a vertical milling attachment shall be furnished complete with a minimum of a Number 40 AN Standard taper spindle nose. The head shall swivel in a plane parallel to the face of the column and 90 degrees to both sides of the vertical position of the spindle nose. Spindle speeds of the attachment shall be in a 1-to-1 ratio with the machine spindle.

3.9.3 Universal milling head. When required, a universal milling attachment shall be furnished complete with a minimum of a Number 40 AN Standard taper spindle nose. The head shall have two swivels, one in the vertical plane and one in the horizontal plane, to permit any angular positioning of the spindle that is desired in the horizontal or vertical planes. Each swivel shall rotate a full 360 degrees. Spindle speeds of the attachment shall be in 1-to-1 ratio with the machine spindle.

3.9.4 Rotary table. When required, a rotary table with periphery graduated in degrees shall be furnished complete with a handwheel, T-slots, T-bolts, nuts, washers, and locking clamp for rotary motor. The table shall have a diameter as specified (see 6.2.1). When specified (see 6.2.1), a power driven unit and two trip dogs shall be furnished. When specified (see 6.2.1), an indexing attachment with the required number of indexing plates shall be furnished.

3.9.5 Swivel vise. When required, a swivel vise with the swivel base graduated in degrees shall be furnished complete with T-bolts, nuts, washers, crank, and a jaw opening as specified (see 6.2.1). The vise shall consist of a plain vise mounted on a detachable swivel block so as to be convertible to a plain vise.

3.9.6 Independent overarm spindle. When required, the machine shall have a ram sliding on dovetail or square lock ways equipped with an independent spindle and spindle motor. The machine shall be so designed that arbors and arbor supports for horizontal milling can be used without removing the overarm milling head. The ram shall be a casting fitted to matching ways of the column. The ways shall be precision ground or machined and scraped. Ram positioning shall be by a hand-cranked rack and pinion. Means shall be provided

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:32Z
Check the source to verify that this is the current version before use.

for clamping the ram in any position within its range of travel. The ram movement shall be in a plane parallel to the surface of the table. The machine shall be capable of accurate vertical milling operations of 80 percent of the maximum rated horsepower of the independent vertical spindle motor.

3.9.6.1 Plain vertical swivel milling head. When required, the independent overarm shall have a single-swivel head with a swivel range of 360 degrees in the vertical plane. A graduated scale shall be on the swivel to indicate the amount of angular rotation in increments of not more than 1 degree through 360 degrees. A worm and wheel arrangement shall control the movement of the swivel.

3.9.6.2 Universal milling head. When required, the independent overarm shall have a double-swivel head capable of adjustment to any angle in a plane parallel to the face of the machine column and in a plane perpendicular to the face of the column. A worm and wheel arrangement shall control movement of the swivel that is attached to the overarm. A graduated scale shall be on each swivel to indicate the angular rotation in increments of not more than 1 degree through 360 degrees.

3.9.7 Hardened and ground ball screws. When specified (see 6.2.1), each sliding member shall be equipped with hardened and ground ball screws and recirculating ball nut assemblies in lieu of the feed screws specified in 3.4.11. Mounting of the ball screws shall be as specified in 3.4.11. Bushing or insert type bearings are not acceptable.

3.9.8 Independent axis drives. When specified (see 6.2.1), the machine shall be equipped with separate direct-current (DC) servo motors to provide independent feeds for each axis. If this type drive is specified, the machine shall be equipped with the hardened and ground ball screws and nuts per paragraph 3.9.7.

3.9.9 Infinitely variable feed rates. When specified (see 6.2.1), the machine shall be equipped with a single DC feed motor connected by electromagnetic clutches to the axes.

3.10 Repair parts. Such repair parts as are specified (see 6.2.1) shall be furnished.

3.11 Marking on plates, charts, and decals. All words on plates and charts, shall be in the English language. Characters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background.

3.11.1 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a corrosion-resistant lubrication plate shall be permanently and securely attached to each machine. The plate shall contain the following information:

Points of lubricant application
Servicing interval
Type of lubricant
Viscosity

Source: https://assist.dla.mil Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

3.11.2 Nameplate. Unless otherwise specified (see 6.2.1), a nameplate shall be securely attached to each milling machine and contain the information listed below. If the milling machine is a special model, the model designation shall include the model of the basic standard milling machine and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)
Contract Number of Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.12 Technical data. When technical data (operating manuals, maintenance manuals, parts catalogs, prints, wiring diagrams, lubrication charts, machine alignment and accuracy test results) is required it shall be furnished in accordance with the requirements of DD Form 1423. All technical data furnished shall be written in the English language.

3.13 Workmanship. Workmanship of the milling machine shall be commensurate with all requirements specified herein and shall be of a quality equal to that prevailing among manufacturers producing equipment of the type covered by this specification.

3.14 Training. Training required by the procuring activity shall be provided as specified in the contact.

3.15 Warranty. Warranty requirements shall be as specified in the contract by the procuring activity. The warranty period shall commence upon completion of installation and final acceptance testing.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspections. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own continental United States facilities or any other continental United States facility suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:32Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Quality conformance inspection (see 4.4).

b. Acceptance test (see 4.5).

4.3 Inspection conditions. Unless otherwise specified (see 6.2.1), all inspections, tests, and examinations shall be performed in an indoor facility with ambient conditions of temperature: 55°F to 85°F; humidity: 10 percent to 90 percent relative humidity; and atmospheric pressure: 15.0 to 13.0 psi.

4.4 First article inspection. When a first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.6 and all tests in 4.7. Failure of the item to pass the first article examination or any test shall be cause for rejection.

4.5 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.6, the tests in 4.7.1 through 4.7.4, and the inspection in 4.8. Failure of the item to pass the examination, the tests, or the inspection shall be cause for rejection.

4.6 Examination. The machine shall be visually examined to determine compliance with all requirements of this specification, including compliance with all applicable standards cited in section 2.

4.7 Tests.

4.7.1 Operational test. The machine shall be operated at no load for not less than 30 minutes. Proper operation of all controls, motors, adjusting mechanisms, and accessories shall be verified during the trial period.

4.7.2 Alignment tolerance test. Each machine shall be tested to determine that it complies with the alignment tolerance requirements of 3.7. This test

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

shall be performed prior to the following performance tests and again upon completion of the performance tests. Failure to meet the requirements of 3.7 at any time will be grounds for rejection of the item as noncompliance with the requirements of this specification.

4.7.3 Performance tests. At the option of the procuring agency, each machine shall be subjected to tests in accordance with specific requirements designated by the activity in lieu of or in addition to the following tests (see 6.2.1).

4.7.3.1 Horsepower, milling accuracy, and tool chatter tests. Each machine shall be tested by machining a workpiece of SAE 4140 steel. The workpiece shall be not less than 16 inches long, 6 inches wide, and 3 inches thick. The workpiece may be drilled to facilitate clamping. One of the two surfaces having the largest area shall be ground flat and mounted in contact with the table. Roughing cuts shall be made to mill metal off the horizontal and one vertical surface of the workpiece. The roughing cuts shall be made at sufficient depth and feed rate to load the spindle drive motor to not less than maximum continuous duty rated electrical input. The type of cutting tool, depth of cut, spindle speed, and feed rate shall be determined by the manufacturer, provided the required loading is achieved. There shall be no evidence of chatter, stalling, or permanent distortion during or after the test. Finishing cuts shall be made on the horizontal and vertical surfaces. The finished surfaces shall meet the following accuracies:

4.7.3.2 Squareness. The two milled sides shall be tested for squareness. The sides shall be square with each other within 0.001 inch per foot.

4.7.3.3 Flatness. The two milled sides shall be tested for flatness. The sides shall be flat within 0.001 inch per foot.

4.7.3.4 Parallelism. The finished horizontal surface shall be tested for parallelism. The top surface shall be parallel to the bottom surface within 0.001 inch per foot.

4.7.4 Climb milling test. Each machine shall be tested in accordance with the manufacturer's standard climb milling test, provided that the test proves the capability of the machine to meet all of the requirements for which it was designed.

4.7.5 Electromagnetic interference control tests. Equipment requiring electromagnetic interference control shall be tested for compliance with 3.3.9 using the procedure given in MIL-STD-462.

4.8 Packaging inspection. Packaging of each item shall be inspected to determine compliance with the requirements of section 5.

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified, preservation, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.2.1), level A preservation, level A or level B packing, and marking shall be accomplished in accordance with MIL-M-18058.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The milling machines covered by this specification are to be used for conventional milling operations on a wide range of parts.

6.2 Ordering Data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Type, size, and class (see 1.2).

c. First article, if required (see 3.1).

d. If the milling machine is required to be configured in a specific measurement system (US or SI), state required system (see 3.2.1).

e. If measuring and indicating devices are required to be graduated in a specific measurement system (US or SI), state required system (see 3.2.1.1).

f. Digital readout system, specify axes readout(s) required, if different, (see 3.2.1.2).

g. Specify special digital readout requirements (see 3.2.1.2).

h. Additional safety and health requirements, if required (see 3.2.4).

i. Painting, if different (see 3.3.5).

j. If electromagnetic interference control is required, specify the equipment and subsystem class and the emission and susceptibility required (see 3.3.9).

k. Column and base ways, if different, specify requirement (see 3.4.1).

l. Knee ways, if different, specify requirement (see 3.4.2).

m. Saddle ways, if different, specify requirements (see 3.4.3).

n. Backlash eliminator, if required, specify requirement (see 3.4.5).

o. Controls, front and rear, if required (see 3.4.12).

p. Automatic cycle table control, if required (see 3.4.13).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

q. Automatic knee retraction, if required (see 3.4.13.1).

r. Coolant system, specify type (see 3.4.14).

s. Electrical system, if different, specify requirement and operational voltage (see 3.4.16).

t. Motor enclosure, if different (see 3.4.16.1).

u. Hour meter, if required, specify requirement (see 3.4.16.4).

v. Electrical load meter, if different, specify requirement (see 3.4.16.5).

w. Size and capacity, if different (see 3.5).

x. Additional performance features, if required (see 3.6.1).

y. Standard equipment, if different, specify requirement (see 3.8).

z. Optional equipment (see 3.9); specify requirements (see 3.9.1 through 3.9.9).

aa. Repair parts, specify requirement (see 3.10).

bb. Lubrication chart or plate, if different (see 3.11.1).

cc. Nameplate, if different (see 3.11.2).

dd. Inspection conditions, if different (see 4.3).

ee. First article inspection, if different (see 4.4).

ff. Quality conformance inspection, if different (see 4.5).

gg. Performance test, if different (see 4.7.3).

hh. If preservation, packing, and marking in accordance with MIL-M-18058 is required, specify level required and specification number (see 5.1).

6.2.2 Contract data requirements. Required technical data (operating manuals, parts lists, wiring diagrams, foundation and anchor bolt plans, and acceptance test reports) should be specified on a DD Form 1423, Contract Data Requirements List, incorporated into the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:32Z
Check the source to verify that this is the current version before use.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Subject term (keyword) listing.

Horizontal
Knee type
Machine tools
Milling machine

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

TABLE I. Sizes and capacities.

Characteristics	Type I, plain table, and type II, universal table			
	Size 2	Size 3		
		Class 1	Class 2	Class 3
Table:				
Travel, inches:				
Longitudinal	28	34	34	34
Cross	8	12	12	12
Vertical	16-1/2	16	17	17
Working surface, inches	49 x 10	55 x 12	63 x 13	68 x 15
Top of table to spindle centerline, inches	0 to 16	0 to 16-1/2	0 to 17	0 to 17-1/2
Number of feeds	12	12	16	16
Feedrate range, ipm:				
Longitudinal	5/8 to 24	5/8 to 24	5/8 to 31	3/4 to 31
Cross	5/8 to 24	5/8 to 24	5/8 to 31	3/4 to 31
Vertical	3/8 to 7	3/8 to 9	3/8 to 9	1/4 to 9
Feed motor horsepower	1-1/2	2	2	4
Power rapid traverse, ipm:				
Longitudinal	72	72	118	118
Cross	72	72	118	118
Vertical	20	20	35	35
Spindle:				
Drive motor horsepower	4	7-1/2	10	15
American National Standard Taper	40	50	50	50
Number of speeds	12	12	16	16
Speed range, rpm	40 to 1400	40 to 1400	40 to 1400	18 to 1600
Independent overarm spindle (see 3.9.6):				
Spindle motor, hp	3	5	5	5
Number of speeds	8	8	8	8
Speed range, rpm	100 to 1000	100 to 1400	100 to 1400	100 to 1500
American National Standard Taper	50	50	50	50

NOTE 1: Machine size shall not be less than the stated requirements of the size specified in 6.2.1, nor shall it exceed the size requirements specified in 6.2.1 by more than 10 percent.

NOTE 2: An infinitely variable feed rate is acceptable provided it meets the requirements and ranges shown in the above table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

TABLE I. Sizes and capacities continued.

Characteristics	Type I, plain table, and type II, universal table		
	Size 4		Size 5
	Class 1	Class 2	
Table:			
Travel, inches:			
Longitudinal	42	42	48
Cross	15-3/4	16	16
Vertical	18	20	20
Working surface, inches	71 x 15-3/4	75 x 16-1/2	87 x 16-1/4
Top of table to spindle centerline, inches	0 to 18	0 to 20	0 to 20
Number of feeds	16	16	16
Feedrate range, ipm:			
Longitudinal	5/8 to 30	1/2 to 30	1/2 to 60
Cross	5/8 to 30	1/2 to 30	1/2 to 60
Vertical	1/8 to 9	1/8 to 9	1/4 to 28
Feed motor horsepower	4	4	4-1/2
Power rapid traverse, ipm:			
Longitudinal	118	118	120
Cross	118	118	118
Vertical	35	35	35
Spindle:			
Drive motor horsepower	15	20	20
American National Standard Taper	50	50	50
Number of speeds	16	18	18
Speed range, rpm	40 to 1400	28 to 1400	16 to 1600
Independent overarm spindle (see 3.9.6):			
Spindle motor, hp	5	5	5
Number of speeds	8	8	8
Speed range, rpm	100 to 1400	100 to 1400	100 to 1500
American National Standard Taper	50	50	50

NOTE 1: Machine size shall not be less than the stated requirements of the size specified in 6.2.1, nor shall it exceed the size requirements specified in 6.2.1 by more than 10 percent.

NOTE 2: An infinitely variable feed rate is acceptable provided it meets the requirements and ranges shown in the above table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

TABLE II. Alignment accuracies.

Description	Allowable deviation, not more than
Spindle:	
Axial runout	0.0002 inch TIR
Radial runout	0.0004 inch TIR
Taper runout:	
Measured 1-1/4 inches from spindle	0.0005 inch TIR
Measured 12 inches from spindle	0.001 inch TIR
Cross movement parallel with spindle:	
Vertical plane	0.001 inch in 12 inches
Horizontal plane	0.001 inch in 12 inches
Overarms parallel with spindle:	
Vertical plane	0.001 inch in 12 inches
Horizontal plane	0.001 inch in 12 inches
Alignment of arbor supports with spindle, runout	0.002 inch TIR
Table top parallel with spindle	0.001 inch in 12 inches
Table top square with vertical movement of knee in plane parallel with column	0.001 inch in 12 inches
Rise and fall of table in longitudinal movement	0.001 inch in 12 inches
T-slots square with table top	0.001 inch per inch
Center T-slots parallelwith table movement	0.001 inch in 12 inches
Center T-slot square with spindle	0.001 inch in 12 inches
Vertical movement parallel with column face	0.001 inch in 12 inches
Movement of knee when clamp is locked	0.001 inch

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:32Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review activities:
Army - AL
Navy - YD
Air Force - 84
DLA - GS

User activities:
Navy - MC

Preparing activity:
DLA-IP

(Project 3417-0178)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-80044D	Milling Machines, Horizontal Spindle, Knee Type, Size Numbers 2, 3, 4, and 5

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:32Z
Check the source to verify that this is the current version before use.