INCH-POUND
MIL-PRF-39001/5C
28 August 1997
SUPERSEDING
MIL-C-39001/5B
10 May 1976


PERFORMANCE SPECIFICATION SHEET


CAPACITORS, FIXED, MICA DIELECTRIC, ESTABLISHED RELIABILITY, STYLES CMR03, CMR04, CMR05, CMR06, CMR07, AND CMR08

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-39001.

FAILURE RATE LEVEL 'L' IS INACTIVE FOR DESIGN AFTER 29 JULY 1983





CIRCUIT DIAGRAM

NOTES:
1. Dimensions are in inches (see table I).
2. Millimeters are in parenthesis (see table I).
3. Metric equivalents (to the nearest .01 mm) are given for general information only.
4. The "R" dimension may not be solderable as it may be covered by a clear epoxy or resinous coating.

FIGURE 1. Styles CMR03, CMR04, CMR05, CMR06, CMR07, and CMR08 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

TABLE 1. Dimensions.

STYLE CMR03												
	300 V			100 V			50 V			300 V, 100 V, and 50 V		
Capacitance	L	W	T	L	W	T	L	W	T	R MAX	A spacing	M DIA
(pF)	MAXIMUM			MAXIMUM			MAXIMUM				.031 (.79)	.002 (.05)
1 to 12 inclusive	.270 (6.86)	.190 (4.83)	.110 (2.79)							.078 (1.98)	.120 (3.05)	.016 (.41)
15	.270 (6.86)	.190 (4.83)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.110 (2.79)				.078 (1.98)	.120 (3.05)	.016 (.41)
18 & 20	.270 (6.86)	.200 (5.08)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.110 (2.79)				.078 (1.98)	.120 (3.05)	.016 (.41)
22 & 24	.270 (6.86)	.200 (5.08)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.110 (2.79)	.078 (1.98)	.120 (3.05)	.016 (.41)
27	.270 (6.86)	.200 (5.08)	.130 (3.30)	.270 (6.86)	.190 (4.83)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.110 (2.79)	.078 (1.98)	.120 (3.05)	.016 (.41)
30 & 33	.270 (6.86)	.200 (5.08)	.130 (3.30)	.270 (6.86)	.200 (5.08)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.110 (2.79)	.078 (1.98)	.120 (3.05)	.016 (.41)
36	.270 (6.86)	.210 (5.33)	.130 (3.30)	.270 (6.86)	.200 (5.08)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.110 (2.79)	.078 (1.98)	.120 (3.05)	.016 (.41)
39	.270 (6.86)	.210 (5.33)	.130 (3.30)	.270 (6.86)	.200 (5.08)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.120 (3.05)	.078 (1.98)	.120 (3.05)	.016 (.41)
43	.270 (6.86)	.210 (5.33)	.140 (3.56)	.270 (6.86)	.200 (5.08)	.120 (3.05)	.270 (6.86)	.190 (4.83)	.120 (3.05)	.078 (1.98)	.120 (3.05)	.016 (.41)
47 & 51	.270 (6.86)	.210 (5.33)	.140 (3.56)	.270 (6.86)	.200 (5.08)	.130 (3.30)	.270 (6.86)	.190 (4.83)	.120 (3.05)	.078 (1.98)	.120 (3.05)	.016 (.41)
56	.270 (6.86)	.220 (5.59)	.150 (3.81)	.270 (6.86)	.200 (5.08)	.130 (3.30)	.270 (6.86)	.190 (4.83)	.120 (3.05)	.078 (1.98)	.120 (3.05)	.016 (.41)
62	.270 (6.86)	.220 (5.59)	.150 (3.81)	.270 (6.86)	.210 (5.33)	.130 (3.30)	.270 (6.86)	.200 (5.08)	.120 (3.05)	.078 (1.98)	.120 (3.05)	.016 (.41)
68	.270 (6.86)	.220 (5.59)	.150 (3.81)	.270 (6.86)	.210 (5.33)	.140 (3.56)	.270 (6.86)	.200 (5.08)	.120 (3.05)	.078 (1.98)	.120 (3.05)	.016 (.41)
75 & 82	.270 (6.86)	.230 (5.84)	.160 (4.06)	.270 (6.86)	.210 (5.33)	.140 (3.56)	.270 (6.86)	.200 (5.08)	.120 (3.05)	.078 (1.98)	.120 (3.05)	.016 (.41)
91	.270 (6.86)	.230 (5.84)	.170 (4.32)	.270 (6.86)	.210 (5.33)	.140 (3.56)	.270 (6.86)	.200 (5.08)	.130 (3.30)	.078 (1.98)	.120 (3.05)	.016 (.41)
100 & 110	.270 (6.86)	.240 (6.10)	.180 (4.57)	.270 (6.86)	.220 (5.59)	.150 (3.81)	.270 (6.86)	.200 (5.08)	.130 (3.30)	.078 (1.98)	.120 (3.05)	.016 (.41)
120	.270 (6.86)	.250 (6.35)	.190 (4.83)	.270 (6.86)	.220 (5.59)	.160 (4.06)	.270 (6.86)	.200 (5.08)	.130 (3.30)	.078 (1.98)	.120 (3.05)	.016 (.41)
130				.270 (6.86)	.230 (5.84)	.160 (4.06)	.270 (6.86)	.210 (5.33)	.130 (3.30)	.078 (1.98)	.120 (3.05)	.016 (.41)
150				.270 (6.86)	.230 (5.84)	.170 (4.32)	.270 (6.86)	.210 (5.33)	.140 (3.56)	.078 (1.98)	.120 (3.05)	.016 (.41)
160				.270 (6.86)	.240 (6.10)	.170 (4.32)	.270 (6.86)	.210 (5.33)	.140 (3.56)	.078 (1.98)	.120 (3.05)	.016 (.41)
170 & 180				.270 (6.86)	.240 (6.10)	.180 (4.57)	.270 (6.86)	.210 (5.33)	.140 (3.56)	.078 (1.98)	.120 (3.05)	.016 (.41)
200				.270 (6.86)	.250 (6.35)	.190 (4.83)	.270 (6.86)	.220 (5.59)	.150 (3.81)	.078 (1.98)	.120 (3.05)	.016 (.41)
220							.270 (6.86)	.220 (5.59)	.150 (3.81)	.078 (1.98)	.120 (3.05)	.016 (.41)
240							.270 (6.86)	.220 (5.59)	.160 (4.06)	.078 (1.98)	.120 (3.05)	.016 (.41)
270							.270 (6.86)	.230 (5.84)	.160 (4.06)	.078 (1.98)	.120 (3.05)	.016 (.41)
300							.270 (6.86)	.230 (5.84)	.170 (4.32)	.078 (1.98)	.120 (3.05)	.016 (.41)
330 & 360							.270 (6.86)	.240 (6.10)	.180 (4.57)	.078 (1.98)	.120 (3.05)	.016 (.41)
390 & 400							.270 (6.86)	.250 (6.35)	.190 (4.83)	.078 (1.98)	.120 (3.05)	.016 (.41)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions - Continued.

Capacitance (pF)	L		T		W, max	R, max	A spacing ±0.31 (.79)	M Dia ±.002 (.05)
	Min	Max	Min	Max				
STYLE CMR04								
1 to 24, inclusive	.300 (7.62)	.360 (9.14)	.100 (2.54)	.190 (4.83)	.330 (8.38)	.125 (3.18)	.150 (3.81)	.016 (.41)
27	.300 (7.62)	.370 (9.40)	.100 (2.54)	.190 (4.83)	.330 (8.38)	.125 (3.18)	.150 (3.81)	.016 (.41)
30 to 68, inclusive	.300 (7.62)	.370 (9.40)	.100 (2.54)	.190 (4.83)	.340 (8.64)	.125 (3.18)	.150 (3.81)	.016 (.41)
75	.300 (7.62)	.370 (9.40)	.110 (2.79)	.200 (5.08)	.340 (8.64)	.125 (3.18)	.150 (3.81)	.016 (.41)
82	.300 (7.62)	.370 (9.40)	.110 (2.79)	.200 (5.08)	.350 (8.89)	.125 (3.18)	.150 (3.81)	.016 (.41)
91 & 100	.300 (7.62)	.370 (9.40)	.110 (2.79)	.200 (5.08)	.350 (8.89)	.125 (3.18)	.150 (3.81)	.016 (.41)
110 & 120	.300 (7.62)	.380 (9.65)	.110 (2.79)	.200 (5.08)	.350 (8.89)	.125 (3.18)	.150 (3.81)	.016 (.41)
130	.300 (7.62)	.380 (9.65)	.110 (2.79)	.200 (5.08)	.360 (9.14)	.125 (3.18)	.150 (3.81)	.016 (.41)
150 & 160	.300 (7.62)	.380 (9.65)	.120 (3.05)	.210 (5.33)	.360 (9.14)	.125 (3.18)	.150 (3.81)	.016 (.41)
180	.300 (7.62)	.390 (9.91)	.120 (3.05)	.210 (5.33)	.370 (9.40)	.125 (3.18)	.150 (3.81)	.016 (.41)
220 to 390, inclusive	.300 (7.62)	.390 (9.91)	.140 (3.56)	.220 (5.59)	.380 (9.65)	.125 (3.18)	.150 (3.81)	.016 (.41)
STYLE CMR05								
1 to 62, inclusive	.400 (10.16)	.450 (11.43)	.090 (2.29)	.170 (4.32)	.360 (9.14)	.125 (3.18)	.225 (5.72)	.025 (.64)
68 to 82, inclusive	.400 (10.16)	.450 (11.43)	.095 (2.41)	.180 (4.57)	.360 (9.14)	.125 (3.18)	.225 (5.72)	.025 (.64)
91 & 100	.400 (10.16)	.460 (11.68)	.095 (2.41)	.180 (4.57)	.360 (9.14)	.125 (3.18)	.225 (5.72)	.025 (.64)
110 to 130, inclusive	.400 (10.16)	.460 (11.68)	.095 (2.41)	.180 (4.57)	.370 (9.40)	.125 (3.18)	.225 (5.72)	.025 (.64)
150 to 180, inclusive	.400 (10.16)	.460 (11.68)	.110 (2.79)	.190 (4.83)	.370 (9.40)	.125 (3.18)	.225 (5.72)	.025 (.64)
200	.400 (10.16)	.460 (11.68)	.110 (2.79)	.190 (4.83)	.380 (9.65)	.125 (3.18)	.225 (5.72)	.025 (.64)
220 & 240	.400 (10.16)	.460 (11.68)	.110 (2.79)	.200 (5.08)	.380 (9.65)	.125 (3.18)	.225 (5.72)	.025 (.64)
270 to 330, inclusive	.400 (10.16)	.470 (11.94)	.110 (2.79)	.210 (5.33)	.390 (9.91)	.125 (3.18)	.225 (5.72)	.025 (.64)
360 & 390	.400 (10.16)	.470 (11.94)	.120 (3.05)	.220 (5.59)	.400 (10.16)	.125 (3.18)	.225 (5.72)	.025 (.64)
STYLE CMR06								
430 & 470	.550 (13.97)	.640 (16.26)	.090 (2.29)	.200 (5.08)	.510 (12.95)	.141 (3.58)	.350 (8.89)	.032 (.81)
510 to 620, inclusive	.560 (14.22)	.650 (16.51)	.090 (2.29)	.200 (5.08)	.510 (12.95)	.141 (3.58)	.350 (8.89)	.032 (.81)
680 to 910, inclusive	.560 (14.22)	.650 (16.51)	.100 (2.54)	.210 (5.33)	.510 (12.95)	.141 (3.58)	.350 (8.89)	.032 (.81)
1000 & 1100	.560 (14.22)	.650 (16.51)	.110 (2.79)	.220 (5.59)	.520 (13.21)	.141 (3.58)	.350 (8.89)	.032 (.81)
1200 & 1300	.570 (14.48)	.660 (16.76)	.110 (2.79)	.220 (5.59)	.520 (13.21)	.141 (3.58)	.350 (8.89)	.032 (.81)
1500	.570 (14.48)	.660 (16.76)	.120 (3.05)	.230 (5.84)	.520 (13.21)	.141 (3.58)	.350 (8.89)	.032 (.81)
1600	.570 (14.48)	.660 (16.76)	.120 (3.05)	.230 (5.84)	.530 (13.46)	.141 (3.58)	.350 (8.89)	.032 (.81)
1800 & 2000	.580 (14.73)	.670 (17.02)	.130 (3.30)	.240 (6.10)	.530 (13.46)	.141 (3.58)	.350 (8.89)	.032 (.81)
2200	.580 (14.73)	.670 (17.02)	.140 (3.56)	.250 (6.35)	.530 (13.46)	.141 (3.58)	.350 (8.89)	.032 (.81)
2400	.580 (14.73)	.670 (17.02)	.150 (3.81)	.260 (6.60)	.540 (13.72)	.141 (3.58)	.350 (8.89)	.032 (.81)
2700	.590 (14.99)	.680 (17.27)	.160 (4.06)	.270 (6.86)	.540 (13.72)	.141 (3.58)	.350 (8.89)	.032 (.81)
3000	.590 (14.99)	.680 (17.27)	.170 (4.32)	.280 (7.11)	.550 (13.97)	.141 (3.58)	.350 (8.89)	.032 (.81)
3300	.590 (14.99)	.680 (17.27)	.180 (4.57)	.290 (7.37)	.550 (13.97)	.141 (3.58)	.350 (8.89)	.032 (.81)
3600	.590 (14.99)	.680 (17.27)	.190 (4.83)	.300 (7.62)	.560 (14.22)	.141 (3.58)	.350 (8.89)	.032 (.81)
3900	.600 (15.24)	.690 (17.53)	.200 (5.08)	.310 (7.87)	.560 (14.22)	.141 (3.58)	.350 (8.89)	.032 (.81)
4300	.600 (15.24)	.690 (17.53)	.220 (5.59)	.330 (8.38)	.570 (14.48)	.141 (3.58)	.350 (8.89)	.032 (.81)
4700	.610 (15.49)	.700 (17.78)	.220 (5.59)	.350 (8.89)	.570 (14.48)	.141 (3.58)	.350 (8.89)	.032 (.81)
STYLE CMR07								
5100	.680 (17.27)	.780 (19.81)	.150 (3.81)	.280 (7.11)	.860 (21.84)	.141 (3.58)	.425 (10.80)	.040 (1.02)
5600 & 6200	.680 (17.27)	.780 (19.81)	.150 (3.81)	.290 (7.37)	.870 (22.10)	.141 (3.58)	.425 (10.80)	.040 (1.02)
6800	.680 (17.27)	.780 (19.81)	.150 (3.81)	.300 (7.62)	.870 (22.10)	.141 (3.58)	.425 (10.80)	.040 (1.02)
7500	.690 (17.53)	.790 (20.07)	.150 (3.81)	.310 (7.87)	.880 (22.35)	.141 (3.58)	.425 (10.80)	.040 (1.02)
8200	.690 (17.53)	.790 (20.07)	.150 (3.81)	.320 (8.13)	.880 (22.35)	.141 (3.58)	.425 (10.80)	.040 (1.02)
9100	.690 (17.53)	.790 (20.07)	.150 (3.81)	.330 (8.38)	.880 (22.35)	.141 (3.58)	.425 (10.80)	.040 (1.02)
10,000	.700 (17.78)	.800 (20.32)	.200 (5.08)	.340 (8.64)	.890 (22.61)	.141 (3.58)	.425 (10.80)	.040 (1.02)
11,000	.700 (17.78)	.800 (20.32)	.200 (5.08)	.350 (8.89)	.890 (22.61)	.141 (3.58)	.425 (10.80)	.040 (1.02)
12,000	.700 (17.78)	.800 (20.32)	.200 (5.08)	.360 (9.14)	.890 (22.61)	.141 (3.58)	.425 (10.80)	.040 (1.02)
13,000	.710 (18.03)	.810 (20.57)	.250 (6.35)	.370 (9.40)	.890 (22.61)	.141 (3.58)	.425 (10.80)	.040 (1.02)
15,000	.710 (18.03)	.810 (20.57)	.250 (6.35)	.390 (9.91)	.900 (22.86)	.141 (3.58)	.425 (10.80)	.040 (1.02)
16,000	.720 (18.29)	.820 (20.83)	.250 (6.35)	.410 (10.41)	.900 (22.86)	.141 (3.58)	.425 (10.80)	.040 (1.02)
18,000	.720 (18.29)	.820 (20.83)	.250 (6.35)	.430 (10.92)	.910 (23.11)	.141 (3.58)	.425 (10.80)	.040 (1.02)
20,000	.730 (18.54)	.830 (21.08)	.250 (6.35)	.450 (11.43)	.920 (23.37)	.141 (3.58)	.425 (10.80)	.040 (1.02)
STYLE CMR08								
22,000	1.300 (33.02)	1.420 (36.07)	.180 (4.57)	.310 (7.87)	.880 (22.35)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
24,000	1.310 (33.27)	1.430 (36.32)	.180 (4.57)	.320 (8.13)	.880 (22.35)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
27,000	1.320 (33.53)	1.430 (36.32)	.180 (4.57)	.330 (8.38)	.880 (22.35)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
30,000	1.330 (33.78)	1.440 (36.58)	.180 (4.57)	.350 (8.89)	.890 (22.61)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
33,000	1.330 (33.78)	1.440 (36.58)	.180 (4.57)	.360 (9.14)	.890 (22.61)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
36,000	1.340 (34.04)	1.450 (36.83)	.180 (4.57)	.380 (9.65)	.900 (22.86)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
39,000	1.340 (34.04)	1.450 (36.83)	.220 (5.59)	.400 (10.16)	.900 (22.86)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
43,000	1.350 (34.29)	1.460 (37.08)	.225 (5.72)	.420 (10.67)	.910 (23.11)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
47,000	1.360 (34.54)	1.470 (37.34)	.250 (6.35)	.450 (11.43)	.910 (23.11)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
51,000	1.370 (34.80)	1.480 (37.59)	.250 (6.35)	.470 (11.94)	.920 (23.37)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
56,000	1.350 (34.29)	1.460 (37.08)	.225 (5.72)	.420 (10.67)	.910 (23.11)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
62,000	1.360 (34.54)	1.470 (37.34)	.250 (6.35)	.450 (11.43)	.920 (23.37)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
68,000	1.370 (34.80)	1.480 (37.59)	.260 (6.60)	.470 (11.94)	.920 (23.37)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
75,000	1.370 (34.54)	1.470 (37.34)	.240 (6.10)	.440 (11.18)	.910 (23.11)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
82,000	1.370 (34.80)	1.480 (37.59)	.310 (7.87)	.460 (11.68)	.920 (23.37)	.141 (3.58)	1.050 (26.67)	.040 (1.02)
91,000	1.390 (35.31)	1.500 (38.10)	.340 (8.64)	.500 (12.70)	.940 (23.88)	.141 (3.58)	1.050 (26.67)	.040 (1.02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimension: See figure 1 and table I.

Case: Resin (dipped).

Capacitance value: See table II.

Capacitance tolerance: See table II.

DC rated voltage: 50 V (Y); 100 V (A); 300 V (C); or 500 V(D), as shown in table II.

Operating temperature range: See table II.

Characteristic: See table II.

Failure rate level: See table II.

Barometric pressure: Method 105 of MIL-STD-202, condition D (100,000 ft). Test potential - 100 percent of rated dc voltage for style CMR04, 500 volts; 150 percent for lesser voltages and all other styles.

Insulation resistance (IR): Method 302 of MIL-STD-202, test condition A: (Minimum requirements):

At 25°C:
0 to 10,000 pF..... 100,000 megohms
10,000 pF and greater.. 1,000 megohm-microfarads

At 125°C:
0 to 3,300 pF..... 10,000 megohms
3,300 pF and greater.... 33 megohm-microfarads

At 150°C
0 to 1,500 pF..... 5,000 megohms
1,500 pF and greater.... 7.5 megohm-microfarads

Dissipation factor (DF): See MIL-PRF-39001.

High voltage stabilization: 200 percent of rated dc voltage for 48 hours at a minimum temperature of 125°C or 150°C, as applicable.

Thermal shock and immersion:

Thermal shock: In accordance with MIL-PRF-39001 except high temperature shall be as follows:
Symbol O - +125°C.
Symbol P - +150°C.

Immersion: In accordance with MIL-PRF-39001 except ΔCap.- shall not exceed ±1 percent or 1pF,whichever is greater, of reference measurement.

Terminal strength:

Pull test - For style CMR03, pull shall be applied in the direction of the leads.

Moisture resistance: In accordance with MIL-PRF-39001 except ΔCap. -shall not exceed ±1 percent or pF, whichever is greater, of reference measurement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

Life:

Forty eight hours, minimum, at 55°C +0°C, -2°C immediately followed by qualification or quality conformance test, as applicable.

Qualification test: 2,000 hours at applicable high test temperature with 100 percent or 150 percent of rated dc voltage applied, as applicable.

DWV	-	Meet initial requirement.
IR	-	Meet initial requirement.
ΔCap.	-	Shall not exceed ±1 percent or 1 pF, whichever is greater, or the initial measurement.
DF	-	Not greater than 150 percent of initial requirement.

Quality conformance test: 2,000 hours (M, P, R, and S FRLs) at applicable high test temperature and 150 percent of rated dc voltage; requirements as specified for qualification.

Resistance to soldering heat: In accordance with MIL-PRF-39001 except ΔCap. shall not exceed ±1 percent or 1 pF, whichever is greater, of the initial measurement.

Marking: Capacitors shall be marked as indicated in examples on figure 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.




FIGURE 2. Marking examples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

TABLE II. Type designations.

STYLE CMR03				
Type designation 1/	Capacitance value	DC rated voltage	Operating temperature range	Capacitance tolerance available
	(pF)	(volts)		
CMR03C1R0DOC-	1.0	300	O	D
CMR03C1R5DOC-	1.5	300	O	D
CMR03C2R0DOC-	2.0	300	O	D
CMR03C2R5DOC-	2.5	300	O	D
CMR03C3R0DOC-	3.0	300	O	D
CMR03C3R5DOC-	3.5	300	O	D
CMR03C4R0DOC-	4.0	300	O	D
CMR03C4R5DOC-	4.5	300	O	D
CMR03C5R0DOC-	5.0	300	O	D
CMR03C6R0DOC-	6.0	300	O	D
CMR03C7R0DOC-	7.0	300	O	D
CMR03C8R0DOC-	8.0	300	O	D
CMR03C9R0DOC-	9.0	300	O	D
CMR03C10R0DOC-	10	300	O	D
CMR03C11R0DOC-	11	300	O	D
CMR03C12R0DOC-	12	300	O	D
CMR03C150DO--	15	300, 100	O	D
CMR03C180DO--	18	300, 100	O	D
CMR03E200DO--	20	300, 100	O	D
CMR03E220DO--	22	300, 100, 50	O	D
CMR03E240DO--	24	300, 100, 50	O	D
CMR03E270 -O--	27	300, 100, 50	O	G, J
CMR03E300 -O--	30	300, 100, 50	O	G, J
CMR03E330 -O--	33	300, 100, 50	O	G, J
CMR03E360 -O--	36	300, 100, 50	O	G, J
CMR03E390 -O--	39	300, 100, 50	O	G, J
CMR03E430 -O--	43	300, 100, 50	O	G, J
CMR03E470 -O--	47	300, 100, 50	O	G, J
CMR03E510 -O--	51	300, 100, 50	O	G, J
CMR03E560JO--	56	300, 100, 50	O	G, J
CMR03E620JO--	62	300, 100, 50	O	G, J
CMR03E680JO--	68	300, 100, 50	O	G, J
CMR03E750JO--	75	300, 100, 50	O	G, J
CMR03E820JO--	82	300, 100, 50	O	G, J
CMR03F910JO--	91	300, 100, 50	O	G, J
CMR03F101JO--	100	300, 100, 50	O	G, J
CMR03F111JO--	110	300, 100, 50	O	G, J
CMR03F121JO--	120	300, 100, 50	O	G, J
CMR03F131JO--	130	100, 50	O	G, J
CMR03F151JO--	150	100, 50	O	G, J
CMR03F161JO--	160	100, 50	O	G, J
CMR03F171JO--	170	100, 50	O	G, J
CMR03F181JO--	180	100, 50	O	G, J
CMR03F201JO--	200	100, 50	O	G, J
CMR03F221JOY-	220	50	O	G, J
CMR03F241JOY-	240	50	O	G, J
CMR03F271JOY-	270	50	O	G, J
CMR03F301JOY-	300	50	O	G, J
CMR03F331JOY-	330	50	O	G, J
CMR03F361JOY-	360	50	O	G, J
CMR03F391JOY-	390	50	O	G, J
CMR03F401JOY-	400	50	O	G, J

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

TABLE II. Type designations - Continued.

STYLE CMR04				
Type designation 1/	Capacitance value	DC rated voltage	Operating temperature range	Capacitance tolerance available
	(pF)	(volts)		
CMR04C1R0DOC-	1.0	500	O, P	D
CMR04C1R5DOC-	1.5	500	O, P	D
CMR04C2R0DOC-	2.0	500	O, P	D
CMR04C2R5DOC-	2.5	500	O, P	D
CMR04C3R0DOC-	3.0	500	O, P	D
CMR04C3R5DOC-	3.5	500	O, P	D
CMR04C4R0DOC-	4.0	500	O, P	D
CMR04C4R5DOC-	4.5	500	O, P	D
CMR04C5R0DOC-	5.0	500	O, P	D
CMR04C6R0DOC-	6.0	500	O, P	D
CMR04C7R0DOC-	7.0	500	O, P	D
CMR04C8R0DOC-	8.0	500	O, P	D
CMR04C9R0DOC-	9.0	500	O, P	D
CMR04C10R0DOC-	10	500	O, P	D
CMR04C11R0DOC-	11	500	O, P	D
CMR04C12R0DOC-	12	500	O, P	J
CMR04C150J-D-	15	500	O, P	J
CMR04C180J-D-	18	500	O, P	J
CMR04E200J-D-	20	500	O, P	J
CMR04E220J-D-	22	500	O, P	J
CMR04E240J-D-	24	500	O, P	J
CMR04E270 --D-	27	500	O, P	G, J
CMR04E300 --D-	30	500	O, P	G, J
CMR04E330 --D-	33	500	O, P	G, J
CMR04E360 --D-	36	500	O, P	G, J
CMR04E390 --D-	39	500	O, P	G, J
CMR04E430 --D-	43	500	O, P	G, J
CMR04E470 --D-	47	500	O, P	G, J
CMR04E510 --D-	51	500	O, P	F, G, J
CMR04E560--D-	56	500	O, P	F, G, J
CMR04E620--D-	62	500	O, P	F, G, J
CMR04E680--D-	68	500	O, P	F, G, J
CMR04E750--D-	75	500	O, P	F, G, J
CMR04E820--D-	82	500	O, P	F, G, J
CMR04F910--D-	91	500	O, P	F, G, J
CMR04F101--D-	100	500	O, P	F, G, J
CMR04F111--D-	110	500	O, P	F, G, J
CMR04F121--D-	120	500	O, P	F, G, J
CMR04F131--D-	130	500	O, P	F, G, J
CMR04F151--D-	150	500	O, P	F, G, J
CMR04F161--D-	160	500	O, P	F, G, J
CMR04F171--D-	170	500	O, P	F, G, J
CMR04F181--D-	180	500	O, P	F, G, J
CMR04F201--D-	200	500	O, P	F, G, J
CMR04F221--D-	220	500	O, P	F, G, J
CMR04F241--D-	240	500	O, P	F, G, J
CMR04F271--C-	270	300	O, P	F, G, J
CMR04F301--C-	300	300	O, P	F, G, J
CMR04F331--A-	330	100	O, P	F, G, J
CMR04F361--A-	360	100	O, P	F, G, J
CMR04F391--A-	390	100	O, P	F, G, J

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

TABLE II. Type designations - Continued.

STYLE CMR05				
Type designation 1/	Capacitance value	DC rated voltage	Operating temperature range	Capacitance tolerance available
	(pF)	(volts)		
CMR05C1R0D-D-	1.0	500	O, P	D
CMR05C1R5D-D-	1.5	500	O, P	D
CMR05C2R0D-D-	2.0	500	O, P	D
CMR05C2R5D-D-	2.5	500	O, P	D
CMR05C3R0D-D-	3.0	500	O, P	D
CMR05C3R5D-D-	3.5	500	O, P	D
CMR05C4R0D-D-	4.0	500	O, P	D
CMR05C4R5D-D-	4.5	500	O, P	D
CMR05C5R0D-D-	5.0	500	O, P	D
CMR05C6R0D-D-	6.0	500	O, P	D
CMR05C7R0D-D-	7.0	500	O, P	D
CMR05C8R0D-D-	8.0	500	O, P	D
CMR05C9R0D-D-	9.0	500	O, P	D
CMR05C100D-D-	10	500	O, P	D
CMR05C110D-D-	11	500	O, P	D
CMR05C120D-D-	12	500	O, P	J
CMR05C150J-D-	15	500	O, P	J
CMR05C18OJ-D-	18	500	O, P	J
CMR05E20OJ-D-	20	500	O, P	J
CMR05E22OJ-D-	22	500	O, P	J
CMR05E24OJ-D-	24	500	O, P	J
CMR05E270 --D-	27	500	O, P	G, J
CMR05E300 --D-	30	500	O, P	G, J
CMR05E330 --D-	33	500	O, P	G, J
CMR05E360 --D-	36	500	O, P	G, J
CMR05E390 --D-	39	500	O, P	G, J
CMR05E430 --D-	43	500	O, P	G, J
CMR05E470 --D-	47	500	O, P	G, J
CMR05E510 --D-	51	500	O, P	F, G, J
CMR05E560--D-	56	500	O, P	F, G, J
CMR05E620--D-	62	500	O, P	F, G, J
CMR05E680--D-	68	500	O, P	F, G, J
CMR05E750--D-	75	500	O, P	F, G, J
CMR05E820--D-	82	500	O, P	F, G, J
CMR05F910--D-	91	500	O, P	F, G, J
CMR05F101--D-	100	500	O, P	F, G, J
CMR05F111--D-	110	500	O, P	F, G, J
CMR05F121--D-	120	500	O, P	F, G, J
CMR05F131--D-	130	500	O, P	F, G, J
CMR05F151--D-	150	500	O, P	F, G, J
CMR05F161--D-	160	500	O, P	F, G, J
CMR05F171--D-	170	500	O, P	F, G, J
CMR05F181--D-	180	500	O, P	F, G, J
CMR05F201--D-	200	500	O, P	F, G, J
CMR05F221--D-	220	500	O, P	F, G, J
CMR05F241--D-	240	500	O, P	F, G, J
CMR05F271--D-	270	500	O, P	F, G, J
CMR05F301--D-	300	500	O, P	F, G, J
CMR05F331--D-	330	500	O, P	F, G, J
CMR05F361--D-	360	500	O, P	F, G, J
CMR05F391--D-	390	500	O, P	F, G, J

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

TABLE II. Type designations - Continued.

STYLE CMR06				
Type designation 1/	Capacitance value	DC rated voltage	Operating temperature range	Capacitance tolerance available
	(pF)	(volts)		
CMR06F431--D-	430	500	O, P	F, G, J
CMR06F471--D-	470	500	O, P	F, G, J
CMR06F511--D-	510	500	O, P	F, G, J
CMR06F561--D-	560	500	O, P	F, G, J
CMR06F621--D-	620	500	O, P	F, G, J
CMR06F681--D-	680	500	O, P	F, G, J
CMR06F751--D-	750	500	O, P	F, G, J
CMR06F821--D-	820	500	O, P	F, G, J
CMR06F911--D-	910	500	O, P	F, G, J
CMR06F102--D-	1,000	500	O, P	F, G, J
CMR06F112--D-	1,100	500	O, P	F, G, J
CMR06F122--D-	1,200	500	O, P	F, G, J
CMR06F132--D-	1,300	500	O, P	F, G, J
CMR06F152--D-	1,500	500	O, P	F, G, J
CMR06F162--D-	1,600	500	O, P	F, G, J
CMR06F182--D-	1,800	500	O, P	F, G, J
CMR06F202--D-	2,000	500	O, P	F, G, J
CMR06F222--D-	2,200	500	O, P	F, G, J
CMR06F242--D-	2,400	500	O, P	F, G, J
CMR06F272--D-	2,700	500	O, P	F, G, J
CMR06F302--D-	3,000	500	O, P	F, G, J
CMR06F332--D-	3,300	500	O, P	F, G, J
CMR06F362--D-	3,600	500	O, P	F, G, J
CMR06F392--D-	3,900	500	O, P	F, G, J
CMR06F432--D-	4,300	500	O, P	F, G, J
CMR06F472--D-	4,700	500	O, P	F, G, J
STYLE CMR07				
CMR07F512--D-	5,100	500	O, P	F, G, J
CMR07F562--D-	5,600	500	O, P	F, G, J
CMR07F622--D-	6,200	500	O, P	F, G, J
CMR07F682--D-	6,800	500	O, P	F, G, J
CMR07F752--D-	7,500	500	O, P	F, G, J
CMR07F822--D-	8,200	500	O, P	F, G, J
CMR07F912--D-	9,100	500	O, P	F, G, J
CMR07F103--D-	10,000	500	O, P	F, G, J
CMR07F113--D-	11,000	500	O, P	F, G, J
CMR07F123--D-	12,000	500	O, P	F, G, J
CMR07F133--D-	13,000	500	O, P	F, G, J
CMR07F153--D-	15,000	500	O, P	F, G, J
CMR07F163--D-	16,000	500	O, P	F, G, J
CMR07F183--D-	18,000	500	O, P	F, G, J
CMR07F203--D-	20,000	500	O, P	F, G, J

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

TABLE II. Type designations - Continued.

STYLE CMR08				
Type designation 1/	Capacitance value	DC rated voltage	Operating temperature range	Capacitance tolerance available
	(pF)	(volts)		
CMR08F223--D-	22000	500	O, P	F, G, J
CMR08F243--D-	24000	500	O, P	F, G, J
CMR08F273--D-	27000	500	O, P	F, G, J
CMR08F303--D-	30000	500	O, P	F, G, J
CMR08F333--D-	33000	500	O, P	F, G, J
CMR08F363--D-	36000	500	O, P	F, G, J
CMR08F393--D-	39000	500	O, P	F, G, J
CMR08F433--D-	43000	500	O, P	F, G, J
CMR08F473--D-	47000	500	O, P	F, G, J
CMR08F513--D-	51000	500	O, P	F, G, J
CMR08F563--C-	56000	300	O, P	F, G, J
CMR08F623--C-	62000	300	O, P	F, G, J
CMR08F683--C-	68000	300	O, P	F, G, J
CMR08F753--A-	75000	100	O, P	F, G, J
CMR08F823--A-	82000	100	O, P	F, G, J
CMR08F913--A-	91000	100	O, P	F, G, J

1/ Complete type designation will include additional letter symbols to indicate the following, where applicable:

Capacitance tolerance: D (±.5 F); F(±1%); G(±2%); or J(±5%).
Operating temperature range: 0 (-55° to 125°C) or P (-55° to +150°C).
Rated voltage: Y (50v); A (100v); C (300v); or D (500v).
Failure rate level: M (1.0%); P (0.1%); R (0.01%); or S (0.001%).

TABLE III. Substitutability data.

Substitute item:	Substitute for:
MIL-C-39001/5B	MIL-C-39001/5
CMR04C1R0D-D-	CMR04C010D-D-
CMR04C5R0D-D-	CMR04C050D-D-
CMR04C6R0D-D-	CMR04C060D-D-
CMR04C7R0D-D-	CMR04C070D-D-
CMR04C8R0D-D-	CMR04C080D-D-
CMR05C1R0D-D-	CMR05C010D-D-
CMR05C5R0D-D-	CMR05C050D-D-
CMR05C6R0D-D-	CMR05C060D-D-
CMR05C7R0D-D-	CMR05C070D-D-
CMR05C8R0D-D-	CMR05C080D-D-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AV, MI
Navy - MC
Air Force - 17, 19
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-1945-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:59Z
Check the source to verify that this is the current version before use.