
MILITARY SPECIFICATION SHEET

RESISTOR, VARIABLE, WIRE-WOUND
SEMI-PRECISION, STYLE RK11

This specification sheet is approved for use by the Electronics Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the resistor described herein shall consist of this document and the latest issue of Specification MIL-R-39002.



INCHES	MM	INCHES	MM	INCHES	MM
.018	.46	.095	2.41	.396	10.06
.03	.8	.115	2.92	.408	10.36
.04	1.0	.1245	3.162	.585	14.86
.047	1.19	.1250	3.175	.600	15.24
.062	1.57	.250	6.35	.615	15.62
.063	1.60	.285	7.24	.825	20.96
.075	1.90	.312	7.92	.855	21.72
.085	2.16	.315	8.00	4.000	101.60
.088	2.24	.320	8.13		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.

FIGURE 1. Style RK11 resistor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:01Z
Check the source to verify that this is the current version before use.




FIGURE 2. Shaft to bushing seal test.

Source: https://assist.dla.mil -- Downloaded: 202610-21T16:01Z
Check the source to verify that this is the current version before use.

TABLE I. Style RR11 resistor.

Type 1/ designation	Shaft length inches ± .015 shaft style	Nominal total resistor value (ohms)	Nominal 2/ resolution (percent)	Rated ac and dc working voltage (volts)	Terminal	Dash number
RK11SLCS502	.840 inch slotted	5000	0.17	122	S	0001

1/ For reference purpose only.
2/ Percent of resolution = $\frac{1}{N} X\ 100$. N = number of turns.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Resistance value: 5,000 ohms ± 5 percent.

Shaft length: See table I.

Shaft style: See table I.

Bushing: See figure I.

Power rating: 1.5 watt at full load operation at an ambient temperature of 85°C.

Nominal resolution: See table I.

Rated working voltage: See table I.

Hardware: Hardware shall be as specified in figure I and shall be corrosion resistant. (Hardware optional between supplier and prime contractor).

Mechanical travels 360°.

Actual effective electrical travel: 300° ± 3°.

Linearity: Independent linearity ± 1 percent.

Dielectric withstanding voltage: At atmospheric pressure - Method 301 of MIL-STD-202, test voltage 900 volts rms. At reduced barometric pressure - Method 105, test condition D, MIL-STD-202.

Electrical output: The electrical output (in terms of percent of applied voltage) is linear with respect to the angular position of the contact arm.

Insulation resistance: Method 302, test condition A, MIL-STD-202.

Torque: The torque required to effect rotation shall be 0.5 ounce-inches to 6 ounce-inches.

Thermal shock: Method 107, test condition B, MIL-STD-202.

Resistance temperature characteristic: Method 304 of MIL-STD-202.

Moisture resistance: Method 106 of MIL-STD-202.

Shock, specified pulse: Method 205, test condition G, MIL-STD-202.

Vibration, high frequency: Method 204, test condition D, MIL-STD-202.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:01Z
Check the source to verify that this is the current version before use.

Salt spray: Method 101, test condition A, MIL-STD-202.

Resistance to soldering heat: Method 210, test condition A, MIL-STD-202.

Life: Method 108, test condition D, MIL-STD-202.

Rotational life: In accordance with MIL-R-39002 except the cycle angle shall be not less than 98 percent of the effective electrical travel angle. Electrical continuity shall be maintained throughout the cycle.

Terminal strength: Method 211, test condition A, MIL-STD-202.

Strength of mounting bushing: The potentiometer shall withstand, without damage, a torque of from 15.5 to 16.5 inch-pounds applied to tighten the mounting nut for five seconds.

Shaft-to-bushing seal (O-ring shaft seal):

a. Condition the sample at -80°F and + 160°F for 15 minutes at each temperature extreme with five minutes maximum between temperature extremes and return to room temperature.

b. Mount the test units as shown in figure 2. The mounting nut shall be torqued to 15.5 to 16.5 inch pounds.

c. Immerse the test chamber in water as shown in figure 2. Pressurize the sealed test chamber with dry air or nitrogen to 5 ± 0.5 psig for 60 ± 10 seconds.

d. There shall be no evidence of a continuous stream of bubbles emanating from the shaft to bushing seal.

e. The AQL (percent defective) major shall be 0.65.


Qualification: Those manufacturers qualified to Style RK09 can extend qualifications to Style RK11 by submitting and passing the following additional test: 13 units tested to the strength of mounting bushing test, and 12 units to the shaft-to-bushing seal test. No failures are allowed.

Quality conformance inspection: The following test shall be included for group A inspection:

Shaft-to-bushing seal	AQL = 0.65 major

Part number: Consists of the basic number of this specification sheet and a dash number taken from table I.

Example:



Custodian:
Army - ER

Review activity:
DLA - ES

User activity
Army - AR

Preparing activity:
Army - ER

Agents
DLA - ES

(Project 5905-A272)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:01Z
Check the source to verify that this is the current version before use.