INCH-POUND
MIL-PRF-39003H
SUPPLEMENT 1A
18 July 2000

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM, ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39003H, dated 20 March 1992

MIL-PRF-39003/1	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR13.
MIL-PRF-39003/2	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR09.
MIL-PRF-39003/3	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR23.
MIL-PRF-39003/4	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Nonpolarized, Sintered Slug), Established Reliability, Style CSR91.
MIL-PRF-39003/6	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug) Established Reliability, Style CSR33.
MIL-PRF-39003/9	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), High Frequency, Established Reliability, Style CSR21.
MIL-PRF-39003/10	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Styles CSS13 and CSS33 (High Reliability Applications).

Preparing activity:
DLA - CC

(Project 5910-2094)

AMSC N/A FSC 5910
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:02Z
Check the source to verify that this is the current version before use.