INCH-POUND
MIL-PRF-39003M
SUPPLEMENT 1
15 May 2009

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39003M, dated 12 May 2009

SPECIFICATION SHEETS

MIL-PRF-39003/1	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR13.
MIL-PRF-39003/2	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR09.
MIL-PRF-39003/3	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR23.
MIL-PRF-39003/4	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Nonpolarized, Sintered Slug), Established Reliability, Style CSR91.
MIL-PRF-39003/6	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Style CSR33.
MIL-PRF-39003/9	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), High Frequency, Established Reliability, Style CSR21.
MIL-PRF-39003/10	Capacitors, Fixed, Electrolytic (Solid Electrolyte), Tantalum, (Polarized, Sintered Slug), Established Reliability, Styles CSS13 and CSS33 (High Reliability Applications).

Custodians:
Army – CR
Navy - EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2009-036)

Review activities:
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at http://assist.daps.dla.mil .

AMSC N/A

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:01Z
Check the source to verify that this is the current version before use.