INCH-POUND

MIL-C-39003/1G
AMENDMENT 2
10 November 1994
SUPERCEEDING
AMENDMENT 1
10 June 1993

MILITARY SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM,
(POLARIZED, SINTERED SLUG), ESTABLISHED RELIABILITY,
STYLE CSR13

This amendment forms a part of MIL-C-39003/1G, dated 31 January 1992, and is approved for use by all Department and Agencies of the Department of Defense.

PAGE 2

* Leads: Delete "Type N-4, N-5, W-4 or W-5 of MIL-STD-1276." and substitute "Type N-32, N-52, W-32, or W-52 of MIL-STD-1276."

PAGE 3

* Life, At 25°C (As applicable), ΔCap: Delete "±2 percent" and substitute "±5 percent".

* Life, following "4,000, 6,000, 8,000, and 10,000 hours": Add "(exponential only)".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - AS, MC, OS, SH
Air Force - 17, 19, 99

Preparing activity:
DLA - ES

(Project 5910-1911)

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.