INCH-POUND
MIL-PRF-39003/2K
16 May 2022
SUPERSEDING
MIL-PRF-39003/2J
23 August 2012

PERFORMANCE SPECIFICATION SHEET

CAPACITOR, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM (POLARIZED, SINTERED SLUG), ESTABLISHED RELIABILITY, STYLE CSR09

FAILURE RATE LEVELS “M”, “P”, AND “R” ARE INACTIVE FOR NEW DESIGN AFTER 2 FEBRUARY 1984.

FAILURE RATE LEVEL “S” IS INACTIVE FOR NEW DESIGN AFTER 15 AUGUST 1984.

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-39003.




FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.

Case size	Dimensions					
	L			D		
	Min	Nom	Max	Min	Nom	Max
A1	.235 (5.97)	.250 (6.35)	.281 (7.14)	.081 (2.06)	.090 (2.29)	.099 (2.51)
B1	.375 (9.52)	.390 (9.91)	.405 (10.29)	.128 (3.25)	.138 (3.51)	.148 (3.76)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (in parentheses) are in millimeters and are given for general information only.
3. These capacitors are not intended to be mounted by their leads.
4. The case insulation shall extend .015 inch (0.38 mm) minimum beyond each end. However, when a shrink-fitted insulation is used, it shall lap over the ends of the capacitor body.
5. Lead length may be a minimum of 1 inch long for use in tape and reel automatic insertion equipment, when specified.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS

Dimensions and configuration: See figure 1.

Case type: Tubular, insulated.

Material: Metal (alloy unspecified).

Type of seal: Hermetic.

Leads (gold-plated leads optional; see MIL-PRF-39003 acquisition requirements):

Anode lead: Nickel-iron-alloy.

Cathode lead: Nickel-iron-alloy or nickel.

DC rated voltage: See table I. Above +85°C voltage derating is required (see MIL-PRF-39003).

DC leakage (DCL): See table I.

Capacitance (Cap.) (nom): See table I.

Cap. tolerance: 5 or 10 percent, see table I.

Dissipation factor (DF): See table I.

Operating temperature: -55°C to +125°C.

Failure rate level: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.

TABLE I. Style CSR09 characteristics and dash numbers.

DC rated voltage	Capacitance (nom)	Capacitance tolerance	DC leakage at			Dissipation factor at			Case size	Dash number M39003/02- 1/ Failure rate level for percent per 1000 hours							
			+25°C	+85°C	+125°C	-55°C	+25°C	+85°C +125°C									
Volts	µF	%	µA	µA	µA	%	%	%		M (1.0)	P (0.1)	R (0.01)	S (0.001)	G (1.0)	B (0.1)	C (0.01)	D (0.001)
6	2.7	5	0.6	6	8	8	6	6	A1	1001-	1061-	1121-	1181-	5001-	2001-	3001-	4001-
6	2.7	10	0.6	6	8	8	6	6	A1	0001-	0061-	0121-	0181-	5002-	2002-	3002-	4002-
6	18	5	1.4	21.6	36.7	8	6	6	B1	1002-	1062-	1122-	1182-	5003-	2003-	3003-	4003-
6	18	10	1.4	21.6	36.7	8	6	6	B1	0002-	0062-	0122-	0182-	5004-	2004-	3004-	4004-
10	1.8	5	0.6	6	8	8	6	6	A1	1007-	1067-	1127-	1187-	5005-	2005-	3005-	4005-
10	1.8	10	0.6	6	8	8	6	6	A1	0007-	0067-	0127-	0187-	5006-	2006-	3006-	4006-
10	2.2	5	0.6	6	8	8	6	6	A1	1008-	1068-	1128-	1188-	5007-	2007-	3007-	4007-
10	2.2	10	0.6	6	8	8	6	6	A1	0008-	0068-	0128-	0188-	5008-	2008-	3008-	4008-
10	10	5	2.5	20	34	8	6	6	B1	1009-	1069-	1129-	1189-	5009-	2009-	3009-	4009-
10	10	10	2.5	20	34	8	6	6	B1	0009-	0069-	0129-	0189-	5010-	2010-	3010-	4010-
10	12	5	2.5	24	40.8	8	6	6	B1	1010-	1070-	1130-	1190-	5011-	2011-	3011-	4011-
10	12	10	2.5	24	40.8	8	6	6	B1	0010-	0070-	0130-	0190-	5012-	2012-	3012-	4012-
10	15	5	2.5	30	51	8	6	6	B1	1011-	1071-	1131-	1191-	5013-	2013-	3013-	4013-
10	15	10	2.5	30	51	8	6	6	B1	0011-	0071-	0131-	0191-	5014-	2014-	3014-	4014-
15	1	5	0.6	6	8	8	6	6	A1	1012-	1072-	1132-	1192-	5015-	2015-	3015-	4015-
15	1	10	0.6	6	8	8	6	6	A1	0012-	0072-	0132-	0192-	5016-	2016-	3016-	4016-
15	1.2	5	0.6	6	8	8	6	6	A1	1013-	1073-	1133-	1193-	5017-	2017-	3017-	4017-
15	1.2	10	0.6	6	8	8	6	6	A1	0013-	0073-	0133-	0193-	5018-	2018-	3018-	4018-
15	1.5	5	0.6	6	8	8	6	6	A1	1014-	1074-	1134-	1194-	5019-	2019-	3019-	4019-
15	1.5	10	0.6	6	8	8	6	6	A1	0014-	0074-	0134-	0194-	5020-	2020-	3020-	4020-
15	8.2	5	1.8	24.6	42	8	6	6	B1	1015-	1075-	1135-	1195-	5021-	2021-	3021-	4021-
15	8.2	10	1.8	24.6	42	8	6	6	B1	0015-	0075-	0135-	0195-	5022-	2022-	3022-	4022-
20	0.56	5	0.6	6	8	4	3	4	A1	1016-	1076-	1136-	1196-	5023-	2023-	3023-	4023-
20	0.56	10	0.6	6	8	4	3	4	A1	0016-	0076-	0136-	0196-	5024-	2024-	3024-	4024-
20	0.68	5	0.6	6	8	4	3	4	A1	1017-	1077-	1137-	1197-	5025-	2025-	3025-	4025-
20	0.68	10	0.6	6	8	4	3	4	A1	0017-	0077-	0137-	0197-	5026-	2026-	3026-	4026-
20	0.82	5	0.6	6	8	4	3	4	A1	1018-	1078-	1138-	1198-	5027-	2027-	3027-	4027-
20	0.82	10	0.6	6	8	4	3	4	A1	0018-	0078-	0138-	0198-	5028-	2028-	3028-	4028-
20	1	5	0.6	6	8	4	3	4	A1	1019-	1079-	1139-	1199-	5029-	2029-	3029-	4029-
20	1	10	0.6	6	8	4	3	4	A1	0019-	0079-	0139-	0199-	5030-	2030-	3030-	4030-
20	3.3	5	1	13.2	22.4	4	3	4	B1	1020-	1080-	1140-	1200-	5031-	2031-	3031-	4031-
20	3.3	10	1	13.2	22.4	4	3	4	B1	0020-	0080-	0140-	0200-	5032-	2032-	3032-	4032-
20	3.9	5	2	15.6	26.5	4	3	4	B1	1021-	1081-	1141-	1201-	5033-	2033-	3033-	4033-
20	3.9	10	2	15.6	26.5	4	3	4	B1	0021-	0081-	0141-	0201-	5034-	2034-	3034-	4034-
20	4.7	5	2	18.8	32	4	3	4	B1	1022-	1082-	1142-	1202-	5035-	2035-	3035-	4035-
20	4.7	10	2	18.8	32	4	3	4	B1	0022-	0082-	0142-	0202-	5036-	2036-	3036-	4036-
20	5.6	5	2	22.4	38.1	4	3	4	B1	1023-	1083-	1143-	1203-	5037-	2037-	3037-	4037-
20	5.6	10	2	22.4	38.1	4	3	4	B1	0023-	0083-	0143-	0203-	5038-	2038-	3038-	4038-
20	6.8	5	2	27.2	46.2	4	3	4	B1	1024-	1084-	1144-	1204-	5039-	2039-	3039-	4039-
20	6.8	10	2	27.2	46.2	4	3	4	B1	0024-	0084-	0144-	0204-	5040-	2040-	3040-	4040-
35	0.33	5	0.6	6	8	4	3	4	A1	1025-	1085-	1145-	1205-	5041-	2041-	3041-	4041-
35	0.33	10	0.6	6	8	4	3	4	A1	0025-	0085-	0145-	0205-	5042-	2042-	3042-	4042-
35	0.39	5	0.6	6	8	4	3	4	A1	1026-	1086-	1146-	1206-	5043-	2043-	3043-	4043-
35	0.39	10	0.6	6	8	4	3	4	A1	0026-	0086-	0146-	0206-	5044-	2044-	3044-	4044-
35	0.47	5	0.6	6	8	4	3	4	A1	1027-	1087-	1147-	1207-	5045-	2045-	3045-	4045-
35	0.47	10	0.6	6	8	4	3	4	A1	0027-	0087-	0147-	0207-	5046-	2046-	3046-	4046-
35	2.2	5	1.4	15.4	26.2	4	3	4	B1	1028-	1088-	1148-	1208-	5047-	2047-	3047-	4047-
35	2.2	10	1.4	15.4	26.2	4	3	4	B1	0028-	0088-	0148-	0208-	5048-	2048-	3048-	4048-
35	2.7	5	1.4	18.9	32.1	4	3	4	B1	1029-	1089-	1149-	1209-	5049-	2049-	3049-	4049-
35	2.7	10	1.4	18.9	32.1	4	3	4	B1	0029-	0089-	0149-	0209-	5050-	2050-	3050-	4050-
50	0.22	5	0.6	6	8	4	3	4	A1	1030-	1090-	1150-	1210-	5051-	2051-	3051-	4051-
50	0.22	10	0.6	6	8	4	3	4	A1	0030-	0090-	0150-	0210-	5052-	2052-	3052-	4052-
50	0.27	5	0.6	6	8	4	3	4	A1	1031-	1091-	1151-	1211-	5053-	2053-	3053-	4053-
50	0.27	10	0.6	6	8	4	3	4	A1	0031-	0091-	0151-	0211-	5054-	2054-	3054-	4054-

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.

TABLE I. Style CSR09 characteristics and dash numbers - Continued.

DC rated voltage	Capacitance (nom)	Capacitance tolerance	DC leakage at			Dissipation factor at			Case size	Dash number M39003/02- 1/ Failure rate level for percent per 1000 hours							
			+25°C	+85°C	+125°C	-55°C	+25°C	+85°C +125°C									
Volts	µF	%	µA	µA	µA	%	%	%		M (1.0)	P (0.1)	R (0.01)	S (0.001)	G (1.0)	B (0.1)	C (0.01)	D (0.001)
50	1.5	5	1.4	15	25.5	4	3	4	B1	1032-	1092-	1152-	1212-	5055-	2055-	3055-	4055-
50	1.5	10	1.4	15	25.5	4	3	4	B1	0032-	0092-	0152-	0212-	5056-	2056-	3056-	4056-
50	1.8	5	1.4	18	30.6	4	3	4	B1	1033-	1093-	1153-	1213-	5057-	2057-	3057-	4057-
50	1.8	10	1.4	18	30.6	4	3	4	B1	0033-	0093-	0153-	0213-	5058-	2058-	3058-	4058-
75	0.047	5	0.6	6	8	4	3	4	A1	1034-	1094-	1154-	1214-	5059-	2059-	3059-	4059-
75	0.047	10	0.6	6	8	4	3	4	A1	0034-	0094-	0154-	0214-	5060-	2060-	3060-	4060-
75	0.056	5	0.6	6	8	4	3	4	A1	1035-	1095-	1155-	1215-	5061-	2061-	3061-	4061-
75	0.056	10	0.6	6	8	4	3	4	A1	0035-	0095-	0155-	0215-	5062-	2062-	3062-	4062-
75	0.068	5	0.6	6	8	4	3	4	A1	1036-	1096-	1156-	1216-	5063-	2063-	3063-	4063-
75	0.068	10	0.6	6	8	4	3	4	A1	0036-	0096-	0156-	0216-	5064-	2064-	3064-	4064-
75	0.082	5	0.6	6	8	4	3	4	A1	1037-	1097-	1157-	1217-	5065-	2065-	3065-	4065-
75	0.082	10	0.6	6	8	4	3	4	A1	0037-	0097-	0157-	0217-	5066-	2066-	3066-	4066-
75	0.1	5	0.6	6	8	4	3	4	A1	1038-	1098-	1158-	1218-	5067-	2067-	3067-	4067-
75	0.1	10	0.6	6	8	4	3	4	A1	0038-	0098-	0158-	0218-	5068-	2068-	3068-	4068-
75	0.12	5	0.6	6	8	4	3	4	A1	1039-	1099-	1159-	1219-	5069-	2069-	3069-	4069-
75	0.12	10	0.6	6	8	4	3	4	A1	0039-	0099-	0159-	0219-	5070-	2070-	3070-	4070-
75	0.15	5	0.6	6	8	4	3	4	A1	1040-	1100-	1160-	1220-	5071-	2071-	3071-	4071-
75	0.15	10	0.6	6	8	4	3	4	A1	0040-	0100-	0160-	0220-	5072-	2072-	3072-	4072-
75	0.18	5	0.6	6	8	4	3	4	A1	1041-	1101-	1161-	1221-	5073-	2073-	3073-	4073-
75	0.18	10	0.6	6	8	4	3	4	A1	0041-	0101-	0161-	0221-	5074-	2074-	3074-	4074-
75	0.22	5	0.6	6	8	4	3	4	B1	1042-	1102-	1162-	1222-	5075-	2075-	3075-	4075-
75	0.22	10	0.6	6	8	4	3	4	B1	0042-	0102-	0162-	0222-	5076-	2076-	3076-	4076-
75	0.27	5	0.6	6	8	4	3	4	B1	1043-	1103-	1163-	1223-	5077-	2077-	3077-	4077-
75	0.27	10	0.6	6	8	4	3	4	B1	0043-	0103-	0163-	0223-	5078-	2078-	3078-	4078-
75	0.33	5	0.6	6	8.4	4	3	4	B1	1044-	1104-	1164-	1224-	5079-	2079-	3079-	4079-
75	0.33	10	0.6	6	8.4	4	3	4	B1	0044-	0104-	0164-	0224-	5080-	2080-	3080-	4080-
75	0.39	5	0.6	6	9.9	4	3	4	B1	1045-	1105-	1165-	1225-	5081-	2081-	3081-	4081-
75	0.39	10	0.6	6	9.9	4	3	4	B1	0045-	0105-	0165-	0225-	5082-	2082-	3082-	4082-
75	0.47	5	0.6	7	12	4	3	4	B1	1046-	1106-	1166-	1226-	5083-	2083-	3083-	4083-
75	0.47	10	0.6	7	12	4	3	4	B1	0046-	0106-	0166-	0226-	5084-	2084-	3084-	4084-
75	0.56	5	0.6	8.4	14.3	4	3	4	B1	1047-	1107-	1167-	1227-	5085-	2085-	3085-	4085-
75	0.56	10	0.6	8.4	14.3	4	3	4	B1	0047-	0107-	0167-	0227-	5086-	2086-	3086-	4086-
75	0.68	5	0.6	10.2	17.3	4	3	4	B1	1048-	1108-	1168-	1228-	5087-	2087-	3087-	4087-
75	0.68	10	0.6	10.2	17.3	4	3	4	B1	0048-	0108-	0168-	0228-	5088-	2088-	3088-	4088-
75	0.82	5	0.7	12.3	20.9	4	3	4	B1	1049-	1109-	1169-	1229-	5089-	2089-	3089-	4089-
75	0.82	10	0.7	12.3	20.9	4	3	4	B1	0049-	0109-	0169-	0229-	5090-	2090-	3090-	4090-
75	1	5	0.9	15	25.5	4	3	4	B1	1050-	1110-	1170-	1230-	5091-	2091-	3091-	4091-
75	1	10	0.9	15	25.5	4	3	4	B1	0050-	0110-	0170-	0230-	5092-	2092-	3092-	4092-
75	1.2	5	0.9	18	30.6	4	3	4	B1	1051-	1111-	1171-	1231-	5093-	2093-	3093-	4093-
75	1.2	10	0.9	18	30.6	4	3	4	B1	0051-	0111-	0171-	0231-	5094-	2094-	3094-	4094-

1/ Dash number shall include a letter that indicates user preference for surge current/high temperature solder or the dash will be deleted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.

Stability at low and high temperatures: In accordance with MIL-PRF-39003.

Step 1 (+25°C):

DCL: See table I.

Capacitance: Within tolerance of table I value.

DF: See table I.

Step 2 (-55°C):

Capacitance: Shall not change more than ± 8 percent of step 1 measured value.

DF: See table I.

Step 3 (+25°C):

DCL: See table I.

Capacitance: Shall not change more than ± 2 percent of step 1 measured value.

DF: See table I.

Step 4 (+85°C):

DCL: See table I.

Capacitance: Shall not change more than ± 8 percent of step 1 measured value (6, 10, and 15 volt units).

Capacitance: Shall not change more than ± 6 percent of step 1 measured value (20 volts and higher).

DF: See table I.

Step 5 (+125°C):

DCL: See table I.

Capacitance: Shall not change more than ±12 percent of step 1 measured value.

DF: See table I.

Step 6 (+25°C):

DCL: See table I.

Capacitance: Shall not change more than ± 2 percent of step 1 measured value.

DF: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.

Surge voltage: In accordance with MIL-PRF-39003.

DCL: See table I.

Capacitance: Shall not change more than ± 2 percent from initial measured value.

DF: See table I.

Life: MIL-STD-202-108.

240, 1,000, and 2,000 hours.

At +25°C (as applicable).

DCL: See table I.

Capacitance: Not greater than ± 5 percent of initial measured value.

DF: See table I.

At +85°C:

DCL: See table I.

At +125°C:

DCL: See table I.

4,000, 6,000, 8,000, and 10,000 hours (exponential only):

At +25°C (as applicable):

DCL: 200 percent of initial limit.

Capacitance: Not greater than ± 10 percent of initial measured value.

DF: See table I.

At +85°C:

DCL: 200 percent of initial limit.

At +125°C:

DCL: 200 percent of initial limit.

Marking: In accordance with MIL-PRF-39003.

Part or Identifying Number (PIN): M39003/02-(dash number from table I).

Substitutability data: Substitutability for failure rate levels and capacitance tolerances shall be in accordance with MIL-PRF-39003.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.

Reference documents. In addition to MIL-PRF-39003, this specification sheet references the following documents:

MIL-STD-202-108

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where modifications from this revision were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity
DLA - CC

(Project 5910-2022-015)

Review activities
Navy - AS, MC, OS, SH
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.