The documentation and process conversion measures necessary to comply with this revision shall be completed by 5 January 2023.

INCH-POUND

MIL-PRF-19500/572D
w/AMENDMENT 1
5 October 2022
SUPERSEDING
MIL-PRF-19500/572D
5 January 2017

PERFORMANCE SPECIFICATION SHEET

LIGHT EMITTING DIODE,
TYPES 1N6493, 1N6494, 1N6495, 1N6500, 1N6501, AND 1N6502,
QUALITY LEVELS JAN AND JANTX

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for red, yellow, and green light-emitting diodes (LED). Two levels of product assurance (JAN and JANTX) are provided for each device type as specified in MIL-PRF-19500.

1.2 Package outlines. The device packages for device types 1N6493 through 1N6495 are in accordance with figure 1 and for device types 1N6500 through 1N6502 are in accordance with figure 2.

1.3 Maximum ratings.

I_F	I_{FM} (1)	$V_{(BR)}$ (2)	P_{FM} (3)	T_{op} and T_{stg}
mA dc	mA (pk)	V dc	mW (pk)	°C
35	60	5	105	-65 to +100

(1) Pulse width ≤ 0.5 ms, $P_{FM(AV)} \leq P_F$.
(2) I_R = 10 µA dc.
(3) Derate linearly from +25°C at 1.4 mW/°C.

1.4 Characteristics, radiometric (physical), and photometric (visual).

Type	Color	I_F	I_V $\Theta = 0°$	V_F	λ_V	λ_V	I_R at V_R = 3 V	C at V_R = 0 V
		mA dc	mcd	V dc	nm	nm	µA dc	pF
					Min	Max		
1N6493, 1N6500	Red	20	1	3	595	695	1	100
1N6494, 1N6501	Yellow	20	1	3	570	595	1	100
1N6495, 1N6502	Green	25	0.8	3	525	580	1	100

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
FSC 5980

* DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level. The quality level designators for encapsulated devices that are applicable for this specification sheet are "JAN" and "JANTX".

1.5.2 Device type. The designation system for the device types of semiconductors covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The semiconductors of this specification sheet use the first number and letter symbols "1N".

1.5.2.2 Second number symbols. The second number symbols for the semiconductors covered by this specification sheet are "6493", "6494", "6495", "6500", "6501", and "6502".

1.5.3 Suffix symbols. Suffix symbols are not applicable to this specification sheet.

1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 – Semiconductor Devices, General Specification for.


DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 – Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at https://quicksearch.dla.mil.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.




Ltr	Inches	Inches	mm	mm	Notes
	Min	Max	Min	Max	
A_1	.003	.005	0.08	0.13	2
BD	.112	.128	2.84	3.25	
BL	.385	.445	9.78	11.30	
BL_1	.123	.127	3.12	3.23	
BW	.093	.099	2.36	2.51	
D	.045	Nominal	1.14	Nominal	
e	.100	BSC	2.54	BSC	3
K	.015	.045	0.38	1.14	
LD	.018	.022	0.46	0.56	
LL	.125	.145	3.17	3.68	
LW	.020	.022	0.51	0.56	
∅M	.075	.082	1.90	2.08	

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. The front and back pins are recessed on the two sides to prevent shorting of an adjacent device.
3. The basic pin spacing is between centerlines.

FIGURE 1. Physical dimensions for types 1N6493, 1N6494, and 1N6495.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.



Ltr	Inches	Inches	mm	mm	Notes
	Min	Max	Min	Max	
A_1	.003	.005	0.08	0.13	2
BD	.312	.328	7.92	8.33	
BL	.385	.445	9.78	11.30	
BL_1	.123	.127	3.12	3.23	
BW	.093	.099	2.36	2.51	
D	.045	Nominal	1.14	Nominal	
e	.300	BSC	7.62	BSC	3
K	.015	.045	0.38	1.14	
LD	.018	.022	0.46	0.56	
LL	.125	.145	3.17	3.68	
LW	.020	.022	0.51	0.56	
∅M	.075	.082	1.90	2.08	

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. The front and back pins are recessed on the two sides to prevent shorting of an adjacent device.
3. The basic pin spacing is between centerlines.

FIGURE 2. Physical dimensions for types 1N6500, 1N6501, and 1N6502.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows.

I_{FM}	Forward current (subscript M indicates maximum).
I_V	Luminous intensity (the subscript V is used to designate a photometric or visual quantity to differentiate from I used herein for current).
λ_V	Peak radiometric wavelength of diode light emission.
mcd	Milli-candela; the candela is a unit of luminous intensity defined such that the luminance of a blackbody radiator at the temperature of solidification of platinum is 60 candelas per square centimeter.
P_{FM}	Forward power dissipation (the subscript M indicates maximum).
Θ	The angle at or off the axis of symmetry of a light source at which luminous intensity is measured.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figures 1 and 2.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.3).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500. Manufacturer's identification and date code shall be marked on the devices. Initial container package marking shall be in accordance with MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be as specified in table I herein.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4, and tables I and II herein).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Group E qualification. The group E inspections of table II herein shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not require the performance of group E inspection, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

* 4.3 Screening (quality levels JANTX). Screening shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. Specified electrical measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for Quality level JANTX
7	Method 1071 of MIL-STD-750, fine leak, test condition G or H. For condition H, leak testing 30 minutes after pressurization shall be acceptable. Method 1071 of MIL-STD-750, gross leak, test condition A or E.
9 and 10	Not applicable.
11	Subgroup 2 of table I herein.
12	I_F = 35 mA dc; T_A = +25°C, t = 168 hours.
13	Subgroup 2 of table I herein; ΔI_{V1} = -20 percent of initial readings. ΔV_F = ±50 mV dc.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-V of MIL-PRF-19500, table I herein, and as specified herein. Electrical measurements (end-points) shall be in accordance with subgroup 2 of table I herein.

* 4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in E-VIB (JAN, and JANTX) of MIL-PRF-19500 and herein.

Subgroup	Method	Condition
B2	1051	Test condition A, except $T_{(high)}$ = +100°C (10 cycles); time at temperature extremes 15 minutes minimum.
B2	1071	Fine leak: Test condition G or H. For condition H, leak testing 30 minutes after pressurization shall be acceptable.
		Gross leak: Test condition A or E.
B3	1027	I_F = 25 mA dc; T_A = +25°C; t = 340 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table E-VII of MIL-PRF-19500 and as follows.

Subgroup	Method	Condition
C2	1056	Test condition A.
C2	2036	Test condition E.
C2	1071	Fine leak: Test condition G or H. For condition H, leak testing 30 minutes after pressurization shall be acceptable. Gross leak: Test condition A or E.
C3	2016	Non-operating; 1,500 G's; t = 0.5 ms; 5 blows in each orientation: X1, Y1, and Y2.
C3	2056	Non-operating.
C3	2006	Non-operating; 20,000 G's; X1, Y1, and Y2.
C6	1026	I_F = 35 mA dc; T_A = +25°C.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Luminous intensity. This measurement is made with a photometer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

	Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
		Method	Conditions		Min	Max	
	Subgroup 1						
	Visual and mechanical examination	2071					
	Subgroup 2						
	Luminous intensity		Θ = 0 degrees (see 4.5.1)	I_{V1}			
	1N6493, 1N6494 1N6500, 1N6501		I_F = 20 mA dc		1		mcd
	1N6495, 1N6502		I_F = 25 mA dc		0.8		mcd
	Luminous intensity		Θ = 15 degrees (see 4.5.1)	I_{V2}			
	1N6493, 1N6494 1N6500, 1N6501		I_F = 20 mA dc		0.5		mcd
	1N6495, 1N6502		I_F = 25 mA dc		0.4		mcd
*	Reverse current	4016	Condition A or B, DC method; V_R = 3 V dc	I_R		1.0	µA dc
*	Forward voltage	4011	Condition B, DC method	V_F			
	1N6493, 1N6494 1N6500, 1N6501		I_F = 20 mA dc			3	V dc
	1N6495, 1N6502		I_F = 25 mA dc			3	V dc
	Subgroup 3						
	High temperature:		T_A = +100°C				
*	Reverse current	4016	Condition A or B, DC method; V_R = 3 V dc	I_R		1.0	µA dc
*	Forward voltage	4011	Condition B, DC method	V_F			
	1N6493, 1N6494 1N6500, 1N6501		I_F = 20 mA dc		1.5		V dc
	1N6495, 1N6502		I_F = 25 mA dc		1.5		V dc

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection – Continued.

	Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
		Method	Conditions		Min	Max	
	Subgroup 3 – Continued						
	Low temperature:		T_A = -55°C				
*	Reverse current	4016	Condition A or B, DC method; V_R = 3 V dc	I_R		1.0	µA dc
*	Forward voltage	4011	Condition B, DC method	V_F			
	1N6493, 1N6494 1N6500, 1N6501		I_F = 20 mA dc			3.25	V dc
	1N6495, 1N6502		I_F = 25 mA dc			3.25	V dc
	Subgroup 4						
	Capacitance	4001	V_R = 0; f = 1 MHz	C		100	pF
	Subgroups 5, 6, and 7						
	Not applicable						

1/ For sampling plans, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) for qualification and requalification only.

Inspection	MIL-STD-750		Qualification inspection
	Method	Conditions	
Subgroup 1			n = 45, c = 0
Thermal shock (glass strain)	1056	100 cycles, 0°C to 100°C	
Temperature cycling	1051	500 cycles, -65°C to +100°C	
Hermetic seal	1071		
Electrical measurement		See subgroup 2 of table I herein.	
Subgroup 2			
Intermittent operating life	1037	10,000 cycles.	
Electrical measurements		See subgroup 2 of table I herein.	
Subgroups 4 and 5			
Not applicable			
Subgroup 6			n = 11, c = 0
ESD	1020		
Subgroups 7, 8, and 9			
Not applicable			

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).


c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

e. Destructive physical analysis when requested.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

6.4 PIN construction examples. The PINs for through-hole mount devices are in the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.

6.5 List of PINs. The following is a list of all possible PINs for the devices available on this specification sheet.

PIN	Description
JAN1N6493	LED, red, narrow body through-hole mount, quality level JAN.
JANTX1N6493	LED, red, narrow body through-hole mount, quality level JANTX.
JAN1N6494	LED, yellow, narrow body through-hole mount, quality level JAN.
JANTX1N6494	LED, yellow, narrow body through-hole mount, quality level JANTX.
JAN1N6495	LED, green, narrow body through-hole mount, quality level JAN.
JANTX1N6495	LED, green, narrow body through-hole mount, quality level JANTX.
JAN1N6500	LED, red, wide body through-hole mount, quality level JAN.
JANTX1N6500	LED, red, wide body through-hole mount, quality level JANTX.
JAN1N6501	LED, yellow, wide body through-hole mount, quality level JAN.
JANTX1N6501	LED, yellow, wide body through-hole mount, quality level JANTX.
JAN1N6502	LED, green, wide body through-hole mount, quality level JAN.
JANTX1N6502	LED, green, wide body through-hole mount, quality level JANTX.

6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at semiconductor@dla.mil or by facsimile (614) 693-1642 or DSN 850-6939.

* 6.7 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5980-2022-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:31Z
Check the source to verify that this is the current version before use.