A-A-1267A
December 7, 1987
SUPERSEDING
A-A-1267
February 29, 1980

COMMERCIAL ITEM DESCRIPTION

TAP, THREAD CUTTING (SPIRAL POINTED)

The General Services Administration has authorized the use of this commercial item description in preference to Type II of Federal Specification GGG-T-70.

This commercial item description covers ground thread, high-speed steel taps with spiral points and straight flutes for use in hand and machine tapping operations.

Salient characteristics:

Design. Taps shall be of the spiral point, full length flute type in accordance with the latest revision of American National Standard ANSI B94.9, except as otherwise indicated by an asterisk in the table below.

Material. Material shall be high-speed steel of the same grade used for taps supplied to the commercial market for general purpose applications.

Hardness. Taps shall be hardened and tempered so as to indicate a Rockwell C62-66 hardness in at least eighty percent of the threaded section from the threaded end. The shank and square drive end may have other suitable heat treatment characteristics to prevent twisting and breaking of the tap.

Finish. Threads shall have a ground finish. Other areas shall be finished in accordance with commercial practice. Coatings or surface treatments, if provided, shall be suitable for general purpose tapping applications.

Chamfer type. Taps shall be of the plug style with 3 to 5 threads chamfered.

Quantity of flutes. Taps through size 5/16 inch shall have two flutes. Larger sizes shall have three flutes.

Thread size and pitch diameter. Thread size and pitch diameter (in inches) shall be as shown in the following table for the National Stock Number (NSN) specified. Except as indicated, threads shall be right hand direction.

NATIONAL STOCK NUMBER	SIZE AND THREAD SERIES	PITCH DIAMETER SYMBOL	PITCH DIAMETER MINIMUM	PITCH DIAMETER MAXIMUM
5136-00-261-3200	NO. 2-56 UNC	L1*	0.0739	0.0744
5136-00-261-3208	NO. 1-64 UNC	H1	0.0629	0.0634
5136-00-261-3209	NO. 2-56 UNC	H1	0.0744	0.0749
5136-00-261-3210	NO. 3-48 UNC	H1*	0.0855	0.0860
5136-00-261-3211	NO. 4-40 UNC	H1	0.0958	0.0963
5136-00-261-3213	NO. 6-32 UNC	H1	0.1177	0.1182
5136-00-261-3214	NO. 8-32 UNC	H1	0.1437	0.1442
5136-00-261-3215	NO. 10-24 UNC	H1	0.1629	0.1634
5136-00-261-3220	NO. 4-40 UNC	H2	0.0963	0.0968
5136-00-261-3226	NO. 0-80 UNF	L1*	0.0514	0.0519
5136-00-261-3227	NO. 1-72 UNF	L1*	0.0635	0.0640
5136-00-261-3236	NO. 0-80 UNF	H1	0.0519	0.0524
5136-00-261-3237	NO. 1-72 UNF	H1	0.0640	0.0645
5136-00-261-3239	NO. 3-56 UNF	H1	0.0874	0.0879
5136-00-261-3240	NO. 4-48 UNF	H1	0.0985	0.0990
5136-00-261-3244	NO. 10-32 UNF	H1	0.1697	0.1702
5136-00-261-3246	NO. 0-80 UNF	H2	0.0524	0.0529
5136-00-261-3247	NO. 1-72 UNF	H2	0.0645	0.0650
5136-00-261-3248	NO. 2-64 UNF	H2	0.0764	0.0769

FSC 5136

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:12Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

NATIONAL STOCK NUMBER	SIZE AND THREAD SERIES	PITCH DIAMETER SYMBOL	MINIMUM	MAXIMUM
5136-00-261-3259	1/4-20 UNC	H1	0.2175	0.2180
5136-00-261-3260	5/16-18 UNC	H1	0.2764	0.2769
5136-00-261-3261	3/8-16 UNC	H1	0.3344	0.3349
5136-00-261-3262	1/4-20 UNC	H2	0.2180	0.2185
5136-00-261-3263	5/16-18 UNC	H2	0.2769	0.2774
5136-00-261-3264	3/8-16 UNC	H2	0.3349	0.3354
5136-00-261-3268	1/4-28 UNF	H1	0.2268	0.2273
5136-00-261-3270	3/8-24 UNF	H1	0.3479	0.3484
5136-00-261-3273	3/8-24 UNF	H2	0.3484	0.3489
5136-00-585-7880	1/4-20 UNC	H3	0.2185	0.2190
5136-00-585-7881	1/4-28 UNF	H3	0.2278	0.2283
5136-00-585-7882	5/16-18 UNC	H3	0.2774	0.2779
5136-00-585-7883	5/16-24 UNF	H3	0.2864	0.2869
5136-00-585-7884	3/8-16 UNC	H3	0.3354	0.3359
5136-00-585-7885	3/8-24 UNF	H3	0.3489	0.3494
5136-00-585-7886	7/16-14 UNC	H3	0.3921	0.3926
5136-00-585-7887	7/16-20 UNF	H3	0.4060	0.4065
5136-00-585-7888	1/2 13 UNC	H3	0.4510	0.4515
5136-00-585-7889	1/2-20 UNF	H3	0.4685	0.4690
5136-00-585-7890	NO. 3-48 UNC	H2	0.0860	0.0865
5136-00-585-7891	NO. 3-56 UNF	H2	0.0879	0.0884
5136-00-585-7892	NO. 4-48 UNF	H2	0.0990	0.0995
5136-00-585-7893	NO. 5-40 UNC	H2	0.1093	0.1098
5136-00-585-7894	NO. 5-44 UNF	H2	0.1107	0.1112
5136-00-585-7895	NO. 6-32 UNC	H2	0.1182	0.1187
5136-00-585-7896	NO. 6-40 UNF	H2	0.1223	0.1228
5136-00-585-7897	NO. 8-32 UNC	H2	0.1442	0.1447
5136-00-585-7898	NO. 8-36 UNF	H2	0.1465	0.1470
5136-00-585-7900	NO. 10-24 UNC	H2	0.1634	0.1639
5136-00-585-7901	NO. 10-32 UNF	H2	0.1702	0.1707
5136-01-060-1690	NO. 12-24 UNC	H3	0.1899	0.1904
5136-01-060-1691	NO. 12-28 UNF	H3	0.1938	0.1943

* Exception to ANSI B94.9

Workmanship. All taps shall be free from imperfections which may affect their appearance, serviceability or durability.

Quality assurance provisions. Sampling for inspection shall be in accordance with MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes, except where otherwise indicated herein. The lot size shall consist of all taps with the same NSN offered for acceptance at one time. A sample unit shall be one tap.

Visual and dimensional requirements. Each sample unit shall be examined and measured for compliance with applicable requirements of ANSI B94.9, and for workmanship as specified above. The inspection level shall be S-3 with an AQL of 1.5 percent defective.

Hardness test. Hardness testing shall be in accordance with ASTM E 18. The inspection level shall be S-2 with an AQL of 1.5 percent defective.

Performance test. When specified in the contract or purchase order, a sample consisting of three taps of the same manufacturing design shall be tested to demonstrate the ability of the tap to perform in various metals.

Each tap shall be tested by tapping ten through holes into one of three metal bars or plates, each composed of a different composition (one copper alloy, one carbon steel, and one corrosion resisting steel) of the suppliers option. The bars or plates shall have a minimum thickness equal to the major diameter of the tap, and the hole diameters shall be such as to produce a theoretical 75% thread height. Other test factors not specified shall be at the manufacturer's option. Failure of any of the three taps to produce smooth, well-defined Unified National Form threads of a size which is consistent from the first to the last tapped hole shall be considered cause for rejection of the entire preproduction sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:12Z
Check the source to verify that this is the current version before use.

Packaging inspection. An examination shall be made to determine compliance with all preservation, packaging, packing, labeling, and marking requirements as specified in the contract or purchase order. The inspection level shall be S-2 with an AQL of 2.5 defects per hundred units.

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Note: Copies of American National Standard ANSI B94.9, Taps, Cut and Ground Threads may be obtained from the American National Standards Institute, 1430 Broadway, New York, New York 10018.

Copies of ASTM Standard E 18, Tests for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Copies of Military Standards are available from the Naval Publication and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

MILITARY INTERESTS:

Military Coordinating Activity

Army - GL

Custodians

Army - GL
Air Force - 99

Review Activity

Air Force - 84

PREPARING ACTIVITY:

GSA-FSS

Project 5136-0042

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:12Z
Check the source to verify that this is the current version before use.