[INCH-POUND]
A-A-2999
July 12, 1996
SUPERCEDES
H-B-00600
January 6, 1969

COMMERCIAL ITEM DESCRIPTION

APPLICATOR, WAX

The General Services Administration has authorized the use of this commercial item description, for all Federal agencies.

1. SCOPE

1.1 Scope. This commercial item description covers a wax applicator with a handle, a pad holder, and a replaceable pad made of wool pile faced knitted fabric, for use in manual application of floor waxes.

2. SALIENT CHARACTERISTICS

2.1 Block. The wood block used to secure the handle and pad shall be of two piece construction. The two sections of the block shall be constructed from smoothly finished, clear, close-grained hardwood. The top section of the block shall be coated on all surfaces with transparent varnish, clear lacquer, or other suitable organic coating. The bottom section of the block may also be coated.

2.1.1 Top section of block. The top section of the block shall have either a flat or convex face and shall measure 12 ±1/8 inches (30.5 ±0.3 cm) long, 2-1/2 ±1/8 inches (6.4 ±0.3 cm) wide, and no less than 3/4 inch (1.9 cm) thick at the center. The top section of the block shall have a standard Acme threaded handle hole to accommodate the handle specified in paragraph 2.4. The center of the boring shall be 6 inches (15.3 cm) from the end of the block and bored through the block at an angle that will permit the entire face of the pad to touch the surface of the floor when in use. The perimeter of the handle hole shall extend to within 1/4 ±1/16 inch (0.6 ±0.2 cm) from the edge of the block. Two holes, each approximately 2 inches (5.1 cm) from the ends of the block, shall be drilled through the top section of the block to accommodate two bolts for attaching the bottom section of the block.

2.1.2 Bottom section of block. The bottom section of the block shall be flat, measuring 12 ±1/8 inches (30.5 ±0.3 cm) long, 2-1/2 -1/8 +1/2 inches (6.4 -0.3 +1.3 cm) wide, and not less than 3/8 inch (1.0 cm) thick. Two holes, each approximately 2 inches (5.1 cm) from the ends of the bottom section of block, and coinciding with the holes in the top section of the block, shall be drilled through the block to accommodate the bolts. The holes shall be of a diameter not to exceed the bolt used by more than 1/64 inch (0.04 cm). The holes on the bottom section shall be countersunk in such a manner that the supplied bolt head does not protrude from the bottom face of the block.

2.2 Bolts and wing-nuts. The bolts and wing-nuts shall be made from a good commercial quality metal having a tensile strength suitable for the intended purpose. The metal shall be either inherently corrosion resistant or steel which has been coated with zinc, cadmium, or other suitable permanent coating to prevent corrosion. The bolts used for joining the top and bottom sections of the block shall be, as a minimum, 1-1/2 inches (3.8 cm) long. There shall be two wing-nuts, threaded to match the bolts, for securing the wax applicator pad between the top and bottom sections of the block.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEB), 819 Taylor Street, Fort Worth, TX 76102

DISTRIBUTION STATEMENT A: Approved for public release, distribution is unlimited.

FSC 7920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

2.3. Wax applicator pad. The wax applicator pad shall be constructed from a wool pile fabric. The pile face of the pad fabric shall be 100 percent wool when tested in accordance with FED-STD-191, Test Method 1100. The finished pile height shall be 3/4 inch (1.9 cm) minimum. The knitted backing fabric shall have a minimum of 12 wales and 21 courses per inch when tested in accordance with FED-STD-191, Test Method 5070. The knitted backing of the pad fabric shall be cotton when tested in accordance with FED-STD-191, Test Method 1200; polyester when tested in accordance with FED-STD-191, Test Method 1600 or ASTM D 629; or a cotton/polyester blend when tested according to ASTM D 629. The finished wax applicator pad shall be rectangular and 12 ±1/4 inches by 6 ±1/4 inches (30.5 ±0.6 cm by 15.3 ±0.6 cm). The wax applicator pad shall be of one piece construction. The minimum finished weight of the pad shall be 1.5 ounces (42.5 g) when tested according to FED-STD-191 Test Method 5040.

2.4 Handle. The handle shall be of close-grained and straight-grained hardwood and shall have an Acme threaded end. The handle shall conform to type 1, size 1 or 2, length 4-1/2 feet (1.37 m) of NN-H-104 except that, if necessary, the thread length shall be modified so that after assembly in the block, the threaded end of the handle will not protrude beyond the under surface of the block.

2.5 Marking for identification. The supplier shall permanently and legibly mark on the block of each wax applicator its name or trademark so that the product is easily identifiable with the manufacturer.

2.6 Workmanship. The wax applicator shall function smoothly for manually spreading wax over floor surfaces and shall be free from defects that would affect the function, serviceability, component compatibility, or appearance of the product.

2.7 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met.

2.8 Commercial item. The use of the term "commercial item" in this document does not imply that any item or items offered are not required to conform with all requirements specified herein.

3. REGULATORY REQUIREMENTS.

3.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS

4.1 Product conformance. The products provided shall meet the salient characteristics of this CID, shall conform to the producer's own drawings, specifications, standards, and quality assurance practices, and shall be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PACKAGING, PACKING AND MARKING

5.1. Packaging, packing and marking. The packaging, packing and marking shall be as specified in the contract or order.


6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number and date of this CID.
b. Whether entire unit or just pad is being purchased.
b. The packaging, packing, and marking desired.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

6.2 Part Identification Number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.



6.3 National Stock Numbers (NSNs): The following is a list of the known NSNs which reference this CID:

NSN	Name	PN
7920-00-633-8774	Floor wax applicator (with pad)	AA2999-A
7920-00-633-9274	Floor wax applicator pad	AA2999-B

PREPARING ACTIVITY:
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.