[METRIC]

A-A-355B
March 16,1994
SUPERSEDING
A-A-355A
September 5,1986

COMMERCIAL ITEM DESCRIPTION

RULER, WOOD (DESK)

The General Services Administration has authorized the use of this Commercial Item Description, for all Federal agencies.

1. SCOPE:

A. This commercial item description covers wood desk rulers for general office use.

2. Salient characteristics:

A. The rulers shall be made of selected hard woods, that meet the characteristic requirements of a wooden desk ruler. Wood shall be kiln dried stock, free from imperfections such as chips, dents, flaws, and chipouts, which mar the appearance or which might impair t serviceability of the rulers. Characteristics common to wood such as mineral specks, burls, tight knots not exceeding 1/4 inch in diameter and birdseye will be permitted.

Beneficial comments, recommendations, additions, deletions, clarification, etc. and any data which may improve this document should be sent to:

General Services Administration
Engineering Branch (2FYEE), Rm. 20-130
26 Federal Plaza
New York, NY 10278
Attn: Specification Engineering

FSC 7510

DISTRIBUTION STATEMENT A: Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.

B. Dimensions and tolerances of the ruler shall be as shown below.

Size Length cm (Inches)	Width Min. cm (Inches)	Width Max. cm (Inches)	Thickness Minimum cm (Inches)
30.48 + 0.16 cm (12 + 1/16 IN.)	3.18 cm (1.25 IN.)	3.81 cm (1.50 IN.)	0.57 cm (0.225 IN.)
45.72 + 0.16 cm (18 + 1/16 IN.)	3.18 cm (1.25 IN.)	3.81 cm (1.50 IN.)	0.57 cm (0.225 IN.)
60.96 + 016 cm (24 + 1/16 IN.)	3.18 cm (1.25 IN.)	3.81 cm (1.50 IN.)	0.57 cm (0.225 IN.)

C. A tolerance of minus 0 cm (0 inch) plus 0.16 cm (1/16 inch) will be permitted in the overall length.

D. Permissible departure from a straight edge measured at point of maximum departure shall be plus or minus 0.08 cm (1/32 inch) for 30.48 cm (12 inch) ruler and plus or minus 0.16 cm (1/16 inch) for 45.72 and 60.96 cm (18 and 24 inch rulers) see note.

Note. Permissible departure from the straight edge refers to the distance between two lines parallel to the length of the ruler, one line touching points on the edge of the ruler of maximum bulge, the other line touching points on the edge where there is a maximum depression.

E. The rulers graduations shall be scaled in black in inches and sixteenths inch. A different length of scaling shall be used to indicate each individual fractions of an inch (i.e., 1/16, 1/8, 1/4, and 1/2).

F. The rulers shall have one beveled edge provided with a liquor finish steel edging at least 0.24 cm (3/32 inch) wide and not less than 0.03 cm (0.011 inch) thick securely inserted into the edge. The metal edging shall not project beyond the body of the ruler at either end. A minus tolerance of 0.16 cm (1/16 inch) in the length of the edging will be permitted.

G. The rulers shall have the manufacturer's standard commercial finish.

H. Unless otherwise specified, identification product marking shall be in accordance with standard commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.

I. Workmanship. The finished rulers shall exhibit no evidence of jagged or rough work. The ruler shall be free from any defects which may affect its durability, serviceability or appearance.

3. Quality Assurance

A. Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the government. The Government reserves the right to perform any of the inspections set forth in the Commercial Item Description, where such inspections are deemed necessary to assure that supplies and services conform to the prescribed requirements.

B. Each lot of scales shall be inspected for conformance to the requirements herein. Sampling for inspection shall be in accordance with MIL-STD-105 using the plans specified below.

C. Visual characteristics - Inspection Level S-2 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one scale.

D. Dimensional characteristics - Inspection Level S-2 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one scale.

E. Packaging, Packing, and Marking - Inspection Level S-2 with an AQL of 4.0 percent defective. The sample unit shall be one fully prepared shipping container.

4. Preparation for delivery

Packaging, packing and marking shall be as specified in the contract or purchase order.

5. Regulatory Requirements

The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.

6. Application for copies of technical documents referenced herein:

The issue date in effect on date of invitation for bids or request for proposal shall apply.

A. Military Specifications:

MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes.

Available from: Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094

B. Federal Acquisition Regulation:

Available from: Superintendent of Documents, Government Printing Office (GPO), Washington, DC 20402

7. Notes:
A. Ordering Data:

Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

1) Packaging, packing and marking.

No Official DOD Interest
Has Been Registered

Preparing Activity:
GSA/FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:07Z
Check the source to verify that this is the current version before use.