MIL-C-45003F(AL)
21 February 1986
SUPERSEDING
MIL-C-45003E
14 September 1983

MILITARY SPECIFICATION

CLEANER, STEAM, PRESSURE JET, DIESEL FUEL FIRED, SKID MOUNTED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a skid mounted, electric motor driven, diesel fuel fired, pressure jet steam cleaner and pressure washer. The cleaner is a continuous coil type, with no space for steam accumulation, in which water is heated to a temperature below the saturation temperature for the pressure in the coil and is discharged from the nozzle at high velocity. The cleaner discharges no less than 600 gallons per hour (gph) of saturated steam at a pressure of no less than 200 pounds per square inch gage (psig) and no less than 500 gph of hot and cold water at a pressure of no less than 400 psig.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS), and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

O-A-548	-	Antifreeze/Coolant, Engine: Ethylene Glycol, Inhibited, Concentrated.
P-S-120	-	Scale Removing Compound (Solid and Liquid Form).
CC-M-1807	-	Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, ATTN: SMCAR-EST-S (R), Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4940

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

TT-P-636 - Primer Coating, Alkyd, Wood and Ferrous Metal.
ZZ-H-561 - Hose, Rubber, and Hose Assemblies, Rubber, Smooth Bore, Water Suction and Discharge.
ZZ-H-601 - Hose and Hose Assemblies, Rubber (Yarn or Fabric Reinforced) Water Service.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-1055 - Barrier Material, Waterproof, Flexible.
PPP-C-843 - Cushioning Material, Cellulosic.
PPP-T-60 - Tape, Packaging, Waterproof.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-V-173 - Varnish, Moisture-and-Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment).
MIL-C-5501 - Caps and Plugs, Protective, Dust and Moisture Seal, General Specification for.
MIL-E-16298 - Electric Machines Having Rotating Parts and Associated Repair Parts: Packaging of.
MIL-B-22191 - Barrier Materials, Transparent, Flexible, Heat-Sealable.
MIL-C-22542 - Cleaning Compound, High Pressure Cleaner, Liquid.
MIL-C-52950 - Crates, Wood, Open and Covered.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-889 - Dissimilar Metals.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods.

2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

US DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and other documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI S1.4 - Sound Level Meters

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D2156-80 - Smoke Density in Flue Gases from Burning Distillate Fuels.
ASTM D3951-82 - Standard Practice for Commercial Packaging.
ASTM E380-84 - Standard for Metric Practice.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 70 - National Electrical Code.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE J356 - Welded Flash Controlled Low Carbon Steel Tubing Normalized for Bending, Double Flaring, and Beading.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096-0001.)

UNDERWRITERS LABORATORIES (UL)

UL 296 - Oil Burners.

(Application for copies should be addressed to the Underwriters Laboratories, 333 Pfingsten Road, North Brook, IL 60062.

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.2.1).

3.2 Design. The cleaner shall be designed for one gun and two gun operation and shall provide both steam and water (hot and cold) sprays to remove dirt, grease, and heavy oil deposits. The cleaner shall be designed for use with liquid self-emulsion cleaning compound conforming to MIL-C-22542 and for operation with fuels in the classification of diesel fuel grades No. 1 and No. 2. The unit shall have an output capacity of 600 (gph) in the steam vapor discharge mode and 500 gph in the hot and cold water discharge modes. Components shall be applied in accordance with standard commercial practice and shall function within rated design capacity. Components of the cleaners shall be designed, located, constructed, or protected so that exposure to the weather shall not interfere with any operation or function specified herein. Components shall be mounted on a common chassis of welded steel construction. The cleaner shall be designed to withstand multiple relocations without damage and without the need for any disassembly. Drive chains, variable pulleys, and plastic hose or tubing shall not be used. Mounted motors and pumps shall not be operated above the manufacturer's recommended rated revolutions per minute (rpm) for the purpose of meeting the performance requirements specified herein. The steam cleaners shall perform as specified when operating from a 208 volt ±10 percent, single phase, 50/60 hertz (Hz) power supply. The power supply may be transformed at the control panel to operate control circuits at lower voltages.

3.2.1 Transport. The design of the steam cleaner shall incorporate the capability to accommodate without degradation (i.e., cracked welds, permanent deformation, damaged equipment, etc) the following:

(a) Truck and trailer bed transport at speeds up to 50 miles per hour (mph) on primary roads, up to 35 mph on secondary roads, and up to 5 mph on rough terrain.
(b) Truck and trailer bed operation.
(c) Fork lift handling.
(d) Hoisting and lifting equipments (cranes, hoists, helicopters, etc).

3.2.2 Safety provisions. Protection against electrical, mechanical, and thermal hazards shall be incorporated in the cleaner. Steam and water outlet fittings and safety relief unloader valves shall be located away from electrical controls and the operator's control panel. The operator, during normal operation of the steam cleaner, shall be protected from contacting any component surfaces that exceed 130°F are the positioning relative to cooler components, by direct shielding, or by insulation. Typical components are: burner assembly, coil assembly, coil jacket, and vapor/hot water piping. Valves or controls that operate at temperatures greater than 130°F shall be insulated so that contact

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

surface temperatures do not exceed 130°F. There shall be no fuel leakage during any operational or idle phase. V-belt drives, if used, shall have protective safety shielding.

3.2.2.1 Power input. The steam cleaner shall have a manually actuated master switch that provides control for all electrical power to, and used by, the cleaner. The master switch shall not allow the cleaner to restart automatically after a power failure or interruption. A ground fault protection device shall be incorporated in the master control circuit. An external grounding terminal shall be provided for connection of a separate grounding lead to prevent electrical shock.

3.2.2.2 Burner operation safety controls and devices. The steam cleaner shall include the safety controls and devices specified in 3.2.2.2.1 through 3.2.2.2.5. These controls and devices shall be capable of terminating burner operation by shuting off at least the fuel flow to the burner, when the conditions enumerated in 3.2.2.2.1 through 3.2.2.2.5 are encountered. For conditions in 3.2.2.2.2 through 3.2.2.2.5 the burner shall automatically reignite when the stated condition is corrected. When changing from steam vapor mode to high pressure rinse mode, the high temperature and high pressure limiting devices shall be changed to the correct limiting value automatically. Because of the potential hazard to personnel if steam pressures exceed the steam hose rated working pressures, controls design shall prevent temperatures from exceeding 210 degrees F when the pressure by-pass system is in the high pressure rinse mode and if the temperature of mode selector is in the steam mode. When the cleaner is operating in the steam mode, the output pressure and temperature shall not exceed the rated working pressure and temperature of the steam hose.

3.2.2.2.1 Flame control sensing device. The flame control sensing device shall be either of a flame or heat sensing type but not aided by a reflective device. A spark sensing device shall not be permissible. The flame control sensing device shall:

(a) Sense the absense of a flame in the burner combustion chamber.
(b) Terminate steam cleaner operation when:

(1) A flame is not established within 15 seconds during starting.
(2) A flameout occurs.

Manual reset shall be required for reignition.

3.2.2.2.2 Inlet water flow control. The inlet water flow control shall be capable of terminating burner operation when the water flow to the pump is interrupted or the flow rate is reduced to less than 150 gph because of:

(a) Interruption of flow in the pressure water supply to supply tank.
(b) Blockage and/or collapse of the suction line.
(c) Restriction in the inlet strainer.

3.2.2.2.3 Outlet water flow control. The inlet water flow control shall be capable of terminating burner operation when the water flow from the pump is blocked or reduced to less than 150 gph due to any of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

(a) Coil inlet downstream of the pump is blocked.
(b) Increased resistance to water flow through the coil.
(c) Coil outlet is blocked.
(d) Delivery gun valve is closed.

3.2.2.2.4 High temperature limit device. The high temperature limit device shall be capable of terminating operation when the fluid temperature at the coil outlet approaches the greatest specified working temperature to +0, -10 degrees F in each mode of operation. Water shall continue to flow through the coil.

3.2.2.2.5 High pressure limit device. The high pressure limit device shall be capable of terminating burner operation when the fluid pressure at the coil outlet is 25, +0, -10, psig or greater than the specified working pressure in each mode of operation. Water shall continue to flow through the coil.

3.2.2.3 Bypass system. In addition to the above, each steam cleaner shall have a mechanical or hydraulic (non-electric) bypass system that shall bypass the entire pump output to the pump inlet when:

(a) The working pressure is exceeded for the mode of operation. Bypass must actuate within -0, +15 psig of the specified working pressure.
(b) The coil inlet/coil outlet is blocked.
(c) The delivery gun valve is closed.

During bypass, the pump motor shall keep running. The pressure regulator devices for each mode of operation shall be separate and shall be automatically engaged. Readjustment of a regulator shall not be required when changing from the low pressure vapor mode to the high pressure rinse mode.

3.2.2.4 Safety relief system. A self-resetting pressure relief valve shall be mounted at the coil outlet. The relief valve shall have the capacity to relieve the full pump output plus the heat absorbed by the water in the heating coil at the greatest heat input. The valve shall discharge to atmosphere toward the ground and away from the operator. The pressure relief valve shall discharge the fluid upon reaching 425, -0 +40, psig. In testing for the safety provisions of 3.2.2, the high temperature and high pressure limit devices, as well as the bypass and safety relief systems, shall be disconnected or defeated as necessary to complete the tests.

3.2.3 Lubrication. All bearings, except sealed-for-life type, and all other working parts shall be provided with standard means for lubrication. When shipped, all oil reservoirs, grease fittings, and those parts requiring lubrication shall be full of the manufacturer's recommended lubricant (see 6.5).

3.2.4 Interchangeability. All replaceable parts shall be manufactured to such standards as shall permit replacement without the need for modification. Threads shall comply with FED-STD-H28 and the applicable Detailed Standard section therein. No testing in FED-STD-H28 shall be required.

3.2.5 Dimensions and weight. The dimensions and weight of the cleaner shall not exceed the following:

Width	46 inches

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

Length	82 inches
Height	66 inches
Dry weight	3,000 pounds

3.2.6 Measurement system. The US Customary System of Units (US) or the International System of Units (SI) may be used in the design and construction of the cleaner. In this specification, all measurements, dimensions, sizes, and capacities are given in the US system. These measurements may be converted to the SI system by using the conversion factors and methods specified in ASTM E380-84.

3.2.6.1 Measuring and indicating devices. When specified (see 6.2.1), measuring and indicating devices shall be graduated in both the US and SI systems of measurement. When a dual US and SI system is furnished, dials shall have independent zero adjustments and shall be calibrated so that the last dial graduation progresses into, and is continuous with, the first dial graduation as the dial is rotated through the zero position. When only one system of graduation is acceptable, the particular graduation required shall be as specified (see 6.2.1). Regardless of the measurement system used, all measuring and indicating devices on the cleaner shall be graduated in the same system.

3.3 Materials. Materials not specifically designated herein shall be at least equal to those being supplied in the manufacturer's commercial steam cleaners for which a proven service record exists and which have been accepted by industry for the use intended. Where dissimilar metals are in contact, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.4 General construction. All parts and materials used in fabrication of the cleaner shall be new and free of defects. In no event shall patching processes be used for reclaimingf defective parts. All surfaces of all parts shall be clean and free of extraneous materials. external surfaces shall be free of sharp edges and burrs. All screws, pins, and similar parts shall be installed to prevent loss of tightness. However, such parts subject to adjustment or removal shall not be permanently deformed.

3.4.1 Electrical construction. All controls and wiring shall conform to NFPA 70 and shall be designed, located, constructed, or protected so that exposure to the weather shall not interfere with any operation specified herein. Exposed non-current carrying conductive parts which could become energized shall be grounded. Connections of conductors and terminal parts shall be of the screw, pressure, or solder type. When soldered connections are used, the conductors and terminal parts shall be mechanically secured before soldering. Only rosin base fluxes shall be used in soldering operations. Connections to screw type terminals shall be mechanically secured to prevent loss of tightness. All wiring shall be secured and protected to prevent contact with hot surfaces, vibration, and chafing. There shall be no exposed electrical connections.

3.4.2 Service accessibility. The cleaner shall be constructed to provide ready access to components in order that maintenance may be performed using standard tools and maintenance equipment. The cleaner shall be designed and constructed to allow any repair (including coil replacement) to be accomplished in no more than four hours by one person.

3.5 Performance and product characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

3.5.1 Starting sequence. Water flow and combustion air flow shall be established and maintained before fuel is supplied to the burner nozzle.

3.5.2 Thermal efficiency. In both the hot water and steam modes, the cleaner shall have a thermal efficiency not less than 80 percent while operating at full capacity. The efficiency shall be met using No. 1 and No. 2 diesel fuel and using 50 and 60 Hz power sources. Tests may be conducted with No. 2 diesel fuel only. The thermal efficiency after 200 hours of operation shall be no less than 80 percent. Thermal efficiency shall be the ratio of the heat energy units added to the discharged water divided by the heat energy units released by the oxidation of the fuel. Stack temperatures measured no more than six inches from the exhaust opening shall not exceed 450°F above ambient temperature. Smoke density measured in accordance with ASTM D2156-80 shall be no greater than No. 2 during the first 400 hours of operation. In order to achieve the efficiencies required, a heat reflector shield shall be installed between the outside of the coil and any insulation to allow hat flow around the coil periphery. A cold water coil may also be used outside the hot water coil to achieve the required thermal efficiency. Readjustment of fuel delivery rate shall not be permitted to satisfy other performance requirements.

3.5.3 Discharge requirements. The cleaner shall be provided with stop and start controls as well as regulating controls to achieve and automatically maintain a burner capacity commensurate with any desired vapor or pressure rinse output. The steam cleaner shall meet the pressure and discharge requirements of this specification when operating with either one or both guns. The two-gun discharge pressure shall be within 25 psig of the one-gun discharge pressure, but still no less than that required in 3.5.3.1.

3.5.3.1 Vapor discharge. The cleaner, with or without cleaning compound, shall have the ability to raise and maintain the temperature of no less than 600 gph, of no greater than 35°F inlet water, to no less than 350° ±10°F within five minutes of initial combustion from a cold start, and discharge it from a spray gun at a pressure of no less than 200 psig. The cleaner shall be suited for one and two gun operation as follows:

(a) No less than 600 gph at no less than 200 psig through one gun.
(b) No less than 300 gph at no less than 200 psig through one gun with the appropriate smaller nozzle.
(c) No less than 300 gph at no less than 200 psig through each of two guns.

3.5.3.1.1 Vapor discharge continuity. The cleaner shall allow switching from two gun operation at 300 gph per gun to one gun operation at 300 gph without stopping the cleaner.

3.5.3.1.2 Vapor discharge impact force. The cleaner shall meet the following impact requirements while shooting a vapor spray at a circular target two square inches in size (equal to 1.6 inches in diameter) when using the 600 gph straight, round, high-pressure nozzle specified in 3.6.8.3:

Distance	Impact
One foot	Eight pounds

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

Two feet	Five pounds
Three feet	Three pounds

3.5.3.2 Hot water discharge. The cleaner shall have the ability to raise and maintain the temperature of no less than 500 gph of inlet water (at no greater than 40°F) to an outlet temperature of 185° to 210°F, and discharge it through the rinse gun at no less than 400 psig as measured at the discharge manifold.

3.5.3.3 Cold water discharge. The cleaner shall have the ability to discharge no less than 500 gph of inlet water (at no greater than 50°F) through the rinse gun at a pressure of no less than 400 psig as measured at the discharge manifold.

3.5.4 Continuous operation. The cleaner shall withstand without damage, and shall perform within the requirements of 3.5.3, while being subjected to continuous operation as follows:

(a) As a vapor cleaner, for a period of 400 hours.
(b) As a hot rinse unit, for a period of 48 hours.

The steam cleaner shall be capable of operating for no less than the periods stated above without requiring desooting. Smoke density, measured as specified in ASTM D2156-80, shall be no greater than number 2 at the beginning and throughout the above specified periods. The steam cleaner shall also be capable of operating no less than the periods specified above with no breakdown or replacement of major components such as pumps, motors, burners, safety controls and devices, heating coils, and transformers. Compliance with this continuous 400 hour steam mode/vapor discharge and the 48 hour hot water rinse test shall be performed for no less than eight hours per calendar day and shall be completed within 56 consecutive calendar days.

3.5.5 Tilted position operation. The cleaner shall not leak fuel and shall perform within the requirements of 3.5.3 when all the tanks are filled to their full mark and the cleaner is tilted to any and all angles from a horizontal plane to 15 degrees in any and all directions from the horizontal plane.

3.5.6 Altitude. The cleaner shall perform within the requirements of 3.5.3 at altitudes up to 6,000 feet in ambient air temperatures up to +107°F. Stoichiometric calculations based on fuel analysis and velocity pressure in the combustion chamber may be used in lieu of high altitude tests.

3.5.7 Noise level. The sound level of the cleaner under all operating modes, excluding the discharge gun(s) sound, shall not exceed 85 decibels. Measurements are to be made on the A scale at slow response on a sound level meter meeting the Type I requirements of ANSI S1.4. Readings shall be taken at a height of five feet above the ground plane and at ten feet from the perimeter of the cleaner. A warning instruction plate shall be attached to the cleaner at the control panel stating "OPERATING HEARING PROTECTION IS REQUIRED WHEN OPERATING THE CLEANER." (Reference: The eight hour exposure limit of Title 29, CFR, Section 19 (OSHA 2206).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

3.5.8 Dielectric strength. The conductors and all electrical components shall withstand, without damage, twice the rated voltage plus 1000 volts root mean square (rms) at 60 Hz for a period of one minute between mutually insulated circuits, and between ground and insulated circuits.

3.5.9 Operating temperatures. The cleaner shall meet the requirements of 3.5.3 while being operated in air temperatures from +35°, -0° +5°F to +115°, -5, +0°F.

3.5.10 Storage temperatures. The steam cleaner and all components shall withstand without damage, and shall meet the requirements of 3.5.3, when stabilized at a temperature of +70°F after having been subjected to:

(a) A temperature of -50°F for a period of 72 hours.
(b) A 24 hour cycle of temperatures, starting with ten hours at +90°F, followed by five hours of steady increase to +155°F, four hours at +155°F, and five hours of steady decrease to +90°F.

3.5.11 Humidity conditions. The cleaner shall not be damaged, and shall be capable of meeting the requirements of 3.5.3 through 3.5.3.3, after having been exposed for 24 hours to, and while still at, a relative humidity of 97 to 100 percent and an air temperature of +80° to +85°F, air movement and radiation negligible.

3.6 Component details. The cleaner shall include, but not be limited to, the components covered in 3.6.1 through 3.6.13.

3.6.1 Heating coil. The heating coil shall be one continuous length of normalized, electric resistance welded, flash controlled, single wall, low carbon steel pressure tubing conforming to SAE J356. The entire tube shall be normalized, not just the weld joint area. The finished tubing hydrostatic proof test of SAE J356 shall be required. There shall be no circumferential welds or joints in the coil except those required to attach end fittings. The coil assembly shall be thermal stress relief treated and uniformly cooled at a controlled rate. Thermal stress relief shall be considered to be heating metal to a suitable temperature and holding that temperature long enough to reduce residual stresses in the metal, then cooling the metal slow enough to minimize the development of new residual stresses. The contractor shall submit a thermal stress relief treatment plan to the government prior to first article inspection. The completed coil assembly shall withstand a hydrostatic pressure test of 2000 psi for no less than ten minutes with a pressure drop not to exceed 10 psig. The entire assembled water piping system shall withstand a hydrostatic pressure of two times the minimum relief valve pressure (850 psig) for no less than ten minutes with a pressure drop not to exceed ten psig. The coil shall be designed for easy removal and replacement without damage to the coil, coil jacket, or supports using only common hand tools (pipe wrench, end wrench, etc). For delivery, the vapor and water system shall be protected against corrosion as specified in Section 5 herein or elsewhere in the contract.

3.6.1.1 Coil pressure gages. Dial type pressure gages, reading from 0 to 600 pound-force psig, shall be attached at the intake and outlet of the heating coil. The gages shall be damped to permit clear readings. In addition, each cleaner shall have a temperature gage to monitor the outlet temperature. All

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

gages shall be no less than three inches in diameter and shall be mounted on the control panel. All gages shall withstand the temperatures and pressures of blowdown without damage, or the pressure gages shall be equipped with shut-off valves, accessible from the control panel, to isolate them during blowdown. Gages shall be accurate within five percent of full scale value.

3.6.1.2 Coil valves and fittings. Suitable valves and fittings shall be provided on both the intake and outlet of the heating coil to permit complete drainage and blowdown, and to permit the introduction and circulation of scale removing compound conforming to P-S-120. The solution acts as a scale remover without the need for an auxiliary pumping medium. All necessary hoses, screening, and filtering required to perform scale removing, as recommended by the manufacturer, shall be provided with each cleaner.

3.6.1.3 Blowdown provisions. The steam cleaner shall have provision for periodic blowdown for removing scale and other deposits from the inside of the coil to minimize the necessity for frequent descaling. The blowdown procedure shall consist of allowing the fire to remain on, with no water supply to the coils, for the length of time specified by the manufacturer so that the heat dries and cracks the deposits. The pump shall continue running with pump output bypassed or, if an electromagnetic clutch is used, the drive motor shall continue to operate. Then allow a full volume of water to enter the hot coil where it flashes into steam and creates sufficient pressure to loosen scale and sludge and blow it out of the coil. Blowdown controls and steam outlets shall be designed to preclude injury to the operator and damage to the steam cleaner. Blowdown instructions and safety caution notes shall be illustrated and permanently attached to the steam cleaner near the controls. The steam cleaner shall be capable of operating in the steam mode no less than eight consecutive hours without requiring blowdown and no less than 80 consecutive hours without chemical descaling.

3.6.2 Burner. The burner shall be of the fuel pressure atomizing or air atomizing type equipped with an ignition system using a continuous electric spark. The fuel line to the nozzle shall be equipped with a dirt and water separator, with a removable fuel strainer, enclosed in a metallic housing to prevent passage of any foreign material to the nozzle. Provision shall be incorporated to prevent any fuel leakage into the combustion chamber until proper fuel pressure is obtained. All wiring and controls for the ignition system shall be designed, located, constructed, or protected so that exposure to the weather shall not interfere with any operation specified herein. The wiring shall conform to NFPA 70. The burner shall conform to UL 296 and shall be Underwriters Laboratory listed.

3.6.2.1 Burner position. The burner shall be positioned to facilitate cleaning and replacement and shall be designed or located to prevent condensation from damaging the burner components. The burner shall be so designed that removal and replacement can be accomplished without lifting any portion of the cleaner from the ground or removing the cleaner from the bed of the trailer, if so mounted. Operation of the burner shall not be affected by vibration or sudden shock.

3.6.3 Combustion chamber. Deflectors and the top of the combustion chamber shall be corrosion resistant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

3.6.4 Fuel tank. The fuel tank shall be fabricated of standard commercial mild steel. For delivery, the tank shall be protected against corrosion as specified in Section 5 herein, or elsewhere in the contract. The fuel tank capacity shall permit no less than four hours of continuous operation under maximum heat load. The tank shall be subject to atmospheric pressure only and shall be protected to prevent possible seepage, splashing, or leakage of other liquids into the tank. The tank filler opening shall have a minimum internal diameter of two inches, a removable 20 mesh (.033 inch opening) strainer, and a chain-secured, vented, filler cap. The fuel tank shall be located to prevent fuel from dripping onto any component of the electrical system. A shutoff valve and a dirt and water separator with a removable 100 mesh (.005 inch opening) fuel strainer or a fuel filter shall be installed at the fuel tank outlet. In addition, a drain valve shall be incorporated with such standard pipe and fittings as are required to provide accessibility for manual control of discharge flow. The drain outlet shall be located so that the fuel cannot drain onto other components or structural members of the cleaner. The fuel tank shall incorporate a break resistant visual gage that allows the fuel level to be observed while filling the tank. A dip stick shall not be acceptable. The visual gage shall be provided with protective guard(s) to prevent breakage. The fuel lines shall be copper, brass, or steel tubing or pipe. Fittings, other than steel pipe fittings, shall be the flare type. All fuel lines shall be anchored to prevent movement, vibration and chafing.

3.6.5 Cleaning compound system. The cleaner shall be provided with at least one cleaning compound tank, of no less than ten gallon capacity, fabricated of either stainless steel of the same material specified in 3.6.7.1, or high density polyethylene no less than 0.100 inches thick. The cleaning compound tank shall be equipped with means for metering and introducing the liquid compound into the water flow at various rates. Provision shall be made to prevent back siphonage of the cleaning compound into the water supply. The tank shall be equipped with a compound level indicator marked in intervals no greater than one gallon. The level indicator shall indicate the level in the tank while the tank is being filled. If the tank is transparent or translucent, no level indicator is needed. The level indicator shall be protected against breakage and shall not be made of glass. The cleaning compound tank shall be vented and shall have a filler opening of no less than two inches inside diameter. The filler cap shall be chained or cabled to the tank or cleaner frame. The cleaning compound tank shall be equipped with a drain.

3.6.5.1 Compound metering device. The metering device shall inject liquid cleaning compound into a chosen volume of clear water. The metering device shall adjustable for rates of from 0 to no less than ten percent, cleaning compound-to-water, by volume. The metering device shall have an indicator showing the mix ratio in one-half percent increments and marked at one percent intervals. When adjusted to the desired rate, the device shall maintain a constant delivery to within $\pm$10 percent of the setting.

3.6.6 Pump. The pump shall be self-priming (a quick air release may be incorporated to comply with the self-priming criteria if necessary), shall be corrosion resistant to water, cleaning solutions, and acid deliming solutions, and shall be of sufficient capacity to lift and deliver water to meet the requirements of 3.5.3 through 3.5.4. The pump shall not be damaged during the deliming process. A Y-pattern sediment strainer, with a full flow blow-off valve

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

on the branch, shall be provided on the inlet side of the pump. The pump output shall be by-passed any time there is a flow restriction that could damage the pump. Reciprocating or impulse-type pumps shall be equipped with a shock absorbing device e.g., pulsation dampener in the discharge line. The pump shall be equipped with connections to allow pumping water from a tank, stream, or outside source directly through the coil and dispensing system. The pump shall be capable of lifting water to meet the requirements of 3.5.3 through 3.5.3.3 no less than 20 feet at sea level. The pump shall evidence no wear or damage from repeated starts and stops when obtaining water from a tank or well. Provision for draining the pump shall be incorporated.

3.6.7 Water supply system. The cleaner shall be equipped to secure water from the following sources:

(a) Tap pressure system from a minimum pressure range of 25 to 125 psig.
(b) Suction line or vacuum pickup from well, stream, or other outside source of water.

3.6.7.1 Water supply tank. A water supply tank shall be furnished to provide a constant supply of water to the cleaner from the sources specified in 3.6.7 (a) to meet all performance requirements specified herein. The water tank shall be stainless steel conforming to one of the following AISI designations: 302, 304, 316, 317, 318, 319, 347, or 348. Surface finish is optional. The tank shall be located for accessibility and shall be such that leakage, spillage, or overflow of water shall not come in direct contact with electrical components. The tank shall be provided with a drain valve piped to the cleaner exterior which shall permit complete draining of the tank. The tank outlet to the pump shall have a fine mesh stainless steel screen. No plastic parts shall be used. The tank shall be designed and manufactured to prevent back siphonage into the water supply in the event of reduced pressure or failure of the water supply.

3.6.7.2 Water supply hose and connections. The water hose shall conform to grade 1 of ZZ-H-601. It shall be a minimum of one inch inside diameter and fitted with standard male and female hose couplings with 0.75-11.5 National Hose coupling threads. One water supply hose having a minimum length of 50 feet shall be supplied with each cleaner.

3.6.7.3 Water supply suction hose. The cleaner shall be supplied with a suction hose (in addition to the hose in 3.6.7.2) to permit the cleaner to obtain water from a well, stream, or other outside source. The suction hose shall be a minimum of 25 feet in length. It shall have an inside diameter of 1.25 inches, shall conform to grade B, type I of ZZ-H-561, and shall be provided with all necessary standard couplings. A foot valve and strainer shall be provided for attachment to the suction hose. The strainer shall be designed to keep the foot valve suspended so that the valve does not become clogged or bury itself in the bottom of the tank or well.

3.6.8 Delivery equipment. Delivery equipment shall consist of a delivery hose, guns, nozzles, fittings, valves, and drain valves necessary for safe and efficient operation of the cleaner. An outlet manifold with shutoff valves shall be provided at the cleaner discharge for controlling the operation of each delivery gun. The cleaner shall have sufficient discharge outlets to permit

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

performance of the vapor spray and rinse operations specified in 3.5.3.1 through 3.5.3.3 without relocation of any hose. The manifold outlets shall be equipped with swivel couplings for the attachment of the hoses.

3.6.8.1 Delivery hose. The steam hoses shall be rated for a working steam pressure of no less than 250 psig and a temperature of no less than 450°F. The burst pressure shall be no less than 2500 psig. The hose shall have an inside diameter of no less than 3/4 inch. Standard, male pipe thread hose nipples shall be held in place with four bolt, interlocking type, clamps. The cleaner shall be supplied with a sufficient number of 50 foot hoses to perform the operations specified in 3.5.3.1 through 3.5.3.3 without relocation of any hose. Hose shall be braided steel, reinforced with a protective cover that is oil and abrasion resistant, with at least 50 effective pricked holes per foot.

3.6.8.2 Delivery guns. The cleaning gun assembly shall not be less than 4.5 feet in overall length, and shall be equipped with a self closing shut-off valve to control steam flow at the nozzle. The discharge end of the wand shall be straight and have a removable 45 degree fitting threaded such that the delivery nozzles can be mounted on either the straight wand or the 45 degree fitting. The cleaner shall permit remote control by the use of this valve. Discharge from the cleaner shall not occur until the valve is opened by the operator. The valve shall be located on or near the rear handle grip and its use shall be concurrent with the operator's secure hold on the assembly. The valve shall shut off when the operator removes his hand from the rear grip of the gun assembly. Disassembly of the valve for removal of scale particles in the water passages shall be possible using standard tools. The forward gun assembly shall include a cylindrically shaped front swivel handgrip, no less than 12 inches long, insulated and shielded to protect the operator from heat when handling without gloves. The swivel assembly shall rotate the entire portion of the cleaning gun forward, and inclusive of, the front handgrip 360 degrees. The cleaner shall be provided with a sufficient number of guns to perform the operations specified in 3.5.3.1 through 3.5.3.3.

3.6.8.3 Delivery nozzles. Nozzles shall be designed and fabricated for corrosion and wear resistance. The following nozzles shall be furnished to operate the cleaner at rated pressure (see 3.5.3.1 through 3.5.3.3):

(a) One straight, round, high-pressure vapor nozzle, 600 gph minimum.
(b) Two straight, round, high-pressure vapor nozzles, 300 gph minimum.
(c) Four 30 degree offset, high-pressure vapor nozzles, 300 gph minimum.
(d) Two 30 degree offset, high-pressure vapor nozzles, 600 gph minimum.
(e) Two high-pressure rinse nozzles, 500 gph minimum.

3.6.9 Hourmeter. The cleaner shall be provided with a 50/60 Hz, electrically driven hourmeter. The hourmeter shall be a digital counter type and shall record 9,999 operating hours in 1/10 hour increments. The hourmeter shall be mounted on the control panel of the cleaner and connected to the pump motor circuit.

3.6.10 Electric motors. The drive motor shall be an induction, squirrel cage type conforming to CC-M-1807. The motor shall operate on 208 volt ±10 percent, 50/60 Hz, single phase alternating current, shall have sealed ball or roller bearings, shall be drip proof, and shall be designed for continuous duty

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

operation. The motor shall have Class B insulation or better. The motor shall be provided with integral manual reset thermal overload protection. Auxiliary motors shall be standard commercial types, conforming to CC-M-1807 as applicable. All motors shall be provided with the motor manufacturer's standard commercial nonhygroscopic treatment compatible with steam service. As an alternate to the integral manual reset, a full voltage starter, with manual reset, for squirrel cage motors may be used to provide both running thermal overload and locked rotor thermal overload protection.

3.6.10.1 Power cable. The cleaner shall be supplied with not less than 75 usable (external to the cleaner housing) feet of AWG No. 14 (or larger, as required by current draw) conductor cable with two line conductors and one neutral conductor. The cable shall be Underwriters Laboratories Type SO or equal. A flexible strain relief connector shall be attached to the cleaner and the power cable in a manner to prevent tension or strain at the cable electrical connections. The cable conductors shall terminate in one inch of stripped, tinned wire.

3.6.11 Skid mount. The cleaner shall be equipped with a welded, heavy structural steel frame with two runners. All frame members shall be braced and gusseted to provide a rigid, sturdy base and to prevent sagging or distortion of the frame. The runners shall be curved upward at both ends to facilitate pulling the cleaner over rough or uneven ground. Both ends of each runner shall be equipped with eyes, not less than three inches inside diameter, to allow the cleaner to be lifted and towed. The skid shall allow for operation and maintenance of the cleaner without removal. Skid runners shall be designed so that water, fuel, or debris shall not collect and stand. Pipe or tube runners shall be capped on both ends to prevent water, fuel, and debris from entering. The cleaner frame and skids shall be designed so that the cleaner, with maximum load, can be lifted by a standard fork lift from each of the four sides without damage. The use of fork extensions shall not be permitted.

3.6.12 Lifting, pulling, and tie-down provisions. Each lifting, pulling, and tie-down device shall be identified and marked as specified in 3.9.2. Lifting and pulling rings or eyes shall be not less than three inches in inside diameter, shall be located at the ends of the skid, and shall maintain clearance between slings and exterior parts of the cleaner (spreader bars considered). The lifting rings or eyes shall support the cleaner and skid loaded to no less than 2 1/2 times the cleaner's wet weight (the weight with all tanks full and all hoses and guns stowed). The lifting, pulling, and tie-down devices shall withstand a horizontal longitudinal load four times the weight and a horizontal transverse load of no less than two times the wet weight. The loads shall be divided equally between the lifting, pulling, and tie-down devices.

3.6.13 Racks. Racks shall be attached to the cleaner for stowing the cleaning gun assemblies, nozzles, hoses, and the power cable when not in use. The racks shall be positioned so that stowed equipment is not exposed to heat from the burner.

3.7 Fungus treatment. The use of fungus supporting nutrient materials shall be avoided whenever possible. If any such materials are used in the cleaner, they shall be treated with varnish conforming to MIL-V-173, using one percent copper 8 - quinolinolate except as specified in (a) and (b) below:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

(a) Components of circuit elements that are inherently fungus and moisture resistant, or which are hermetically sealed, shall not be treated.
(b) Components of circuit elements whose functions shall be adversely affected by the varnish shall not be treated.

3.8 Painting. Painting and finishing shall be in accordance with the best practices of the steam cleaner industry. Immediately prior to painting, all surfaces shall be clean and dried and free of all foreign matter. The protecting paint coating shall be not less than two mil in thickness. The paint adhesion shall be such that no point shall be peeled by fiberglass tape when two intersecting cuts expose the base metal for a distance of not less than two inches. The surface hardness of the paint shall be between the industrial standards of H to Hb for pencil lead. The color shall be non-glossy forest green and the markings shall be glossy black.

3.9 Information marking.

3.9.1 Identification marking. The cleaner shall be marked for identification in accordance with MIL-STD-130 and shall include the National Stock Number. Identification markings shall also include the statement: "Cleaner wired for 208 volts, 50/60 Hz, single phase current."

3.9.2 Control marking. All controls shall be identified for the function performed and for direction of operation for the change desired. Control marking shall be on securely attached name plates, etched or embossed plastic or metal, or on adhesive backed metal (mylar) type plates. Decalcomania shall not be acceptable.

3.9.3 Instruction panel. An instruction panel, which shall be impervious to oil, grease, and weather, shall be mounted on the cleaner in an accessible and practical location. The instructions shall be on etched or embossed plastic or metal or on adhesive backed metal (mylar) type plates. Decalcomania shall not be acceptable. The panel shall include the following information:

(a) Detailed operating instructions.
(b) Lubricating instructions.
(c) Instructions for water supply connection.
(d) Instructions for blowdown.

3.9.4 Cleaning compound identification. The words "Use only steam cleaning compound conforming to Military Specification MIL-C-22542" shall be conspicuously marked on the exterior of the cleaner.

3.9.5 Fuel identification. A plate shall be securely attached near the fuel filler stating "Use Only Diesel Fuel Grade No. 1 and No. 2." The plate shall be impervious to oil, grease, and weather and shall conform to the requirements of 3.9.2.

3.9.6 Discharge information. The rated discharge pressures shall be permanently marked on the exterior of the cleaner.

3.9.7 Electrical ground identification. The electrical grounding terminal specified in 3.2.2.1 shall be conspicuously identified and marked.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

3.10 Operation diagrams. Instruction or operation manuals shall contain diagrams that illustrate all components and their interconnections for each operational system on the steam cleaner. Systems to be illustrated shall include, but not be limited to:

(a) Water flow.
(b) Electrical, both component diagram and ladder diagram.
(c) Fuel flow.
(d) Cleaning compound.
(e) Operational and safety controls.

3.11 Workmanship. The steam cleaner, including all parts and accessories, shall be free of corrosion, blemishes, and defects which would affect appearance, serviceability, and durability. Surfaces shall be clean and free of extraneous materials and sharp edges. Painted surfaces shall be free of flaking, spatters, and runs.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to a preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests under 4.7. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to production items offered for acceptance under the contract. Quality conformance inspection shall consist of (a) through (j) below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

(a) Product examination (4.5).
(b) Hydrostatic pressure tests (4.7.1).
(c) Dielectric strength test (4.7.2).
(d) Safety controls tests (4.7.3).
(e) Cold water discharge test (4.7.4.1).
(f) Hot water discharge test (4.7.4.2).
(g) Operational test (4.7.4.3.2).
(h) Continuous duty test (4.7.5).
(i) Noise level tests (4.7.6.2).
(j) Packaging inspection (4.8).

4.4.1 Sampling. Sampling for quality conformance inspection shall be in accordance with MIL-STD-105, using the following Inspection Levels and Acceptable Quality Levels (AQL) specified below, unless 100 percent inspection is specified. A sample lot shall consist of the quantity produced in one month or 80 cleaners, whichever is less.

Inspection Test	Inspection Level	AQL
Product Examination	100 percent	-
Hydrostatic pressure tests	100 percent	-
Dielectric strength test	S-4	2.5
Safety controls tests	100 percent	-
Cold water discharge test	100 percent	-
Hot water discharge test	100 percent	-
Operational test	100 percent	-
Continuous duty test	2/	-
Noise level test	1/	-
Packaging inspection	S-4	4.0

1/ The noise level test shall be conducted even if a first article test is not required by the contract. The test shall be performed on the first production cleaner only (see 3.5.7).

2/ The continuous duty test shall be conducted on the first three cleaners produced if a first article test is not required by the contract. If a first article test is required, the continuous duty test shall be performed as part of the first article test.

4.5 Product Examination. Visually and manually examine the steam cleaner to determine conformance with the requirements of 3.2 through 3.4.2 and 3.6 through 3.11. Visual examination shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from defects. Manual examination shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the cleaner has passed the examinations prescribed for it by the contractor's inspection system shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

4.6 Test conditions. The cleaner shall be tested and inspected under the conditions specified in 4.6.1 through 4.6.5.

4.6.1 Preparation for test. The cleaner shall be prepared for test by servicing, lubricating, adjusting, and running-in as specified by the operator's manual. All controls, valves, and pump(s) shall be checked to assure proper operation.

4.6.2 Measurements.

4.6.2.1 Pressure. Pressure shall be measured at the inlet and outlet sides of the heating coil. Pressure shall be measured using calibrated equipment capable of providing accuracy within one percent of the measured value, reading in psig.

4.6.2.2 Temperature. Temperature measurements shall be taken at the inlet and outlet sides of the heating coil. Temperature shall be measured using calibrated equipment capable of providing accuracy within one percent of the measured value, reading in degrees F.

4.6.2.3 Fuel consumption. Fuel usage shall be determined by the weight loss method. The period between weighing of the fuel shall represent at least five minutes of burner operation. Fuel weight shall be measured on a calibrated scale or balance having an accuracy within two percent of the measured value, reading in pounds.

4.6.2.4 Liquid flow. Liquid flow rates shall be determined by use of a flow meter which shall be of the totalizing and recording type and accurate within three percent of the measured value. Readings shall be in gallons per time period. Instantaneous flowmeter readings shall not be used.

4.6.3 Fuel. The cleaner shall be supplied with No. 2 Diesel fuel for all tests specified herein.

4.6.4 Water supply. The water supply for the tests shall be sufficient to supply the cleaner with a flow of at least 600 gph. Tap water under pressure of up to 125 psig may be used for all tests except the suction supply water source test (see 4.7.6.1). The temperature of the water supplied to the cleaner shall be as specified for the individual tests.

4.6.5 Chemical additives. Chemical additives such as cleaning solution or descaling solution shall be used in the cleaner only when specified for the individual tests.

4.7 Tests. Cleaners shall be tested and inspected under the test conditions specified in 4.6 through 4.6.5.

4.7.1 Hydrostatic pressure tests.

4.7.1.1 Heating coil. The fabricated heating coil assembly shall be pressure tested prior to assembly into the cleaner. Fill the coil with water and apply hydrostatic pressure of no less than 2000 psig. Block the inlet and observe for a period of ten minutes. Pressure drop in excess of ten psig resulting from leakage shall be cause for rejection (see 3.6.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

4.7.1.2 Water piping. Replace the 600 psig pressure gages at the heating coil inlet and outlet with an appropriate test gage at the pump outlet. Block the flow at the gun nozzle. Fill all water piping components between the pump and nozzle with water and apply hydrostatic pressure of no less than 850 psig. Block the inlet and observe for a period of ten minutes. Pressure drop in excess of ten psig resulting from leakage shall be cause for rejection (see 3.6.1.1).

4.7.2 Dielectric strength test. The cleaner shall be subjected to 1,420 volts rms at 60 Hz between mutually insulated circuits, and between insulated circuits and ground. Voltage shall be applied at the rate of approximately 500 volts per second until the specified voltage is reached. Voltage shall be maintained at 1,420 volts for a period of one minute. During the one minute period, the circuitry shall be observed for evidence of flashover (surface discharge), sparkover (air discharge) and breakdown (puncture discharge), or heating. The applied voltage shall then be gradually reduced to zero. Any evidence of flashover, sparkover, breakdown or damage to the unit due to heat or other effects of the applied voltage shall be cause for rejection (see 3.5.8).

4.7.3 Safety controls tests. The cleaner safety devices shall be tested as specified in 4.7.3.1 through 4.7.3.6 as listed. All safety controls tests shall be conducted with the cleaner operating under 60 Hz power.

4.7.3.1 Power loss test. With the cleaner operating in the cold water mode, the cleaner electrical power shall be momentarily interrupted by removing the power cord from its socket and then reconnecting it. The cleaner electrical power shall then be interrupted in the same manner while the cleaner is operating in the hot water mode and in the vapor discharge mode. Automatic restart of any function of the cleaner after a power interruption in any mode (without resetting the master switch) shall be cause for rejection (see 3.2.2.1). With the cleaner operating in the hot water mode, depress the test button on the ground fault protection device located in the master control panel. Failure of the cleaner to stop shall be cause for rejection (see 3.2.2.1).

4.7.3.2 Burner malfunction test. The cleaner shall be subjected to each of the following conditions while set up for operation in the hot water mode, and in the vapor discharge mode:

(a) The continuous spark ignition device shall be displaced from the fuel flow so that the device will continue to operate without causing ignition. An attempt shall then be made to start up and operate the cleaner in the normal manner. The ignition device shall then be returned to its normal position, and the cleaner started.
(b) With the cleaner operating with a normal flame, the air inlet for the burner shall be blocked so that a flameout occurs. An attempt shall be made to start and operate the cleaner in the normal manner. The blockage shall then be removed and the cleaner re-started.

Failure of the cleaner to automatically stop all flow of fuel to the burner within fifteen seconds of the occurance of either of the above conditions, or the ability to re-start the cleaner without activating a manual reset, shall be cause for rejection (see 3.2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

4.7.3.3 Inadequate water flow test. The cleaner over-temperature and over-pressure safety devices shall be disconnected or otherwise defeated, and the cleaner subjected to each of the following conditions while operating in the hot water mode and in the vapor mode:

(a) The ammount of water supplied to the cleaner shall gradually be reduced to zero, such that the cleaner is allowed to draw air and pump itself dry. The water supply to the cleaner shall then be restored. Failure of the cleaner to automatically stop all flow of fuel to the burner before the water flow rate falls below 150 gph or failure of the burner to automatically re-start when the water supply is restored shall be cause for rejection (see 3.2.2).
(b) The flow of water at the pump inlet shall be gradually restricted until the pump inlet is completely blocked. The blockage shall then be removed. Failure of the cleaner to automatically stop all flow of fuel to the burner before the water flow falls below 150 gph, or failure of the burner to automatically re-start when the blockage is removed, shall be cause for rejection (see 3.2.2).
(c) The flow of water at the coil inlet shall be gradually restricted until the coil inlet is completely blocked. The blockage shall then be removed. Failure of the pump bypass system to bypass the entire pump output before the water pressure exceeds 415 psig in the hot water mode of 215 psig in the steam mode, failure of the cleaner to automatically stop all flow of fuel to the burner before the water flow rate falls below 150 gph, or failure of the burner to automatically re-start when the blockage is removed shall be cause for rejection (see 3.2.2).

NOTE: Following this test, all cleaner safety devices shall be returned to their original state.

4.7.3.4 Temperature limit device malfunction test. With the cleaner operating in the hot water mode, the device(s) controlling the water temperature shall be defeated or adjusted so that, as the water temperature increases, fuel flow to the burner shall automatically stop between 200° and 210°F. If the fuel flow is automatically terminated, the cleaner shall be allowed to cool down until the burner automatically re-starts. The cleaner shall then be operated in the vapor mode, and the device(s) controlling the vapor temperature defeated or adjusted so that, as the vapor temperature increases, fuel flow to the burner shall automatically stop between 340° and 350°F. If the fuel flow is automatically terminated, the cleaner shall be allowed to cool down until the burner automatically re-starts. Failure of the cleaner to automatically stop all flow of fuel to the burner before the water temperature exceeds 210°F in the hot water mode, and before the vapor temperature exceeds 350°F in the vapor mode; failure of the cleaner to maintain the flow of water through the coil after fuel flow has been terminated; or failure of the burner to automatically re-start after the temperature falls back within acceptable limits shall be cause for rejection (see 3.2.2). NOTE: If necessary, the cleaner pressure regulating device(s) may be bypassed or taken out of the circuit for the duration of this test. At the conclusion of this test, all safety devices shall be returned to their original state.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

4.7.3.5 Pressure limit device malfunction test. With the cleaner operating in the hot water mode, and the valves on the discharge guns closed so that the pump is operating in full bypass, the pressure controlling device(s) for that mode shall be adjusted or defeated so that the pressure at the discharge manifold is raised until either the cleaner ceases operation or the pressure exceeds 425 psig. If the cleaner automatically ceases operation, it shall be allowed to cool down until the pressure drops to within the operating limits. The cleaner shall then be operated in the vapor mode with the valves on the discharge guns closed and the pressure regulating device(s) for that mode adjusted or defeated so that the pressure at the discharge manifold is raised until either the cleaner ceases operation or the pressure exceeds 225 psig. If the cleaner automatically ceases operation, it shall be allowed to cool until the pressure drops to within the operating limits. Failure of the cleaner to automatically and completely cease operating before the pressure exceeds 425 psig in the hot water mode and 225 psig in the vapor mode or failure of the cleaner to automatically re-start after the pressure falls back within the operating limits shall be cause for rejection (see 3.2.2). NOTE: If necessary, the cleaner temperature regulating and flow sensing devices may be defeated or removed from the circuit for the duration of this test. Following this test, all safety devices shall be returned to their original state.

4.7.3.6 Pressure relief valve test. With the cleaner safety devices other than the pressure relief valve defeated or removed from the circuit, the cleaner shall be operated in the hot water mode with the valves on the discharge guns closed. If necessary, the cleaner devices regulating temperature and pressure shall be adjusted or defeated so that the pressure in the coil gradually rises above 425 psig until either the pressure relief valve actuates or the pressure exceeds 465 psig. Failure of the pressure relief valve to actuate at a pressure greater than 425 psig but less than 465 psig, failure of the pressure relief valve to direct its discharge away from the operator(s) and all electrical components of the cleaner, or failure of the pressure relief valve to automatically reset before the pressure decreases to less than 425 psig shall be cause for rejection (see 3.2.2.4). Following this test, all cleaner safety and regulating devices shall be returned to their original state.

4.7.4 Performance tests.

4.7.4.1 Cold water discharge test. The cleaner shall be operated in the cold water mode for at least 15 minutes under 60 Hz power and for at least 15 minutes under 50 Hz power. For the first article test only, the temperature of the inlet water shall be less than 50°F for at least five minutes of both the 50 and 60 Hz portions of the test. Failure of the cleaner to continuously discharge at least 500 gph of water through the rinse gun at a pressure of at least 400 psig for the full period of operation under either source of power shall be cause for rejection (see 3.5.3.3).

4.7.4.2 Hot water discharge test. The cleaner shall be operated in the hot water mode under 60 Hz power for 15 minutes after the water temperature at the coil outlet has stabilized, and for the same period of time under 50 Hz power. During the first article test only, the temperature of the inlet water shall be 40°F or less for the duration of both 50 and 60 Hz portions of the test. Failure of the cleaner to continuously discharge at least 500 gph of water heated to a

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

temperature of at least 185°F at a pressure of at least 400 psig for 15 minutes, while operating under either source of power, shall be cause for rejection (see 3.5.3.2).

4.7.4.3 Vapor discharge tests.

4.7.4.3.1 Cold start test. The cleaner shall be configured for operation under 50 Hz power and operated in the cold water mode for five minutes to insure that the coil is cool. The cleaner shall then be set for operation in the vapor mode, supplied with water at a temperature of not more than 40°F, and operated for eight minutes. Failure of the cleaner to discharge vapor heated to a temperature of at least 325°F at a pressure of at least 200 psig, and a rate of at least 600 gph by the end of the eight minute period, shall be cause for rejection (see 3.5.3.1).

4.7.4.3.2 Operational test. The cleaner shall be operated in the vapor mode under 50 Hz power and under 60 Hz power. The cleaner shall be operated for 15 minutes under each source of power after the temperature at the coil outlet has stabilized. During each 15 minute operating period, the pressure at the pump outlet and at the gun nozzle shall be measured and recorded. Failure of the cleaner to continuously discharge water vapor heated to a temperature of at least 325°F at a pressure of at least 200 psig and at a rate of at least 600 gph for the full 15 minute period, while operating under each source of power, shall be cause for rejection (see 3.5.3 and 3.5.3.1). NOTE: When this test is done as a part of first article test, the cleaner shall also be tested for suitability of operation with an appropriate small nozzle in conformance with 3.5.3.1(b) and suitability of operation with two guns in conformance with 3.5.3 and 3.5.3.1(c). Vapor discharge continuity shall be verified by switching from two gun operation at 300 gph per gun to one gun operation at 300 gph in conformance with 3.5.3.1.1. Then, change from the vapor discharge mode to the hot water discharge mode and verify that the pressure change is accomplished without requiring a pressure regulator or similar device to be adjusted (see 3.2.2).

4.7.4.3.3 Vapor discharge impact test. The cleaner shall be operated in the vapor mode with the temperature at the coil outlet stabilized. Using the 600 gph straight round high-pressure vapor nozzle specified in 3.6.8.3, the vapor spray discharge shall be directed against a flat, solid, circular target 1.6 inches in diameter. The target device shall register the pounds of impact on a scale or gage having an accuracy of five percent of the measured value. The test shall be conducted at both 50 Hz and 60 Hz. Failure of the cleaner to equal or exceed the impact requirements specified in 3.5.3.1.2 shall be cause for rejection.

4.7.5 Continuous duty test. The cleaner shall be operated in the vapor mode for a period of 400 hours. The cleaner shall then be operated in the hot water mode for 48 hours. This 448 hour test shall be performed for no less than eight hours per calendar day and shall be completed within 56 consecutive calendar days. During these tests, data shall be recorded as specified in 4.7.5.1.

During the continuous duty test, testing shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

(a) During the vapor mode, the cleaner shall be operated in each of the five attitudes for a period of 80 consecutive hours. These attitudes are horizontal and tipped 15 degrees to the front, rear, and to each side. Verify cleaner operation and that there is no leakage from the tanks during the tilted tests (see 3.5.5).
(b) Verify that the cleaning solution tank has a capacity of at least 10 gallons and then operate the cleaner for at least four hours using the cleaning solution (see 3.6.5).
(c) Verify that the fuel tank has sufficient capacity to operate the cleaner for a minimum of four hours in the vapor mode (see 3.6.4).
(d) Conduct the thermal efficiency test during the first five hours, at 190 $\pm$8 hours, and within five hours of the end of the test. Verify that efficiency is no less than 80 percent at any time (see 3.5.2).
(e) Conduct a smoke density test at 190 $\pm$8 hours and at 390 $\pm$8 hours. Verify that the density is no greater than a number 2 smoke spot (see 3.5.2).
(f) Measure the temperature on all valve, control, and component surfaces contacted by the operator and verify that none exceed 130°F (see 3.2.2).
(g) After completion of the test, verify that the heating coil can be replaced without damage to the coil, coil jacket, or support, and that it can be removed by one person, using only common hand tools, in no more than four hours (see 3.4.2). (Replace with a new coil.)

During the continuous duty test, servicing shall be as follows:

(a) Blowdown frequency shall not exceed one per eight consecutive operating hours (see 3.6.1.3).
(b) Chemical descaling frequency shall not exceed one per 80 operating hours (see 3.6.1.3).
(c) Desooting shall not be required during the 448 hour test (see 3.5.4).

Any breakdown or replacement of major components such as pumps, motors, burners, safety controls and devices, heating coil, and transformers, or failure to meet requirements of 4.7.5 (a) through (c) and (a) through (g), shall be cause for rejection (see 3.5.4).

4.7.5.1 Data readings. During the continuous duty test specified in 4.7.5, the following performance data shall be recorded, as a minimum, at intervals of not more than one operating hour, except where shorter intervals are required to determine compliance with specified requirements. The maintenance information specified below shall be recorded each time the cleaner is maintained, serviced, or adjusted during the continuous duty test.

4.7.5.1.1 Performance data.

(a) Date.
(b) Time.
(c) Hour meter reading (cleaner).
(d) Inlet pressure at coil.
(e) Outlet pressure at coil.
(f) Liquid flow rate in gph (water or solution).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

(g) Feed water temperature entering cleaner.
(h) Liquid temperature leaving cleaner (water or solution at coil outlet).
(i) Ambient temperature.
(j) Voltage.
(k) Amperage.
(l) Fuel consumption in pounds per minute and BTU rating (only required when determining thermal efficiency).
(m) Motor and/or pump speeds (rpm).
(n) Cleaner serial number.

4.7.5.1.2 Maintenance information.

(a) Date, time, and cleaner hourmeter reading at which the action was initiated.
(b) Type of maintenance, servicing, or adjustments performed and manhours to accomplish.
(c) Date, time, and cleaner hourmeter reading when the action was completed.

4.7.5.1.3 Corrective action. Failure of a cleaner to meet the continuous duty test requirement shall be cause for deferring further submission of cleaners for Government acceptance until the contractor has completed the following actions:

(a) Conduct a failure analysis study, performing a dimensional, physical, and visual examination, as required, of the component(s) or condition(s) suspected to be the cause of failure.
(b) Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect in future production.
(c) Examine cleaners awaiting submittal for Government acceptance, partially assembled cleaners, and components (including components and subassemblies at in-process or final assembly) to insure that material containing the same defect(s) is purged from the inventory and not presented to the Government for acceptance.
(d) Provide objective evidence of the results of the failure analysis and corrective actions to the Government representative prior to submitting the reconditioned test sets for retest.

4.7.5.2 Thermal efficiency test. With the cleaner operating in the vapor mode and the coil outlet temperature stabilized, measurements of fuel consumption, water flow, and coil inlet and outlet temperatures during a period of at least 15 minutes of operation shall be recorded. The cleaner thermal efficiency calculated as:

Calculation - Thermal Efficiency:

$$E = \frac{Qw\ (T)\ (C)\ (D)}{Qf\ (H)} \times 100$$

Where:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

Qw = water flowing through the coil (gal).
C = specific heat of water (1.0 BTU/lbm F).
D = 8.33 lbm/gal.
Qf = fuel consumed (lbm).
H = energy content of fuel (BTU/lbm).
T = difference between coil inlet and outlet water temperatures (F).

Failure of the cleaner to demonstrate a thermal efficiency of at least 80 percent shall be cause for rejection (see 3.5.2). This test shall be performed as a part of the continuous duty test.

4.7.5.3 Blowdown test. After the cleaner has been in operation a sufficient amount of time to build up scale deposits, as demonstrated by a decrease in the coil outlet pressure, a blowdown operation shall be performed in accordance with the manufacturer's instructions. Failure of the blowdown operation to return the coil outlet pressure to normal, or evidence of damage to any component of the cleaner as a result of the blowdown operation, shall be cause for rejection (see 3.6.1.3). This test shall be performed as a part of the continuous duty test.

4.7.6 Environmental and function tests.

4.7.6.1 Suction supply water source. With the 25 foot suction hose, foot valve, and suction strainer attached, the cleaner shall be operated under 50 Hz power in the cold water mode to draw water against a resistance equivalent to a 20 foot vertical rise. This may be accomplished either by drawing from a standing body of water whose surface is at least 20 feet lower in altitude than the water pump inlet, or by drawing against an equivalent vacuum of 20 feet at standard atmospheric pressure at sea level. Failure of the cleaner to draw the water and discharge it at a rate of at least 500 gph and a pressure of at least 400 psig shall be cause for rejection (see 3.5.3.3).

4.7.6.2 Noise level tests. With the cleaner in operation in the vapor mode with the burner on, noise level readings shall be taken with a sound level meter meeting Type 1 requirements of ANSI S1.4, set on the slow response of the A scale. Cleaner noise level measurements shall be taken at a distance no greater than ten feet from the perimeter of the cleaner at a height of five feet, with no effect on the measurements from the cleaner gun and nozzle. Noise levels measured in excess of 85 dbA shall be cause for rejection. (See 3.5.7).

4.7.6.3 Cleaning solution metering test. The metering valve shall be set at 10. The cleaner shall then be operated in the hot water mode at a flow rate of approximately 500 gph. Record the time to use one gallon of cleaning solution and record the total gun output in gallons for the same period of time. The metering valve shall be set at 5 and the test repeated. Failure of the metering valve to provide cleaning solution to water ratio within ten percent of the value setting shall be cause for rejection (see 3.6.5.1).

4.7.6.4 Altitude test. The cleaner shall be placed in a test chamber, or tested under conditions to maintain a pressure equivalent to a 6,000 foot altitude and a maximum ambient temperature of +107°F. The cleaner shall then be subjected to the tests in 4.7.4.2 and 4.7.4.3.2. Scientific computation (stoichiometric calculations based on fuel analysis and velocity pressure in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

combustion chamber) may be submitted in lieu of conducting this test. Failure of the cleaner to pass the tests of 4.7.4.2 and 4.7.4.3.2 under the above conditions shall be cause for rejection (see 3.5.6).

4.7.6.5 High operating temperature test. The cleaner, after being in an ambient air temperature of +110°F to +115°F until stabilized, and while at that temperature, shall be tested in accordance with 4.7.4.2 and 4.7.4.3.2. Failure of the cleaner to pass the tests of 4.7.4.2 and 4.7.4.3.2 while in the above condition shall be cause for rejection (see 3.5.9).

4.7.6.6 Low operating temperature test. The cleaner, after being in an ambient air temperature of +35°F to +40°F until stabilized, and while at that temperature, shall be tested in accordance with 4.7.4.2 and 4.7.4.3.2. Failure of the cleaner to pass the tests of 4.7.4.2 and 4.7.4.3.2 while in the above condition shall be cause for rejection (see 3.5.9).

4.7.6.7 High storage temperature test. The cleaner and accessories shall be submitted to a 24 hour cycle of temperature starting with ten hours at +90°F, followed by five hours of steady increase to +155°F, four hours at +155°F, and five hours of steady decrease to +90°F. The equipment shall then be inspected for evidence of damage and tested in accordance with 4.7.4.2 and 4.7.4.3.2. Failure of the cleaner to pass the tests of 4.7.4.2 and 4.7.4.3.2, or evidence of damage to any cleaner component after exposure to the above conditions, shall be cause for rejection (see 3.5.10).

4.7.6.8 Low storage temperature test. The cleaner and accessories shall be placed in an ambient air temperature of -50°F for a period of 72 hours. At the end of this time, the equipment shall be removed and allowed to stabilize at an air temperature of +70°F. The equipment shall then be inspected for evidence of damage and tested in accordance with 4.7.4.2 and 4.7.4.3.2. Failure of the cleaner to pass the tests of 4.7.4.2 and 4.7.4.3.2, or evidence of damage to any cleaner component after exposure to the above conditions, shall be cause for rejection (see 3.5.10).

4.7.6.9 Humidity test. The cleaner and accessories shall be subjected to a 24 hour exposure of 97 to 100 percent relative humidity at +80° to +85°F air temperature, air movement and radiation effects negligible. The cleaner shall then be tested in accordance with 4.7.4.2 and 4.7.4.3.2. Failure of the cleaner to pass the tests of 4.7.4.2 and 4.7.4.3.2, or evidence of damage to any cleaner component after exposure to the above conditions, shall be cause for rejection (see 3.5.11).

4.7.7 Transportability tests. Any visible permanent deformation or breakage of the lifting, pulling, or tie-down devices or visible damage to the cleaner, its components, frame, or skid as a result of any of the tests specified shall be cause for rejection (see 3.6.12).

4.7.7.1 Lifting rings or eyes (vertical loading). Sufficient weight shall be attached to the cleaner to bring the total weight of the cleaner plus the added weight to a minimum of 2 1/2 times the wet weight (the weight of the cleaner with all tanks full and all hoses and guns stowed). The cleaner shall then be suspended from its four lifting eyes or rings at a height of approximately one foot above the ground for a minimum of 30 seconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

4.7.7.2 Lifting, pulling, and tie-down devices (horizontal loading). The lifting, pulling, and tie-down devices shall be subjected to the following horizontal load tests (see 3.6.12).

4.7.7.2.1 Horizontal longitudinal load. A load equal to four times the cleaner's wet weight shall be equally divided among the lifting, pulling or tie-down devices and applied in each horizontal longitudinal direction for a minimum of 30 seconds.

4.7.7.2.2 Horizontal transverse load. A load equal to 2 1/2 times the wet weight of the cleaner shall be equally divided among the lifting, pulling or tie-down devices and applied in each horizontal transverse direction for a minimum of 30 seconds.

4.7.7.3 Fork lift test. The cleaner shall have all hoses and guns mounted. The water and fuel tanks shall be full (wet weight). The cleaner shall then be lifted from each of its four sides by using a fork lift truck without fork extentions. The cleaner shall be raised to a height of no less than one foot each time (see 3.6.11).

4.7.7.4 Trailer transport test. The cleaner shall be mounted on the M105, 1 1/2 ton, cargo trailer. The trailer shall be towed for a distance of 13 miles consisting of five miles of primary (paved) road at speeds up to 50 mph, five miles of secondary (gravel) road at speeds up to 35 mph, and three miles rough terrain (unimproved) at speeds up to five mph. Damage to or displacement of any component, accessory, part or tool, or evidence of defective welded, bolted, or riveted connections, or inability of the cleaner to function properly, shall be cause for rejection (see 3.2.1). To determine if cleaner is functioning properly, start and operate in the vapor mode for five minutes.

4.8 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5 PACKAGING

5.1 Disassembly. Cleaners shall be disassembled to the extent necessary to assure that all surfaces requiring a preservative are accessible for processing, to assure minimum cube for packing, and to permit reassembly without special skills or tools. Disassembly shall be in accordance with MIL-STD-1186.

5.2 Preservation. Preservation shall be Level A or Industrial, as specified in the contract (see 6.2.1).

5.2.1 Level A.

5.2.1.1 Cleaning and drying. Cleaner components and accessories, and all tanks, tubing, piping, fittings, and valves shall be drained, cleaned, dried, and treated with preservative prior to submission for acceptance. All procedures shall be in accordance with the applicable procedures of MIL-P-116.

5.2.1.2 Preservation application. Immediately after cleaning and drying, apply a coat of type P-2 preservative of MIL-P-116 to all exterior, critical, bare, ferrous metal surfaces of the cleaner, except the inside of the stainless

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

steel water tank. All surfaces coated with P-2 shall be covered with barrier material conforming to MIL-B-121 and secured with tape coforming to PPP-T-60. Exterior, noncritical, bare, ferrous metal surfaces, which have not been painted or plated, shall be coated with type P-1 or type P-19 preservative. Interior surfaces of the delivery gun(s) shall be preserved with type P-10, grade 30, preservative oil. Interior surfaces of the fuel system shall be completely flushed (lines and internal filters) and completely fogged (tank and filter) with type P-10, grade 30, preservative oil. Interior surfaces of the water system shall be flushed with a solution consisting of 50 percent antifreeze (ethylene glycol) conforming to O-A-548 and 50 percent clean fresh water. Induce sufficient air pressure into the system to remove residual water.

5.2.1.3 Unit protection. Basic cleaners shall be unit packaged in accordance with method I of MIL-P-116. Small openings in the cleaner shall be sealed with tape conforming to PPP-T-60, type IV, or with plastic cap or plugs conforming to MIL-C-5501. Large apertures shall be covered with barrier material conforming to PPP-B-1055, class E-2. The barrier material shall be secured in place with PPP-T-60 tape. Components of the cleaner and accessories shall be provided unit protection as specified in 5.2.1.3.1 through 5.2.1.3.8.

5.2.1.3.1 Gages and meters. Gages and meters shall be covered with one inch thick uncompressed cushioning material conforming to PPP-C-843, type II. The cushioning shall be secured with PPP-T-60 tape. When gages and meters are protected by an integral cover, cushioning material will not be required.

5.2.1.3.2 Drive belts. Drive belts shall be either removed or released from tension. The grooves of all ferrous metal pulleys shall be coated with primer conforming to TT-P-636. Belts removed from the cleaner shall be packaged in accordance with method III of MIL-P-116.

5.2.1.3.3 Electric motors. Electric motors shall be packaged in accordance with Level A requirements of MIL-E-16298 and the applicable requirements for assembled machines.

5.2.1.3.4 Switch boxes. Electric switch boxes shall be completely sealed with PPP-T-60 tape.

5.2.1.3.5 Power cable and delivery hose. The ends of the hoses and power cable shall be wrapped with barrier material conforming to MIL-B-22191, type III. The barrier material shall be secured with PPP-T-60 tape by encircling the hose or cable, as applicable, making a water tight closure. Individually coil the hose and cable to a minimum safe diameter and secure the coils with a minimum of three ties of cotton tape or twine to prevent uncoiling. Alternatively, the hoses and cable may be coiled on their respective stowage racks and secured to prevent loosening.

5.2.1.3.6 Tools and delivery nozzles. Maintenance tools and delivery nozzles shall be wrapped with barrier material conforming to MIL-B-22191, type, grade, and class optional, and placed in their respective stowage compartments.

5.2.1.3.7 Delivery guns. Delivery guns shall be placed and secured in the stowage device provided on the cleaner. Apertures shall be sealed with tape conforming to PPP-T-60, type IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

5.2.1.3.8 Publications. Technical publications issued with the cleaners shall be packaged in accordance with method IC-1 of MIL-P-116.

5.2.1.3.9 Consolidated packaging. All packaged accessories, technical publications, and disassembled parts, which have not been placed in stowage racks or applicable compartments of the cleaner, shall be adequately cushioned with material conforming to PPP-C-843, type II, and packaged in one or more snug-fitting fiberboard boxes conforming to PPP-B-636, class weather resistant, type CF. The container shall be waterproof sealed as specified in the appendix to that box specification.

5.2.2 Industrial preservation. Industrial preservation shall be as specified in ASTM D3951-82.

5.3 Packing. Packing shall be Level A or Industrial, as specified in the contract (see 6.2.1).

5.3.1 Level A. Cleaners shall be packed in crates conforming to MIL-C-52950, type V, style B, and covered. Blocking, bracing, anchoring, and cushioning shall be in accordance with the container specification and MIL-STD-1186. The consolidated packages of 5.2.1.3.9 shall be included, as applicable.

5.3.2 Industrial. Industrial packing shall be as specified in ASTM D3951-82.

5.4 Marking. Marking shall be military or industrial, as specified in the contract (see 6.2.1).

5.4.1 Military. Marking of interior packages and exterior shipping containers shall be as specified in MIL-STD-129. The shipping container shall also be marked "DO NOT STACK".

5.4.2 Industrial. Industrial marking shall be as specified in ASTM D3951-82, with the shipping container marked "DO NOT STACK".

6. NOTES

6.1 Intended use. The steam cleaner covered by this specification is used for cleaning dirt, grease, and heavy oil deposits from transportation vehicles, construction equipment, and miscellaneous items for maintenance and overhaul. The steam cleaner is used in fixed shops as well as in the field.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) First article when required (see 3.1 and 4.3).
(c) Measuring and indicating device graduation(s) required (see 3.2.6.1).
(d) Level of preservation, packing, and marking required (see 5.2, 5.3, and 5.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

6.3.1 Repair part manuals. Repair part identification in repair part manuals should include the prime contractor's name, nomenclature, part number, and price. Repair part identification shall also include the name of the original equipment/part manufacturer (OEM - actual part manufacturer), Federal Supply Code for Manufacturer's (FSCM), nomenclature, part number, and price of the part immediately after the prime contractor's part identification. High mortality rate items shall be so identified as shown in MIL-M-7298.

6.4 Safety and health requirements. In order that equipment integrated into the user's operational environment will comply with OSHA limitations and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc, as applicable, specific requirements concerning such points of operation, and other health and safety requirements, should be specified by the user.

6.5 Standard lubricants. The cleaner manufacturer should specify and use to the maximum extent possible those lubricants (see 3.2.3) that are presently in the Department of Defense supply system. MIL-HDBK-113, MIL-HDBK-267, and MIL-STD-838 may be used as selection guides.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army - AL

Review activity:

Army - SM

User activity:

Army - ME

Preparing activity:

Army - AL

Project No. 4940-A492

 U.S. GOVERNMENT PRINTING OFFICE: 1986 - 605-034/41241

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research and
Development Center
ATTN: SMCAR-EST-S
Rock Island, IL 61299-7300

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-10-03T02:11Z
Check the source to verify that this is the current version before use.