MIL-C-45008
21 NOVEMBER 1957
SUPERSEDING
SAPD-P-104
1 FEBRUARY 1952

MILITARY SPECIFICATION

CARBINE, CALIBER .30, M1, M2 AND M3 PACKAGING OF

This specification has been approved by the Department of Defense, and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers the packaging and packing of Carbine, Caliber .30, M1, M2 and M3 for each level of protection. (See 6.1.)

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification.

SPECIFICATIONS

MILITARY

JAN-P-100 — Packaging and Packing for Overseas Shipment-General Specification

MIL-P-116 — Preservation, Methods of

JAN-C-372 — Cleaner, Rifle Bore

MIL-P-3420 — Packaging Materials, Volatile Corrosion Inhibitor Treated

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129 — Marking For Shipment And Storage

DRAWINGS

ORDNANCE CORPS

B-7160000 — Brush, Cleaning, M31

C-5564174 — Brush, Cleaning, Cal. .30

F-7267831 — Packing and Packing for Carbine, Cal. .30, M1 and M2 List of Drawings and Specifications

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:12Z
Check the source to verify that this is the current version before use.

2.2 **Other publications.** The following documents form a part of this specification. Unless otherwise indicated the issue in effect on date of invitation for bids shall apply.

CONSOLIDATED FREIGHT CLASSIFICATION RATINGS, RULES AND REGULATIONS

(Application for copies shall be addressed to the Consolidated Freight Classification Committee, 202 Union Station, 526 West Jackson Blvd., Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 **Materials and methods.** The materials and methods used in preparing Carbine, Cal. .30, M1, M2 and M3 for shipment and storage shall be in accordance with this specification and other applicable documents. The time intervals between all processes of preparation shall be of the practicable minimum.

3.1.1 *Materials.* Unless otherwise specified in the contract, the contractor shall provide the inspector certification of adherence to the requirements of material specifications for each lot of materials used. The following data shall apply wherever packaging materials are referred to in this specification by name only:

Reference	*Full identification*
Hot water	Water maintained at a minimum temperature of 200°F.
Rifle bore cleaner	Specification JAN–C–372.
Saturated brush or patch	Saturation medium shall be rifle bore cleaner.
Moldable VCI treated material	Material conforming to type I, grade A, of Specification MIL–P–3420. (Shall consist of a treated neutral kraft paper laminated to a moldable self-adhering greaseproof material.) (See 6.3.)

3.1.2 *Methods.* Unless otherwise specified herein, the methods and procedures for cleaning, drying, preserving, packaging, and packing shall be in accordance with the requirements of Specification MIL–P–116 and Drawing F–7267831.

3.2 **Preservation and packaging.**

3.2.1 *Level A.*

3.2.1.1 *Cleaning.* The carbine shall be disassembled and the metallic surfaces of component parts and assemblies thoroughly cleaned by process C–3. Surfaces subjected to burned powder residues shall be scrubbed clean with a saturated, non-metallic bristle brush prior to cleaning by process C–3.

3.2.1.1.1 *Barrel assembly.* The bore and chamber shall be purged with steam or hot water, dried by procedure D–1, then followed by cleaning as specified in 3.2.1.1.1.1.

3.2.1.1.1.1 *Bore, chamber and gas cylinder.* A minimum of three full passes (forward and rearward) with a saturated close fitting wire brush conforming to Drawing C–5564174, followed by three passes with individual dry patches, and one pass with a saturated patch shall be made through the bore. The inside of the gas cylinder shall be scrubbed clean with rifle bore cleaner. The chamber shall be cleaned by the use of a saturated brush, conforming to Drawing B–7160000, followed by a saturated double patch, a dry double patch, and finally a saturated double patch in respective sequence. This procedure shall be repeated as necessary to obtain the required cleanliness.

3.2.1.1.2 *Components and assemblies.* The components and assemblies removed from the carbine shall be cleaned in accordance with table I.

3.2.1.2 *Drying.* Unless otherwise specified herein, all cleaned surfaces shall be dried in accordance with procedure D–1. Barrel bore and chamber shall be dried in accordance with procedure D–4 using clean dry patches. All moisture and residual cleaning solvents shall be thoroughly removed from the car-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:12Z
Check the source to verify that this is the current version before use.

TABLE I. *Cleaning of components and Assemblies*

Component or assembly	Process
Piston nut	Immerse in hot water and as specified in 3.2.1.1. Stake after reassembly.
Piston	Immerse in hot water and as specified in 3.2.1.1.
Operating slide	Immerse in hot water and as specified in 3.2.1.1. Brush inside face with a non-metallic brush.
Bolt	As specified in 3.2.1.1. Brush face with a non-metallic brush.
Recoil spring	As specified in 3.2.1.1.
Receiver	Breech end cleaned as specified in 3.2.1.1.
Magazine (disassembled	As specified in 3.2.1.1.
Oiler	C–3

bine, magazine assembly, and oiler prior to applying the preservative oil.

3.2.1.3 *Preservative application.*

3.2.1.3.1 The carbine shall be preserved with type P–9 oil and P–18 VCI applied as specified herein. The magazine assembly, oiler, and the metallic surfaces of the carbine shall be completely coated with type P–9 oil. The carbine action with the slide lever retracted shall be coated by the dipping procedure. The metallic surfaces of the stock and hand guard assemblies shall be coated by the brushing procedure. If the oil is heated to accelerate drainage the temperature of the oil shall not exceed 120°F.

3.2.1.3.1.1 *Drainage.* Each magazine assembly, oiler, and carbine shall be completely drained of excess oil prior to reassembly and packaging. The draining position of the carbine shall be changed as necessary to accomplish thorough drainage.

3.2.1.4 *Cushioning and wrapping.*

3.2.1.4.1 *Carbine.* The front and rear sights of the M1 and M2 carbines shall be cushioned and wrapped with moldable VCI treated material. The front sight area and the scope mount brackets of the M3 carbine shall be cushioned and wrapped with moldable VCI treated material. (See 6.4.)

3.2.1.4.2 *Magazine assembly and oiler.* The magazine assembly and oiler shall be individually wrapped with moldable VCI treated material. The magazine assembly shall be attached to the carbine and the oiler placed in the recess of the stock assembly as indicated on the drawing.

3.2.1.4.3 *Sling.* The sling shall be rolled or folded flat and wrapped with type 1, grade C, VCI treated material conforming to Specification MIL–P–3420.

3.2.1.4.4 *Barrel bore protection.* The VCI bore tube, specified on the drawing, shall be inserted into the bore of the barrel and the protruding portion bent over the outside surface of the muzzle.

3.2.1.5 *Unit packaging.* Each carbine, with one each magazine assembly, oiler, and sling shall be unit packaged together in accordance with method 1A–8 as indicated on the drawing. The VCI liner shall be folded over the butt end of the carbine and the excess air shall be expelled from the bag prior to heat sealing the closure. The bag shall be capable of passing the heat seal and quick leak tests specified in section 4.

3.2.1.6 *Intermediate package.* Two carbines, unit packaged in accordance with 3.2.1.5, shall be packaged in a fiberboard box in accordance with the drawing. The carbines shall be properly and firmly positioned in the end blocks, and the box sealed with the specified sealing tape.

3.2.2 *Level B* (see 6.1).

3.2.2.1 *Cleaning, drying and preservative*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:12Z
Check the source to verify that this is the current version before use.

application. Cleaning, drying, and preservative application shall be in accordance with the requirements of 3.2.1.1, 3.2.1.2, and 3.2.1.3.

3.2.2.2 *Wrapping*. The magazine assembly, oiler, and sling shall be individually wrapped as specified in 3.2.1.4.2 and 3.2.1.4.3.

3.2.2.3 *Unit package*. Each carbine, with one each magazine assembly, oiler and sling shall be wrapped together with moldable VCI treated material and packaged in accordance with method I as indicated on the drawing.

3.2.2.4 *Intermediate package*. Two carbines, unit packaged in accordance with 3.2.2.3, shall be packaged in a fiberboard box in accordance with the drawing. The VCI treated material shall be folded around the ends of the carbine in a manner to provide a firm position in the end blocks. The box shall be sealed with the specified sealing tape.

3.3 **Packing.**

3.3.1 *Level A*. Five intermediate packages containing ten carbines, unit packaged in accordance with 3.2.1.6, shall be packed in a nailed wood box in accordance with the drawing. Completed packs shall be capable of passing the rough handling test specified in 4.5.1.

3.3.2 *Level B* (see 6.1).

3.3.2.1 Five intermediate packages containing ten carbines, unit packaged in accordance with 3.2.2.4, shall be packed in a wood box in accordance with the drawing.

3.3.3 *Level C*. Ten carbines, packaged in accordance with 3.2.2.3 and 3.2.2.4, shall be packed for shipment in accordance with the drawing.

3.4 **Marking.** Interior packages and shipping containers shall be marked in accordance with the requirements of Standard MIL–STD–129 and the drawing.

3.5 **Pilot pack.** When level A or level B is specified, a pilot pack consisting of a complete and packed shipping container shall be forwarded prepaid by the contractor to the testing agency designated by the procuring activity for approval.

3.6 **Workmanship.** Adequate controls shall be utilized to check for contamination of cleaning solvents and preservative oils. Wraps shall be conforming and firmly secured. Heat seals shall be uniform in appearance. Sealing tape shall be applied to boxes uniformly and shall adhere to joints and seams.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Inspection and tests.** The inspection procedures specified in this section are those that will be conducted by the Government. The tests shall be accomplished by the contractor or his agent under the surveillance of the Government inspector.

4.1.1 *Pilot pack*. Inspection and testing of the pilot pack (see 3.5) shall be performed at the designated testing agency. The pilot pack shall be subjected to the inspection and tests specified herein, and such other inspection and tests as are necessary to determine compliance with the preservation, packaging, and packing requirements of this specification for levels A and B. The level A pilot pack shall be subjected to the rough handling test specified in 4.5.1. Acceptance of the initial lot shall be deferred pending approval of the pilot pack.

4.2 **Lot.** The lot size submitted for acceptance purposes shall be determined by the procuring activity or Government inspection agency and shall be as large as is practicable, consistent with available facilities, and delivery schedules.

4.3 **Sampling.**

4.3.1 *For inspection*. Sampling for inspection shall be conducted in accordance with

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:12Z
Check the source to verify that this is the current version before use.

inspection level I of Standard MIL–STD–105.

4.3.2 *For tests.* Sampling for tests shall be conducted in accordance with inspection level L6 of Appendix to Standard MIL–STD–105.

4.4 Inspection.

4.4.1 *Classification of defects.* Visual inspection for defects established in table II shall apply to each item of the applicable sample of carbines, interior packages, or exterior containers as applicable.

TABLE II. *Classification of defects*

Categories and defects	AQL
Major	
1. Illegible marking	1.0
2. Incorrect marking	1.0
3. Missing parts	1.0
4. Improper level of packaging and packing	1.0
Minor	
51. Improper preservation application and drainage	2.5
52. Improper cushioning and wrapping	2.5
53. Improper closure of bags and interior packages	2.5
54. Non-adherence to drawing requirements	2.5
55. Improper closure and strapping of shipping containers	2.5
56. Carbines not properly inserted in end blocks	2.5
101. Workmanship	6.5

4.5 Tests

4.5.1 *Rough handling test.* The pilot pack, for level A only, shall be subjected to the rough handling test in accordance with the requirements of Specification JAN–P–100. The drop shall be 30 inches.

4.5.2 *Heat seal and quick leak tests.* Each level A package of the applicable test sample shall be subjected to the heat seal and quick leak tests of Specification MIL–P–116. The lot acceptance shall be based on an AQL of 6.5 percent defective for each test.

4.5.3 *Determination of cleanliness test.* From each test lot, the inspector shall subject the applicable surfaces (except for barrel bores and chambers) of each sample unit to the determination of cleanliness test in accordance with Specification MIL–P–116. Barrel bores and chambers of these units shall be tested for cleanliness by passing a clean, dry, chloride-free patch through the bore and chambers. Chemical analysis of these patches shall show no corrosion promoting residues such as chlorides. The lot acceptance shall be based on an AQL of 6.5 percent defective.

5. PREPARATION FOR DELIVERY

(There are no applicable requirements.)

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.

(b) Selection of applicable levels of preservation and packaging and packing.

(1) Level B preservation and packaging is intended to provide adequate and economical protection during multiple domestic shipments, handling, and indoor storage periods up to 12 months from date of initial packaging.

(c) Shipping instructions for pilot pack (see 3.5).

6.2 Storage surveillance. Carbines pre-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:12Z
Check the source to verify that this is the current version before use.

served and packaged in accordance with level B requirements must be inspected to determine condition when not used within a one-year period. Carbines not used within this period should be reserved or repackaged in accordance with this specification as determined necessary by storage conditions and anticipated storage time.

6.3 Moldable VCI materials described in 3.1.1 are presently listed in Qualified Products List, QPL–3420–3, dated 2 March 1955 as 204 VPI, Seal-Tite grade C, 159 CA, and 2300 GM.

6.4 Modification of the filler sheet on Drawing F–7267831 is required when Carbine, Cal. .30, M3 is packaged in accordance with the specification.

Notice. This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restriction, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance, Department of the Army.

Custodians:
Army—Ordnance Corps
Navy—Bureau of Ordnance
Air Force

Other interest:
Navy—MC

Preparing activity:
Army—Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:12Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Naval Sea Systems Command
Engineering Support Division
ATTN: SEA 605
Department of the Navy
Washington, DC20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:12Z
Check the source to verify that this is the current version before use.